Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Malta

# **SAFETY DATA SHEET**



TEKNOCOMBI 2917-62 - All variants

### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1	Produ	uct ide	entifier
-----	-------	---------	----------

Product name : TEKNOCOMBI 2917-62 - All variants

**1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use**: Wood preservative.

### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091. e-mail address of person : Prod-safe@teknos.com responsible for this SDS

### **National contact**

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

### **1.4 Emergency telephone number**

### National advisory body/Poison Centre

 Telephone number
 : Malta Competition and Consumer Affairs Authority (MCCAA): +356 2395 2000

### **SECTION 2: Hazards identification**

2.1	Classif	icatio	n of	the	subs	tance	or m	ixture	•

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements Signal word : No signal word. **Hazard statements** : H412 - Harmful to aquatic life with long lasting effects. **Precautionary statements** General : P102 - Keep out of reach of children. Prevention : P273 - Avoid release to the environment. Response : Not applicable. Storage : P404 - Store locked up. **Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations. Contains 3-iodo-2-propynyl-butyl carbamate, 1,2-benzisothiazol-3(2H)-one and **Supplemental label** ŝ, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and elements 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

SECTION 2: Hazards	identification
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: For professional users only.
2.3 Other hazards	
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

# **SECTION 3: Composition/information on ingredients**

Г

3.2 Mixtures Product/ingredient name	: Mixture	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥10 - ≤25	Carc. 2, H351 (inhalation)	-	[1] [*]
2-(2-butoxyethoxy)ethanol	REACH #: 01-2119475104-44 EC: 203-961-6 CAS: 112-34-5 Index: 603-096-00-8	≤3	Eye Irrit. 2, H319	-	[1] [2]
Dipropylene glycol dibenzoate	REACH #: 01-2119529241-49 EC: 248-258-5 CAS: 27138-31-4	≤3	Aquatic Chronic 3, H412	-	[1]
3-iodo-2-propynyl-butyl carbamate	EC: 259-627-5 CAS: 55406-53-6 Index: 616-212-00-7	<1	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 400 mg/kg ATE [Inhalation (dusts and mists)] = 0.67 mg/l M [Acute] = 10 M [Chronic] = 1	[1]
2-Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	≤0.3	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	ATE [Oral] = 1200 mg/kg ATE [Inhalation (vapours)] = 3 mg/l	[1] [2]
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.036	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 450 mg/kg ATE [Inhalation (dusts and mists)] = $0.21$ mg/l Skin Sens. 1, H317: C $\ge 0.036\%$ M [Acute] = 1 M [Chronic] = 1	[1]
reaction mass of: 5-chloro-	EC: 911-418-6	<0.001	Acute Tox. 3, H301	ATE [Oral] = 53 mg/	[1]

## **SECTION 3: Composition/information on ingredients**

SECTION 3. Compo	Sillon/informati	on on ingreatents		
2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:1)	CAS: 55965-84-9 Index: 613-167-00-5	Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071 See Section 16 for the full text of the H statements declared above.	kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: $C \ge 0.6\%$ Eye Dam. 1, H318: $C \ge 0.6\%$ Eye Irrit. 2, H319: $0.06\% \le C < 0.6\%$ Skin Sens. 1, H317: $C \ge 0.0015\%$ M [Acute] = 100 M [Chronic] = 100	

There are no additional ingredients present which, within the current knowledge of the supplier and in the

concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[\*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter  $\leq$  10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

the second se		
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lowe eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.	
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing	
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.	
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomitin unless directed to do so by medical personnel.	g
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.	

### 4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Our a stift a first after a state	No. No. and a star and

**Specific treatments** : No specific treatment.

# **SECTION 5: Firefighting measures**

SECTION 5. Fileligi	iy measures	
5.1 Extinguishing media		
Suitable extinguishing media	Use an extinguishing agent suitable for the surrounding fire.	
Unsuitable extinguishing media	None known.	
5.2 Special hazards arising	m the substance or mixture	
Hazards from the substance or mixture	In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.	
Hazardous combustion products	Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides	
5.3 Advice for firefighters		
Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incide there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>	ent if
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection chemical incidents.	)

## **SECTION 6: Accidental release measures**

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

## **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

: Not available.
: Not available.

### SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

### **Occupational exposure limits**

Exposure limit values
EU OEL (Europe, 1/2022)
TWA 8 hours: 67.5 mg/m <sup>3</sup> .
TWA 8 hours: 10 ppm.
STEL 15 minutes: 101.2 mg/m <sup>3</sup> .
STEL 15 minutes: 15 ppm.
EU OEL (Europe, 1/2022) Absorbed through skin.
TWA 8 hours: 20 ppm.
TWA 8 hours: 98 mg/m <sup>3</sup> .
STEL 15 minutes: 50 ppm.
STEL 15 minutes: 246 mg/m³.

### **Biological exposure indices**

Product/ingredien	t name	Exposure indices			
No exposure indices known.					
Recommended monitoring procedures	European Star assessment of values and me atmospheres - of exposure to (Workplace atu for the measur	ndard EN 689 (Workpl f exposure by inhalatic easurement strategy) Guide for the applica chemical and biologic mospheres - General rement of chemical ag	oring standards, such as t ace atmospheres - Guida on to chemical agents for European Standard EN 1- tion and use of procedure cal agents) European Sta requirements for the perfo ents) Reference to nation rmination of hazardous su	ance for the comparison v 4042 (Workpl es for the asse indard EN 482 ormance of pr nal guidance	vith limit lace essment 2 rocedures
ate of issue/Date of revision	: 10/07/2025	Date of previous issue	: No previous validation	Version :1	5/20

TEKNOCOMBI 2917-62 - All variants

# S

SECTION 8: Exposure controls/personal protection			
DNELs/DMELs Product/ingredient name titanium dioxide	<b>Result</b> DNEL - General population - Long term - Inhalation 28 μg/m³ <u>Effects</u> : Local		
	<b>DNEL - Workers - Long term - Inhalation</b> 170 μg/m³ <u>Effects</u> : Local		
2-(2-butoxyethoxy)ethanol	<b>DNEL - General population - Long term - Oral</b> 6.25 mg/kg bw/day <u>Effects</u> : Systemic		
	<b>DNEL - Workers - Long term - Inhalation</b> 67.5 mg/m <sup>3</sup> <u>Effects</u> : Local		
	<b>DNEL - Workers - Short term - Inhalation</b> 101.2 mg/m³ <u>Effects</u> : Local		
Dipropylene glycol dibenzoate	<b>DNEL - General population - Long term - Dermal</b> 2.5 mg/kg bw/day <u>Effects</u> : Systemic		
	<b>DNEL - General population - Long term - Oral</b> 5 mg/kg bw/day <u>Effects</u> : Systemic		
	<b>DNEL - General population - Long term - Inhalation</b> 8.69 mg/m <sup>3</sup> <u>Effects</u> : Systemic		
	<b>DNEL - General population - Short term - Inhalation</b> 8.7 mg/m <sup>3</sup> <u>Effects</u> : Systemic		
	<b>DNEL - Workers - Long term - Inhalation</b> 8.8 mg/m <sup>3</sup> <u>Effects</u> : Systemic		
	<b>DNEL - Workers - Long term - Dermal</b> 10 mg/kg bw/day <u>Effects</u> : Systemic		
	<b>DNEL - Workers - Short term - Inhalation</b> 35.08 mg/m <sup>3</sup> <u>Effects</u> : Systemic		
	<b>DNEL - General population - Short term - Oral</b> 80 mg/kg bw/day <u>Effects</u> : Systemic		
	<b>DNEL - General population - Short term - Dermal</b> 80 mg/kg bw/day <u>Effects</u> : Systemic		
	<b>DNEL - Workers - Short term - Dermal</b> 170 mg/kg bw/day <u>Effects</u> : Systemic		
3-iodo-2-propynyl-butyl carbamate	<b>DNEL - Workers - Long term - Inhalation</b> 0.023 mg/m <sup>3</sup>		

: 10/07/2025 Date of previous issue

Date of issue/Date of revision TEKNOCOMBI 2917-62 - All variants

0.023 mg/m³ <u>Effects</u>: Systemic

: No previous validation

Version :1 6/20 Label No :122333

# SECTION 8: Exposure controls/personal protection

	DNEL - Workers - Short term - Inhalation 0.07 mg/m³ <u>Effects</u> : Systemic
	<b>DNEL - Workers - Short term - Inhalation</b> 1.16 mg/m³ <u>Effects</u> : Local
	<b>DNEL - Workers - Long term - Inhalation</b> 1.16 mg/m³ <u>Effects</u> : Local
	<b>DNEL - Workers - Long term - Dermal</b> 2 mg/kg bw/day <u>Effects</u> : Systemic
2-Butoxyethanol	<b>DNEL - General population - Long term - Oral</b> 6.3 mg/kg bw/day <u>Effects</u> : Systemic
	<b>DNEL - General population - Short term - Oral</b> 26.7 mg/kg bw/day <u>Effects</u> : Systemic
	<b>DNEL - General population - Long term - Inhalation</b> 59 mg/m <sup>3</sup> <u>Effects</u> : Systemic
	<b>DNEL - Workers - Long term - Inhalation</b> 98 mg/m³ <u>Effects</u> : Systemic
	DNEL - General population - Short term - Inhalation 147 mg/m <sup>3</sup> <u>Effects</u> : Local
	<b>DNEL - Workers - Short term - Inhalation</b> 246 mg/m³ <u>Effects</u> : Local
	<b>DNEL - General population - Short term - Inhalation</b> 426 mg/m <sup>3</sup> <u>Effects</u> : Systemic
	DNEL - Workers - Short term - Inhalation 1091 mg/m³ <u>Effects</u> : Systemic
1,2-benzisothiazol-3(2H)-one	<b>DNEL - General population - Long term - Dermal</b> 0.345 mg/kg bw/day <u>Effects</u> : Systemic
	<b>DNEL - Workers - Long term - Dermal</b> 0.966 mg/kg bw/day <u>Effects</u> : Systemic
	<b>DNEL - General population - Long term - Inhalation</b> 1.2 mg/m <sup>3</sup> <u>Effects</u> : Systemic
	<b>DNEL - Workers - Long term - Inhalation</b> 6.81 mg/m <sup>3</sup> <u>Effects</u> : Systemic
reaction mass of: 5-chloro-2-methyl-	DNEL - General population - Long term - Inhalation
Date of issue/Date of revision : 10/07/2025 Date of	of previous issue : No previous validation Version : 1 7

TEKNOCOMBI 2917-62 - All variants

i previous issue . No

ious validation Version : 1 7/20 Label No :122333

### **SECTION 8: Exposure controls/personal protection**

4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) 0.02 mg/m³ <u>Effects</u>: Local

**DNEL - Workers - Long term - Inhalation** 0.02 mg/m<sup>3</sup> <u>Effects</u>: Local

**DNEL - General population - Short term - Inhalation** 0.04 mg/m<sup>3</sup> <u>Effects</u>: Local

DNEL - Workers - Short term - Inhalation 0.04 mg/m<sup>3</sup> Effects: Local

**DNEL - General population - Long term - Oral** 0.09 mg/kg bw/day <u>Effects</u>: Systemic

**DNEL - General population - Short term - Oral** 0.11 mg/kg bw/day <u>Effects</u>: Systemic

### **PNECs**

Not available.

8.2 Exposure controls	
Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection meas	ures
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
	Recommendations : Wear suitable gloves tested to EN374.
	> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm
	Not recommended polyvinyl alcohol (PVA) gloves
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Date of issue/Date of revision	: 10/07/2025 Date of previous issue : No previous validation Version : 1 8/20

### **SECTION 8: Exposure controls/personal protection**

•	• •
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
	Filter type (spray application): A P
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

### **Appearance**

Physical state	: Liquid.
Colour	: Various
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	:

Ingredient name	°C	°F	Method
water	100	212	
2-(2-butoxyethoxy)ethanol	225 to 227.6	437 to 441.7	

Flammability	: Not available.	
Lower and upper explosion limit	: Lower: 0.8% (2-(2-butoxyethoxy)ethan Upper: 9.4% (2-(2-butoxyethoxy)ethan	
Flash point	: Closed cup: >100°C (>212°F)	

2

### **Auto-ignition temperature**

Ingredient name	°C	°F	Method
2-(2-butoxyethoxy)ethanol	210	410	DIN 51794
Dipropylene glycol dibenzoate	>400	>752	EU A.15

Decomposition temperature	: Not available.
рН	: 8 to 8.3 [Conc. (% w/w): 100%]
Viscosity	: Not available.
Solubility(ies)	:
Not available.	
Solubility in water	: Not available.
Partition coefficient: n-octanol/ water	: Not applicable.

ż

### Vapour pressure

	Va	Vapour Pressure at 20°C		Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
water	17.5	2.3				
2-(2-butoxyethoxy)ethanol	0.022	0.0029				
Relative density	: Not	available.		ł	•	·
Density	: 1.2	g/cm³				
Vapour density	: Not	available.				
Particle characteristics						
Date of issue/Date of revision	: 10/07/2	025 Date o	f previous issue	: No previous	validation	Version : 1

Date of issue/Date of revision TEKNOCOMBI 2917-62 - All variants

Label No :122333

# **SECTION 9: Physical and chemical properties**

Median particle size

: Not applicable.

9.2 Other information	
9.2.1 Information with rega	rd to physical hazard classes
Explosive properties	: Not available.
<b>Oxidising properties</b>	: Not available.
9.2.2 Other safety characte	ristics
Not applicable.	

SECTION 10: Stabilit	y and reactivity
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: No specific data.
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological information**

11.1 Information on hazard classes as defin	ed in Regulation (EC) No 1272/2008
Acute toxicity	
Product/ingredient name	Result
2-(2-butoxyethoxy)ethanol	<b>Rabbit - Dermal - LD50</b> 2700 mg/kg
	<b>Rat - Oral - LD50</b> 4500 mg/kg <u>Toxic effects</u> : Behavioral - Tetany Lung, Thorax, or Respiration - Dyspnea Liver - Other changes
Dipropylene glycol dibenzoate	<b>Rat - Oral - LD50</b> 3295 mg/kg <u>Toxic effects</u> : Brain and Coverings - Other degenerative changes Cardiac - Cardiomyopathy, including infarction Liver - Other changes
3-iodo-2-propynyl-butyl carbamate	<b>Rat - Oral - LD50</b> 400 mg/kg
	<b>Rat - Dermal - LD50</b> >2000 mg/kg
	Rat - Inhalation - LC50 Dusts and mists 0.763 mg/l [4 hours]
	Rat - Inhalation - LC50 Dusts and mists 0.67 g/m <sup>3</sup> [4 hours]
1,2-benzisothiazol-3(2H)-one	<b>Rat - Oral - LD50</b> 1020 mg/kg
reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and	<b>Rat - Oral - LD50</b> 53 mg/kg

Label No :122333

TEKNOCOMBI 2917-62 - All variants

### **SECTION 11: Toxicological information**

2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

<u>Toxic effects</u>: Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration - Respiratory depression

Conclusion/Summary [Product] : Not available.

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
TEKNOCOMBI 2917-62 2-(2-butoxyethoxy)ethanol Dipropylene glycol dibenzoate 3-iodo-2-propynyl-butyl carbamate 2-Butoxyethanol 1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro-2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6] (3:1)	N/A 4500 3295 400 1200 450 53	N/A 2700 N/A N/A N/A N/A 50	N/A N/A N/A N/A N/A N/A N/A	1666.7 N/A N/A 3 N/A 0.5	223.3 N/A 0.67 N/A 0.21 N/A

#### **Skin corrosion/irritation**

#### **Product/ingredient name**

titanium dioxide

2-Butoxyethanol

1,2-benzisothiazol-3(2H)-one

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Conclusion/Summary [Product] : Not available.

#### Serious eye damage/eye irritation Product/ingredient name

2-(2-butoxyethoxy)ethanol

### Result

Human - Skin - Mild irritant Duration of treatment/exposure: 72 hours Amount/concentration applied: 300 ug l

Rabbit - Skin - Mild irritant Amount/concentration applied: 500 mg

#### Human - Skin - Mild irritant Duration of treatment/exposure: 48 hours Amount/concentration applied: 5 %

Human - Skin - Severe irritant Amount/concentration applied: 0.01 %

#### Result

Rabbit - Eyes - Moderate irritant Duration of treatment/exposure: 24 hours Amount/concentration applied: 20 mg

Rabbit - Eyes - Severe irritant Amount/concentration applied: 20 mg

3-iodo-2-propynyl-butyl carbamate

2-Butoxyethanol

#### **Rabbit - Eyes - Severe irritant**

Rabbit - Eyes - Moderate irritant Duration of treatment/exposure: 24 hours Amount/concentration applied: 100 mg

Rabbit - Eyes - Severe irritant Amount/concentration applied: 100 mg

#### Conclusion/Summary [Product] : Not available.

 Date of issue/Date of revision
 : 10/07/2025
 Date of previous issue
 : No previous validation

 TEKNOCOMBI 2917-62 - All variants

### **SECTION 11: Toxicological information**

### **Respiratory corrosion/irritation**

Not available.

**Conclusion/Summary [Product]** : Not available.

Respiratory or skin sensitization Product/ingredient name

3-iodo-2-propynyl-butyl carbamate

### Result

Guinea pig - skin <u>Result</u>: Not sensitizing

Skin

Conclusion/Summary [Product] : Not available.

Respiratory Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Product/ingredient name 3-iodo-2-propynyl-butyl carbamate

### Result

In vitro - Bacteria Result: Negative

**Conclusion/Summary [Product]** : Not available.

### **Carcinogenicity**

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. Not available.

**Conclusion/Summary [Product]** : Not available.

Reproductive toxicity

Product/ingredient name 3-iodo-2-propynyl-butyl carbamate

### Result

Rabbit - Female - Oral 50 mg/kg [7 days per week] [13 days] <u>Maternal toxicity</u>: Positive Developmental: Negative

### Rabbit - Female - Oral

20 mg/kg [7 days per week] [13 days] <u>Maternal toxicity</u>: Negative <u>Developmental</u>: Negative

Conclusion/Summary [Product] : Not available.

### Specific target organ toxicity (single exposure) Not available.

Specific target organ toxicity (repeated exposure) Product/ingredient name 3-iodo-2-propynyl-butyl carbamate

Result STOT RE 1, H372 (larynx)

### Aspiration hazard

Not available.

Date of issue/Date of revision : 1 TEKNOCOMBI 2917-62 - All variants

: 10/07/2025 Date of previous issue

: No previous validation

# **SECTION 11: Toxicological information**

Information on likely routes	<u>of exposure</u>
Not available.	
Potential acute health effects	<u>s</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the phy	ysical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Delayed and immediate effect	cts as well as chronic effects from short and long-term exposure
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	<u>cts</u>
Not available.	
Conclusion/Summary [Pro	duct] : Not available.
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.
11.2 Information on other haz 11.2.1 Endocrine disrupting	
Not available	h

Not available.

**Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

### 11.2.2 Other information

Not available.

# **SECTION 12: Ecological information**

12.1 Toxicity	
Product/ingredient name	Result
titanium dioxide	Acute - LC50 - Marine water
	Fish - Mummichog - Fundulus heteroclitus
	>1000000 µg/l [96 hours]
	<u>Effect</u> : Mortality
	Acute - LC50 - Fresh water
	Crustaceans - Water flea - Ceriodaphnia dubia - Neonate
	<u>Age</u> : <24 hours
	3 mg/l [48 hours]
	<u>Effect</u> : Mortality
2-(2-butoxyethoxy)ethanol	Acute - LC50 - Fresh water
	Fish - Bluegill - Lepomis macrochirus
	Size: 33 to 75 mm
Date of issue/Date of revision : 10/02	2025 Date of previous issue : No previous validation Version : 1 13/20
TEKNOCOMBI 2917-62 - All variants	Label No :122333

	1300000 µg/l [96 hours]
	Effect: Mortality
-iodo-2-propynyl-butyl carbamate	<b>Acute - LC50 - Fresh water</b> EU Fish - Trout - <i>Oncorhynchus myki</i> ss
	0.067 mg/l [96 hours]
	<b>Acute - NOEC - Fresh water</b> EU Fish - Trout - <i>Oncorhynchus mykiss</i> 0.049 mg/l [96 hours]
	Acute - EC50 - Fresh water EU
	Daphnia - Daphnia <i>- Daphnia magna</i> 0.16 mg/l [48 hours]
	<b>Chronic - NOEC - Fresh water</b> EU
	Daphnia - Daphnia - <i>Daphnia Magna</i> 0.05 mg/l [21 days]
	Acute - EC50 - Fresh water
	Algae - Algae - <i>Scenedemus subspicatus</i> 0.022 mg/l [72 hours]
P-Butoxyethanol	<b>Acute - LC50 - Marine water</b> Fish - Inland silverside - <i>Menidia beryllina</i> <u>Size</u> : 40 to 100 mm 1250000 μg/l [96 hours] <u>Effect</u> : Mortality
	<b>Acute - LC50 - Marine water</b> Crustaceans - Common shrimp, sand shrimp - <i>Crango</i> <i>crangon</i> 800000 μg/l [48 hours] <u>Effect</u> : Mortality
2-benzisothiazol-3(2H)-one	<b>Acute - LC50 - Fresh water</b> OECD [Fish, Acute Toxicity Test] Fish - Trout - <i>Onorhynchus Mykiss</i> 1.9 mg/l [96 hours]
	<b>Acute - EC50</b> OECD 202 [Daphnia sp. Acute Immobilization Test and Reproduction Test] Daphnia - Daphnia - <i>Daphnia Magna</i> 3.7 mg/l [48 hours]
	<b>Acute - EC50 - Marine water</b> OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - <i>Skeletonema Costatum</i> 0.36 mg/l [72 hours]
	<b>Acute - NOEC - Marine water</b> OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - <i>Skeletonema Costatum</i> 0.15 mg/l [72 hours]
Conclusion/Summary [Product] : Not	
2 Persistence and degradability	
Product/ingredient name	Result

TEKNOCOMBI 2917-62 - All variants

Version :1 14/20 Label No :122333

# **SECTION 12: Ecological information**

1,2-benzisothiazol-3(2H)-one

24% [28 days]

EU

### **Conclusion/Summary [Product]** : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
3-iodo-2-propynyl-butyl carbamate	-	-	Not readily
1,2-benzisothiazol-3(2H)-one	-	-	Inherent

#### **12.3 Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
2-(2-butoxyethoxy)ethanol	1	-	Low
3-iodo-2-propynyl-butyl carbamate	>1	-	Low
2-Butoxyethanol	0.81	-	Low
1,2-benzisothiazol-3(2H)-one	-	3.2	Low

### 12.4 Mobility in soil

### Soil/water partition coefficient

Product/ingredient name	logKoc	Кос
2-(2-butoxyethoxy)ethanol	1.6	36.5981
3-iodo-2-propynyl-butyl carbamate	1.1	13.4558
2-Butoxyethanol	1.8	67.3685
1,2-benzisothiazol-3(2H)-one	1.9	73.142

### **Results of PMT and vPvM assessment**

Product/ingredient name	PMT	Р	Μ	т	vPvM	vP	vM
titanium dioxide	No	No	No	No	No	No	No
2-(2-butoxyethoxy)ethanol	No	No	No	No	No	No	No
Dipropylene glycol dibenzoate	No	No	No	No	No	No	No
3-iodo-2-propynyl-butyl carbamate	No	No	No	No	No	No	No
2-Butoxyethanol	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No

Mobility

**Conclusion/Summary** 

: Not available.

: The product does not meet the criteria to be considered as a PMT or vPvM.

### 12.5 Results of PBT and vPvB assessment Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	Р	В	Т	vPvB	vP	vB	
titanium dioxide	No	No	No	No	No	No	No	
2-(2-butoxyethoxy)ethanol	No	N/A	N/A	No	N/A	N/A	N/A	
Dipropylene glycol dibenzoate	No	N/A	N/A	No	N/A	N/A	N/A	
3-iodo-2-propynyl-butyl carbamate	N/A	N/A	N/A	Yes	N/A	N/A	N/A	
2-Butoxyethanol	No	N/A	N/A	No	N/A	N/A	N/A	
1,2-benzisothiazol-3(2H)-one	No	N/A	No	No	No	N/A	No	
reaction mass of: 5-chloro-	No	N/A	N/A	No	N/A	N/A	N/A	
ate of issue/Date of revision	: 10/07	/2025 Date or	f previous iss	ue :N	o previous validat	tion Versio	on :1 1	5/20

Date of issue/Date of revision

TEKNOCOMBI 2917-62 - All variants

Label No :122333

SECTION 12: Ecological information		
2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7]		
and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:		
1)		

#### Regulation (EC) No. 1272/2008 [CLP]

No No No	No No	No	No	No	NI-	
	No		110		No	No
No		No	No	No	No	No
NU	No	No	No	No	No	No
No	No	No	No	No	No	No
No	No	No	No	No	No	No
No	No	No	No	No	No	No
No	No	No	No	No	No	No
L	No No No	No No No No No No	No No No No No No No No No	No No No No No No No No No No No No	No No No No No No No No No No No No No No No No	NoNoNoNoNoNoNoNoNoNoNoNoNoNoNo

**Conclusion/Summary** 

```
Regulation (EC) No. 1272/2008
```

### [CLP]

### 12.6 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** 

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

### **SECTION 13: Disposal considerations**

13.1 Waste treatment meth	ods
Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

### SECTION 14. Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

: Not relevant/applicable due to nature of the product.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

#### 14.7 Maritime transport in bulk according to IMO instruments

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed.

### Substances of very high concern

None of the components are listed.

### Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name		%	Designation [Usage]			
TEKNOCOMBI 2917-62 2-(2-butoxyethoxy)ethanol		≥90 ≤3	3 55 [Consumer paint]			
Labelling	: For profession	onal users on	iy.			
Other EU regulations						
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed					
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed					
Explosive precursors	: Not applicab	le.				
Ozone depleting substance	<u>es (EU 2024/590</u>	<u>0)</u>				
Not listed.						
Prior Informed Consent (PI	<u>C) (649/2012/E</u>	<u>U)</u>				
Not listed.						
te of issue/Date of revision	: 10/07/2025	Date of previo	us issue : No previous validation	Version	:1	17/20
EKNOCOMBI 2917-62 - All va	riants			Label No	:12233	33

### **SECTION 15: Regulatory information**

#### Persistent Organic Pollutants Not listed.

### **Seveso Directive**

This product is not controlled under the Seveso Directive.

### International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals Not listed.

### Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC) Not listed.

### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

# **15.2 Chemical safety**<br/>assessment: This product contains substances for which Chemical Safety Assessments are still<br/>required.

# SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
	1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification	
Aquatic Chronic 3, H412	Calculation method	

### Full text of abbreviated H statements

ed exposure.

18/20

## **SECTION 16: Other information**

### Full text of classifications [CLP/GHS]

I un text of classificati	
Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
Date of issue/ Date of	: 10/07/2025
revision	
Date of previous issue	No previous validation
Version	: 1

#### Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision: 1TEKNOCOMBI 2917-62 - All variants

: 10/07/2025 Date of previous issue