

SAFETY DATA SHEET



TEKNOCRYL AQUA 2781-20 - All variants

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : TEKNOCRYL AQUA 2781-20 - All variants

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS : Prod-safe@teknos.com

National contact

Teknos (UK) Limited, 7 Longlands Rd, Bicester, Oxfordshire OX26 5AH, United Kingdom. Tel. +44 (0) 1869 208005.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : NHS: 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to UK CLP/GHS

Skin Sens. 1, H317

Aquatic Chronic 3, H412

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 - May cause an allergic skin reaction.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : P280 - Wear protective gloves.
P273 - Avoid release to the environment.
P261 - Avoid breathing vapour.

Response : P302 + P352 - IF ON SKIN: Wash with plenty of water.
P362 + P364 - Take off contaminated clothing and wash it before reuse.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

SECTION 2: Hazards identification

Supplemental label elements :

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Type
Ammonia, anhydrous	EC: 231-635-3 CAS: 7664-41-7 Index: 007-001-00-5	<1	Flam. Gas 2, H221 Press. Gas (Comp.), H280 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1)	[1] [2]
Dipropyleneglycolmethylether	REACH #: 01-2119450011-60 EC: 252-104-2 CAS: 34590-94-8	≤1	Not classified.	[2]
3-iodo-2-propynyl-butyl carbamate	EC: 259-627-5 CAS: 55406-53-6 Index: 616-212-00-7	≤0.22	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)	[1]
Kaolin	EC: 310-194-1 CAS: 1332-58-7	≤0.1	Not classified.	[2]
2-(2-butoxyethoxy)ethanol	REACH #: 01-2119475104-44 EC: 203-961-6 CAS: 112-34-5 Index: 603-096-00-8	≤0.1	Eye Irrit. 2, H319	[1] [2]
4,5-dichloro-2-octyl-2H-isothiazol-3-one	EC: 264-843-8 CAS: 64359-81-5 Index: 613-335-00-8	≤0.022	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071	[1]
Ammonia	REACH #: 01-2119488876-14 EC: 215-647-6	<0.1	Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1] [2]

Date of issue/Date of revision : 20/05/2025 Date of previous issue : 17/11/2022 Version : 2 2/23

TEKNOCRYL AQUA 2781-20 - All variants

Label No : 18834

SECTION 3: Composition/information on ingredients

2-Ethoxyethanol	CAS: 1336-21-6 Index: 007-001-01-2 EC: 203-804-1 CAS: 110-80-5 Index: 603-012-00-X	<0.1	Aquatic Acute 1, H400 (M=1) Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 3, H331 Repr. 1B, H360FD	[1] [2] [3]
2-aminoethanol	EC: 205-483-3 CAS: 141-43-5 Index: 603-030-00-8	≤0.1	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1] [2]
2,6-di-tert-butyl-p-cresol	EC: 204-881-4 CAS: 128-37-0	<0.1	Aquatic Chronic 1, H410 (M=1)	[1] [2]
Dibutyltindilaurate	REACH #: 01-2119496068-27 EC: 201-039-8 CAS: 77-58-7	<0.1	Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Repr. 1B, H360 STOT SE 1, H370 STOT RE 1, H372 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1) See Section 16 for the full text of the H statements declared above.	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance with carcinogenic, mutagenic or reproductive toxicity properties

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get

SECTION 4: First aid measures

medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides

5.3 Advice for firefighters



- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

SECTION 6: Accidental release measures

- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- 6.2 Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
- 6.3 Methods and material for containment and cleaning up**
- Small spill** :  Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** :  Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.


SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

 Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Ammonia, anhydrous

EH40/2005 WELs (United Kingdom (UK), 1/2020) [ammonia]

STEL 15 minutes: 25 mg/m³. Form: anhydrous.

STEL 15 minutes: 35 ppm. Form: anhydrous.

TWA 8 hours: 25 ppm. Form: anhydrous.

TWA 8 hours: 18 mg/m³. Form: anhydrous.

Dipropyleneglycolmethylether

EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin.

TWA 8 hours: 308 mg/m³.

TWA 8 hours: 50 ppm.

Kaolin

EH40/2005 WELs (United Kingdom (UK), 1/2020)

TWA 8 hours: 2 mg/m³. Form: respirable dust.

2-(2-butoxyethoxy)ethanol

EH40/2005 WELs (United Kingdom (UK), 1/2020)

TWA 8 hours: 10 ppm.

TWA 8 hours: 67.5 mg/m³.

STEL 15 minutes: 15 ppm.

STEL 15 minutes: 101.2 mg/m³.

Ammonia

EH40/2005 WELs (United Kingdom (UK), 1/2020) [ammonia]

STEL 15 minutes: 25 mg/m³. Form: anhydrous.

STEL 15 minutes: 35 ppm. Form: anhydrous.

TWA 8 hours: 25 ppm. Form: anhydrous.

TWA 8 hours: 18 mg/m³. Form: anhydrous.

2-Ethoxyethanol

EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin.

TWA 8 hours: 2 ppm.

TWA 8 hours: 8 mg/m³.

2-aminoethanol

EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin.

STEL 15 minutes: 7.6 mg/m³.

STEL 15 minutes: 3 ppm.

TWA 8 hours: 1 ppm.

TWA 8 hours: 2.5 mg/m³.

2,6-di-tert-butyl-p-cresol

EH40/2005 WELs (United Kingdom (UK), 1/2020)

TWA 8 hours: 10 mg/m³.

Dibutyltindilaurate

EH40/2005 WELs (United Kingdom (UK), 1/2020) [tin compounds, organic, except cyhexatin (ISO)] Absorbed through skin.

STEL 15 minutes: 0.2 mg/m³ (as Sn).

TWA 8 hours: 0.1 mg/m³ (as Sn).

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name

Ammonia, anhydrous

Result

DNEL - General population - Long term - Inhalation

2.8 mg/m³

Effects: Local

DNEL - General population - Short term - Oral

6.8 mg/kg bw/day

Effects: Systemic

SECTION 8: Exposure controls/personal protection

DNEL - General population - Long term - Oral

6.8 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Dermal

6.8 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

6.8 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Short term - Dermal

6.8 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

6.8 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Inhalation

7.2 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

14 mg/m³

Effects: Local

DNEL - General population - Short term - Inhalation

23.8 mg/m³

Effects: Systemic

DNEL - General population - Long term - Inhalation

23.8 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Inhalation

36 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

47.6 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

47.6 mg/m³

Effects: Systemic

Dipropyleneglycolmethylether

DNEL - General population - Long term - Oral

36 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

37.2 mg/m³

Effects: Systemic

DNEL - General population - Long term - Dermal

121 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

283 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

308 mg/m³

SECTION 8: Exposure controls/personal protection

3-iodo-2-propynyl-butyl carbamate

Effects: Systemic

DNEL - Workers - Long term - Inhalation

0.023 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Inhalation

0.07 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Inhalation

1.16 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

1.16 mg/m³

Effects: Local

DNEL - Workers - Long term - Dermal

2 mg/kg bw/day

Effects: Systemic

2-(2-butoxyethoxy)ethanol

DNEL - General population - Long term - Oral

6.25 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

67.5 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

101.2 mg/m³

Effects: Local

2-Ethoxyethanol

DNEL - Workers - Long term - Inhalation

83 µg/m³

Effects: Systemic

DNEL - Workers - Long term - Dermal

0.3 mg/kg bw/day

Effects: Systemic

2-aminoethanol

DNEL - General population - Long term - Inhalation

0.18 mg/m³

Effects: Systemic

DNEL - General population - Long term - Inhalation

0.28 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

0.51 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

1 mg/m³

Effects: Systemic

DNEL - General population - Long term - Oral

1.5 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

1.5 mg/kg bw/day

Effects: Systemic

SECTION 8: Exposure controls/personal protection

2,6-di-tert-butyl-p-cresol

DNEL - Workers - Long term - Dermal

3 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Oral

0.25 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

0.25 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

0.435 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Dermal

0.5 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

1.76 mg/m³

Effects: Systemic

Dibutyltindilaurate

DNEL - General population - Long term - Oral

0.0031 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

0.0046 mg/m³

Effects: Systemic

DNEL - General population - Short term - Oral

0.02 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

0.02 mg/m³

Effects: Systemic

DNEL - General population - Short term - Inhalation

0.04 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Inhalation

0.059 mg/m³

Effects: Systemic

DNEL - General population - Long term - Dermal

0.16 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

0.43 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Dermal

0.5 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Short term - Dermal

2.08 mg/kg bw/day

Effects: Systemic

PNECs

Date of issue/**Date of revision**

: 20/05/2025

Date of previous issue

: 17/11/2022

Version : 2

9/23

TEKNOCRYL AQUA 2781-20 - All variants

Label No : 18834

SECTION 8: Exposure controls/personal protection

Not available.

8.2 Exposure controls

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations : Wear suitable gloves tested to EN374.

> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm

Not recommended polyvinyl alcohol (PVA) gloves

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type (spray application): A P

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.

Colour : Various

Odour : Slight

Odour threshold : Not available.

Melting point/freezing point : Not available.

SECTION 9: Physical and chemical properties

Initial boiling point and boiling range :

Ingredient name	°C	°F	Method
Water	100	212	
Ethyldiglycol	196	384.8	

Flammability (solid, gas) : Not available.

Upper/lower flammability or explosive limits : Lower: 1.2% (2-(2-ethoxyethoxy)ethanol)
Upper: 23.5% (2-(2-ethoxyethoxy)ethanol)

Flash point : Closed cup: >100°C (>212°F)

Auto-ignition temperature :

Ingredient name	°C	°F	Method
Ethyldiglycol	204	399.2	

Decomposition temperature : Not available.

pH : 8 to 9.2 [Conc. (% w/w): 100%]

Viscosity : Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C): Not available.

Solubility(ies) :
Not available.

Solubility in water : Not available.

Partition coefficient: n-octanol/ water : Not applicable.

Vapour pressure :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Water	17.5	2.3				
Ethyldiglycol	0.14	0.019				

Relative density : Not available.

Density : 1.1 g/cm³

Vapour density : Not available.

Explosive properties : Not available.

Oxidising properties : Not available.

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

Not available.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

SECTION 10: Stability and reactivity

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name

Ammonia, anhydrous

Result

Rat - Inhalation - LC50 Gas.

2000 ppm [4 hours]

Rat - Inhalation - LC50 Gas.

9500 ppm [1 hours]

Rat - Inhalation - LC50 Vapour

4673 mg/m³ [4 hours]

3-iodo-2-propynyl-butyl carbamate

Rat - Oral - LD50

400 mg/kg

Rat - Dermal - LD50

>2000 mg/kg

Rat - Inhalation - LC50 Dusts and mists

0.763 mg/l [4 hours]

Rat - Inhalation - LC50 Dusts and mists

0.67 g/m³ [4 hours]

2-(2-butoxyethoxy)ethanol

Rabbit - Dermal - LD50

2700 mg/kg

Rat - Oral - LD50

4500 mg/kg

Toxic effects: Behavioral - Tetany Lung, Thorax, or Respiration
- Dyspnea Liver - Other changes

4,5-dichloro-2-octyl-2H-isothiazol-3-one

Rat - Oral - LD50

1585 mg/kg

OECD [Acute Oral Toxicity]

Rabbit - Dermal - LD50

>652 mg/kg

OECD [Acute Dermal Toxicity]

Rat - Male, Female - Inhalation - LC50 Dusts and mists

0.26 mg/l [4 hours]

OECD [Acute Inhalation Toxicity]

Ammonia

Rat - Oral - LD50

350 mg/kg

Toxic effects: Gastrointestinal - Other changes Liver - Other changes Kidney, Ureter, and Bladder - Other changes

2-Ethoxyethanol

Rat - Oral - LD50

2125 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity) Behavioral - Withdrawal Lung, Thorax, or Respiration - Respiratory depression

Rat - Dermal - LD50

3900 mg/kg

Rabbit - Dermal - LD50

3.6 g/kg

SECTION 11: Toxicological information

2-aminoethanol	Rat - Oral - LD50 1720 mg/kg
2,6-di-tert-butyl-p-cresol	Rat - Oral - LD50 890 mg/kg
Dibutyltindilaurate	Rat - Oral - LD50 175 mg/kg

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
TEKNOCRYL AQUA 2781-20	N/A	N/A	357099.7	834.4	343.0
ammonia, anhydrous	N/A	N/A	2000	4.673	N/A
3-iodo-2-propynyl-butyl carbamate	400	N/A	N/A	N/A	0.67
2-(2-butoxyethoxy)ethanol	4500	2700	N/A	N/A	N/A
4,5-dichloro-2-octyl-2H-isothiazol-3-one	567	N/A	N/A	N/A	0.16
2-Ethoxyethanol	500	3600	N/A	3	N/A
2-aminoethanol	1720	1100	N/A	11	N/A

Skin corrosion/irritation

Product/ingredient name

Diipropyleneglycolmethylether

Result

Rabbit - Skin - Mild irritant

Amount/concentration applied: 500 mg

2-Ethoxyethanol

Rabbit - Skin - Mild irritant

Amount/concentration applied: 500 mg

2-aminoethanol

Rabbit - Skin - Moderate irritant

Amount/concentration applied: 505 mg

2,6-di-tert-butyl-p-cresol

Human - Skin - Mild irritant

Duration of treatment/exposure: 48 hours

Amount/concentration applied: 500 mg

Rabbit - Skin - Moderate irritant

Duration of treatment/exposure: 48 hours

Amount/concentration applied: 500 mg

Dibutyltindilaurate

Rabbit - Skin - Severe irritant

Amount/concentration applied: 500 mg

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Product/ingredient name

Diipropyleneglycolmethylether

Result

Human - Eyes - Mild irritant

Amount/concentration applied: 8 mg

Rabbit - Eyes - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

3-iodo-2-propynyl-butyl carbamate

Rabbit - Eyes - Severe irritant

2-(2-butoxyethoxy)ethanol

Rabbit - Eyes - Moderate irritant

Duration of treatment/exposure: 24 hours

SECTION 11: Toxicological information

Ammonia	<u>Amount/concentration applied</u> : 20 mg
	Rabbit - Eyes - Severe irritant <u>Amount/concentration applied</u> : 20 mg
	Rabbit - Eyes - Severe irritant <u>Amount/concentration applied</u> : 250 ug
	Rabbit - Eyes - Severe irritant <u>Amount/concentration applied</u> : 44 ug
2-Ethoxyethanol	Rabbit - Eyes - Severe irritant <u>Duration of treatment/exposure</u> : 0.5 minutes <u>Amount/concentration applied</u> : 1 mg
	Guinea pig - Eyes - Mild irritant <u>Amount/concentration applied</u> : 10 ug
	Rabbit - Eyes - Mild irritant <u>Duration of treatment/exposure</u> : 24 hours <u>Amount/concentration applied</u> : 500 mg
	Rabbit - Eyes - Moderate irritant <u>Amount/concentration applied</u> : 50 mg
2-aminoethanol	Rabbit - Eyes - Severe irritant <u>Amount/concentration applied</u> : 250 ug
2,6-di-tert-butyl-p-cresol	Rabbit - Eyes - Moderate irritant <u>Duration of treatment/exposure</u> : 24 hours <u>Amount/concentration applied</u> : 100 mg
Dibutyltindilaurate	Rabbit - Eyes - Moderate irritant <u>Duration of treatment/exposure</u> : 24 hours <u>Amount/concentration applied</u> : 100 mg

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Product/ingredient name

3-iodo-2-propynyl-butyl carbamate

Result

Guinea pig - skin

Result: Not sensitizing

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Product/ingredient name

3-iodo-2-propynyl-butyl carbamate

Result

In vitro - Bacteria

Result: Negative

Conclusion/Summary [Product] : Not available.

SECTION 11: Toxicological information

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Product/ingredient name

3-iodo-2-propynyl-butyl carbamate

Result

Rabbit - Female - Oral

50 mg/kg [7 days per week] [13 days]

Maternal toxicity: Positive

Developmental: Negative

Rabbit - Female - Oral

20 mg/kg [7 days per week] [13 days]

Maternal toxicity: Negative

Developmental: Negative

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name

Ammonia

2-aminoethanol

Dibutyltindilaurate

Result

STOT SE 3, H335 (Respiratory tract irritation)

STOT SE 3, H335 (Respiratory tract irritation)

STOT SE 1, H370

Specific target organ toxicity (repeated exposure)

Product/ingredient name

3-iodo-2-propynyl-butyl carbamate

Dibutyltindilaurate

Result

STOT RE 1, H372 (larynx)

STOT RE 1, H372

Aspiration hazard

Not available.

Information on likely routes of exposure

Not available.

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
 - irritation
 - redness
- Ingestion** : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

SECTION 11: Toxicological information

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name

Ammonia, anhydrous

Result

Acute - LC50 - Fresh water

Fish - Carp - *Hypophthalmichthys nobilis*

300 µg/l [96 hours]

Effect: Mortality

Acute - LC50 - Fresh water

Daphnia - Water flea - *Daphnia magna*

0.53 ppm [48 hours]

Effect: Mortality

Acute - EC50 - Marine water

Algae - Sea Lettuce - *Ulva fasciata* - Zoea

29.2 mg/l [96 hours]

Effect: Reproduction

Chronic - NOEC - Marine water

Fish - Sea bass - *Dicentrarchus labrax*

Weight: 131.3 g

0.204 mg/l [62 days]

Effect: Biochemistry

3-iodo-2-propynyl-butyl carbamate

Acute - LC50 - Fresh water

EU

Fish - Trout - *Oncorhynchus mykiss*

0.067 mg/l [96 hours]

Acute - NOEC - Fresh water

EU

Fish - Trout - *Oncorhynchus mykiss*

0.049 mg/l [96 hours]

Acute - EC50 - Fresh water

EU

Daphnia - Daphnia - *Daphnia magna*

0.16 mg/l [48 hours]

Chronic - NOEC - Fresh water

EU

SECTION 12: Ecological information

Daphnia - Daphnia - *Daphnia Magna*
0.05 mg/l [21 days]

Acute - EC50 - Fresh water

EU

Algae - Algae - *Scenedemus subspicatus*
0.022 mg/l [72 hours]

2-(2-butoxyethoxy)ethanol

Acute - LC50 - Fresh water

Fish - Bluegill - *Lepomis macrochirus*

Size: 33 to 75 mm

1300000 µg/l [96 hours]

Effect: Mortality

4,5-dichloro-2-octyl-2H-isothiazol-3-one

Acute - EC50 - Fresh water

Algae - Green algae - *Pseudokirchneriella subcapitata*
0.003 mg/l [72 hours]

Effect: Population

Acute - EC50 - Fresh water

Daphnia - Water flea - *Daphnia magna*

0.001 mg/l [48 hours]

Effect: Intoxication

Acute - LC50 - Fresh water

US EPA

Fish - Rainbow trout,donaldson trout - *Oncorhynchus mykiss*

Weight: 1.2 g

2.7 ppb [96 hours]

Effect: Mortality

Chronic - NOEC

US EPA

Fish - Rainbow trout,donaldson trout - *Oncorhynchus mykiss*

0.56 ppb [97 days]

Effect: Growth

Chronic - NOEC - Marine water

OECD

Algae - Diatom - *Nitzschia pungens*

19.789 µg/l [96 hours]

Effect: Population

Ammonia

Acute - LC50 - Fresh water

Fish - Western mosquitofish - *Gambusia affinis* - Adult

37 ppm [96 hours]

Effect: Mortality

2-Ethoxyethanol

Acute - LC50 - Fresh water

Fish - Bluegill - *Lepomis macrochirus*

Size: 33 to 75 mm

>10000000 µg/l [96 hours]

Effect: Mortality

2-aminoethanol

Acute - LC50 - Marine water

Crustaceans - Common shrimp, sand shrimp - *Crangon crangon* - Adult

>100000 µg/l [48 hours]

Effect: Mortality

Acute - EC50 - Fresh water

ISO

Algae - Green algae - *Desmodesmus subspicatus*

8.42 mg/l [72 hours]

Effect: Population

SECTION 12: Ecological information

Acute - LC50 - Fresh water

Fish - Goldfish - *Carassius auratus*

Size: 6.2 cm; Weight: 3.3 g

170 mg/l [96 hours]

Effect: Mortality

2,6-di-tert-butyl-p-cresol

Acute - EC50 - Fresh water

Daphnia - Water flea - *Daphnia pulex* - Neonate

Age: <24 hours

1440 µg/l [48 hours]

Effect: Intoxication

Dibutyltindilaurate

Chronic - EC10 - Fresh water

Algae - Green algae - *Scenedesmus subspicatus*

>2 mg/l [96 hours]

Effect: Histology

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Not available.

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
3-iodo-2-propynyl-butyl carbamate	-	-	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Dipropyleneglycolmethylether	0.004	-	Low
3-iodo-2-propynyl-butyl carbamate	>1	-	Low
2-(2-butoxyethoxy)ethanol	1	-	Low
2-Ethoxyethanol	-0.32	-	Low
2-aminoethanol	-1.31	-	Low
2,6-di-tert-butyl-p-cresol	5.1	330 to 1800	High
Dibutyltindilaurate	4.44	2.91	Low

12.4 Mobility in soil

Soil/water partition coefficient : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

SECTION 12: Ecological information

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Ammonia, anhydrous	No	No	No	No	No	No	No
Dipropyleneglycolmethylether	No	No	No	No	No	No	No
3-iodo-2-propynyl-butyl carbamate	No	No	No	Yes	No	No	No
Kaolin	No	No	No	No	No	No	No
2-(2-butoxyethoxy)ethanol	No	No	No	No	No	No	No
4,5-dichloro-2-octyl-2H-isothiazol-3-one	No	No	No	Yes	No	No	No
Ammonia	No	No	No	No	No	No	No
2-Ethoxyethanol	No	No	No	Yes	No	No	No
2-aminoethanol	No	No	No	No	No	No	No
2,6-di-tert-butyl-p-cresol	No	No	No	No	No	No	No
Dibutyltindilaurate	No	No	No	Yes	No	No	No

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

European waste catalogue (EWC) : 080111*, 200127*

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

SECTION 14: Transport information

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information


15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
UK (GB)/REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

Intrinsic property	Ingredient name	Status	Reference number	Date of revision
 Toxic to reproduction	2-ethoxyethanol	Candidate	-	12/15/2010

Ozone depleting substances

Not listed.


Prior Informed Consent (PIC)

Not listed.

Persistent Organic Pollutants

Not listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
 EKNOCRYL AQUA 2781-20 2-(2-butoxyethoxy)ethanol	≥90 ≤0.1	3 55 [Consumer paint]

Seveso Directive

This product is not controlled under the Seveso Directive.

EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

SECTION 15: Regulatory information

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate
GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = GB CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

Classification	Justification
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

H221	Flammable gas.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H360	May damage fertility or the unborn child.
H360FD	May damage fertility. May damage the unborn child.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Gas 2	FLAMMABLE GASES - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Muta. 2	GERM CELL MUTAGENICITY - Category 2

Date of issue/Date of revision

: 20/05/2025

Date of previous issue

: 17/11/2022

Version : 2

21/23

TEKNOCRYL AQUA 2781-20 - All variants

Label No : 18834

SECTION 16: Other information

Press. Gas (Comp.)	GASES UNDER PRESSURE - Compressed gas
Repr. 1B	REPRODUCTIVE TOXICITY - Category 1B
Skin Corr. 1	SKIN CORROSION/IRRITATION - Category 1
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT SE 1	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 1
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of issue/ Date of revision : 20/05/2025

Date of previous issue : 17/11/2022

Version : 2

TEKNOCRYL AQUA 2781-20

All variants

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

