Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Ireland

SAFETY DATA SHEET



TEKNOCRYL AQUA COMBI 2780-70 - All variants

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name : TEKNOCRYL AQUA COMBI 2780-70 - All variants

1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use: Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091. e-mail address of person : Prod-safe@teknos.com responsible for this SDS

National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : National Poisons Information Centre: 01 809 2566

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture <u>Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]</u> Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements		
Signal word	No signal word.	
Hazard statements	No known significant effects or critical hazards.	
Precautionary statements		
Prevention	Not applicable.	
Response	Not applicable.	
Storage	Not applicable.	
Disposal	Not applicable.	
Supplemental label elements	Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Safety data sheet available on request. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains biocidal products for in-can preservation: BIT and DTBMA and MBIT.	ł
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles		

2.3 Other hazards

 Date of issue/Date of revision
 : 31/08/2023
 Date of previous issue

 TEKNOCRYL AQUA COMBI 2780-70 - All variants

SECTION 2: Hazards identification

Product meets the criteria : for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do : None known. not result in classification

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
i fanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≤5	Carc. 2, H351 (inhalation)	-	[1] [*]
2-Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	≤5	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	ATE [Oral] = 1200 mg/kg ATE [Inhalation (vapours)] = 3 mg/l	[1] [2]
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 1020 mg/kg Skin Sens. 1, H317: C ≥ 0.05% M [Acute] = 1	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Туре</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter \leq 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures				
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.			
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.			
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. 			
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.			
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.			

Date of issue/Date of revision	: 31/08/2023	Date of previous issue	: 27/09/2022	Version : 2	2/13
TEKNOCRYL AQUA COMBI 2780)-70 - All vari	ants		Label No :3895	52

SECTION 4: First aid measures

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
	•

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides
5.3 Advice for firefighters	
Special protective actions	: Promptly isolate the scene by removing all persons from the vicinity of the incident if

for fire-fighters	there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection to chemical incidents.	for

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	ote	ective equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

SECTION 6: Accidental release measures

Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

 Dut on appropriat 	o porconal protoctive	o autinmont (c	an Saction 8)
: Put on appropriat	e personal protective	equipinent (S	

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

Recommendations

: Not available.

Industrial sector specific solutions

: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
2-Butoxyethanol	NAOSH (Ireland, 5/2021). Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values
	OELV-8hr: 20 ppm 8 hours. OELV-8hr: 98 mg/m ³ 8 hours. OELV-15min: 50 ppm 15 minutes. OELV-15min: 246 mg/m ³ 15 minutes.

Biological exposure indices

Product/ingredient name	Exposure indices
₽ Butoxyethanol	NAOSH (Ireland, 1/2011) BMGV: 200 mg/g creatinine, BAA [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases.

Date of issue/Date of revision	: 31/08/2023	Date of previous issue	: 27/09/2022	Version	:2	4/13
TEKNOCRYL AQUA COMBI 2780-	-70 - All varia	ints		Label No	:38952	2

SECTION 8: Exposure controls/personal protection

procedures

Recommended monitoring : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
2-Butoxyethanol	DNEL	Long term Oral	6.3 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	26.7 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	59 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	98 mg/m³	Workers	Systemic
	DNEL	Short term Inhalation	147 mg/m³	General population	Local
	DNEL	Short term Inhalation	246 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	426 mg/m ³	General population	Systemic
	DNEL	Short term Inhalation	1091 mg/ m³	Workers	Systemic
1,2-benzisothiazol-3(2H)-one	DNEL	Long term Dermal	0.345 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.966 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.2 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	6.81 mg/m ³		Systemic

PNECs

No PNECs available

8.2 Exposure controls	
Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection meas	<u>ures</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	 Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Recommendations : Wear suitable gloves tested to EN374. > 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm

Date of issue/Date of revision	: 31/08/2023	Date of previous issue	: 27/09/2022	Version	:2	5/13
TEKNOCRYL AQUA COMBI 2780	-70 - All varia	ants		Label No :	3895	2

SECTION 8: Exposure controls/personal protection

	Not recommended polyvinyl alcohol (PVA) gloves
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
	Filter type (spray application): A P
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance	
Physical state	: Liquid.
Colour	: Various
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	:

Ingredient name	°C	°F	Method
water	100	212	
2-Butoxyethanol	171 to 171.5	339.8 to 340.7	IP 123-93

Flammability	: Not available.
Lower and upper explosion limit	: Lower: Not applicable. Upper: Not applicable.
Flash point	: Closed cup: >100°C (>212°F)
Auto-ignition temperature	:

Auto-ignition temperature

Ingredient name	°C	°F	Method
2-Butoxyethanol	230	446	DIN 51794
29H, 31H-PHTHALOCYANINATO(2-)-N29,N30,N31, N32 COPPER (PIGMENT BLUE 15:3)	356	672.8	EU A.16

Decomposition temperature	:	Not available.
рН	:	8.7 to 9.3
Viscosity	:	Not available.
Solubility(ies)	:	
Not available.		
Solubility in water	:	Not available.
Partition coefficient: n-octanol/ water	:	Not applicable.
Vapour pressure	;	

	Va	Vapour Pressure at 20°C		Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
water	17.5	2.3				
2-Butoxyethanol	0.75006	0.1				
elative density	: Not	available.				•
ensity	: 1.2	g/cm³				
apour density	: Not	available.				
xplosive properties	: Not	available.				
xidising properties	: Not	available.				
article characteristics						
Median particle size	: Not	applicable.				

SECTION 10: Stability and reactivity			
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.		
10.2 Chemical stability	: The product is stable.		
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.		
10.4 Conditions to avoid	: No specific data.		
10.5 Incompatible materials	: No specific data.		
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.		

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
√,2-benzisothiazol-3(2H)- one	LD50 Oral	Rat	1020 mg/kg	-
Conclusion/Summary : Based on available data, the classification criteria are not met.				

Acute toxicity estimates

Route	ATE value	
	34192.84 mg/kg 85.48 mg/l	

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
inanium dioxide	Skin - Mild irritant	Human	-	72 hours 300 ug l	-
2-Butoxyethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100	-
	Eyes - Severe irritant	Rabbit	-	mg 100 mg	-
1,2-benzisothiazol-3(2H)-one	Skin - Mild irritant Skin - Mild irritant	Rabbit Human	-	500 mg 48 hours 5 %	-
Conclusion/Summary	: Based on available data, the	he classification o	riteria are	not met.	
<u>Sensitisation</u>					
Conclusion/Summary	: Based on available data, the	he classification of	riteria are	e not met.	
ate of issue/Date of revision	: 31/08/2023 Date of previou	is issue : 27	/09/2022	Versi	ion : 2 7/13

SECTION 11: Toxicological information

Mutagenicity

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

Conclusion/Summary	1	Based on available data, the classification criteria are not met.
Reproductive toxicity		
Conclusion/Summary	:	Based on available data, the classification criteria are not met.
Teratogenicity		
Conclusion/Summary	:	Based on available data, the classification criteria are not met.
Specific target organ toxicit	V	(single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes : Not available. of exposure

Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

: Not available.
: Not available.
: Not available.
: Not available.
ects
: Not available.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.

11.2 Information on other hazards

SECTION 11: Toxicological information

11.2.1 Endocrine disrupting properties Not available. **11.2.2 Other information**

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - <i>Daphnia pulex -</i> Neonate	48 hours
	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours
2-Butoxyethanol	Acute EC50 >1000 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 800000 µg/l Marine water	Crustaceans - Crangon crangon	48 hours
	Acute LC50 1250000 µg/l Marine water	Fish - Menidia beryllina	96 hours
1,2-benzisothiazol-3(2H)-one	Acute EC50 0.36 mg/l Marine water	Algae - Skeletonema Costatum	72 hours
	Acute EC50 3.7 mg/l	Daphnia - Daphnia Magna	48 hours
	Acute LC50 1.9 mg/l Fresh water	Fish - Onorhynchus Mykiss	96 hours
	Acute NOEC 0.15 mg/l Marine water	Algae - Skeletonema Costatum	72 hours

Conclusion/Summary : Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

Product/ingredient name	Test	Result		Dose	Inoculum
7,2-benzisothiazol-3(2H)-one	EU	24 % - 28 days		-	-
Conclusion/Summary : This product has not been tested for biodegradation.					
Product/ingredient name	Aquatic half-life		Photolysis	5	Biodegradability
2-benzisothiazol-3(2H)-one	-		-		Inherent

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
P-Butoxyethanol1,2-benzisothiazol-3(2H)-one	0.81	-	Low
	-	3.2	Low

12.4 Mobility in soil Soil/water partition coefficient (Koc) Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment meth	ods
Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	 Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.
European waste catalogue (EWC)	: 080112, 200128
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
SECTION 14: Trans	sport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in : Not relevant/applicable due to nature of the product. bulk according to IMO instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

_

SECTION 15: Regulatory information
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous
substances, mixtures and articles
Labelling :
Other EU regulations
Industrial emissions : Not listed (integrated pollution prevention and control) - Air
Industrial emissions : Not listed (integrated pollution prevention and control) - Water
Explosive precursors : Not applicable.
Ozone depleting substances (1005/2009/EU)
Not listed.
Prior Informed Consent (PIC) (649/2012/EU) Not listed.
Persistent Organic Pollutants Not listed.
Seveso Directive This product is not controlled under the Seveso Directive. International regulations Chemical Weapon Convention List Schedules I, II & III Chemicals Not listed.
Montreal Protocol Not listed.
Stockholm Convention on Persistent Organic Pollutants Not listed.
Rotterdam Convention on Prior Informed Consent (PIC) Not listed.
UNECE Aarhus Protocol on POPs and Heavy Metals Not listed.
15.2 Chemical safety assessment : This product contains substances for which Chemical Safety Assessments are still required.
SECTION 16: Other information
Indicates information that has changed from previously issued version.

Indicates informatio	n that has changed from previously issued version.
Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative
Procedure used to del	<u>ive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]</u>

Not classified.

Date of issue/Date of revision	: 31/08/2023	Date of previous issue	: 27/09/2022	Version	:2	11/13
TEKNOCRYL AQUA COMBI 2780	-70 - All varia	ants		Label No	3895	2

	6: Other information	
Full text of abbr	eviated H statements	
H302	Harmful if swallowed.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H331	Toxic if inhaled.	
H351	Suspected of causing cancer.	
H400 Very toxic to aquatic life.		
Full text of class	sifications [CLP/GHS]	
Acute Tox. 3	ACUTE TOXICITY - Category 3	
Acute Tox. 4	ACUTE TOXICITY - Category 4	
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1	
Carc. 2	CARCINOGENICITY - Category 2	
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1	
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2	
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2	
Skin Sens. 1	SKIN SENSITISATION - Category 1	
Date of issue/ Date of issue/ Date of issue/ Date of issue	ate of : 31/08/2023	
Date of previous	sissue : 27/09/2022	
-		

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision: 31/08/2023Date of previous issueTEKNOCRYL AQUA COMBI 2780-70 - All variants

: 27/09/2022