

# SAFETY DATA SHEET



TEKNOCRYL AQUA COMBI 2780-82 - All variants

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : TEKNOCRYL AQUA COMBI 2780-82 - All variants

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Paint.

### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

**e-mail address of person responsible for this SDS** : Prod-safe@teknos.com

#### National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

**Telephone number** : In an emergency, call 112

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Signal word** : No signal word.

**Hazard statements** : No known significant effects or critical hazards.

#### Precautionary statements

**Prevention** : Not applicable.

**Response** : Not applicable.

**Storage** : Not applicable.

**Disposal** : Not applicable.

**Supplemental label elements** : ☒ Contains neodecanoic acid, cobalt salt and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.  
Safety data sheet available on request.  
Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains biocidal products for in-can preservation: BIT and 2,2'-dithiobis[N-methylbenzamide] and MBIT.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** :

## SECTION 2: Hazards identification

### 2.3 Other hazards

**Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification** : None known.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥10 - ≤25	Carc. 2, H351 (inhalation)	-	[1] [*]
2-Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	≤5	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	ATE [Oral] = 1200 mg/kg ATE [Inhalation (vapours)] = 3 mg/l	[1] [2]
neodecanoic acid, cobalt salt	REACH #: 01-2119970733-31 EC: 248-373-0 CAS: 27253-31-2	≤0.3	Acute Tox. 4, H302 Skin Sens. 1, H317 STOT RE 1, H372 Aquatic Chronic 3, H412	ATE [Oral] = 500 mg/kg	[1]
propylidynetrimethanol	REACH #: 01-2119486799-10 EC: 201-074-9 CAS: 77-99-6	≤0.3	Repr. 2, H361fd	-	[1]
1,2-benzisothiazol-3(2H)-one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.036	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410  <b>See Section 16 for the full text of the H statements declared above.</b>	ATE [Oral] = 450 mg/kg ATE [Inhalation (dusts and mists)] = 0.21 mg/l Skin Sens. 1, H317: C ≥ 0.036% M [Acute] = 1 M [Chronic] = 1	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[\*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter ≤ 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
- Ingestion** : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
metal oxide/oxides

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and material for containment and cleaning up

- Small spill** :  Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** :  Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contain and collect spillage with non-combustible, absorbent material e. g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

### 6.4 Reference to other sections

- : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8).
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

-  Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
2-Butoxyethanol	<p><b>Regulation on Limit Values - MAC (Austria, 4/2021)</b> Absorbed through skin.  TWA 8 hours: 20 ppm.  TWA 8 hours: 98 mg/m<sup>3</sup>.  PEAK 30 minutes: 40 ppm 4 times per shift.  PEAK 30 minutes: 200 mg/m<sup>3</sup> 4 times per shift.</p>
neodecanoic acid, cobalt salt	<p><b>Regulation on Limit Values - Technical Guidance Values (Austria, 4/2021) [Cobalt und seine Verbindungen (Cobalt als Cobaltmetall, Cobaltoxid und Cobaltsulfid, Staub von Cobaltlegierungen), im übrigen.]</b> Absorbed through skin , Inhalation sensitiser , Skin sensitiser.  TWA 8 hours: 0.1 mg/m<sup>3</sup> (measured as Co). Form: Inhalable fraction.  PEAK 15 minutes: 0.4 mg/m<sup>3</sup> (measured as Co), 4 times per shift. Form: Inhalable fraction.</p> <p><b>Regulation on Limit Values - Technical Guidance Values (Austria, 4/2021) [Cobalt und seine Verbindungen (Cobalt als Cobaltmetall, Cobaltoxid und Cobaltsulfid, Staub von Cobaltlegierungen). Herstellung von Cobaltpulver und Katalysatoren, Hartmetall- und Magnetherstellung.]</b> Absorbed through skin , Inhalation sensitiser , Skin sensitiser.  TWA 8 hours: 0.5 mg/m<sup>3</sup> (measured as Co). Form: Inhalable fraction.  PEAK 15 minutes: 2 mg/m<sup>3</sup> (measured as Co), 4 times per shift. Form: Inhalable fraction.</p> <p><b>Regulation on Limit Values - MAC (Austria, 4/2021) [Cobalt und seine Verbindungen (Cobalt als Cobaltmetall, Cobaltoxid, Cobaltsulfid und Cobaltsulfat, Staub von Cobaltlegierungen)]</b> Carc A2.</p>
2-Butoxyethanol	<p><b>Limit values (Belgium, 12/2023)</b> Absorbed through skin.  TWA 8 hours: 20 ppm.  TWA 8 hours: 98 mg/m<sup>3</sup>.  STEL 15 minutes: 50 ppm.  STEL 15 minutes: 246 mg/m<sup>3</sup>.</p>
2-Butoxyethanol	<p><b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024)</b> Absorbed through skin.  Limit value 8 hours: 98 mg/m<sup>3</sup>.  Limit value 15 minutes: 246 mg/m<sup>3</sup>.  Limit value 15 minutes: 50 ppm.  Limit value 8 hours: 20 ppm.</p>
neodecanoic acid, cobalt salt	<p><b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024) [Cobalt and inorganic compounds]</b>  Limit value 8 hours: 0.1 mg/m<sup>3</sup> (as cobalt).</p>
propylidynetrimethanol	<p><b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024)</b>  Limit value 8 hours: 50 mg/m<sup>3</sup>.</p>

## SECTION 8: Exposure controls/personal protection

2-Butoxyethanol	<p><b>Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023)</b> Absorbed through skin.</p> <p>STELV 15 minutes: 246 mg/m<sup>3</sup>.</p> <p>STELV 15 minutes: 50 ppm.</p> <p>ELV 8 hours: 98 mg/m<sup>3</sup>.</p> <p>ELV 8 hours: 20 ppm.</p>
neodecanoic acid, cobalt salt	<p><b>Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023) [kobalt i spojevi]</b> Skin sensitiser , Inhalation sensitiser.</p> <p>ELV 8 hours: 0.1 mg/m<sup>3</sup> (as Co).</p>
2-Butoxyethanol	<p><b>Department of labour inspection (Cyprus, 7/2021)</b> Absorbed through skin.</p> <p>STEL 15 minutes: 50 ppm.</p> <p>STEL 15 minutes: 246 mg/m<sup>3</sup>.</p> <p>TWA 8 hours: 20 ppm.</p> <p>TWA 8 hours: 98 mg/m<sup>3</sup>.</p>
2-Butoxyethanol	<p><b>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 12/2023)</b> Absorbed through skin.</p> <p>TWA 8 hours: 98 mg/m<sup>3</sup>.</p> <p>TWA 8 hours: 20 ppm.</p> <p>STEL 15 minutes: 200 mg/m<sup>3</sup>.</p> <p>STEL 15 minutes: 40.7 ppm.</p>
neodecanoic acid, cobalt salt	<p><b>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 12/2023) [kobalt a jeho sloučeniny]</b> Carc, Repr. Sensitiser.</p> <p>TWA 8 hours: 0.05 mg/m<sup>3</sup> (as Co). Form: aerosol, inhalable fraction..</p> <p>STEL 15 minutes: 0.1 mg/m<sup>3</sup> (as Co). Form: aerosol, inhalable fraction..</p>
2-Butoxyethanol	<p><b>Working Environment Authority (Denmark, 3/2024)</b> Absorbed through skin.</p> <p>TWA 8 hours: 20 ppm.</p> <p>TWA 8 hours: 98 mg/m<sup>3</sup>.</p> <p>STEL 15 minutes: 246 mg/m<sup>3</sup>.</p> <p>STEL 15 minutes: 50 ppm.</p>
neodecanoic acid, cobalt salt	<p><b>Working Environment Authority (Denmark, 3/2024) [uorganiske kobaltforbindelser] K.</b></p> <p>TWA 8 hours: 0.01 mg/m<sup>3</sup> (calculated as Co).</p>
2-Butoxyethanol	<p><b>Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024)</b> Absorbed through skin , Sensitiser.</p> <p>TWA 8 hours: 98 mg/m<sup>3</sup>.</p> <p>TWA 8 hours: 20 ppm.</p> <p>STEL 15 minutes: 246 mg/m<sup>3</sup>.</p> <p>STEL 15 minutes: 50 ppm.</p>
neodecanoic acid, cobalt salt	<p><b>Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024) [koobalt ja anorgaanilised ühendid]</b> Sensitiser.</p> <p>TWA 8 hours: 0.05 mg/m<sup>3</sup> (calculated as Co).</p>
2-Butoxyethanol	<p><b>EU OEL (Europe, 1/2022)</b> Absorbed through skin.</p> <p>TWA 8 hours: 20 ppm.</p> <p>TWA 8 hours: 98 mg/m<sup>3</sup>.</p> <p>STEL 15 minutes: 50 ppm.</p> <p>STEL 15 minutes: 246 mg/m<sup>3</sup>.</p>
2-Butoxyethanol	<p><b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021)</b> Absorbed through skin.</p> <p>TWA 8 hours: 20 ppm.</p> <p>TWA 8 hours: 98 mg/m<sup>3</sup>.</p> <p>STEL 15 minutes: 50 ppm.</p> <p>STEL 15 minutes: 250 mg/m<sup>3</sup>.</p>
neodecanoic acid, cobalt salt	<p><b>Institute of Occupational Health, Ministry of Social Affairs</b></p>



## SECTION 8: Exposure controls/personal protection

2-Butoxyethanol

(Finland, 10/2021) [Koboltti ja sen epäorgaaniset yhdisteet]

TWA 8 hours: 0.02 mg/m<sup>3</sup> (calculated as Co).

**Ministry of Labor (France, 6/2024)** Absorbed through skin.

TWA 8 hours: 10 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)

TWA 8 hours: 49 mg/m<sup>3</sup>. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)

STEL 15 minutes: 246 mg/m<sup>3</sup>. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)

STEL 15 minutes: 50 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)

2-Butoxyethanol

**TRGS 900 OEL (Germany, 6/2024)** Absorbed through skin.

TWA 8 hours: 49 mg/m<sup>3</sup>.

PEAK 15 minutes: 98 mg/m<sup>3</sup>.

TWA 8 hours: 10 ppm.

PEAK 15 minutes: 20 ppm.

**DFG MAC-values list (Germany, 7/2023)** Develop C. Absorbed through skin.

TWA 8 hours: 10 ppm.

PEAK 15 minutes: 20 ppm 4 times per shift [Interval: 1 hour].

TWA 8 hours: 49 mg/m<sup>3</sup>.

PEAK 15 minutes: 98 mg/m<sup>3</sup> 4 times per shift [Interval: 1 hour].

neodecanoic acid, cobalt salt

**DFG MAC-values list (Germany, 7/2023) [Cobalt and cobalt compounds]** Carc 2, Muta 3A. Absorbed through skin, Inhalation sensitiser, Skin sensitiser.

**DFG MAC-values list (Germany, 7/2023)** Skin sensitiser.

1,2-benzisothiazol-3(2H)-one

2-Butoxyethanol

**Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021)** Absorbed through skin.

TWA 8 hours: 25 ppm.

TWA 8 hours: 120 mg/m<sup>3</sup>.

neodecanoic acid, cobalt salt

**Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021) [κοβαλτίου ενώσεις]**

TWA 8 hours: 0.1 mg/m<sup>3</sup> (as Co).

2-Butoxyethanol

**5/2020. (II. 6.) ITM Decree (Hungary, 12/2023)** Absorbed through skin.

TWA 8 hours: 98 mg/m<sup>3</sup>.

PEAK 15 minutes: 246 mg/m<sup>3</sup>.

PEAK 15 minutes: 50 ppm.

TWA 8 hours: 20 ppm.

neodecanoic acid, cobalt salt

**5/2020. (II. 6.) ITM Decree (Hungary, 12/2023) [KOBALT ÉS SZERVETLEN VEGYÜLETEI]** Sensitiser.

TWA 8 hours: 0.02 mg/m<sup>3</sup> (as Co).

2-Butoxyethanol

**Ministry of Welfare, List of Exposure Limits (Iceland, 11/2023)** Absorbed through skin.

STEL 15 minutes: 246 mg/m<sup>3</sup>.

STEL 15 minutes: 50 ppm.

TWA 8 hours: 100 mg/m<sup>3</sup>.

TWA 8 hours: 20 ppm.

neodecanoic acid, cobalt salt

**Ministry of Welfare, List of Exposure Limits (Iceland, 11/2023) [Kóbalt og ólífræn sambönd]** Sensitiser.

TWA 8 hours: 0.02 mg/m<sup>3</sup> (as Co). Form: Dust and fumes.

2-Butoxyethanol

**NAOSH (Ireland, 4/2024)** Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values

OELV 8 hours: 20 ppm.

OELV 8 hours: 98 mg/m<sup>3</sup>.

OELV 15 minutes: 50 ppm.

OELV 15 minutes: 246 mg/m<sup>3</sup>.

neodecanoic acid, cobalt salt

**NAOSH (Ireland, 4/2024) [cobalt & cobalt compounds]** Carc 1B, Repr 1B. Sensitiser. Notes: Advisory Occupational Exposure Limit Values (OELVs)







OELV 8 hours: 0.02 mg/m<sup>3</sup> (as Co).

## SECTION 8: Exposure controls/personal protection

2-Butoxyethanol	<p><b>Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 6/2020)</b>  Absorbed through skin.  Limit value 8 hours: 20 ppm.  Limit value 8 hours: 98 mg/m<sup>3</sup>.  Short Term 15 minutes: 50 ppm.  Short Term 15 minutes: 246 mg/m<sup>3</sup>.</p>
2-Butoxyethanol	<p><b>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024)</b>  Absorbed through skin.  TWA 8 hours: 98 mg/m<sup>3</sup>.  TWA 8 hours: 20 ppm.  STEL 15 minutes: 50 ppm.  STEL 15 minutes: 246 mg/m<sup>3</sup>.</p>
2-Butoxyethanol	<p><b>Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024)</b>  Absorbed through skin.  TWA 8 hours: 50 mg/m<sup>3</sup>.  TWA 8 hours: 10 ppm.  STEL 15 minutes: 100 mg/m<sup>3</sup>.  STEL 15 minutes: 20 ppm.</p>
neodecanoic acid, cobalt salt	<p><b>Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024)</b>  <b>[kobaltas ir jo neorganiniai junginiai]</b> Carc, Muta. Sensitiser.  TWA 8 hours: 0.05 mg/m<sup>3</sup> (as Co).</p>
propylidynetrimethanol	<p><b>Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024)</b>  CEIL: 5 ppm.</p>
2-Butoxyethanol	<p><b>Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021)</b> Absorbed through skin.  TWA 8 hours: 20 ppm.  TWA 8 hours: 98 mg/m<sup>3</sup>.  STEL 15 minutes: 50 ppm.  STEL 15 minutes: 246 mg/m<sup>3</sup>.</p>
2-Butoxyethanol	<p><b>EU OEL (Europe, 1/2022)</b> Absorbed through skin.  TWA 8 hours: 20 ppm.  TWA 8 hours: 98 mg/m<sup>3</sup>.  STEL 15 minutes: 50 ppm.  STEL 15 minutes: 246 mg/m<sup>3</sup>.</p>
2-Butoxyethanol	<p><b>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 5/2024)</b> Absorbed through skin.  TWA 8 hours: 100 mg/m<sup>3</sup>.  STEL 15 minutes: 246 mg/m<sup>3</sup>.  TWA 8 hours: 20.4 ppm.  STEL 15 minutes: 50 ppm.</p>
2-Butoxyethanol	<p><b>FOR-2011-12-06-1358 (Norway, 12/2022)</b> Absorbed through skin.  TWA 8 hours: 10 ppm.  TWA 8 hours: 50 mg/m<sup>3</sup>.</p>
neodecanoic acid, cobalt salt	<p><b>FOR-2011-12-06-1358 (Norway, 12/2022) [uorganiske koboltforbindelser (unntatt Co(II))]</b> Repr. Sensitiser.  TWA 8 hours: 0.02 mg/m<sup>3</sup> (calculated as Co).</p>
2-Butoxyethanol	<p><b>Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 8/2023)</b> Absorbed through skin.  TWA 8 hours: 98 mg/m<sup>3</sup>.  STEL 15 minutes: 200 mg/m<sup>3</sup>.</p>
neodecanoic acid, cobalt salt	<p><b>Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 8/2023) [cobalt and its inorganic compounds]</b>  TWA 8 hours: 0.02 mg/m<sup>3</sup> (calculated as Co).</p>



## SECTION 8: Exposure controls/personal protection

<p> Butoxyethanol</p> <p>neodecanoic acid, cobalt salt</p>	<p><b>Portuguese Institute of Quality (Portugal, 11/2014)</b> A3. TWA 8 hours: 20 ppm.</p> <p><b>Portuguese Institute of Quality (Portugal, 11/2014) [cobalto, compostos inorgânicos]</b> A3. TWA 8 hours: 0.02 mg/m<sup>3</sup> (expressed as Co).</p> <p><b>Portuguese Institute of Quality (Portugal, 11/2014) [cobalto e compostos inorgânicos]</b> A3. TWA 8 hours: 0.02 mg/m<sup>3</sup> (expressed as Co).</p>
<p> Butoxyethanol</p>	<p><b>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024)</b> Absorbed through skin. VLA 8 hours: 98 mg/m<sup>3</sup>. VLA 8 hours: 20 ppm. Short term 15 minutes: 246 mg/m<sup>3</sup>. Short term 15 minutes: 50 ppm.</p>
<p> Butoxyethanol</p> <p>neodecanoic acid, cobalt salt</p>	<p><b>Government regulation SR c. 355/2006 (Slovakia, 7/2024)</b> Absorbed through skin , Inhalation sensitiser. TWA 8 hours: 98 mg/m<sup>3</sup>. TWA 8 hours: 20 ppm. STEL 15 minutes: 246 mg/m<sup>3</sup>. STEL 15 minutes: 50 ppm.</p> <p><b>Government regulation SR c. 355/2006 (Slovakia, 7/2024) [kobalt a jeho zlúčeniny]</b> Sensitiser , Inhalation sensitiser. TWA 8 hours: 0.05 mg/m<sup>3</sup> (Cobalt and its compounds, as Co).</p>
<p> Butoxyethanol</p>	<p><b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024)</b> Absorbed through skin. TWA 8 hours: 98 mg/m<sup>3</sup>. TWA 8 hours: 20 ppm. KTV 15 minutes: 246 mg/m<sup>3</sup> 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes]. KTV 15 minutes: 50 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].</p>
<p> Butoxyethanol</p> <p>neodecanoic acid, cobalt salt</p>	<p><b>National institute of occupational safety and health (Spain, 1/2024)</b> Absorbed through skin. TWA 8 hours: 20 ppm. TWA 8 hours: 98 mg/m<sup>3</sup>. STEL 15 minutes: 245 mg/m<sup>3</sup>. STEL 15 minutes: 50 ppm.</p> <p><b>National institute of occupational safety and health (Spain, 1/2024) [compuestos inorgánicos de cobalto excepto los expresamente indicados]</b> Inhalation sensitiser , Skin sensitiser. TWA 8 hours: 0.02 mg/m<sup>3</sup> (as Co).</p>
<p> Butoxyethanol</p> <p>neodecanoic acid, cobalt salt</p> <p>propylidynetrimethanol</p>	<p><b>Work environment authority Regulation 2018:1 (Sweden, 11/2022)</b> Absorbed through skin. TWA 8 hours: 10 ppm. TWA 8 hours: 50 mg/m<sup>3</sup>. STEL 15 minutes: 50 ppm. STEL 15 minutes: 246 mg/m<sup>3</sup>.</p> <p><b>Work environment authority Regulation 2018:1 (Sweden, 11/2022) [cobalt and inorganic compounds]</b> Carc. Absorbed through skin , Sensitiser. TWA 8 hours: 0.02 mg/m<sup>3</sup> (as Co). Form: inhalable fraction.</p> <p><b>Work environment authority Regulation 2018:1 (Sweden, 11/2022)</b> TWA 8 hours: 5 mg/m<sup>3</sup>.</p>

## SECTION 8: Exposure controls/personal protection

<p>2-Butoxyethanol</p> <p>neodecanoic acid, cobalt salt</p>	<p><b>SUVA (Switzerland, 1/2024)</b> Absorbed through skin. TWA 8 hours: 10 ppm. TWA 8 hours: 49 mg/m<sup>3</sup>. STEL 15 minutes: 20 ppm. STEL 15 minutes: 98 mg/m<sup>3</sup>.</p> <p><b>SUVA (Switzerland, 1/2024) [Cobalt und seine Verbindungen]</b> Carc 1B, Muta 2, Repr 1B. Absorbed through skin, Sensitiser. TWA 8 hours: 0.05 mg/m<sup>3</sup> (calculated as Co). Form: inhalable dust and aerosol.</p>
<p>2-Butoxyethanol</p> <p>neodecanoic acid, cobalt salt</p>	<p><b>EH40/2005 WELs (United Kingdom (UK), 1/2020)</b> Absorbed through skin. STEL 15 minutes: 50 ppm. TWA 8 hours: 25 ppm. STEL 15 minutes: 246 mg/m<sup>3</sup>. TWA 8 hours: 123 mg/m<sup>3</sup>.</p> <p><b>EH40/2005 WELs (United Kingdom (UK), 1/2020) [cobalt and cobalt compounds]</b> Carc. Inhalation sensitiser. TWA 8 hours: 0.1 mg/m<sup>3</sup> (as Co).</p>

### Biological exposure indices

Product/ingredient name	Exposure indices
<p>neodecanoic acid, cobalt salt</p> <p>No exposure indices known.</p> <p>No exposure indices known.</p> <p>No exposure indices known.</p> <p>No exposure indices known.</p>	<p><b>VGU BEI (Austria, 9/2020) [cobalt or its compounds]</b> BEI Fitness: 10 µg/l, cobalt [in urine]. Sampling time: one year.</p>
<p>2-Butoxyethanol</p> <p>No exposure indices known.</p> <p>No exposure indices known.</p> <p>No exposure indices known.</p>	<p><b>Government regulation of Czech Republic Limit Values of Biological Exposure Tests (Czech Republic, 9/2015)</b> Biological limit values: 0.17 mmol/mmol creatinine, butoxyacetic acid (after hydrolysis) [in urine]. Sampling time: the end of the shift at the end of the week. Biological limit values: 200 mg/g creatinine, butoxyacetic acid (after hydrolysis) [in urine]. Sampling time: the end of the shift at the end of the week.</p>
<p>neodecanoic acid, cobalt salt</p>	<p><b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 9/2020) [Cobalt and its inorganic compounds]</b> BEI: 130 nmol/l, cobalt [in urine]. Sampling time: at the end of each work shift work step or a week or exposure period.</p>
<p>2-Butoxyethanol</p>	<p><b>Biological limit values (BLV) - Labour Code / ANSES (France, 4/2023) [2-butoxyethanol and its acetate]</b> BLV: 100 mg/g Cr, 2-butoxyacetic acid [in urine]. Sampling time: end of shift (regardless of the day of the week).</p>
<p>neodecanoic acid, cobalt salt</p>	<p><b>Biological limit values (BLV) - Labour Code / ANSES (France, 4/2023) [cobalt and mineral compounds]</b> BLV: 5 µg/g Cr, cobalt [in urine]. Sampling time: end of shift and weekend.</p>
<p>2-Butoxyethanol</p>	<p><b>DFG BEI-values list (Germany, 7/2023)</b> Notes: danger from percutaneous absorption (see p. 211 and p. 228). BEI: 150 mg/g creatinine, butoxyacetic acid (after hydrolysis) [in urine]. Sampling time: end of exposure or end of shift / for long-term exposures: at the end of the shift after several shifts.</p> <p><b>TRGS 903 - BEI Values (Germany, 2/2024)</b> BEI: 150 mg/g creatinine, butoxy acetic acid (after hydrolysis) [in</p>

## SECTION 8: Exposure controls/personal protection

neodecanoic acid, cobalt salt


No exposure indices known.

No exposure indices known.

No exposure indices known.

 Butoxyethanol

No exposure indices known.

 neodecanoic acid, cobalt salt

No exposure indices known.

No exposure indices known.


No exposure indices known.


No exposure indices known.

No exposure indices known.

No exposure indices known.

 Butoxyethanol

 neodecanoic acid, cobalt salt

 neodecanoic acid, cobalt salt

 Butoxyethanol

urine]. Sampling time: end of exposure or end of shift; for long-term exposures: at the end of shift after several shifts.

**DFG BEI-values list (Germany, 7/2023) [Cobalt and its compounds]** Notes: danger from percutaneous absorption (see p. 211 and p. 228).

BGV: 35 µg/l, cobalt [in urine]. Sampling time: for long-term exposures: at the end of the shift after several shifts.

BEI: 1.5 µg/l, cobalt [in urine]. Sampling time: for long-term exposures: at the end of the shift after several shifts.

**NAOSH (Ireland, 1/2011)**

BMGV: 200 mg/g creatinine, BAA [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases.

**Minister Cabinet Regulations No.325 - BEI (Latvia, 3/2024) [cobalt and its compounds]**

BEI: 130 nmol/L, cobalt [in urine]. Sampling time: at the end of the exposure or at the end of the shift.

BEI: 7 µg/l, cobalt [in blood]. Sampling time: at the end of the exposure or at the end of the shift.

**Portuguese Institute of Quality (Portugal, 11/2014)**

BEI: 200 mg/g creatinine, butoxyacetic acid (BAA) [in urine]. Sampling time: end of shift.

**HG 1218/2006, Annex 2, with subsequent modifications and additions (Romania, 3/2024) [Cobalt compounds]**

OBLV: 1 µg/l, cobalt [in blood]. Sampling time: end of the week.

OBLV: 15 µg/l, cobalt [in urine]. Sampling time: end of the week.

**Government regulation SR c. 355/2006 (Slovakia, 5/2024) [cobalt and its compounds]**

BLV: 38.45 nmol/mmol creatinine, as cobalt [in urine]. Sampling time: no limitation.

BLV: 20.03 µg/g creatinine, as cobalt [in urine]. Sampling time: no limitation.

BLV: 509.8 nmol/l, as cobalt [in urine]. Sampling time: no limitation.

BLV: 30 µg/l, as cobalt [in urine]. Sampling time: no limitation.

**Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024)**

BAT: 150 mg/g creatinine, butoxyacetic acid (after hydrolysis) [in urine]. Sampling time: at the end of the work shift, at long-term exposure: at the end of the work shift after several consecutive workdays.

## SECTION 8: Exposure controls/personal protection

2-Butoxyethanol	<b>National institute of occupational safety and health (Spain, 1/2024)</b> VLB: 200 mg/g creatinine, butoxyacetic acid [in urine]. Sampling time: end of shift.
neodecanoic acid, cobalt salt	<b>National institute of occupational safety and health (Spain, 1/2024) [cobalt and inorganic compounds of cobalt, except oxides]</b> VLB: 1 µg/l, cobalt [in blood]. Sampling time: end of workweek. VLB: 15 µg/l, cobalt [in urine]. Sampling time: end of workweek.
No exposure indices known.	
2-Butoxyethanol	<b>SUVA (Switzerland, 1/2024)</b> BEI: 150 mg/g creatinine, 2-butoxy acetic acid (after hydrolisis) [in urine]. Sampling time: immediately after exposure or after working hours. In case of long-term exposure: after more than one shift.
neodecanoic acid, cobalt salt	<b>SUVA (Switzerland, 1/2024) [Cobalt and its compounds]</b> BEI: 30 µg/l, cobalt [in urine]. Sampling time: immediately after exposure or after working hours. BEI: 509 nmol/l, cobalt [in urine]. Sampling time: immediately after exposure or after working hours.
2-Butoxyethanol	<b>EH40/2005 BMGVs (United Kingdom (UK), 1/2020)</b> BGV: 240 mmol/mol creatinine, butoxyacetic acid [in urine]. Sampling time: post shift.

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs/DMELs

Product/ingredient name	Result
Titanium dioxide	<b>DNEL - General population - Long term - Inhalation</b> 28 µg/m³ <u>Effects</u> : Local  <b>DNEL - Workers - Long term - Inhalation</b> 170 µg/m³ <u>Effects</u> : Local
2-Butoxyethanol	<b>DNEL - General population - Long term - Oral</b> 6.3 mg/kg bw/day <u>Effects</u> : Systemic  <b>DNEL - General population - Short term - Oral</b> 26.7 mg/kg bw/day <u>Effects</u> : Systemic  <b>DNEL - General population - Long term - Inhalation</b> 59 mg/m³ <u>Effects</u> : Systemic  <b>DNEL - Workers - Long term - Inhalation</b> 98 mg/m³ <u>Effects</u> : Systemic  <b>DNEL - General population - Short term - Inhalation</b> 147 mg/m³

## SECTION 8: Exposure controls/personal protection

Effects: Local

**DNEL - Workers - Short term - Inhalation**

246 mg/m<sup>3</sup>

Effects: Local

**DNEL - General population - Short term - Inhalation**

426 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Short term - Inhalation**

1091 mg/m<sup>3</sup>

Effects: Systemic

neodecanoic acid, cobalt salt

**DNEL - General population - Long term - Oral**

32 µg/kg bw/day

Effects: Systemic

**DNEL - General population - Long term - Inhalation**

43 µg/m<sup>3</sup>

Effects: Local

**DNEL - Workers - Long term - Inhalation**

273.2 µg/m<sup>3</sup>

Effects: Local

propylidynetrimethanol

**DNEL - General population - Long term - Oral**

0.34 mg/kg bw/day

Effects: Systemic

**DNEL - General population - Long term - Dermal**

0.34 mg/kg bw/day

Effects: Systemic

**DNEL - General population - Long term - Inhalation**

0.58 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Long term - Dermal**

0.94 mg/kg bw/day

Effects: Systemic

**DNEL - Workers - Long term - Inhalation**

3.3 mg/m<sup>3</sup>

Effects: Systemic

1,2-benzisothiazol-3(2H)-one

**DNEL - General population - Long term - Dermal**

0.345 mg/kg bw/day

Effects: Systemic

**DNEL - Workers - Long term - Dermal**

0.966 mg/kg bw/day

Effects: Systemic

**DNEL - General population - Long term - Inhalation**

1.2 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Long term - Inhalation**

6.81 mg/m<sup>3</sup>

Effects: Systemic

### PNECs

Not available.

## SECTION 8: Exposure controls/personal protection

### 8.2 Exposure controls

**Appropriate engineering controls** : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

#### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Recommendations : Wear suitable gloves tested to EN374.

> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm

Not recommended polyvinyl alcohol (PVA) gloves

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type (spray application): A P

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

**Physical state** : Liquid.

**Colour** : Various

**Odour** : Slight

**Odour threshold** : Not available.

**Melting point/freezing point** : Not available.

**Initial boiling point and boiling range** :

Ingredient name	°C	°F	Method
Water	100	212	
2-Butoxyethanol	171 to 171.5	339.8 to 340.7	IP 123-93

**Flammability** : Not available.



## SECTION 9: Physical and chemical properties

**Lower and upper explosion limit** : Lower: Not applicable.  
Upper: Not applicable.

**Flash point** : Closed cup: >100°C (>212°F)

**Auto-ignition temperature** :

Ingredient name	°C	°F	Method
2-Butoxyethanol	230	446	DIN 51794

**Decomposition temperature** : Not available.

**pH** : 8.9 to 9.5

**Viscosity** : ☒ Not available.

**Solubility(ies)** :

Not available.

**Solubility in water** : Not available.

**Partition coefficient: n-octanol/ water** : Not applicable.

**Vapour pressure** :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Water	17.5	2.3				
2-Butoxyethanol	0.75006	0.1				

**Relative density** : Not available.

**Density** : 1.3 g/cm<sup>3</sup>

**Vapour density** : Not available.

### Particle characteristics

**Median particle size** : Not applicable.

## 9.2 Other information

### 9.2.1 Information with regard to physical hazard classes

**Explosive properties** : Not available.

**Oxidising properties** : Not available.

### 9.2.2 Other safety characteristics

Not applicable.

## SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : No specific data.

**10.5 Incompatible materials** : No specific data.

**10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Product/ingredient name

propylidynetrimethanol

##### Result

**Rat - Oral - LD50**  
14000 mg/kg

1,2-benzisothiazol-3(2H)-one

**Rat - Oral - LD50**  
1020 mg/kg

**Conclusion/Summary [Product]** : Not available.

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
TEKNOCRYL AQUA COMBI 2780-82	38139.0	N/A	N/A	95.3	N/A
2-Butoxyethanol	1200	N/A	N/A	3	N/A
neodecanoic acid, cobalt salt	500	N/A	N/A	N/A	N/A
propylidynetrimethanol	14000	N/A	N/A	N/A	N/A
1,2-benzisothiazol-3(2H)-one	450	N/A	N/A	N/A	0.21

#### Skin corrosion/irritation

##### Product/ingredient name

titanium dioxide

##### Result

**Human - Skin - Mild irritant**  
Duration of treatment/exposure: 72 hours  
Amount/concentration applied: 300 ug l

2-Butoxyethanol

**Rabbit - Skin - Mild irritant**  
Amount/concentration applied: 500 mg

1,2-benzisothiazol-3(2H)-one

**Human - Skin - Mild irritant**  
Duration of treatment/exposure: 48 hours  
Amount/concentration applied: 5 %

**Conclusion/Summary [Product]** : Not available.

#### Serious eye damage/eye irritation

##### Product/ingredient name

2-Butoxyethanol

##### Result

**Rabbit - Eyes - Moderate irritant**  
Duration of treatment/exposure: 24 hours  
Amount/concentration applied: 100 mg

**Rabbit - Eyes - Severe irritant**  
Amount/concentration applied: 100 mg

**Conclusion/Summary [Product]** : Not available.

#### Respiratory corrosion/irritation

Not available.

**Conclusion/Summary [Product]** : Not available.

#### Respiratory or skin sensitization

Not available.

#### Skin

## SECTION 11: Toxicological information

**Conclusion/Summary [Product]** : Not available.

### Respiratory

**Conclusion/Summary [Product]** : Not available.

### Germ cell mutagenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

Not available.

**Conclusion/Summary [Product]** : Not available.

### Reproductive toxicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

#### **Product/ingredient name**

Tridecanoic acid, cobalt salt

#### **Result**

STOT RE 1, H372

### Aspiration hazard

Not available.

### Information on likely routes of exposure

Not available.

### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact** : No known significant effects or critical hazards.

**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : No specific data.

**Inhalation** : No specific data.

**Skin contact** : No specific data.

**Ingestion** : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

## SECTION 11: Toxicological information

### Potential chronic health effects

Not available.

**Conclusion/Summary [Product]** : Not available.

**General** : No known significant effects or critical hazards.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Reproductive toxicity** : No known significant effects or critical hazards.

### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

#### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product/ingredient name

Titanium dioxide

#### Result

##### Acute - LC50 - Marine water

Fish - Mummichog - *Fundulus heteroclitus*  
>1000000 µg/l [96 hours]  
Effect: Mortality

##### Acute - LC50 - Fresh water

Crustaceans - Water flea - *Ceriodaphnia dubia* - Neonate  
Age: <24 hours  
3 mg/l [48 hours]  
Effect: Mortality

2-Butoxyethanol

##### Acute - LC50 - Marine water

Fish - Inland silverside - *Menidia beryllina*  
Size: 40 to 100 mm  
1250000 µg/l [96 hours]  
Effect: Mortality

##### Acute - LC50 - Marine water

Crustaceans - Common shrimp, sand shrimp - *Crangon crangon*  
800000 µg/l [48 hours]  
Effect: Mortality

propylidynetrimethanol

##### Acute - EC50 - Fresh water

Daphnia - Water flea - *Daphnia magna*  
Age: 1 to 3 days  
13000000 µg/l [48 hours]  
Effect: Intoxication

##### Acute - LC50 - Marine water

Fish - Sheepshead minnow - *Cyprinodon variegatus*  
14400000 µg/l [96 hours]  
Effect: Mortality

1,2-benzisothiazol-3(2H)-one

##### Acute - LC50 - Fresh water

OECD [Fish, Acute Toxicity Test]  
Fish - Trout - *Onorhynchus Mykiss*  
1.9 mg/l [96 hours]

##### Acute - EC50

OECD 202 [Daphnia sp. Acute Immobilization Test and

## SECTION 12: Ecological information

Reproduction Test]  
Daphnia - Daphnia - *Daphnia Magna*  
3.7 mg/l [48 hours]

### Acute - EC50 - Marine water

OECD 201 [Alga, Growth Inhibition Test]  
Algae - Algae - *Skeletonema Costatum*  
0.36 mg/l [72 hours]

### Acute - NOEC - Marine water

OECD 201 [Alga, Growth Inhibition Test]  
Algae - Algae - *Skeletonema Costatum*  
0.15 mg/l [72 hours]

**Conclusion/Summary [Product]** : Not available.

## 12.2 Persistence and degradability

### Product/ingredient name

1,2-benzisothiazol-3(2H)-one

### Result

EU  
24% [28 days]

**Conclusion/Summary [Product]** : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
1,2-benzisothiazol-3(2H)-one	-	-	Inherent

## 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
2-Butoxyethanol	0.81	-	Low
neodecanoic acid, cobalt salt	-	15600	High
propylidynetrimethanol	-0.47	<1	Low
1,2-benzisothiazol-3(2H)-one	-	3.2	Low

## 12.4 Mobility in soil

### Soil/water partition coefficient

Product/ingredient name	logKoc	Koc
2-Butoxyethanol	1.83	67.3685
propylidynetrimethanol	1.22	16.5101
1,2-benzisothiazol-3(2H)-one	1.86	73.142

### Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
Titanium dioxide	No	No	No	No	No	No	No
2-Butoxyethanol	No	No	No	No	No	No	No
neodecanoic acid, cobalt salt	No	No	No	No	No	No	No
propylidynetrimethanol	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No

**Mobility** : Not available.

**Conclusion/Summary** : The product does not meet the criteria to be considered as a PMT or vPvM.

## 12.5 Results of PBT and vPvB assessment

### Regulation (EC) No. 1907/2006 [REACH]

## SECTION 12: Ecological information

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Titanium dioxide	No	No	No	No	No	No	No
2-Butoxyethanol	No	No	No	No	No	No	No
neodecanoic acid, cobalt salt	No	No	No	No	No	No	No
propylidynetrimethanol	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No

### Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Titanium dioxide	No	No	No	No	No	No	No
2-Butoxyethanol	No	No	No	No	No	No	No
neodecanoic acid, cobalt salt	No	No	No	No	No	No	No
propylidynetrimethanol	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No

**Conclusion/Summary** : The product does not meet the criteria to be considered as a PBT or vPvB.  
**Regulation (EC) No. 1272/2008 [CLP]**

### 12.6 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**European waste catalogue (EWC)** : 080112, 200128

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
<b>14.1 UN number or ID number</b>	Not regulated.	Not regulated.	Not regulated.	Not regulated.
<b>14.2 UN proper shipping name</b>	-	-	-	-



## SECTION 14: Transport information

14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in bulk according to IMO instruments** : Not relevant/applicable due to nature of the product.

## SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
**EU Regulation (EC) No. 1907/2006 (REACH)**

**Annex XIV - List of substances subject to authorisation**

**Annex XIV**

None of the components are listed.

**Substances of very high concern**

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles**

**Labelling** :

**Other EU regulations**

**Industrial emissions (integrated pollution prevention and control) - Air** : Not listed

**Industrial emissions (integrated pollution prevention and control) - Water** : Not listed

**Explosive precursors** : Not applicable.

**Ozone depleting substances (EU 2024/590)**

Not listed.

**Prior Informed Consent (PIC) (649/2012/EU)**

Not listed.

**Persistent Organic Pollutants**

Not listed.

**Seveso Directive**

This product is not controlled under the Seveso Directive.

**National regulations**


**Austria**

**Limitation of the use of organic solvents** : Permitted.

**Belgium**

## SECTION 15: Regulatory information


### Book VI carcinogenic agents annex VI.2-1 - VI.2-3

Ingredient name	Status
 Cobalt et ses composés	Listed
Styrène	Listed


### Czech Republic

Storage code : IV

### Denmark

Fire class : -1

### Executive Order No. 1795/2015

Ingredient name	Annex I Section A	Annex I Section B
 Titanium dioxide	Listed	-
neodecanoic acid, cobalt salt	Listed	-

MAL-code : 1-3

Protection based on MAL : According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:

**General:** Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

 MAL-code: 1-3

**Application:** When using scraper or knife, brush, roller, etc. for pre- and post-treatments in cabins or booths of the existing\* facility type, if the operator is inside the spray zone.

- Coveralls must be worn.

During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents.

- Gas filter mask and coveralls must be worn.

When spraying in existing\* spray booths, if the operator is outside the spray zone.

- Full mask with combined filter, arm protectors and apron must be worn.

During non-atomising spraying in existing\* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone.

- Air-supplied half mask and eye protection must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Air-supplied full mask, coveralls and hood must be worn.

## SECTION 15: Regulatory information

**Drying:** Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

**Polishing:** When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.


**Caution** The regulations contain other stipulations in addition to the above.

\*See Regulations.

- Restrictions on use** : Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.
- List of undesirable substances** : Not listed
- Carcinogenic waste** : Waste containers must be labeled: Contains a substance or substances regulated by Danish working environment legislation on cancer risks.

### Finland


### France

- Social Security Code, Articles L 461-1 to L 461-7** :  Butoxyethanol RG 84  
neodecanoic acid, cobalt salt RG 70

- Reinforced medical surveillance** : Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable

### Germany

### TRGS 905

Ingredient name	Carcinogen	Mutagen	Reproductive toxicity - Fertility	Reproductive toxicity - Development
 Cobalt compounds	K2	M1A	RF1A	RD1A


**Storage class (TRGS 510)** : 10

### Hazardous incident ordinance

This product is not controlled under the Germany Hazardous Incident Ordinance.

**Hazard class for water** : 1

### Technical instruction on air quality control (TA Luft)

Number [Class]	Description	%
 5.2.1	Total dust	36.3
5.2.5	Organic substances	21
5.2.5 [I]	Organic substances	3.4
5.2.7.1.1 [I]	Carcinogenic substances	0.15

- AOX** : The product contains organically bound halogens and can contribute to the AOX value in waste water.

### Italy

- D.Lgs. 152/06** : Not determined.

### Netherlands

- Water Discharge Policy (ABM)** : A(3) Hazardous for aquatic organisms, may have long-term hazardous effects in aquatic environment. Decontamination effort: A

### Norway

### Sweden

### Switzerland

- VOC content** :  VOC (w/w): 3.2%

### International regulations

### Chemical Weapon Convention List Schedules I, II & III Chemicals

## SECTION 15: Regulatory information

Not listed.

### Montreal Protocol

Not listed.

### Stockholm Convention on Persistent Organic Pollutants

Not listed.

### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

#### 15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

✓ Indicates information that has changed from previously issued version.

#### Abbreviations and acronyms

: ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
N/A = Not available  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
SGG = Segregation Group  
vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

#### Full text of abbreviated H statements

✓H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H351	Suspected of causing cancer.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### Full text of classifications [CLP/GHS]

✓Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1

## SECTION 16: Other information

Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1

**Date of issue/ Date of revision** : 13/05/2025

**Date of previous issue** : 06/09/2023

**Version** : 11

TEKNOCRYL AQUA COMBI 2780-82

All variants

### Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

