# SAFETY DATA SHEET



TEKNOCRYL AQUA COMBI 2780-91 - All variants

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

: TEKNOCRYL AQUA COMBI 2780-91 - All variants **Product name** 

1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person

responsible for this SDS

: Prod-safe@teknos.com

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : In an emergency, call 112

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

: No signal word. Signal word

**Hazard statements** : No known significant effects or critical hazards.

**Precautionary statements** 

**Prevention** : Not applicable. Response : Not applicable. : Not applicable. **Storage Disposal** : Not applicable.

Supplemental label

elements

: Contains neodecanoic acid, cobalt salt and 1,2-benzisothiazol-3(2H)-one. May

produce an allergic reaction.

Safety data sheet available on request.

**Annex XVII - Restrictions** on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

2.3 Other hazards

**Product meets the criteria** for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a

vPvB.

Date of issue/Date of revision . 06/11/2025 · 08/05/2025 Version :7 1/24 Date of previous issue Label No : 1/35797

### SECTION 2: Hazards identification

Other hazards which do not result in classification : None known.

### **SECTION 3: Composition/information on ingredients**

: Mixture 3.2 Mixtures

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
<b>2</b> -Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	≤5	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	ATE [Oral] = 1200 mg/kg ATE [Inhalation (vapours)] = 3 mg/l	[1] [2]
neodecanoic acid, cobalt salt	REACH #: 01-2119970733-31 EC: 248-373-0 CAS: 27253-31-2	≤0.3	Acute Tox. 4, H302 Skin Sens. 1, H317 STOT RE 1, H372 Aquatic Chronic 3, H412	ATE [Oral] = 500 mg/kg	[1]
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.036	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 450 mg/kg ATE [Inhalation (dusts and mists)] = 0.21 mg/l Skin Sens. 1, H317: C ≥ 0.036% M [Acute] = 1 M [Chronic] = 1	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

- Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

**Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation

occurs

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Get medical attention if symptoms occur.

Flush contaminated skin with plenty of water. Remove contaminated clothing and Skin contact

shoes. Get medical attention if symptoms occur.

: Wash out mouth with water. If material has been swallowed and the exposed Ingestion

person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

### 4.2 Most important symptoms and effects, both acute and delayed

**Over-exposure signs/symptoms** 

**Eye contact** : No specific data.

Date of issue/Date of revision : 06/11/2025 · 08/05/2025 Version :7 Date of previous issue 2/24 Label No : 1/35797

### **SECTION 4: First aid measures**

Inhalation : No specific data. : No specific data. Skin contact Ingestion : No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

: No specific treatment. Specific treatments

### SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** 

media

: None known.

### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst.

**Hazardous combustion** 

products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide metal oxide/oxides

#### 5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective** equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

### SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Date of issue/Date of revision : 06/11/2025 · 08/05/2025 Version :7 Date of previous issue 3/24 Label No : 1/35797

### **SECTION 6: Accidental release measures**

#### Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contain and collect spillage with non-combustible, absorbent material e. g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

# 6.4 Reference to other sections

: See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

### **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8).

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

### **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### **Occupational exposure limits**

Product/ingredient name	Exposure limit values
<b>2</b> -Butoxyethanol	Regulation on Limit Values - MAC (Austria, 12/2024) Absorbed
	through skin.
	TWA 8 hours: 20 ppm.
	TWA 8 hours: 98 mg/m³.
	PEAK 30 minutes: 40 ppm 4 times per shift.
	PEAK 30 minutes: 200 mg/m³ 4 times per shift.
neodecanoic acid, cobalt salt	Regulation on Limit Values - Technical Guidance Values
	(Austria, 12/2024) [Cobalt und seine Verbindungen (Cobalt als
	Cobaltmetall, Cobaltoxid und Cobaltsulfid, Staub von
	Cobaltlegierungen), im übrigen.] Absorbed through skin,
	Inhalation sensitiser, Skin sensitiser.
	TWA 8 hours: 0.1 mg/m³ (measured as Co). Form: Inhalable
	fraction.
	PEAK 15 minutes: 0.4 mg/m³ (measured as Co), 4 times per shift.
	Form: Inhalable fraction.
	Regulation on Limit Values - Technical Guidance Values
	(Austria, 12/2024) [Cobalt und seine Verbindungen (Cobalt als

Date of issue/Date of revision: 06/11/2025Date of previous issue: 08/05/2025Version: 74/24TEKNOCRYL AQUA COMBI 2780-91 - All variantsLabel No : 1/35797

Cobaltmetall, Cobaltoxid und Cobaltsulfid, Staub von Cobaltlegierungen). Herstellung von Cobaltpulver und Katalysatoren, Hartmetall- und Magnetherstellung.] Absorbed through skin, Inhalation sensitiser, Skin sensitiser.

TWA 8 hours: 0.5 mg/m³ (measured as Co). Form: Inhalable fraction.

PEAK 15 minutes: 2 mg/m³ (measured as Co), 4 times per shift. Form: Inhalable fraction.

Regulation on Limit Values - MAC (Austria, 12/2024) [Cobalt und seine Verbindungen (Cobalt als Cobaltmetall, Cobaltoxid, Cobaltsulfid und Cobaltsulfat, Staub von Cobaltlegierungen)]

Carc A2.

Limit values (Belgium, 12/2023) Absorbed through skin.

TWA 8 hours: 20 ppm. TWA 8 hours: 98 mg/m<sup>3</sup>. STEL 15 minutes: 50 ppm. STEL 15 minutes: 246 mg/m<sup>3</sup>.

Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024) Absorbed through skin.

Limit value 8 hours: 98 mg/m<sup>3</sup>. Limit value 15 minutes: 246 mg/m<sup>3</sup>. Limit value 15 minutes: 50 ppm. Limit value 8 hours: 20 ppm.

Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024) [Cobalt and inorganic compounds]

Limit value 8 hours: 0.1 mg/m³ (as cobalt).

Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023) Absorbed through skin.

STELV 15 minutes: 246 mg/m<sup>3</sup>. STELV 15 minutes: 50 ppm. ELV 8 hours: 98 mg/m<sup>3</sup>. ELV 8 hours: 20 ppm.

Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023) [kobalt i spojevi] Skin sensitiser, Inhalation sensitiser.

ELV 8 hours: 0.1 mg/m³ (as Co).

Department of labour inspection (Cyprus, 7/2021) Absorbed

through skin.

STEL 15 minutes: 50 ppm. STEL 15 minutes: 246 mg/m<sup>3</sup>. TWA 8 hours: 20 ppm. TWA 8 hours: 98 mg/m<sup>3</sup>.

Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 12/2023) Absorbed through skin.

TWA 8 hours: 98 mg/m<sup>3</sup>. TWA 8 hours: 20 ppm. STEL 15 minutes: 200 mg/m<sup>3</sup>. STEL 15 minutes: 40.7 ppm.

Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 12/2023) [kobalt a jeho sloučeniny] Carc, Repr. Sensitiser.

TWA 8 hours: 0.05 mg/m³ (as Co). Form: aerosol, inhalable fraction..

STEL 15 minutes: 0.1 mg/m³ (as Co). Form: aerosol, inhalable fraction..

Label No : 1/35797

2-Butoxyethanol

2-Butoxyethanol

neodecanoic acid, cobalt salt

2-Butoxyethanol

neodecanoic acid, cobalt salt

2-Butoxyethanol

2-Butoxyethanol

neodecanoic acid, cobalt salt

Date of issue/Date of revision : 06/11/2025 · 08/05/2025 Version :7 5/24 Date of previous issue

2-Butoxvethanol

Working Environment Authority (Denmark, 12/2024) Absorbed

through skin.
TWA 8 hours: 20 ppm.

TWA 8 hours: 98 mg/m³. STEL 15 minutes: 246 mg/m³. STEL 15 minutes: 50 ppm.

neodecanoic acid, cobalt salt

Working Environment Authority (Denmark, 12/2024)

[uorganiske cobaltforbindelser] K.

TWA 8 hours: 0.01 mg/m³ (calculated as Co).

Z-Butoxyethanol Occupational exposur

Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024) Absorbed through skin, Sensitiser.

TWA 8 hours: 98 mg/m³. TWA 8 hours: 20 ppm. STEL 15 minutes: 246 mg/m³. STEL 15 minutes: 50 ppm.

Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024) [koobalt ja anorgaanilised ühendid] Sensitiser.

TWA 8 hours: 0.05 mg/m³ (calculated as Co). **EU OEL (Europe, 1/2022)** Absorbed through skin.

TWA 8 hours: 20 ppm. TWA 8 hours: 98 mg/m³. STEL 15 minutes: 50 ppm. STEL 15 minutes: 246 mg/m³.

Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021) Absorbed through skin.

TWA 8 hours: 20 ppm. TWA 8 hours: 98 mg/m³. STEL 15 minutes: 50 ppm. STEL 15 minutes: 250 mg/m³.

Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021) [Koboltti ja sen epäorgaaniset yhdisteet]

TWA 8 hours: 0.02 mg/m³ (calculated as Co).

**Ministry of Labor (France, 6/2024)** Absorbed through skin. TWA 8 hours: 10 ppm. Notes: Binding regulatory limit values

(article R. 4412-149 of the Labor Code)

TWA 8 hours: 49 mg/m³. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)

STEL 15 minutes: 246 mg/m³. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)

STEL 15 minutes: 50 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)

TRGS 900 OEL (Germany, 6/2024) Absorbed through skin.

TWA 8 hours: 49 mg/m³.
PEAK 15 minutes: 98 mg/m³.
TWA 8 hours: 10 ppm.
PEAK 15 minutes: 20 ppm.

DFG MAC-values list (Germany, 7/2024) Develop C. Absorbed

through skin.

TWA 8 hours: 10 ppm.

PEAK 15 minutes: 20 ppm 4 times per shift [Interval: 1 hour].

TWA 8 hours: 49 mg/m<sup>3</sup>.

PEAK 15 minutes: 98 mg/m³ 4 times per shift [Interval: 1 hour].

**DFG MAC-values list (Germany, 7/2024) [Cobalt and cobalt compounds]** Carc 2, Muta 3A. Absorbed through skin, Inhalation sensitiser, Skin sensitiser.

Label No : 1/35797

DFG MAC-values list (Germany, 7/2024) Skin sensitiser.

neodecanoic acid, cobalt salt

2-Butoxyethanol

2-Butoxyethanol

neodecanoic acid, cobalt salt

2-Butoxyethanol

2-Butoxyethanol

neodecanoic acid, cobalt salt

1,2-benzisothiazol-3(2H)-one

Date of issue/Date of revision : 06/11/2025 Date of previous issue : 08/05/2025 Version : 7 6/24

SECTION 8: Exposure controls/personal protection 2-Butoxyethanol Presidential Decree 307/1986: Occupational exposure limit values (Greece, 8/2024) Absorbed through skin. TWA 8 hours: 25 ppm. TWA 8 hours: 120 mg/m<sup>3</sup>. Presidential Decree 307/1986: Occupational exposure limit neodecanoic acid, cobalt salt values (Greece, 8/2024) [κοβαλτίου ενώσεις] TWA 8 hours: 0.1 mg/m³ (as Co). 2-Butoxyethanol 5/2020. (II. 6.) ITM Decree (Hungary, 1/2025) Absorbed through skin. TWA 8 hours: 98 ma/m<sup>3</sup>. PEAK 15 minutes: 246 mg/m<sup>3</sup>. PEAK 15 minutes: 50 ppm. TWA 8 hours: 20 ppm. 5/2020. (II. 6.) ITM Decree (Hungary, 1/2025) [KOBALT ÉS neodecanoic acid, cobalt salt SZERVETLEN VEGYÜLETEI] Sensitiser. TWA 8 hours: 0.02 mg/m³ (as Co).

2-Butoxyethanol

neodecanoic acid, cobalt salt

2-Butoxyethanol

neodecanoic acid, cobalt salt

2-Butoxyethanol

2-Butoxyethanol

2-Butoxyethanol

neodecanoic acid, cobalt salt

TWA 8 hours: 100 mg/m<sup>3</sup>. TWA 8 hours: 20 ppm. Ministry of Welfare, List of Exposure Limits (Iceland, 11/2024)

Ministry of Welfare, List of Exposure Limits (Iceland, 11/2024)

[Kóbalt og ólífræn sambönd] Sensitiser.

TWA 8 hours: 0.02 mg/m³ (as Co). Form: Dust and fumes. NAOSH (Ireland, 4/2024) Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values

OELV 8 hours: 20 ppm. OELV 8 hours: 98 mg/m3.

OELV 15 minutes: 50 ppm. OELV 15 minutes: 246 mg/m<sup>3</sup>.

NAOSH (Ireland, 4/2024) [cobalt & cobalt compounds] Carc 1B, Repr 1B. Sensitiser. Notes: Advisory Occupational Exposure Limit Values (OELVs)

Absorbed through skin.

STEL 15 minutes: 246 mg/m<sup>3</sup>. STEL 15 minutes: 50 ppm.

OELV 8 hours: 0.02 mg/m³ (as Co).

Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 9/2024)

Absorbed through skin. Limit value 8 hours: 20 ppm. Limit value 8 hours: 98 mg/m<sup>3</sup>. Short Term 15 minutes: 50 ppm. Short Term 15 minutes: 246 mg/m<sup>3</sup>.

Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024)

Absorbed through skin. TWA 8 hours: 98 mg/m<sup>3</sup>. TWA 8 hours: 20 ppm. STEL 15 minutes: 50 ppm. STEL 15 minutes: 246 mg/m<sup>3</sup>.

Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024)

Absorbed through skin. TWA 8 hours: 50 mg/m<sup>3</sup>. TWA 8 hours: 10 ppm. STEL 15 minutes: 100 mg/m<sup>3</sup>. STEL 15 minutes: 20 ppm.

Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024) [kobaltas ir jo neorganinai junginiai] Carc, Muta. Sensitiser.

TWA 8 hours: 0.05 mg/m³ (as Co).

Date of issue/Date of revision · 08/05/2025 Version :7 7/24 : 06/11/2025 Date of previous issue Label No : 1/35797

2-Butoxyethanol

Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021) Absorbed through skin.

TWA 8 hours: 20 ppm. TWA 8 hours: 98 mg/m<sup>3</sup>. STEL 15 minutes: 50 ppm. STEL 15 minutes: 246 mg/m<sup>3</sup>.

2-Butoxyethanol

EU OEL (Europe, 1/2022) Absorbed through skin.

TWA 8 hours: 20 ppm. TWA 8 hours: 98 mg/m<sup>3</sup>. STEL 15 minutes: 50 ppm. STEL 15 minutes: 246 mg/m<sup>3</sup>.

2-Butoxyethanol

Ministry of Social Affairs and Employment, Legal limit values

(Netherlands, 5/2024) Absorbed through skin.

TWA 8 hours: 100 mg/m<sup>3</sup>. STEL 15 minutes: 246 mg/m<sup>3</sup>. TWA 8 hours: 20.4 ppm. STEL 15 minutes: 50 ppm.

2-Butoxyethanol

FOR-2011-12-06-1358 (Norway, 5/2024) Absorbed through skin.

TWA 8 hours: 10 ppm. TWA 8 hours: 50 mg/m<sup>3</sup>.

neodecanoic acid, cobalt salt

FOR-2011-12-06-1358 (Norway, 5/2024) [uorganiske koboltforbindelser (unntatt Co(II))] Repr. Sensitiser.

TWA 8 hours: 0.02 mg/m³ (calculated as Co).

2-Butoxyethanol

Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland,

7/2024) Absorbed through skin. TWA 8 hours: 98 mg/m<sup>3</sup>. STEL 15 minutes: 200 mg/m<sup>3</sup>.

neodecanoic acid, cobalt salt

Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024) [cobalt and its inorganic compounds]

TWA 8 hours: 0.02 mg/m³ (calculated as Co).

2-Butoxyethanol

Portuguese Institute of Quality (Portugal, 11/2014) A3.

TWA 8 hours: 20 ppm.

Decree-Law 24/2012 - Occupational exposure limits for chemical agents (Portugal, 6/2021) Absorbed through skin.

STEL 15 minutes: 50 ppm. STEL 15 minutes: 246 mg/m<sup>3</sup>. TWA 8 hours: 20 ppm. TWA 8 hours: 98 mg/m<sup>3</sup>.

neodecanoic acid, cobalt salt

Portuguese Institute of Quality (Portugal, 11/2014) [cobalto, compostos inorgânicos] A3.

TWA 8 hours: 0.02 mg/m³ (expressed as Co).

Portuguese Institute of Quality (Portugal, 11/2014) [cobalto e compostos inorgânicos] A3.

TWA 8 hours: 0.02 mg/m³ (expressed as Co).

2-Butoxyethanol

HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024) Absorbed through skin.

VLA 8 hours: 98 mg/m<sup>3</sup>. VLA 8 hours: 20 ppm.

Short term 15 minutes: 246 mg/m<sup>3</sup>. Short term 15 minutes: 50 ppm.

Date of issue/Date of revision : 06/11/2025 · 08/05/2025 Version :7 8/24 Date of previous issue Label No : 1/35797

2-Butoxvethanol

Government regulation SR c. 355/2006 (Slovakia, 6/2024)

Absorbed through skin, Inhalation sensitiser.

TWA 8 hours: 98 mg/m<sup>3</sup>. TWA 8 hours: 20 ppm. STEL 15 minutes: 246 mg/m<sup>3</sup>. STEL 15 minutes: 50 ppm.

neodecanoic acid, cobalt salt

Government regulation SR c. 355/2006 (Slovakia, 6/2024) [kobalt a jeho zlúčeniny] Sensitiser, Inhalation sensitiser.

TWA 8 hours: 0.05 mg/m<sup>3</sup> (Cobalt and its compounds, as Co).

Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024)

Absorbed through skin. TWA 8 hours: 98 mg/m<sup>3</sup>. TWA 8 hours: 20 ppm.

KTV 15 minutes: 246 mg/m<sup>3</sup> 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes]. KTV 15 minutes: 50 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].

2-Butoxyethanol

2-Butoxyethanol

National institute of occupational safety and health (Spain,

1/2024) Absorbed through skin. TWA 8 hours: 20 ppm.

TWA 8 hours: 98 mg/m<sup>3</sup>. STEL 15 minutes: 245 mg/m3. STEL 15 minutes: 50 ppm.

neodecanoic acid, cobalt salt

National institute of occupational safety and health (Spain, 1/2024) [compuestos inorgánicos de cobalto excepto los expresamente indicados] Inhalation sensitiser, Skin sensitiser.

TWA 8 hours: 0.02 mg/m³ (as Co).

2-Butoxyethanol

Work environment authority Regulation 2018:1 (Sweden,

11/2022) Absorbed through skin.

TWA 8 hours: 10 ppm. TWA 8 hours: 50 mg/m<sup>3</sup>. STEL 15 minutes: 50 ppm. STEL 15 minutes: 246 mg/m<sup>3</sup>.

neodecanoic acid, cobalt salt

Work environment authority Regulation 2018:1 (Sweden, 11/2022) [cobalt and inorganic compounds] Carc. Absorbed

through skin, Sensitiser.

TWA 8 hours: 0.02 mg/m³ (as Co). Form: inhalable fraction.

SUVA (Switzerland, 1/2025) Absorbed through skin.

TWA 8 hours: 10 ppm. TWA 8 hours: 49 mg/m<sup>3</sup>. STEL 15 minutes: 20 ppm. STEL 15 minutes: 98 mg/m<sup>3</sup>.

neodecanoic acid, cobalt salt

SUVA (Switzerland, 1/2025) [Cobalt und seine Verbindungen]

Carc 1B, Muta 2, Repr 1B. Absorbed through skin, Sensitiser. TWA 8 hours: 0.05 mg/m³ (calculated as Co). Form: inhalable

dust and aerosol.

2-Butoxyethanol

2-Butoxyethanol

EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed

through skin.

STEL 15 minutes: 50 ppm. TWA 8 hours: 25 ppm. STEL 15 minutes: 246 mg/m<sup>3</sup>. TWA 8 hours: 123 mg/m<sup>3</sup>.

neodecanoic acid, cobalt salt

EH40/2005 WELs (United Kingdom (UK), 1/2020) [cobalt and

cobalt compounds] Carc. Inhalation sensitiser.

TWA 8 hours: 0.1 mg/m³ (as Co).

**Biological exposure indices** 

Date of issue/Date of revision · 08/05/2025 Version :7 9/24 : 06/11/2025 Date of previous issue Label No : 1/35797

Product/ingredient name	Exposure indices
reodecanoic acid, cobalt salt	VGU BEI (Austria, 9/2020) [Cobalt oder seine Verbindungen] BEI Fitness: 10 µg/l, cobalt [in urine]. Sampling time: one year.
No exposure indices known.	
<b>2</b> -Butoxyethanol	Government regulation of Czech Republic Limit Values of Biological Exposure Tests (Czech Republic, 9/2015)  Biological limit values: 0.17 mmol/mmol creatinine, butoxyacetic acid (after hydrolysis) [in urine]. Sampling time: the end of the shift at the end of the week.  Biological limit values: 200 mg/g creatinine, butoxyacetic acid (after hydrolysis) [in urine]. Sampling time: the end of the shift at the end of the week.
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
reodecanoic acid, cobalt salt	Institute of Occupational Health, Ministry of Social Affairs (Finland, 9/2020) [Koboltti ja sen epäorgaaniset yhdisteet] BEI: 130 nmol/l, cobalt [in urine]. Sampling time: at the end of each work shift work step or a week or exposure period.
<b>2</b> -Butoxyethanol	Biological limit values (BLV) - Labour Code / ANSES (France, 4/2023) [2- butoxyéthanol et son acétate] BLV: 100 mg/g Cr, 2-butoxyacetic acid [in urine]. Sampling time: end of shift (regardless of the day of the week).
neodecanoic acid, cobalt salt	Biological limit values (BLV) - Labour Code / ANSES (France, 4/2023) [cobalt et composés minéraux]  BLV: 5 μg/g Cr, cobalt [in urine]. Sampling time: end of shift and weekend.
<b>2</b> -Butoxyethanol	DFG BEI-values list (Germany, 7/2024) Notes: danger from percutaneous absorption (see p. 211 and p. 228).  BEI: 150 mg/g creatinine, butoxyacetic acid (after hydrolysis) [in urine]. Sampling time: at the end of the shift, for long-term exposures after several previous shifts.  TRGS 903 - BEI Values (Germany, 10/2024)  BEI: 150 mg/g creatinine, butoxy acetic acid (after hydrolysis) [in urine]. Sampling time: at the end of the shift, for long-term exposure after several previous shifts.
neodecanoic acid, cobalt salt	DFG BEI-values list (Germany, 7/2024) [Cobalt and its compounds] Notes: danger from percutaneous absorption (see p. 211 and p. 228).  BGV: 35 µg/l, cobalt [in urine]. Sampling time: at the end of the shift, for long-term exposures after several previous shifts.  BEI: 1.5 µg/l, cobalt [in urine]. Sampling time: at the end of the shift, for long-term exposures after several previous shifts.
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
<b>2</b> -Butoxyethanol	NAOSH BGVs (Ireland, 1/2011) BMGV: 200 mg/g creatinine, BAA [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases.
No exposure indices known.	

Date of issue/Date of revision : 06/11/2025 Date of previous issue : 08/05/2025 Version: 7 10/24 **Label No** : 1/35797

reodecanoic acid, cobalt salt

Minister Cabinet Regulations No.325 - BEI (Latvia, 3/2024) [kobalts]

BEI: 130 nmol/L, cobalt [in urine]. Sampling time: at the end of the exposure or at the end of the shift.

BEI: 7 µg/l, cobalt [in blood]. Sampling time: at the end of the exposure or at the end of the shift.

No exposure indices known.

2-Butoxyethanol

reodecanoic acid, cobalt salt

reodecanoic acid, cobalt salt

2-Butoxyethanol

2-Butoxyethanol

neodecanoic acid, cobalt salt

No exposure indices known.

2-Butoxyethanol

neodecanoic acid, cobalt salt

**2**-Butoxyethanol

Portuguese Institute of Quality (Portugal, 11/2014)

BEI: 200 mg/g creatinine, butoxyacetic acid (BAA) [in urine]. Sampling time: end of shift.

HG 1218/2006, Annex 2, with subsequent modifications and additions (Romania, 3/2024) [cobalt]

OBLV: 1  $\mu$ g/l, cobalt [in blood]. Sampling time: end of the week. OBLV: 15  $\mu$ g/l, cobalt [in urine]. Sampling time: end of the week.

Government regulation SR c. 355/2006 (Slovakia, 6/2024) [kobalt a jeho zlúčeniny]

BLV: 38.45 nmol/mmol creatinine, as cobalt [in urine]. Sampling time: no limitation.

BLV: 20.03 μg/g creatinine, as cobalt [in urine]. Sampling time: no limitation.

BLV: 509.8 nmol/l, as cobalt [in urine]. Sampling time: no limitation.

BLV: 30 µg/l, as cobalt [in urine]. Sampling time: no limitation.

Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024)

BAT: 150 mg/g creatinine, butoxyacetic acid (after hydrolysis) [in urine]. Sampling time: at the end of the work shift, at long-term exposure: at the end of the work shift after several consecutive workdays.

National institute of occupational safety and health (Spain, 1/2024)

VLB: 200 mg/g creatinine, butoxyacetic acid [in urine]. Sampling time: end of shift.

National institute of occupational safety and health (Spain, 1/2024) [Cobalto y compuestos inorgánicos excepto óxidos]

VLB: 1  $\mu$ g/l, cobalt [in blood]. Sampling time: end of workweek. VLB: 15  $\mu$ g/l, cobalt [in urine]. Sampling time: end of workweek.

SUVA (Switzerland, 1/2025)

BEI: 150 mg/g creatinine, 2-butoxy acetic acid (after hydrolisis) [in urine]. Sampling time: immediately after exposure or after working hours. In case of long-term exposure: after more than one shift.

SUVA (Switzerland, 1/2025) [Cobalt und seine Verbindungen]

BEI: 30 µg/l, cobalt [in urine]. Sampling time: immediately after exposure or after working hours.

BEI: 509 nmol/l, cobalt [in urine]. Sampling time: immediately after exposure or after working hours.

EH40/2005 BMGVs (United Kingdom (UK), 1/2020)

BGV: 240 mmol/mol creatinine, butoxyacetic acid [in urine]. Sampling time: post shift.

Date of issue/Date of revision : 06/11/2025 Date of previous issue : 08/05/2025 Version : 7 11/24

TEKNOCRYL AQUA COMBI 2780-91 - All variants

**Label No** : 1/35797

procedures

**Recommended monitoring**: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

**Product/ingredient name** 

2-Butoxyethanol

#### Result

DNEL - General population - Long term - Oral

6.3 mg/kg bw/day Effects: Systemic

DNEL - General population - Short term - Oral

26.7 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Inhalation

59 ma/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Long term - Inhalation** 

98 ma/m<sup>3</sup>

Effects: Systemic

DNEL - General population - Short term - Inhalation

147 mg/m<sup>3</sup> Effects: Local

**DNEL - Workers - Short term - Inhalation** 

246 mg/m<sup>3</sup> Effects: Local

DNEL - General population - Short term - Inhalation

426 mg/m<sup>3</sup> Effects: Systemic

**DNEL - Workers - Short term - Inhalation** 

1091 mg/m<sup>3</sup> Effects: Systemic

neodecanoic acid, cobalt salt DNEL - General population - Long term - Oral

> 32 µg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Inhalation

43 μg/m<sup>3</sup> Effects: Local

**DNEL - Workers - Long term - Inhalation** 

273.2 µg/m<sup>3</sup> Effects: Local

1,2-benzisothiazol-3(2H)-one **DNEL - General population - Long term - Dermal** 

0.345 mg/kg bw/day Effects: Systemic

**DNEL - Workers - Long term - Dermal** 

0.966 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Inhalation

Date of issue/Date of revision

: 06/11/2025

Date of previous issue

: 08/05/2025

Version: 7 12/24

TEKNOCRYL AQUA COMBI 2780-91 - All variants

Label No : 1/35797

1.2 mg/m³ Effects: Systemic

**DNEL - Workers - Long term - Inhalation** 

6.81 mg/m³ Effects: Systemic

#### **PNECs**

Not available.

#### 8.2 Exposure controls

Appropriate engineering

 Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### Individual protection measures

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** 

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

### **Skin protection**

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Recommendations: Wear suitable gloves tested to EN374.

> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm Not recommended polyvinyl alcohol (PVA) gloves

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type (spray application): A P

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Label No : 1/35797

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

**Appearance** 

Physical state: Liquid.Colour: VariousOdour: Slight

Odour threshold : Not available.

Date of issue/Date of revision: 06/11/2025Date of previous issue: 08/05/2025Version: 713/24

### **SECTION 9: Physical and chemical properties**

Melting point/freezing point

: Not available.

Initial boiling point and

boiling range

Ingredient name	°C	°F	Method
water	100	212	
2-Butoxyethanol	171 to 171.5	339.8 to 340.7	IP 123-93

**Flammability** : Not available.

Lower and upper explosion : Lower: Not applicable. limit

Upper: Not applicable.

Flash point : Closed cup: >100°C (>212°F)

**Auto-ignition temperature** 

Ingredient name	°C	°F	Method
Butoxyethanol	230	446	DIN 51794

**Decomposition temperature** : Not available. : 9 to 9.5 pН Not available. **Viscosity** 

Solubility(ies)

Not available.

Solubility in water : Not available. Partition coefficient: n-octanol/ : Not applicable.

water

Vapour pressure

	Vapour Pressure at 20°C			Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
water value	17.5	2.3				
2-Butoxyethanol	0.75006	0.1				

**Relative density** : Not available. : 1.2 g/cm<sup>3</sup> **Density** Vapour density : Not available.

**Particle characteristics** 

Median particle size : Not applicable.

#### 9.2 Other information

9.2.1 Information with regard to physical hazard classes

**Explosive properties** : Not available. **Oxidising properties** : Not available.

9.2.2 Other safety characteristics

Not applicable.

### SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of : Under normal conditions of storage and use, hazardous reactions will not occur. hazardous reactions

10.4 Conditions to avoid : No specific data.

Date of issue/Date of revision : 06/11/2025 : 08/05/2025 Version :7 14/24 Date of previous issue Label No : 1/35797

### **SECTION 10: Stability and reactivity**

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

### **SECTION 11: Toxicological information**

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute toxicity** 

Product/ingredient name Result

1,2-benzisothiazol-3(2H)-one Rat - Oral - LD50

1020 mg/kg

**Conclusion/Summary [Product]**: Not available.

### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
FEKNOCRYL AQUA COMBI 2780-91	32562.2	N/A	N/A	81.4	N/A
2-Butoxyethanol	1200	N/A	N/A	3	N/A
neodecanoic acid, cobalt salt	500	N/A	N/A	N/A	N/A
1,2-benzisothiazol-3(2H)-one	450	N/A	N/A	N/A	0.21

**Skin corrosion/irritation** 

Product/ingredient name Result

Amount/concentration applied: 500 mg

1,2-benzisothiazol-3(2H)-one Human - Skin - Mild irritant

<u>Duration of treatment/exposure</u>: 48 hours Amount/concentration applied: 5 %

**Conclusion/Summary [Product]**: Not available.

Serious eye damage/eye irritation

Product/ingredient name Result

**Z**-Butoxyethanol Rabbit - Eyes - Moderate irritant

<u>Duration of treatment/exposure</u>: 24 hours Amount/concentration applied: 100 mg

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 100 mg

**Conclusion/Summary [Product]**: Not available.

**Respiratory corrosion/irritation** 

Not available.

**Conclusion/Summary [Product]**: Not available.

**Respiratory or skin sensitization** 

Not available.

Skin

Date of issue/Date of revision: 06/11/2025Date of previous issue: 08/05/2025Version: 715/24TEKNOCRYL AQUA COMBI 2780-91 - All variantsLabel No : 1/35797

### **SECTION 11: Toxicological information**

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

**Reproductive toxicity** 

Not available.

**Conclusion/Summary [Product]**: Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

**Product/ingredient name** Result

neodecanoic acid, cobalt salt **STOT RE 1, H372** 

**Aspiration hazard** 

Not available.

Information on likely routes of exposure

Not available.

Potential acute health effects

**Eye contact** : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards. **Skin contact** : No known significant effects or critical hazards. Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data. Inhalation : No specific data. **Skin contact** : No specific data. Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

**Potential immediate** : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

**Potential immediate** : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Date of issue/Date of revision : 06/11/2025 : 08/05/2025 Version :7 16/24 Date of previous issue Label No : 1/35797

### SECTION 11: Toxicological information

Not available.

**Conclusion/Summary [Product]**: Not available.

**General** : No known significant effects or critical hazards. Carcinogenicity : No known significant effects or critical hazards. Mutagenicity : No known significant effects or critical hazards. Reproductive toxicity : No known significant effects or critical hazards.

#### 11.2 Information on other hazards

### 11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine

disrupting properties according to the criteria set out in either Regulation (EC)

No. 1907/2006 or Regulation (EC) No 1272/2008.

#### 11.2.2 Other information

Not available.

### SECTION 12: Ecological information

#### 12.1 Toxicity

2-Butoxyethanol

Product/ingredient name

#### Result

Acute - LC50 - Marine water

Fish - Inland silverside - Menidia beryllina

Size: 40 to 100 mm 1250000 µg/l [96 hours]

Effect: Mortality

#### Acute - LC50 - Marine water

Crustaceans - Common shrimp, sand shrimp - Crangon

crangon

800000 µg/l [48 hours]

Effect: Mortality

1,2-benzisothiazol-3(2H)-one Acute - LC50 - Fresh water

> OECD [Fish, Acute Toxicity Test] Fish - Trout - Onorhynchus Mykiss

1.9 mg/l [96 hours]

#### Acute - EC50

OECD 202 [Daphnia sp. Acute Immobilization Test and

Reproduction Test]

Daphnia - Daphnia - Daphnia Magna

3.7 mg/l [48 hours]

#### Acute - EC50 - Marine water

OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - Skeletonema Costatum

0.36 mg/l [72 hours]

### Acute - NOEC - Marine water

OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - Skeletonema Costatum

0.15 mg/l [72 hours]

**Conclusion/Summary [Product]** Not available.

#### 12.2 Persistence and degradability

Product/ingredient name Result 1,2-benzisothiazol-3(2H)-one

24% [28 days]

**Conclusion/Summary [Product]**: Not available.

Date of issue/Date of revision : 06/11/2025 · 08/05/2025 Version: 7 17/24 Date of previous issue Label No : 1/35797

### **SECTION 12: Ecological information**

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
1,2-benzisothiazol-3(2H)-one	-	-	Inherent

### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Z-Butoxyethanol neodecanoic acid, cobalt salt 1,2-benzisothiazol-3(2H)-one		- 15600 3.2	Low High Low

### 12.4 Mobility in soil

### Soil/water partition coefficient

Product/ingredient name	logKoc	Koc
Z-Butoxyethanol 1,2-benzisothiazol-3(2H)-one	1.8 1.9	67.3685 73.142

### Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
P-Butoxyethanol neodecanoic acid, cobalt salt 1,2-benzisothiazol-3(2H)-one		No No No	No No No	No No No	No No No	No No No	No No No

**Mobility** : Not available.

**Conclusion/Summary** : The product does not meet the criteria to be considered as a PMT or vPvM.

### 12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	В	T	vPvB	vP	vB
P-Butoxyethanol neodecanoic acid, cobalt salt 1,2-benzisothiazol-3(2H)-one		N/A N/A N/A	N/A Yes No	Yes	N/A N/A No	N/A N/A N/A	N/A Yes No

### Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	Р	В	Т	vPvB	vP	vB	
2-Butoxyethanol neodecanoic acid, cobalt salt	No No							
1,2-benzisothiazol-3(2H)-one	No							

Conclusion/Summary **Regulation (EC) No. 1272/2008** [CLP]

: The product does not meet the criteria to be considered as a PBT or vPvB.

### 12.6 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** 

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

Date of issue/Date of revision : 06/11/2025 : 08/05/2025 Version :7 18/24 Date of previous issue Label No : 1/35797

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

#### **Product**

**Methods of disposal** : Avoid release to the environment. Avoid dispersal of spilt material and runoff and

contact with soil, waterways, drains and sewers. Dispose of contents and container

in accordance with all local, regional, national and international regulations. **Hazardous waste** 

: Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

**European waste** catalogue (EWC) : 080112, 200128

**Packaging** 

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Waste

packaging should be recycled. Incineration or landfill should only be considered

when recycling is not feasible.

This material and its container must be disposed of in a safe way. Empty containers **Special precautions** or liners may retain some product residues. Avoid dispersal of spilt material and

runoff and contact with soil, waterways, drains and sewers.

### SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant/applicable due to nature of the product.

### SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Labelling

Date of issue/Date of revision : 06/11/2025 · 08/05/2025 Version: 7 19/24 Date of previous issue Label No : 1/35797

### **SECTION 15: Regulatory information**

Synthetic polymer microparticles - Designation 78

Generic identity of

polymer(s)

microparticles

: 3906 - Acrylic polymers.

Total percentage of synthetic polymer

: 16.7%

The synthetic polymer microparticles supplied is subject to conditions laid down by entry 78 of Annex XVII to Regulation (EC) No 1907/2006 of the European Parliament and of the Council.

#### Other EU regulations

**Industrial emissions** 

: Not listed

(integrated pollution prevention and control) -

Air

**Industrial emissions** 

: Not listed

(integrated pollution prevention and control) -

Water

**Explosive precursors** : Not applicable. Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

**Persistent Organic Pollutants** 

Not listed.

**Seveso Directive** 

This product is not controlled under the Seveso Directive.

**National regulations** 

**Austria** 

Limitation of the use of

: Permitted.

organic solvents

**Belgium** 

Book VI carcinogenic agents annex VI.2-1 - VI.2-3

Ingredient name	Status
Cobalt et ses composés	Listed
Styrène	Listed
Noirs de charbon	Listed

### **Czech Republic**

: IV Storage code

**Denmark** 

Fire class : IV-1 Executive Order No. 1795/2015

Ingredient name	Annex I Section A	Annex I Section B
tranium dioxide	Listed	-
neodecanoic acid, cobalt salt	Listed	-

**MAL-code** 

**Protection based on MAL** 

: According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:

General: Gloves must be worn for all work that may result in soiling. Apron/ coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this

Date of issue/Date of revision : 06/11/2025 Date of previous issue : 08/05/2025 Version :7 20/24 Label No : 1/35797

### **SECTION 15: Regulatory information**

case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

MAL-code: 1-3

**Application:** When using scraper or knife, brush, roller, etc, for pre- and post-treatments in cabins or booths of the existing\* facility type, if the operator is inside the spray zone.

- Coveralls must be worn.

During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents.

- Gas filter mask and coveralls must be worn.

When spraying in existing\* spray booths, if the operator is outside the spray zone.

- Full mask with combined filter, arm protectors and apron must be worn.

During non-atomising spraying in existing\* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone.

- Air-supplied half mask and eye protection must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Air-supplied full mask, coveralls and hood must be worn.

**Drying:** Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

**Polishing:** When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

**Caution** The regulations contain other stipulations in addition to the above.

\*See Regulations.

Restrictions on use

: Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.

List of undesirable substances

: Not listed

Carcinogenic waste

: Waste containers must be labeled: Contains a substance or substances regulated by Danish working environment legislation on cancer risks.

Finland France

Social Security Code, Articles L 461-1 to L 461-7 : Z-Butoxyethanol RG 84 neodecanoic acid, cobalt salt RG 70

Reinforced medical surveillance

: Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable

Label No : 1/35797

Germany TRGS 905

Date of issue/Date of revision : 06/11/2025 Date of previous issue : 08/05/2025 Version : 7 21/24

### **SECTION 15: Regulatory information**

Ingredient name	Carcinogen	Mutagen	Reproductive toxicity - Fertility	Reproductive toxicity - Development
Form atembarer Stäube/ Aerosole), ausge-nommen die in dieser Liste bzw. in Anhang VI Teil 3 der CLP- Verordnung namentlich aufgeführten Cobaltverbindungen, Cobalt- haltigen Spinellen und organischen Cobalt- Sikkativen	K2	M1A	RF1A	RD1A

Storage class (TRGS 510) : 10 **Hazardous incident ordinance** 

This product is not controlled under the Germany Hazardous Incident Ordinance.

Hazard class for water

**Technical instruction on air quality control (TA Luft)** 

Number [Class]	Description	%
<b>5</b> .2.1	Total dust	29.8
5.2.5	Organic substances	23
5.2.5 [I]	Organic substances	3.9
5.2.7.1.1 [I]	Carcinogenic substances	0.16

**AOX** 

: The product contains organically bound halogens and can contribute to the AOX

value in waste water.

<u>Italy</u>

D.Lgs. 152/06 : Not determined.

**Netherlands** 

**Water Discharge Policy** 

(ABM)

: A(3) Hazardous for aquatic organisms, may have long-term hazardous effects in

aquatic environment. Decontamination effort: A

**Norway Sweden Switzerland** 

**VOC** content : VOC (w/w): 3.8%

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

**Montreal Protocol** 

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

**Rotterdam Convention on Prior Informed Consent (PIC)** 

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

Date of issue/Date of revision : 06/11/2025 Date of previous issue : 08/05/2025 Version :7 22/24 Label No : 1/35797

### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

### Full text of abbreviated H statements

<b>⊮</b> 302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

### Full text of classifications [CLP/GHS]

Cute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1

Date of issue/ Date of

Date of previous issue

: 06/11/2025

revision

: 08/05/2025

Version

: 7

TEKNOCRYL AQUA COMBI 2780-91 All vari

#### **Notice to reader**

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision : 06/11/2025 Date of previous issue : 08/05/2025 Version : 7 23/24

Label No : 1/35797

: 08/05/2025 Version :7 Date of issue/Date of revision : 06/11/2025 Date of previous issue 24/24 **Label No** : 1/35797