

# SAFETY DATA SHEET



TEKNODUR 0210 - All variants

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : TEKNODUR 0210 - All variants

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Paint.

### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

**e-mail address of person responsible for this SDS** : Prod-safe@teknos.com

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

**Telephone number** : Emergency medical information: (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland.  
Members of the public Number (8 am-10 pm): +353 (0)1 809 2166  
Healthcare professional telephone Number (24hrs): +353 (0)1 809 2566

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226  
Skin Irrit. 2, H315  
Eye Irrit. 2, H319  
Skin Sens. 1, H317  
STOT SE 3, H335  
STOT SE 3, H336  
STOT RE 2, H373  
Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Warning

**Hazard statements** : H226 - Flammable liquid and vapour.  
H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H335 - May cause respiratory irritation.  
H336 - May cause drowsiness or dizziness.  
H373 - May cause damage to organs through prolonged or repeated exposure.  
H412 - Harmful to aquatic life with long lasting effects.

**Date of issue/Date of revision**

: 25/02/2026

**Date of previous issue**

: 10/10/2022

**Version** : 2 1/26

TEKNODUR 0210 - All variants

**Label No** : 42462

## SECTION 2: Hazards identification

### Precautionary statements

- Prevention** : P280 - Wear protective gloves. Wear eye or face protection.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 - Do not breathe vapour.
- Response** : P314 - Get medical advice/attention if you feel unwell.
- Storage** : P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
- Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazardous ingredients** :  Contains: 2-Methoxy-1-methylethyl acetate; Solvent naphtha (petroleum), light aromatic; Xylene and Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

**Supplemental label elements** :

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** :

### 2.3 Other hazards

**Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification** : None known.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures** : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
<input checked="" type="checkbox"/> 2-Methoxy-1-methylethyl acetate	REACH #: 01-2119475791-29 EC: 203-603-9 CAS: 108-65-6 Index: 607-195-00-7	≥25 - ≤50	Flam. Liq. 3, H226 STOT SE 3, H336	-	[1] [2]
Solvent naphtha (petroleum), light aromatic	REACH #: 01-2119455851-35 EC: 265-199-0 CAS: 64742-95-6 Index: 649-356-00-4	≥10 - ≤17	Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	-	[1]
Xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	≥10 - ≤25	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 (oral, inhalation) Asp. Tox. 1, H304 Aquatic Chronic 3,	ATE [Dermal] = 1100 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]

Date of issue/Date of revision

: 25/02/2026

Date of previous issue

: 10/10/2022

Version : 2

2/26

EK NODUR 0210 - All variants

Label No :  42462

## SECTION 3: Composition/information on ingredients

n-Butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1	≤5	H412 Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	-	[1] [2]
Siliciumdioxide, Amorphous	REACH #: 01-2119379499-16 EC: 231-545-4 CAS: 112945-52-5	≤5	Not classified.	-	[2]
Polyethylene wax	REACH #: 01-2119488076-30 EC: 232-315-6 CAS: 8002-74-2	≤3	Not classified.	-	[2]
Ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≤3	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) (oral, inhalation) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyloxypoly(oxyethylene)	EC: 400-830-7 Index: 607-176-00-3	<1	Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
Reaction mass of Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	REACH #: 01-2119491304-40 EC: 915-687-0 CAS: 1065336-91-5	≤0.72	Skin Sens. 1A, H317 Repr. 2, H361f Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
Styrene	REACH #: 01-2119457861-32 EC: 202-851-5 CAS: 100-42-5	<1	Flam. Liq. 3, H226 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361 STOT SE 3, H335 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 3, H412 <b>See Section 16 for the full text of the H statements declared above.</b>	ATE [Inhalation (gases)] = 2770 ppm	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

## SECTION 3: Composition/information on ingredients

### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

## SECTION 4: First aid measures

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
metal oxide/oxides

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and material for containment and cleaning up

- Small spill** :  Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## SECTION 6: Accidental release measures

**Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

**6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. See Section 10 for incompatible materials before handling or use.

#### Seveso Directive - Reporting thresholds

##### Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c	5000 tonnes	50000 tonnes

### 7.3 Specific end use(s)

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
<p><input checked="" type="checkbox"/> Methoxy-1-methylethyl acetate</p> <p>Xylene</p> <p>n-Butyl acetate</p> <p>Siliciumdioxide, Amorphous</p> <p>Polyethylene wax</p> <p>Ethylbenzene</p> <p>Styrene</p>	<p><b>NAOSH (Ireland, 4/2024)</b> Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values                      OELV 8 hours: 50 ppm.                      OELV 8 hours: 275 mg/m<sup>3</sup>.                      OELV 15 minutes: 100 ppm.                      OELV 15 minutes: 550 mg/m<sup>3</sup>.</p> <p><b>NAOSH (Ireland, 4/2024) [xylene]</b> Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values                      OELV 8 hours: 50 ppm.                      OELV 8 hours: 221 mg/m<sup>3</sup>.                      OELV 15 minutes: 100 ppm.                      OELV 15 minutes: 442 mg/m<sup>3</sup>.</p> <p><b>NAOSH (Ireland, 4/2024)</b> Notes: EU derived Occupational Exposure Limit Values                      OELV 8 hours: 50 ppm.                      OELV 8 hours: 241 mg/m<sup>3</sup>.                      OELV 15 minutes: 150 ppm.                      OELV 15 minutes: 723 mg/m<sup>3</sup>.</p> <p><b>NAOSH (Ireland, 4/2024) [silica, amorphous]</b> Notes: Advisory Occupational Exposure Limit Values (OELVs)                      OELV 8 hours: 6 mg/m<sup>3</sup>. Form: inhalable dust.                      OELV 8 hours: 2.4 mg/m<sup>3</sup>. Form: respirable dust.</p> <p><b>NAOSH (Ireland, 4/2024)</b> Notes: Advisory Occupational Exposure Limit Values (OELVs)                      OELV 8 hours: 2 mg/m<sup>3</sup>. Form: fume.                      OELV 15 minutes: 6 mg/m<sup>3</sup>. Form: fume.</p> <p><b>NAOSH (Ireland, 4/2024)</b> Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values                      OELV 8 hours: 100 ppm.                      OELV 8 hours: 442 mg/m<sup>3</sup>.                      OELV 15 minutes: 200 ppm.                      OELV 15 minutes: 884 mg/m<sup>3</sup>.</p> <p><b>NAOSH (Ireland, 4/2024)</b> Notes: Advisory Occupational Exposure Limit Values (OELVs)                      OELV 8 hours: 20 ppm.                      OELV 8 hours: 85 mg/m<sup>3</sup>.                      OELV 15 minutes: 40 ppm.                      OELV 15 minutes: 170 mg/m<sup>3</sup>.</p>

#### Biological exposure indices

Product/ingredient name	Exposure indices
<p><input checked="" type="checkbox"/> Xylene</p> <p>Ethylbenzene</p>	<p><b>NAOSH BGVs (Ireland, 1/2011) [Xylene]</b>                      BMGV: 1.5 g/g creatinine, methylhippuric acids [in urine].                      Sampling time: end of shift - As soon as possible after exposure ceases.</p> <p><b>NAOSH BGVs (Ireland, 1/2011)</b>                      BMGV: Semi-quantitative, the biological analyte is an indicator of exposure to the substance but the quantitative interpretation of the measurement is ambiguous. These analytes should be used as a screening test if a quantitative test is not practical; or as a confirmatory test if the quantitative test is not specific and the origin of the determinant is in question., ethylbenzene [in endexhaled air].                      Sampling time: not critical.                      BMGV: 0.7 g/g creatinine [Semi-quantitative, the biological</p>

## SECTION 8: Exposure controls/personal protection

Styrene

analyte is an indicator of exposure to the substance but the quantitative interpretation of the measurement is ambiguous. These analytes should be used as a screening test if a quantitative test is not practical; or as a confirmatory test if the quantitative test is not specific and the origin of the determinant is in question.], mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: end of shift at end of workweek.

### NAOSH BGVs (Ireland, 1/2011)

BMGV: 0.2 mg/l [Semi-quantitative, the biological analyte is an indicator of exposure to the substance but the quantitative interpretation of the measurement is ambiguous. These analytes should be used as a screening test if a quantitative test is not practical; or as a confirmatory test if the quantitative test is not specific and the origin of the determinant is in question.], styrene [in venous blood]. Sampling time: end of shift - As soon as possible after exposure ceases.

BMGV: 400 mg/g creatinine, mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases.

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs/DMELs

#### Product/ingredient name

-Methoxy-1-methylethyl acetate

#### Result

##### DNEL - General population - Long term - Inhalation

33 mg/m<sup>3</sup>

Effects: Local

##### DNEL - General population - Long term - Inhalation

33 mg/m<sup>3</sup>

Effects: Systemic

##### DNEL - General population - Long term - Oral

36 mg/kg bw/day

Effects: Systemic

##### DNEL - Workers - Long term - Inhalation

275 mg/m<sup>3</sup>

Effects: Systemic

##### DNEL - General population - Long term - Dermal

320 mg/kg bw/day

Effects: Systemic

##### DNEL - Workers - Short term - Inhalation

550 mg/m<sup>3</sup>

Effects: Local

##### DNEL - Workers - Long term - Dermal

796 mg/kg bw/day

Effects: Systemic

Solvent naphtha (petroleum), light aromatic

##### DNEL - General population - Long term - Inhalation

0.41 mg/m<sup>3</sup>

Effects: Systemic

## SECTION 8: Exposure controls/personal protection

### **DNEL - Workers - Long term - Inhalation**

1.9 mg/m<sup>3</sup>

Effects: Systemic

### **DNEL - General population - Long term - Inhalation**

178.57 mg/m<sup>3</sup>

Effects: Local

### **DNEL - General population - Short term - Inhalation**

640 mg/m<sup>3</sup>

Effects: Local

### **DNEL - Workers - Long term - Inhalation**

837.5 mg/m<sup>3</sup>

Effects: Local

### **DNEL - Workers - Short term - Inhalation**

1066.67 mg/m<sup>3</sup>

Effects: Local

### **DNEL - General population - Short term - Inhalation**

1152 mg/m<sup>3</sup>

Effects: Systemic

### **DNEL - Workers - Short term - Inhalation**

1286.4 mg/m<sup>3</sup>

Effects: Systemic

Xylene

### **DNEL - General population - Long term - Oral**

5 mg/kg bw/day

Effects: Systemic

### **DNEL - General population - Long term - Inhalation**

65.3 mg/m<sup>3</sup>

Effects: Local

### **DNEL - General population - Long term - Inhalation**

65.3 mg/m<sup>3</sup>

Effects: Systemic

### **DNEL - General population - Long term - Dermal**

125 mg/kg bw/day

Effects: Systemic

### **DNEL - Workers - Long term - Dermal**

212 mg/kg bw/day

Effects: Systemic

### **DNEL - Workers - Long term - Inhalation**

221 mg/m<sup>3</sup>

Effects: Local

### **DNEL - Workers - Long term - Inhalation**

221 mg/m<sup>3</sup>

Effects: Systemic

### **DNEL - General population - Short term - Inhalation**

260 mg/m<sup>3</sup>

Effects: Local

### **DNEL - General population - Short term - Inhalation**

260 mg/m<sup>3</sup>

Effects: Systemic

### **DNEL - Workers - Short term - Inhalation**

## SECTION 8: Exposure controls/personal protection

	442 mg/m <sup>3</sup> <u>Effects</u> : Local
	<b>DNEL - Workers - Short term - Inhalation</b> 442 mg/m <sup>3</sup> <u>Effects</u> : Systemic
n-Butyl acetate	<b>DNEL - General population - Long term - Oral</b> 2 mg/kg bw/day <u>Effects</u> : Systemic
	<b>DNEL - General population - Short term - Oral</b> 2 mg/kg bw/day <u>Effects</u> : Systemic
	<b>DNEL - General population - Long term - Dermal</b> 3.4 mg/kg bw/day <u>Effects</u> : Systemic
	<b>DNEL - General population - Short term - Dermal</b> 6 mg/kg bw/day <u>Effects</u> : Systemic
	<b>DNEL - Workers - Long term - Dermal</b> 7 mg/kg bw/day <u>Effects</u> : Systemic
	<b>DNEL - Workers - Short term - Dermal</b> 11 mg/kg bw/day <u>Effects</u> : Systemic
	<b>DNEL - General population - Long term - Inhalation</b> 12 mg/m <sup>3</sup> <u>Effects</u> : Systemic
	<b>DNEL - General population - Long term - Inhalation</b> 35.7 mg/m <sup>3</sup> <u>Effects</u> : Local
	<b>DNEL - Workers - Long term - Inhalation</b> 48 mg/m <sup>3</sup> <u>Effects</u> : Systemic
	<b>DNEL - General population - Short term - Inhalation</b> 300 mg/m <sup>3</sup> <u>Effects</u> : Local
	<b>DNEL - General population - Short term - Inhalation</b> 300 mg/m <sup>3</sup> <u>Effects</u> : Systemic
	<b>DNEL - Workers - Long term - Inhalation</b> 300 mg/m <sup>3</sup> <u>Effects</u> : Local
	<b>DNEL - Workers - Short term - Inhalation</b> 600 mg/m <sup>3</sup> <u>Effects</u> : Local
	<b>DNEL - Workers - Short term - Inhalation</b> 600 mg/m <sup>3</sup> <u>Effects</u> : Systemic
Ethylbenzene	<b>DMEL - Workers - Long term - Inhalation</b> 442 mg/m <sup>3</sup> <u>Effects</u> : Local

## SECTION 8: Exposure controls/personal protection

### DMEL - Workers - Short term - Inhalation

884 mg/m<sup>3</sup>

Effects: Systemic

### DNEL - General population - Long term - Oral

1.6 mg/kg bw/day

Effects: Systemic

### DNEL - General population - Long term - Inhalation

15 mg/m<sup>3</sup>

Effects: Systemic

### DNEL - Workers - Long term - Inhalation

77 mg/m<sup>3</sup>

Effects: Systemic

### DNEL - Workers - Long term - Dermal

180 mg/kg bw/day

Effects: Systemic

### DNEL - Workers - Short term - Inhalation

293 mg/m<sup>3</sup>

Effects: Local

### DNEL - General population - Long term - Oral

0.18 mg/kg bw/day

Effects: Systemic

### DNEL - General population - Long term - Inhalation

0.31 mg/m<sup>3</sup>

Effects: Systemic

### DNEL - General population - Long term - Dermal

0.9 mg/kg bw/day

Effects: Systemic

### DNEL - Workers - Long term - Inhalation

1.27 mg/m<sup>3</sup>

Effects: Systemic

### DNEL - Workers - Long term - Dermal

1.8 mg/kg bw/day

Effects: Systemic

### DNEL - General population - Long term - Oral

7.7 µg/kg bw/day

Effects: Systemic

### DNEL - General population - Long term - Inhalation

1 mg/m<sup>3</sup>

Effects: Local

### DNEL - General population - Long term - Inhalation

1 mg/m<sup>3</sup>

Effects: Systemic

### DNEL - General population - Short term - Inhalation

10 mg/m<sup>3</sup>

Effects: Local

### DNEL - General population - Short term - Inhalation

10 mg/m<sup>3</sup>

Effects: Systemic

### DNEL - Workers - Long term - Inhalation

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Styrene

## SECTION 8: Exposure controls/personal protection

85 mg/m<sup>3</sup>

Effects: Systemic

### **DNEL - Workers - Short term - Inhalation**

100 mg/m<sup>3</sup>

Effects: Local

### **DNEL - Workers - Long term - Inhalation**

100 mg/m<sup>3</sup>

Effects: Local

### **DNEL - Workers - Short term - Inhalation**

100 mg/m<sup>3</sup>

Effects: Systemic

### **DNEL - General population - Long term - Dermal**

343 mg/kg bw/day

Effects: Systemic

### **DNEL - Workers - Long term - Dermal**

406 mg/kg bw/day

Effects: Systemic

### **PNECs**

Not available.

## **8.2 Exposure controls**

### **Appropriate engineering controls**

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### **Individual protection measures**

#### **Hygiene measures**

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Eye/face protection**

- : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### **Skin protection**

#### **Hand protection**

- : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations : Wear suitable gloves tested to EN374.

< 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm

1 - 4 hours (breakthrough time): polyvinyl alcohol (PVA) thickness > 0.3 mm or 4H / Silver Shield® gloves.

> 8 hours (breakthrough time): Viton® thickness > 0.3 mm gloves

Wash hands before breaks and immediately after handling the product.

## SECTION 8: Exposure controls/personal protection

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.  
Filter type: A  
Filter type (spray application): A P
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : Various
- Odour** : Slight
- Odour threshold** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** :

Ingredient name	°C	°F	Method
n-Butyl acetate	126	258.8	OECD 103
Solvent naphtha (petroleum), light aromatic	135 to 210	275 to 410	

- Flammability** : Not available.
- Lower and upper explosion limit** : Lower: 0.8% (xylene)  
Upper: 7.6% (Solvent naphtha (petroleum), light arom.)
- Flash point** : Closed cup: 25°C (77°F)
- Auto-ignition temperature** :

Ingredient name	°C	°F	Method
Polyethylene wax	244.85	472.7	
Solvent naphtha (petroleum), light aromatic	280 to 470	536 to 878	

- Decomposition temperature** : Not available.
- pH** : Not applicable.
- Viscosity** : Kinematic (40°C): >20.5 mm<sup>2</sup>/s
- Solubility(ies)** :  
Not available.
- Solubility in water** : Not available.
- Partition coefficient: n-octanol/ water** : Not applicable.
- Vapour pressure** :

## SECTION 9: Physical and chemical properties

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Butyl acetate	11.25096	1.5	DIN EN 13016-2			
Ethylbenzene	9.30076	1.2				

**Relative density** : Not available.

**Density** : 1 g/cm<sup>3</sup>

**Vapour density** : Not available.

### Particle characteristics

**Median particle size** : Not applicable.

## 9.2 Other information

### 9.2.1 Information with regard to physical hazard classes

**Explosive properties** : Not available.

**Oxidising properties** : Not available.

### 9.2.2 Other safety characteristics

Not applicable.

## SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

**10.5 Incompatible materials** : Reactive or incompatible with the following materials:  
oxidising materials

**10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Product/ingredient name

Methoxy-1-methylethyl acetate

##### Result

**Rat - Oral - LD50**  
8532 mg/kg

**Rabbit - Dermal - LD50**  
>5 g/kg

Solvent naphtha (petroleum), light aromatic

**Rat - Oral - LD50**  
8400 mg/kg  
Toxic effects: Behavioral - Somnolence (general depressed activity) Behavioral - Tremor Lung, Thorax, or Respiration - Other changes

Xylene

**Rat - Oral - LD50**  
4300 mg/kg  
Toxic effects: Liver - Other changes Kidney, Ureter, and Bladder - Other changes

## SECTION 11: Toxicological information

n-Butyl acetate	<p><b>Rat - Inhalation - LC50 Vapour</b> 21.7 mg/l [4 hours]</p> <p><b>Rat - Oral - LD50</b> 10760 mg/kg EU</p> <p><b>Rabbit - Dermal - LD50</b> 14112 mg/kg</p>
Ethylbenzene	<p><b>Rat - Inhalation - LC50 Vapour</b> 0.74 mg/l [4 hours]</p> <p><b>Rat - Oral - LD50</b> 3500 mg/kg</p> <p><b>Rabbit - Dermal - LD50</b> 15400 mg/kg</p> <p><b>Rat - Inhalation - LC50 Dusts and mists</b> 29000 mg/l [4 hours]</p>
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	<p><b>Rat - Oral - LD50</b> 3230 mg/kg</p> <p><b>Rat - Dermal - LD50</b> &gt;3170 mg/kg</p>
Styrene	<p><b>Rat - Oral - LD50</b> 2650 mg/kg <u>Toxic effects:</u> Behavioral - Somnolence (general depressed activity) Liver - Other changes</p> <p><b>Rat - Inhalation - LC50 Vapour</b> 11800 mg/m<sup>3</sup> [4 hours]</p> <p><b>Rat - Inhalation - LC50 Gas.</b> 2770 ppm [4 hours]</p>

**Conclusion/Summary [Product]** : Not available.

### Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
█EKNODUR 0210	N/A	10241.2	N/A	84.0	N/A
2-Methoxy-1-methylethyl acetate	8532	N/A	N/A	N/A	N/A
Solvent naphtha (petroleum), light aromatic	8400	N/A	N/A	N/A	N/A
Xylene	4300	1100	N/A	11	N/A
n-Butyl acetate	10760	14112	N/A	N/A	N/A
Ethylbenzene	3500	15400	N/A	11	29000
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	3230	N/A	N/A	N/A	N/A
Styrene	2650	N/A	2770	11.8	N/A

### Skin corrosion/irritation

<b>Product/ingredient name</b>	<b>Result</b>
--------------------------------	---------------

## SECTION 11: Toxicological information

Xylene

**Rat - Skin - Mild irritant**

Duration of treatment/exposure: 8 hours

Amount/concentration applied: 60 uL

**Rabbit - Skin - Moderate irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

**Rabbit - Skin - Moderate irritant**

Amount/concentration applied: 100 %

n-Butyl acetate

**Rabbit - Skin - Moderate irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

Ethylbenzene

**Rabbit - Skin - Mild irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 15 mg

Styrene

**Rabbit - Skin - Mild irritant**

Amount/concentration applied: 500 mg

**Rabbit - Skin - Moderate irritant**

Amount/concentration applied: 100 %

**Conclusion/Summary [Product]** : Not available.

### Serious eye damage/eye irritation

#### **Product/ingredient name**

Solvent naphtha (petroleum), light aromatic

#### **Result**

**Rabbit - Eyes - Mild irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 uL

Xylene

**Rabbit - Eyes - Mild irritant**

Amount/concentration applied: 87 mg

**Rabbit - Eyes - Severe irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 5 mg

n-Butyl acetate

**Rabbit - Eyes - Moderate irritant**

Amount/concentration applied: 100 mg

Ethylbenzene

**Rabbit - Eyes - Severe irritant**

Amount/concentration applied: 500 mg

Styrene

**Human - Eyes - Mild irritant**

Amount/concentration applied: 50 ppm

**Rabbit - Eyes - Moderate irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 mg

**Rabbit - Eyes - Severe irritant**

Amount/concentration applied: 100 mg

**Conclusion/Summary [Product]** : Not available.

### Respiratory corrosion/irritation

Not available.

**Conclusion/Summary [Product]** : Not available.

## SECTION 11: Toxicological information

### Respiratory or skin sensitization

Not available.

### **Skin**

**Conclusion/Summary [Product]** : Not available.

### **Respiratory**

**Conclusion/Summary [Product]** : Not available.

### Germ cell mutagenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Carcinogenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Reproductive toxicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Specific target organ toxicity (single exposure)

#### **Product/ingredient name**

Methoxy-1-methylethyl acetate  
Solvent naphtha (petroleum), light aromatic

Xylene  
n-Butyl acetate  
Styrene

#### **Result**

STOT SE 3, H336 (Narcotic effects)  
STOT SE 3, H335 (Respiratory tract irritation)  
STOT SE 3, H336 (Narcotic effects)  
STOT SE 3, H335 (Respiratory tract irritation)  
STOT SE 3, H336 (Narcotic effects)  
STOT SE 3, H335 (Respiratory tract irritation)

### Specific target organ toxicity (repeated exposure)

#### **Product/ingredient name**

Xylene  
Ethylbenzene  
Styrene

#### **Result**

STOT RE 2, H373 (oral, inhalation)  
STOT RE 2, H373 (hearing organs) (oral, inhalation)  
STOT RE 1, H372

### Aspiration hazard

#### **Product/ingredient name**

Solvent naphtha (petroleum), light aromatic  
Xylene  
Ethylbenzene  
Styrene

#### **Result**

ASPIRATION HAZARD - Category 1  
ASPIRATION HAZARD - Category 1  
ASPIRATION HAZARD - Category 1  
ASPIRATION HAZARD - Category 1

### Information on likely routes of exposure

Not available.

### Potential acute health effects

- Eye contact** : Causes serious eye irritation.  
**Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.  
**Skin contact** : Causes skin irritation. May cause an allergic skin reaction.  
**Ingestion** : Can cause central nervous system (CNS) depression.

### Symptoms related to the physical, chemical and toxicological characteristics

## SECTION 11: Toxicological information

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Potential chronic health effects

Not available.

**Conclusion/Summary [Product]** : Not available.

**General** : May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Reproductive toxicity** : No known significant effects or critical hazards.

### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

#### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product/ingredient name

☑ Solvent naphtha (petroleum), light aromatic

#### Result

##### Acute - LC50

Fish  
9.2 mg/l [96 hours]

##### Acute - EC50

Daphnia  
3.2 mg/l [48 hours]

n-Butyl acetate

##### Acute - LC50 - Fresh water

Fish - Fathead minnow - *Pimephales promelas*

## SECTION 12: Ecological information

Age: 31 to 32 days; Size: 21.6 mm; Weight: 0.175 g  
18000 µg/l [96 hours]  
Effect: Mortality

### Acute - LC50 - Marine water

Crustaceans - Brine shrimp - *Artemia salina*  
32 mg/l [48 hours]  
Effect: Mortality

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

### Acute - LC50

OECD [Fish, Acute Toxicity Test]  
Fish - *Brachydanio rerio*  
0.9 mg/l [96 hours]

### EC50

OECD [Alga, Growth Inhibition Test]  
Aquatic plants - *Desmodesmodus subspicatus*  
1.68 mg/l [72 hours]

### Chronic - NOEC

OECD [Daphnia Magna Reproduction Test]  
Daphnia - Daphnia  
1 mg/l [21 days]

Styrene

### Acute - LC50 - Fresh water

Fish - Fathead minnow - *Pimephales promelas*  
Age: 30 days; Size: 19 mm; Weight: 0.101 g  
4020 µg/l [96 hours]  
Effect: Mortality

### Acute - EC50 - Fresh water

Daphnia - Water flea - *Daphnia magna*  
Age: ≤24 hours  
4700 µg/l [48 hours]  
Effect: Mortality

### Acute - EC50 - Fresh water

Algae - Green algae - *Pseudokirchneriella subcapitata*  
720 µg/l [96 hours]  
Effect: Population

### Chronic - NOEC - Fresh water

Algae - Green algae - *Pseudokirchneriella subcapitata*  
63 µg/l [96 hours]  
Effect: Population

**Conclusion/Summary [Product]** : Not available.

### 12.2 Persistence and degradability

Not available.

**Conclusion/Summary [Product]** : Not available.

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
2-Methoxy-1-methylethyl acetate	1.2	-	Low
Solvent naphtha (petroleum), light aromatic	-	10 to 2500	High
Xylene	3.12	8.1 to 25.9	Low
n-Butyl acetate	2.3	-	Low
Ethylbenzene	3.6	-	Low
Styrene	2.96	13.49	Low

## SECTION 12: Ecological information

### 12.4 Mobility in soil

#### Soil/water partition coefficient

Product/ingredient name	logKoc	Koc
☑Methoxy-1-methylethyl acetate	0.36	2.31363
n-Butyl acetate	1.5	33.2139
Ethylbenzene	2.2	170.406
Styrene	3	896.322

#### Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
☑Methoxy-1-methylethyl acetate	No	No	No	No	No	No	No
Solvent naphtha (petroleum), light aromatic	No	No	No	No	No	No	No
Xylene	No	No	No	No	No	No	No
n-Butyl acetate	No	No	No	No	No	No	No
Ethylbenzene	No	No	No	No	No	No	No
Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyloxypoly(oxyethylene)	No	No	No	No	No	No	No
Reaction mass of Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	No	No	No	No	No	No	No
Styrene	No	No	No	No	No	No	No

**Mobility** : Not available.

**Conclusion/Summary** : ☑The product does not meet the criteria to be considered as a PMT or vPvM.

### 12.5 Results of PBT and vPvB assessment

#### Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
☑Methoxy-1-methylethyl acetate	No	N/A	N/A	No	N/A	N/A	N/A
Solvent naphtha (petroleum), light aromatic	No	N/A	No	No	No	N/A	No
Xylene	No	N/A	No	Yes	No	N/A	No
n-Butyl acetate	No	N/A	N/A	No	N/A	N/A	N/A
Ethylbenzene	N/A	N/A	N/A	Yes	N/A	N/A	N/A
Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-	No	N/A	N/A	No	N/A	N/A	N/A

## SECTION 12: Ecological information

butyl-4-hydroxyphenyl) propionyloxypoly (oxyethylene)								
Reaction mass of Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	N/A	N/A	N/A	Yes	N/A	N/A	N/A	N/A
Styrene	No	N/A	No	Yes	No	N/A	No	No

### Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
2-Methoxy-1-methylethyl acetate	No	No	No	No	No	No	No
Solvent naphtha (petroleum), light aromatic	No	No	No	No	No	No	No
Xylene	No	No	No	No	No	No	No
n-Butyl acetate	No	No	No	No	No	No	No
Ethylbenzene	No	No	No	No	No	No	No
Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyloxypoly (oxyethylene)	No	No	No	No	No	No	No
Reaction mass of Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	No	No	No	No	No	No	No
Styrene	No	No	No	No	No	No	No

**Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP]** : The product does not meet the criteria to be considered as a PBT or vPvB.

### 12.6 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : Avoid release to the environment. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.

**European waste catalogue (EWC)** : 080111\*, 200127\*

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3 	3 	3 	3 
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	No.	No.	No.	No.

#### Additional information

**ADR/RID** : **Viscous liquid exception** This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.  
**Tunnel code (D/E)**

**ADN** : **Viscous liquid exception** This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.

**IMDG** : **Viscous liquid exception** This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.3.2.5.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in bulk according to IMO instruments** : Not relevant/applicable due to nature of the product.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

###### Annex XIV

None of the components are listed.

###### Substances of very high concern

None of the components are listed.

##### Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
<input checked="" type="checkbox"/> EK NODUR 0210	≥90	3

Labelling :

##### Synthetic polymer microparticles - Designation 78

Generic identity of polymer(s) :  901 - Polymers of ethylene., 3902 - Polymers of propylene or of other olefins.

Total percentage of synthetic polymer microparticles :  3%

The synthetic polymer microparticles supplied is subject to conditions laid down by entry 78 of Annex XVII to Regulation (EC) No 1907/2006 of the European Parliament and of the Council.

##### Other EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Explosive precursors :  Not applicable.

##### Ozone depleting substances (EU 2024/590)

Not listed.

##### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

##### Persistent Organic Pollutants

Not listed.

##### Seveso Directive

This product is controlled under the Seveso Directive.

##### Danger criteria

###### Category

5c

##### International regulations

##### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

##### Montreal Protocol

Not listed.

##### Stockholm Convention on Persistent Organic Pollutants

Not listed.

## SECTION 15: Regulatory information

### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

#### 15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

#### Abbreviations and acronyms

: ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
N/A = Not available  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
SGG = Segregation Group  
vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 3, H226	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1, H317	Calculation method
STOT SE 3, H335	Calculation method
STOT SE 3, H336	Calculation method
STOT RE 2, H373	Calculation method
Aquatic Chronic 3, H412	Calculation method

#### Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H361f	Suspected of damaging fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### Full text of classifications [CLP/GHS]

## SECTION 16: Other information

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

**Date of issue/ Date of revision** : 25/02/2026

**Date of previous issue** : 10/10/2022

**Version** : 2

TEKNODUR 0210

All variants

### Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

