Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Ireland

# **SAFETY DATA SHEET**



TEKNODUR AQUA 3394-03 - All variants

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

# 1.1 Product identifier

Product name : TEKNODUR AQUA 3394-03 - All variants

**1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use**: Paint.

### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091. e-mail address of person : Prod-safe@teknos.com responsible for this SDS

### **National contact**

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

### 1.4 Emergency telephone number

### National advisory body/Poison Centre

Telephone number : National Poisons Information Centre: 01 809 2566

# **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

Hazard pictograms



Signal word	Narning	
Hazard statements	H317 - May cause an allergic skin reaction. H412 - Harmful to aquatic life with long lasting effects.	
Precautionary statements		
Prevention	P280 - Wear protective gloves. P273 - Avoid release to the environment. P261 - Avoid breathing vapour.	
Response	P362 + P364 - Take off contaminated clothing and wash it before reu P302 + P352 - IF ON SKIN: Wash with plenty of water.	se.
Storage	Not applicable.	
Disposal	P501 - Dispose of contents and container in accordance with all local national and international regulations.	, regional,

# **SECTION 2: Hazards identification**

Hazardous ingredients	<ul> <li>Contains: EO bis(benztriazolyl)phenylpropionat; Reaction mass of Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl- 4-piperidyl sebacate and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)</li> </ul>
Supplemental label elements	: Contains biocidal products for in-can preservation: BIT and DTBMA and MBIT.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:
2.3 Other hazards	
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do	: None known.

Other hazards which do not result in classification

# **SECTION 3: Composition/information on ingredients**

Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	≤3	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	ATE [Oral] = 1200 mg/kg ATE [Inhalation (vapours)] = 3 mg/l	[1] [2]
REACH #: 01-0000015075-76 EC: 400-830-7 CAS: 104810-48-2 Index: 607-176-00-3	<1	Skin Sens. 1A, H317 Aquatic Chronic 2, H411	-	[1]
REACH #: 01-2119491304-40 EC: 915-687-0 CAS: 1065336-91-5	≤1	Skin Sens. 1A, H317 Repr. 2, H361f Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
REACH #: 01-2119475467-26 EC: 204-469-4 CAS: 121-44-8 Index: 612-004-00-5	≤0.3	Flam. Liq. 2, H225 Acute Tox. 4, H302 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335	ATE [Oral] = 460 mg/kg ATE [Dermal] = 300  mg/kg ATE [Inhalation (vapours)] = 3 mg/l STOT SE 3, H335: $C \ge 1\%$	[1] [2]
CAS: 55965-84-9 Index: 613-167-00-5	<0.001	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1,	ATE [Oral] = 53 mg/ kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C,	[1]
	REACH #:         01-2119475108-36         EC: 203-905-0         CAS: 111-76-2         Index: 603-014-00-0         REACH #:         01-0000015075-76         EC: 400-830-7         CAS: 104810-48-2         Index: 607-176-00-3         REACH #:         01-2119491304-40         EC: 915-687-0         CAS: 1065336-91-5         REACH #:         01-2119475467-26         EC: 204-469-4         CAS: 121-44-8         Index: 612-004-00-5         CAS: 55965-84-9	REACH #:       ≤3         01-2119475108-36       ≤3         EC: 203-905-0       CAS: 111-76-2         Index: 603-014-00-0       REACH #:         01-0000015075-76       <1	REACH #:       ≤3       Acute Tox. 4, H302         01-2119475108-36       ≤3       Acute Tox. 3, H331         EC: 203-905-0       CAS: 111-76-2       Skin Irrit. 2, H315         Index: 603-014-00-0       REACH #:       <1	Identifiers $7_{0}$ ClassificationLimits, M-factors and ATEs and ATEsREACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0 $\leq$ 3Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319ATE [Oral] = 1200 mg/kg ATE [Inhalation (vapours)] = 3 mg/lREACH #: 01-0000015075-76 EC: 400-830-7 CAS: 104810-48-2 Index: 607-176-00-3 $<1$ Skin Sens. 1A, H317 Aquatic Chronic 2, H411-REACH #: 01-211947940740 CAS: 1065336-91-5 $\leq 1$ Skin Sens. 1A, H317 Repr. 2, H361f Aquatic Chronic 1, H410M [Acute] = 1 M [Chronic] = 1REACH #: 01-2119475467-26 EC: 204-469-4 CAS: 121-44-8 Index: 612-004-00-5 $\leq 0.3$ Flam. Liq. 2, H225 Acute Tox. 3, H311 Acute Tox. 3, H311 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335ATE [Oral] = 460 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (vapours)] = 3 mg/l STOT SE 3, H335CAS: 55965-84-9 Index: 613-167-00-5 $<0.001$ Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H310 AC

# **SECTION 3: Composition/information on ingredients**

H410	H314: C ≥ 0.6%
EUH071	Eye Dam. 1, H318:
	C ≥ 0.6%
	Eye Irrit. 2, H319:
	0.06% ≤ C < 0.6%
	Skin Sens. 1, H317:
	C ≥ 0.0015%
	M [Acute] = 100
	M [Chronic] = 100
See Section 16 for	
the full text of the H	
statements declared	
above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

# **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	-	Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/sym	<u>ptoms</u>			
Eye contact	: No specific			
Inhalation	: No specific			
Skin contact	: Adverse sy irritation redness	mptoms may include the	e following:	
Ingestion	: No specific	data.		
Date of issue/Date of revision	: 26/10/2023	Date of previous issue	: 05/07/2022	Version
TELANOBUE ACUA ACOA	AU · /			

# **SECTION 4: First aid measures**

### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.

# **SECTION 5: Firefighting measures**

5.1 Extinguishing media		
Suitable extinguishing media	:	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	:	None known.
5.2 Special hazards arising f	rom	the substance or mixture
Hazards from the substance or mixture	:	In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

# **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures			
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.	
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.	

#### 6.3 Methods and material for containment and cleaning up

Small spill: Stop leak if without risk. Move containers from spill area. Dilute with water and mop<br/>up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry<br/>material and place in an appropriate waste disposal container. Dispose of via a<br/>licensed waste disposal contractor.

:05/07/2022

## SECTION 6<sup>.</sup> Accidental release measures

olo non o. Accidental release measures		
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.	
6.4 Reference to other sections	<ul> <li>See Section 1 for emergency contact information.</li> <li>See Section 8 for information on appropriate personal protective equipment.</li> <li>See Section 13 for additional waste treatment information.</li> </ul>	

# **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

### 7.3 Specific end use(s)

**Recommendations** 

- : Not available.
- Industrial sector specific solutions
- : Not available.

# SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

### **Occupational exposure limits**

Product/ingredient name	Exposure limit values
₽-Butoxyethanol Triethylamine	<ul> <li>NAOSH (Ireland, 5/2021). Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values</li> <li>OELV-8hr: 20 ppm 8 hours.</li> <li>OELV-8hr: 98 mg/m<sup>3</sup> 8 hours.</li> <li>OELV-15min: 50 ppm 15 minutes.</li> <li>OELV-15min: 246 mg/m<sup>3</sup> 15 minutes.</li> <li>NAOSH (Ireland, 5/2021). Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values</li> <li>OELV-8hr: 2 ppm 8 hours.</li> <li>OELV-8hr: 8.4 mg/m<sup>3</sup> 8 hours.</li> <li>OELV-15min: 3 ppm 15 minutes.</li> </ul>
Date of issue/Date of revision : 26/10/2	23 Date of previous issue : 05/07/2022 Version : 1.04 5/15
TEKNODUR AQUA 3394-03 - All variants	Label No :52215

# SECTION 8: Exposure controls/personal protection

OELV-15min: 12.6 mg/m<sup>3</sup> 15 minutes.

### **Biological exposure indices**

Product/ingredient name	Exposure indices		
2-Butoxyethanol	NAOSH (Ireland, 1/2011) BMGV: 200 mg/g creatinine, BAA [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases.		
procedures European assessmen values and atmospher of exposur (Workplace for the mea	should be made to monitoring standards, such as the following: Standard EN 689 (Workplace atmospheres - Guidance for the nt of exposure by inhalation to chemical agents for comparison with limit measurement strategy) European Standard EN 14042 (Workplace es - Guide for the application and use of procedures for the assessment e to chemical and biological agents) European Standard EN 482 e atmospheres - General requirements for the performance of procedures asurement of chemical agents) Reference to national guidance of or methods for the determination of hazardous substances will also be		

### **DNELs/DMELs**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
2-Butoxyethanol	DNEL	Long term Oral	6.3 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	26.7 mg/	General	Systemic
	DNEL	Long term	kg bw/day 59 mg/m³	population General	Systemic
	DNEL	Inhalation Long term Inhalation	98 mg/m³	population Workers	Systemic
	DNEL	Short term Inhalation	147 mg/m³	General population	Local
	DNEL	Short term Inhalation	246 mg/m³	Workers	Local
	DNEL	Short term Inhalation	426 mg/m³	General population	Systemic
	DNEL	Short term Inhalation	1091 mg/ m³	Workers	Systemic
Triethylamine	DNEL	Long term Inhalation	8.4 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Inhalation	8.4 mg/m³	Workers	Systemic
	DNEL	Long term Dermal	12.1 mg/ kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	12.6 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	12.6 mg/m³	Workers	Systemic
reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6]	DNEL	Long term Inhalation	0.02 mg/m³	General population	Local
(3:1)	DNEL	Long term	0.02 mg/m³	Workers	Local
	DNEL	Inhalation Short term Inhalation	0.04 mg/m³		Local
	DNEL	Short term	0.04 mg/m³	population Workers	Local
	DNEL	Long term Oral	0.09 mg/ kg bw/day	General population	Systemic
	DNEL	Short term Oral	0.11 mg/ kg bw/day	General population	Systemic

### **PNECs**

No PNECs available

Date of issue/Date of revision

# **SECTION 8: Exposure controls/personal protection**

.2 Exposure controls	
Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborn contaminants.
Individual protection measured	<u>ires</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period Appropriate techniques should be used to remove potentially contaminated clothing Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard shoul be worn at all times when handling chemical products if a risk assessment indicate this is necessary. Considering the parameters specified by the glove manufacture check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
	Recommendations : Wear suitable gloves tested to EN374.
	> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm
	Not recommended polyvinyl alcohol (PVA) gloves
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other importan aspects of use.
	Filter type (spray application): A P
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

: Liquid.
: Various
: Slight
: Not available.
: Not available.
:

0/2023 Date of previous issue

Ingredient name		°(	C	°F	Method	
water		1(	00	212		
2-Butoxyethanol		17	71 to 171.5	339.8 to 340.7	IP 123-93	
Flammability	:	Not availa	ble.	1		
-ower and upper explosion imit	:		ot applicable ot applicable			
Flash point	:	Closed cu	p: >100°C (	>212°F)		
Auto-ignition temperature	:					
Ingredient name		°	C	°F	Method	
Propanol, 1-(2-butoxy-1-methylethoxy)		19	94	381.2	EU A.15	
2-Butoxyethanol		23	30	446	DIN 51794	
Decomposition temperature	:	Not availa	ble.			
ЭΗ	:	7.8 to 8.3	[Conc. (% w	ı/w): 100%]		
/iscosity	:	Not availa	ble.			
Solubility(ies)	:					
Not available.						
Solubility in water	:	Not availa	ble.			
Partition coefficient: n-octanol/ water	:	Not applic	able.			

### Vapour pressure

	Va	Vapour Pressure at 20°C			Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
water	17.5	2.3					
2-Butoxyethanol	0.75006	0.1					
elative density	: Not	available.		·		·	
ensity	: 1 g/	cm³					
apour density	: Not	available.					
xplosive properties	: Not	available.					
xidising properties	: Not	available.					
article characteristics							
Median particle size	: Not	applicable.					

# SECTION 10: Stability and reactivity

1

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredie	ents.
10.2 Chemical stability	The product is stable.	
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur	r.
10.4 Conditions to avoid	No specific data.	
10.5 Incompatible materials	No specific data.	
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition product should not be produced.	ts

Date of issue/Date of revision	: 26/10/2023	Date of previous issue	:05/07/2022	Version : 1.04 8/15
TEKNODUR AQUA 3394-03 - AI	l variants			Label No :52215

# **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Reaction mass of Bis (1,2,2,6,6-pentamethyl- 4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl- 4-piperidyl sebacate	LD50 Dermal	Rat	>3170 mg/kg	-
Triethylamine reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	LD50 Oral LD50 Oral LD50 Oral	Rat Rat Rat	3230 mg/kg 460 mg/kg 53 mg/kg	- - -

# **Conclusion/Summary**

: Based on available data, the classification criteria are not met.

### Acute toxicity estimates

Route	ATE value
Øral	62176.17 mg/kg
Dermal	152439.02 mg/kg
Inhalation (vapours)	141.06 mg/l

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation		
2-Butoxyethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100	-		
	Fuer Course inside t	Dabbit		mg			
	Eyes - Severe irritant Skin - Mild irritant	Rabbit Rabbit	-	100 mg 500 mg	-		
Triethylamine	Skin - Mild irritant	Rabbit	-	365 mg	-		
reaction mass of: 5-chloro-	Skin - Severe irritant	Human	-	0.01 %	-		
2-methyl-4-isothiazolin-							
3-one [EC no. 247-500-7]							
and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:							
1)							
Conclusion/Summary	: Based on available data, the classification criteria are not met.						
Sensitisation							
<b>Conclusion/Summary</b>	: May cause an allergic skin re	action.					
<u>Mutagenicity</u>							
<b>Conclusion/Summary</b>	: Based on available data, the	classification cr	riteria are	not met.			
Carcinogenicity							
<b>Conclusion/Summary</b>	: Based on available data, the classification criteria are not met.						
Reproductive toxicity							
Conclusion/Summary	: Based on available data, the classification criteria are not met.						
<u>Teratogenicity</u>							
Conclusion/Summary	: Based on available data, the	classification cr	riteria are	not met.			

**Conclusion/Summary** 

### Specific target organ toxicity (single exposure)

Pi	roduct/ingredient name	Category	Route of exposure	Target organs
Triethylamine		Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure) Not available.

# **SECTION 11: Toxicological information**

Aspiration hazard

Not available.

Information on likely routes of exposure	1	Not available.
Potential acute health effects		
Eye contact	:	No known significant effects or critical hazards.
Inhalation	;	No known significant effects or critical hazards.
Skin contact	1	May cause an allergic skin reaction.
Ingestion	;	No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact Inhalation	<ul><li>No specific data.</li><li>No specific data.</li></ul>
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

: Not available.
: Not available.
: Not available.
: Not available.
<u>its</u>
: Not available.
: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.

### 11.2 Information on other hazards

- **11.2.1 Endocrine disrupting properties** Not available.
- 11.2.2 Other information

Not available.

# **SECTION 12: Ecological information**

12.1 Toxicity

# SECTION 12: Ecological information

Product/ingredient name	Result	Species	Exposure
2-Butoxyethanol	Acute EC50 >1000 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 800000 µg/l Marine water	Crustaceans - Crangon crangon	48 hours
	Acute LC50 1250000 µg/l Marine water	Fish - Menidia beryllina	96 hours
Reaction mass of Bis (1,2,2,6,6-pentamethyl- 4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl- 4-piperidyl sebacate	EC50 1.68 mg/l	Aquatic plants - Desmodesmodus subspicatus	72 hours
	Acute LC50 0.9 mg/l	Fish - <i>Brachydanio rerio</i>	96 hours
	Chronic NOEC 1 mg/l	Daphnia	21 days

Conclusion/Summary

: Harmful to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

Conclusion/Summary

: This product has not been tested for biodegradation.

### **12.3 Bioaccumulative potential**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
P-Butoxyethanol	0.81	-	Low
Triethylamine	1.45	<0.5	Low

12.4 Mobility in soil	
Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

# **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
European waste catalogue (EWC)	: 080111*
Packaging	
Methods of disposal	<ul> <li>The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.</li> </ul>

Date of issue/Date of revision	: 26/10/2023	Date of previous issue	: 05/07/2022	Version : 1.04 11/15
TEKNODUR AQUA 3394-03 -	All variants			Label No :52215

# SECTION 13: Disposal considerations

**Special precautions** 

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

**14.6 Special precautions for** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not relevant/applicable due to nature of the product.

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed.

### Substances of very high concern

None of the components are listed.

#### Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name			%	Designatio	on [Usage]			
FEKNODUR AQUA 3394-0	3		≥90	3				
Labelling	:		1	1				
<u> Other EU regulations</u>								
Industrial emissions (integrated pollution prevention and control) - Air	:	Not listed						
Industrial emissions (integrated pollution prevention and control) - Water	:	Not listed						
Explosive precursors	:	Not applicat	ole.					
ate of issue/Date of revision		: 26/10/2023	Date of previo	ous issue	: 05/07/2022	Version	: 1.04	12/1:

TEKNODUR AQUA 3394-03 - All variants

# **SECTION 15: Regulatory information**

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

### Seveso Directive

This product is not controlled under the Seveso Directive.

### International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

### **Montreal Protocol**

Not listed.

# Stockholm Convention on Persistent Organic Pollutants

Not listed.

### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

15.2 Chemical safety

: Not applicable.

assessment

# SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative
-------------------------------	---

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification	
Skin Sens. 1, H317	Calculation method	
Aquatic Chronic 3, H412	Calculation method	

### Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.		
H301	Toxic if swallowed.		
H302	Harmful if swallowed.		
H310	Fatal in contact with skin.		
H311	Toxic in contact with skin.		
H314	Causes severe skin burns and eye damage.		
H315	Causes skin irritation.		
H317	May cause an allergic skin reaction.		
H318	Causes serious eye damage.		
H319	Causes serious eye irritation.		
H330	Fatal if inhaled.		
Date of issue/	Date of issue/Date of revision : 26/10/2023 Date of previous issue : 05/07/2022 Version : 1.04 13/1		

SECTION 16: Other information			
H331	Toxic if inhaled.		
H335	May cause respiratory irritation.		
H361f	Suspected of damaging fertility.		
H400	Very toxic to aquatic life.		
H410	Very toxic to aquatic life with long lasting effects.		
H411	Toxic to aquatic life with long lasting effects.		
H412	Harmful to aquatic life with long lasting effects.		
EUH071	Corrosive to the respiratory tract.		
Full text of elegenifications [CL B/CHS]			

### Full text of classifications [CLP/GHS]

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Skin Corr. 1A	SKIN CORROSION/IRRITATION - Category 1A
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
Date of issue/ Date of	: 26/10/2023
revision	
Date of previous issue	e : 05/07/2022
Version	: 1.04

### Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision: 26/10/2023DateTEKNODUR AQUA 3394-03 - All variants

: 26/10/2023 Date of previous issue

:05/07/2022

Version : 1.04 15/15 Label No : 52215