

SAFETY DATA SHEET



TEKNODUR COMBI 3430-05 - All variants

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : TEKNODUR COMBI 3430-05 - All variants

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS : Prod-safe@teknos.com

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : In an emergency, call 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

Skin Sens. 1, H317

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 - Flammable liquid and vapour.
H317 - May cause an allergic skin reaction.

Precautionary statements

Prevention : P280 - Wear protective gloves.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 - Avoid breathing vapour.

Response : P302 + P352 - IF ON SKIN: Wash with plenty of water.
P362 + P364 - Take off contaminated clothing and wash it before reuse.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

SECTION 2: Hazards identification

Hazardous ingredients	: Contains: 4-morpholinecarbaldehyde; Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate; Fatty acids, C14-18 and C16-18-unsatd., maleated and 12-hydroxy-N-[6-(12-hydroxyoctadecanamido)hexyl]octadecanamide
Supplemental label elements	:
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1	≤12	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	-	[1] [2]
2-Methoxy-1-methylethyl acetate	REACH #: 01-2119475791-29 EC: 203-603-9 CAS: 108-65-6 Index: 607-195-00-7	≤7.1	Flam. Liq. 3, H226 STOT SE 3, H336	-	[1] [2]
Xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	≤3.7	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 (oral, inhalation) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Dermal] = 1100 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
4-morpholinecarbaldehyde	REACH #: 01-2119987993-12 EC: 224-518-3 CAS: 4394-85-8	<1	Skin Sens. 1, H317	-	[1]
Reaction mass of Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	REACH #: 01-2119491304-40 EC: 915-687-0 CAS: 1065336-91-5	≤0.21	Skin Sens. 1A, H317 Repr. 2, H361f Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]

SECTION 3: Composition/information on ingredients

Fatty acids, C14-18 and C16-18-unsatd., maleated	REACH #: 01-2119976378-19 EC: 288-306-2 CAS: 85711-46-2	≤0.3	Skin Irrit. 2, H315 Skin Sens. 1, H317	-	[1]
12-hydroxy-N-[6-(12-hydroxyoctadecanamido)hexyl]octadecanamide	REACH #: 01-0000018057-71 EC: 611-260-5 CAS: 55349-01-4	≤0.3	Skin Sens. 1, H317 Aquatic Chronic 4, H413	-	[1]
Maleic anhydride	REACH #: 01-2119472428-31 EC: 203-571-6 CAS: 108-31-6 Index: 607-096-00-9	≤0.0015	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1A, H317 STOT RE 1, H372 (respiratory system) (inhalation) EUH071 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 400 mg/kg Skin Sens. 1, H317: C ≥ 0.001%	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

SECTION 4: First aid measures

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
phosphorus oxides
metal oxide/oxides

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flames, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

SECTION 6: Accidental release measures

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c	5000 tonnes	50000 tonnes

7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
n-Butyl acetate	Regulation on Limit Values - MAC (Austria, 12/2024) [Butylacetat alle Isomeren außer tert-Butylacet] CEIL: 480 mg/m ³ . CEIL: 100 ppm. TWA 8 hours: 241 mg/m ³ . TWA 8 hours: 50 ppm.
2-Methoxy-1-methylethyl acetate	Regulation on Limit Values - MAC (Austria, 12/2024) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m ³ . CEIL 5 minutes: 100 ppm 8 times per shift. CEIL 5 minutes: 550 mg/m ³ 8 times per shift.
Xylene	Regulation on Limit Values - MAC (Austria, 12/2024) [Xylo (alle Isomeren, rein)] PEAK 15 minutes: 442 mg/m ³ 4 times per shift. TWA 8 hours: 50 ppm. PEAK 15 minutes: 100 ppm 4 times per shift. TWA 8 hours: 221 mg/m ³ .
Maleic anhydride	Regulation on Limit Values - MAC (Austria, 12/2024) Inhalation sensitiser , Skin sensitiser. TWA 8 hours: 0.1 ppm. TWA 8 hours: 0.4 mg/m ³ . CEIL 5 minutes: 0.2 ppm 8 times per shift. CEIL 5 minutes: 0.8 mg/m ³ 8 times per shift.
n-Butyl acetate	Limit values (Belgium, 12/2023) [butylacetaat] STEL 15 minutes: 712 mg/m ³ . STEL 15 minutes: 150 ppm. TWA 8 hours: 238 mg/m ³ . TWA 8 hours: 50 ppm.
2-Methoxy-1-methylethyl acetate	Limit values (Belgium, 12/2023) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m ³ . STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m ³ .
Xylene	Limit values (Belgium, 12/2023) [Xyleen] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m ³ . STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m ³ .
Maleic anhydride	Limit values (Belgium, 12/2023) TWA 8 hours: 0.0025 ppm. Form: vapour and aerosol. TWA 8 hours: 0.01 mg/m ³ . Form: vapour and aerosol.
n-Butyl acetate	Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024) Limit value 8 hours: 241 mg/m ³ . Limit value 15 minutes: 723 mg/m ³ . Limit value 15 minutes: 150 ppm. Limit value 8 hours: 50 ppm.
2-Methoxy-1-methylethyl acetate	Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024) Absorbed through skin. Limit value 8 hours: 275 mg/m ³ . Limit value 15 minutes: 550 mg/m ³ . Limit value 15 minutes: 100 ppm. Limit value 8 hours: 50 ppm.

SECTION 8: Exposure controls/personal protection

Xylene	<p>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024) [Xylene] Absorbed through skin. Limit value 8 hours: 221 mg/m³. Limit value 15 minutes: 442 mg/m³. Limit value 15 minutes: 100 ppm. Limit value 8 hours: 50 ppm.</p>
Maleic anhydride	<p>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024) Limit value 8 hours: 1 mg/m³.</p>
n-Butyl acetate	<p>Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023) STELV 15 minutes: 723 mg/m³. STELV 15 minutes: 150 ppm. ELV 8 hours: 241 mg/m³. ELV 8 hours: 50 ppm.</p>
2-Methoxy-1-methylethyl acetate	<p>Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023) Absorbed through skin. STELV 15 minutes: 550 mg/m³. STELV 15 minutes: 100 ppm. ELV 8 hours: 275 mg/m³. ELV 8 hours: 50 ppm.</p>
Xylene	<p>Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023) [ksilen] Absorbed through skin. STELV 15 minutes: 442 mg/m³. STELV 15 minutes: 100 ppm. ELV 8 hours: 221 mg/m³. ELV 8 hours: 50 ppm.</p>
Maleic anhydride	<p>Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023) Skin sensitiser , Inhalation sensitiser. STELV 15 minutes: 0.2 ppm. ELV 8 hours: 0.41 mg/m³. STELV 15 minutes: 0.8 mg/m³. ELV 8 hours: 0.1 ppm.</p>
n-Butyl acetate	<p>Department of labour inspection (Cyprus, 7/2021) STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m³. TWA 8 hours: 50 ppm. TWA 8 hours: 241 mg/m³.</p>
2-Methoxy-1-methylethyl acetate	<p>Department of labour inspection (Cyprus, 7/2021) Absorbed through skin. STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m³. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m³.</p>
Xylene	<p>Department of labour inspection (Cyprus, 7/2021) [Ξυλένιο, μικτά ισομερή, καθαρά] Absorbed through skin. STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m³. TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m³.</p>
n-Butyl acetate	<p>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 12/2023) TWA 8 hours: 241 mg/m³. STEL 15 minutes: 723 mg/m³. STEL 15 minutes: 150 ppm. TWA 8 hours: 50 ppm.</p>
2-Methoxy-1-methylethyl acetate	<p>Government regulation of Czech Republic PEL/NPK-P (Czech</p>

SECTION 8: Exposure controls/personal protection

Xylene	<p>Republic, 12/2023) Absorbed through skin. TWA 8 hours: 275 mg/m³. TWA 8 hours: 50 ppm. STEL 15 minutes: 550 mg/m³. STEL 15 minutes: 100 ppm.</p> <p>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 12/2023) [xylen] Absorbed through skin. TWA 8 hours: 200 mg/m³. TWA 8 hours: 45.33 ppm. STEL 15 minutes: 400 mg/m³. STEL 15 minutes: 90.66 ppm.</p>
Maleic anhydride	<p>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 12/2023) Sensitiser. TWA 8 hours: 1 mg/m³. STEL 15 minutes: 2 mg/m³.</p>
n-Butyl acetate	<p>Working Environment Authority (Denmark, 12/2024) [butylacetat, alle isomerer] TWA 8 hours: 50 ppm. TWA 8 hours: 241 mg/m³. STEL 15 minutes: 723 mg/m³. STEL 15 minutes: 150 ppm.</p>
2-Methoxy-1-methylethyl acetate	<p>Working Environment Authority (Denmark, 12/2024) [2-methoxy-1-methylethylacetat] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m³. STEL 15 minutes: 550 mg/m³. STEL 15 minutes: 100 ppm.</p>
Xylene	<p>Working Environment Authority (Denmark, 12/2024) [xylen, alle isomere] Absorbed through skin. TWA 8 hours: 25 ppm. TWA 8 hours: 109 mg/m³. STEL 15 minutes: 442 mg/m³. STEL 15 minutes: 100 ppm.</p>
Maleic anhydride	<p>Working Environment Authority (Denmark, 12/2024) TWA 8 hours: 0.1 ppm. TWA 8 hours: 0.4 mg/m³. STEL 15 minutes: 0.8 mg/m³. STEL 15 minutes: 0.2 ppm.</p>
n-Butyl acetate	<p>Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024) STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m³. TWA 8 hours: 50 ppm. TWA 8 hours: 241 mg/m³.</p>
2-Methoxy-1-methylethyl acetate	<p>Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024) Absorbed through skin , Sensitiser. STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m³. TWA 8 hours: 275 mg/m³. TWA 8 hours: 50 ppm.</p>
Xylene	<p>Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024) [ksüleen] Absorbed through skin. TWA 8 hours: 50 ppm. STEL 15 minutes: 100 ppm. STEL 15 minutes: 450 mg/m³. TWA 8 hours: 200 mg/m³.</p>
Maleic anhydride	<p>Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024) Sensitiser. TWA 8 hours: 1.2 mg/m³. TWA 8 hours: 0.3 ppm. STEL 15 minutes: 2.5 mg/m³. STEL 15 minutes: 0.6 ppm.</p>

SECTION 8: Exposure controls/personal protection

n-Butyl acetate	<p>EU OEL (Europe, 1/2022) STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m³. TWA 8 hours: 241 mg/m³. TWA 8 hours: 50 ppm.</p>
2-Methoxy-1-methylethyl acetate	<p>EU OEL (Europe, 1/2022) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m³. STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m³.</p>
Xylene	<p>EU OEL (Europe, 1/2022) [xylene, mixed isomers] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m³. STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m³.</p>
n-Butyl acetate	<p>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021) TWA 8 hours: 150 ppm. TWA 8 hours: 720 mg/m³. STEL 15 minutes: 200 ppm. STEL 15 minutes: 960 mg/m³.</p>
2-Methoxy-1-methylethyl acetate	<p>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 270 mg/m³. STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m³.</p>
Xylene	<p>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021) [Ksyleeni] Absorbed through skin. STEL 15 minutes: 440 mg/m³. TWA 8 hours: 220 mg/m³. TWA 8 hours: 50 ppm. STEL 15 minutes: 100 ppm.</p>
Maleic anhydride	<p>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021) TWA 8 hours: 0.1 ppm. TWA 8 hours: 0.41 mg/m³. CEIL: 0.2 ppm. CEIL: 0.81 mg/m³.</p>
n-Butyl acetate	<p>Ministry of Labor (France, 6/2024) TWA 8 hours: 50 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) TWA 8 hours: 241 mg/m³. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) STEL 15 minutes: 150 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) STEL 15 minutes: 723 mg/m³. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</p>
2-Methoxy-1-methylethyl acetate	<p>Ministry of Labor (France, 6/2024) Absorbed through skin. STEL 15 minutes: 550 mg/m³. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) STEL 15 minutes: 100 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) TWA 8 hours: 275 mg/m³. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) TWA 8 hours: 50 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</p>
Xylene	<p>Ministry of Labor (France, 6/2024) [xylènes, isomères mixtes, purs] Absorbed through skin. STEL 15 minutes: 442 mg/m³. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</p>

SECTION 8: Exposure controls/personal protection

Maleic anhydride	<p>STEL 15 minutes: 100 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</p> <p>TWA 8 hours: 221 mg/m³. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</p> <p>TWA 8 hours: 50 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</p> <p>Ministry of Labor (France, 6/2024) Sensitiser.</p> <p>STEL 15 minutes: 1 mg/m³. Notes: Permissible limit values (circulars)</p>
n-Butyl acetate	<p>TRGS 900 OEL (Germany, 6/2024)</p> <p>TWA 8 hours: 300 mg/m³.</p> <p>TWA 8 hours: 62 ppm.</p> <p>PEAK 15 minutes: 600 mg/m³.</p> <p>PEAK 15 minutes: 124 ppm.</p> <p>DFG MAC-values list (Germany, 7/2024) Develop C.</p> <p>TWA 8 hours: 100 ppm.</p> <p>PEAK 15 minutes: 200 ppm 4 times per shift [Interval: 1 hour].</p> <p>TWA 8 hours: 480 mg/m³.</p> <p>PEAK 15 minutes: 960 mg/m³ 4 times per shift [Interval: 1 hour].</p>
2-Methoxy-1-methylethyl acetate	<p>TRGS 900 OEL (Germany, 6/2024)</p> <p>TWA 8 hours: 270 mg/m³.</p> <p>PEAK 15 minutes: 270 mg/m³.</p> <p>TWA 8 hours: 50 ppm.</p> <p>PEAK 15 minutes: 50 ppm.</p> <p>DFG MAC-values list (Germany, 7/2024) Develop C.</p> <p>TWA 8 hours: 50 ppm.</p> <p>PEAK 15 minutes: 50 ppm 4 times per shift [Interval: 1 hour].</p> <p>TWA 8 hours: 270 mg/m³.</p> <p>PEAK 15 minutes: 270 mg/m³ 4 times per shift [Interval: 1 hour].</p>
Xylene	<p>TRGS 900 OEL (Germany, 6/2024) [Xylo] Absorbed through skin.</p> <p>TWA 8 hours: 220 mg/m³.</p> <p>PEAK 15 minutes: 440 mg/m³.</p> <p>TWA 8 hours: 50 ppm.</p> <p>PEAK 15 minutes: 100 ppm.</p> <p>DFG MAC-values list (Germany, 7/2024) [Xylene] Develop D.</p> <p>Absorbed through skin.</p> <p>TWA 8 hours: 50 ppm.</p> <p>PEAK 15 minutes: 100 ppm 4 times per shift [Interval: 1 hour].</p> <p>TWA 8 hours: 220 mg/m³.</p> <p>PEAK 15 minutes: 440 mg/m³ 4 times per shift [Interval: 1 hour].</p>
Maleic anhydride	<p>TRGS 900 OEL (Germany, 6/2024) Inhalation sensitiser , Skin sensitiser.</p> <p>TWA 8 hours: 0.081 mg/m³.</p> <p>CEIL: 0.2025 mg/m³.</p> <p>TWA 8 hours: 0.02 ppm.</p> <p>CEIL: 0.05 ppm.</p> <p>PEAK 15 minutes: 0.081 mg/m³.</p> <p>PEAK 15 minutes: 0.02 ppm.</p> <p>DFG MAC-values list (Germany, 7/2024) Develop C. Inhalation sensitiser , Skin sensitiser.</p> <p>TWA 8 hours: 0.02 ppm.</p> <p>CEIL: 0.05 ml/m³.</p> <p>TWA 8 hours: 0.081 mg/m³.</p> <p>CEIL: 0.2 mg/m³.</p> <p>PEAK 15 minutes: 0.081 mg/m³ 4 times per shift [Interval: 1 hour].</p> <p>PEAK 15 minutes: 0.02 ppm 4 times per shift [Interval: 1 hour].</p>

SECTION 8: Exposure controls/personal protection

n-Butyl acetate	<p>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 8/2024) TWA 8 hours: 50 ppm. TWA 8 hours: 241 mg/m³. STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m³.</p>
2-Methoxy-1-methylethyl acetate	<p>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 8/2024) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m³. STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m³.</p>
Xylene	<p>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 8/2024) [ξυλόλια (όλα τα ισομερή)] Absorbed through skin. TWA 8 hours: 100 ppm. TWA 8 hours: 435 mg/m³. STEL 15 minutes: 150 ppm. STEL 15 minutes: 650 mg/m³.</p>
Maleic anhydride	<p>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 8/2024) TWA 8 hours: 0.25 ppm. TWA 8 hours: 1 mg/m³.</p>
n-Butyl acetate	<p>5/2020. (II. 6.) ITM Decree (Hungary, 1/2025) Sensitiser. TWA 8 hours: 241 mg/m³. PEAK 15 minutes: 723 mg/m³. PEAK 15 minutes: 150 ppm. TWA 8 hours: 50 ppm.</p>
2-Methoxy-1-methylethyl acetate	<p>5/2020. (II. 6.) ITM Decree (Hungary, 1/2025) TWA 8 hours: 275 mg/m³. PEAK 15 minutes: 550 mg/m³. PEAK 15 minutes: 100 ppm. TWA 8 hours: 50 ppm.</p>
Xylene	<p>5/2020. (II. 6.) ITM Decree (Hungary, 1/2025) [xilol izomerek keveréke] Absorbed through skin. TWA 8 hours: 221 mg/m³. PEAK 15 minutes: 442 mg/m³. PEAK 15 minutes: 100 ppm. TWA 8 hours: 50 ppm.</p>
Maleic anhydride	<p>5/2020. (II. 6.) ITM Decree (Hungary, 1/2025) Sensitiser. TWA 8 hours: 0.08 mg/m³. PEAK 15 minutes: 0.08 mg/m³. PEAK 15 minutes: 0.2 ppm. TWA 8 hours: 0.2 ppm.</p>
n-Butyl acetate	<p>Ministry of Welfare, List of Exposure Limits (Iceland, 11/2024) [bútýlasetat, allir ísómerar] TWA 8 hours: 241 mg/m³. TWA 8 hours: 50 ppm. STEL 15 minutes: 723 mg/m³. STEL 15 minutes: 150 ppm.</p>
2-Methoxy-1-methylethyl acetate	<p>Ministry of Welfare, List of Exposure Limits (Iceland, 11/2024) Absorbed through skin. STEL 15 minutes: 550 mg/m³. STEL 15 minutes: 100 ppm. TWA 8 hours: 275 mg/m³. TWA 8 hours: 50 ppm.</p>
Xylene	<p>Ministry of Welfare, List of Exposure Limits (Iceland, 11/2024) [Xýlen, allir ísómerar] Absorbed through skin. STEL 15 minutes: 442 mg/m³. STEL 15 minutes: 100 ppm. TWA 8 hours: 109 mg/m³. TWA 8 hours: 25 ppm.</p>

SECTION 8: Exposure controls/personal protection

Maleic anhydride	Ministry of Welfare, List of Exposure Limits (Iceland, 11/2024) Sensitiser. TWA 8 hours: 0.4 mg/m ³ . TWA 8 hours: 0.1 ppm.
n-Butyl acetate	NAOSH (Ireland, 4/2024) Notes: EU derived Occupational Exposure Limit Values OELV 8 hours: 50 ppm. OELV 8 hours: 241 mg/m ³ . OELV 15 minutes: 150 ppm. OELV 15 minutes: 723 mg/m ³ .
2-Methoxy-1-methylethyl acetate	NAOSH (Ireland, 4/2024) Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values OELV 8 hours: 50 ppm. OELV 8 hours: 275 mg/m ³ . OELV 15 minutes: 100 ppm. OELV 15 minutes: 550 mg/m ³ .
Xylene	NAOSH (Ireland, 4/2024) [xylene] Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values OELV 8 hours: 50 ppm. OELV 8 hours: 221 mg/m ³ . OELV 15 minutes: 100 ppm. OELV 15 minutes: 442 mg/m ³ .
Maleic anhydride	NAOSH (Ireland, 4/2024) Sensitiser. Notes: Advisory Occupational Exposure Limit Values (OELVs) OELV 8 hours: 0.01 ppm. Form: The Inhalable Fraction and Vapour note is used when a material exerts sufficient vapour pressure such that it may be present in both particle and vapour phases..
n-Butyl acetate	Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 9/2024) Short Term 15 minutes: 150 ppm. Short Term 15 minutes: 723 mg/m ³ . Limit value 8 hours: 50 ppm. Limit value 8 hours: 241 mg/m ³ .
2-Methoxy-1-methylethyl acetate	Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 9/2024) Absorbed through skin. Limit value 8 hours: 50 ppm. Limit value 8 hours: 275 mg/m ³ . Short Term 15 minutes: 100 ppm. Short Term 15 minutes: 550 mg/m ³ .
Xylene	Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 9/2024) [xilene, isomeri misti, puro] Absorbed through skin. Limit value 8 hours: 50 ppm. Limit value 8 hours: 221 mg/m ³ . Short Term 15 minutes: 100 ppm. Short Term 15 minutes: 442 mg/m ³ .
n-Butyl acetate	Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024) TWA 8 hours: 241 mg/m ³ . STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m ³ . TWA 8 hours: 50 ppm.
2-Methoxy-1-methylethyl acetate	Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m ³ . STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m ³ .
Xylene	Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024) [Ksilols] Absorbed through skin. TWA 8 hours: 221 mg/m ³ .

SECTION 8: Exposure controls/personal protection

Maleic anhydride	TWA 8 hours: 50 ppm. STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m ³ . Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024) TWA 8 hours: 1 mg/m ³ .
n-Butyl acetate	Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024) TWA 8 hours: 241 mg/m ³ . TWA 8 hours: 50 ppm. STEL 15 minutes: 723 mg/m ³ . STEL 15 minutes: 150 ppm.
2-Methoxy-1-methylethyl acetate	Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024) Absorbed through skin. TWA 8 hours: 250 mg/m ³ . TWA 8 hours: 50 ppm. STEL 15 minutes: 400 mg/m ³ . STEL 15 minutes: 75 ppm.
Xylene	Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024) [ksilenas, mišrūs izomerai, grynas] Absorbed through skin. STEL 15 minutes: 442 mg/m ³ . TWA 8 hours: 50 ppm. STEL 15 minutes: 100 ppm. TWA 8 hours: 221 mg/m ³ .
Maleic anhydride	Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024) Sensitiser. TWA 8 hours: 1.2 mg/m ³ . TWA 8 hours: 0.3 ppm. STEL 15 minutes: 2.5 mg/m ³ . STEL 15 minutes: 0.6 ppm.
n-Butyl acetate	Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021) STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m ³ . TWA 8 hours: 50 ppm. TWA 8 hours: 241 mg/m ³ .
2-Methoxy-1-methylethyl acetate	Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m ³ . STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m ³ .
Xylene	Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021) [xylène Isomères mixtes, pures] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m ³ . STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m ³ .
n-Butyl acetate	EU OEL (Europe, 1/2022) STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m ³ . TWA 8 hours: 241 mg/m ³ . TWA 8 hours: 50 ppm.
2-Methoxy-1-methylethyl acetate	EU OEL (Europe, 1/2022) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m ³ . STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m ³ .
Xylene	EU OEL (Europe, 1/2022) [xylene, mixed isomers] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m ³ . STEL 15 minutes: 100 ppm.

SECTION 8: Exposure controls/personal protection

n-Butyl acetate	<p>STEL 15 minutes: 442 mg/m³.</p> <p>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 5/2024)</p> <p>TWA 8 hours: 241 mg/m³. STEL 15 minutes: 723 mg/m³. STEL 15 minutes: 150 ppm. TWA 8 hours: 50 ppm.</p>
2-Methoxy-1-methylethyl acetate	<p>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 5/2024)</p> <p>TWA 8 hours: 550 mg/m³. TWA 8 hours: 100 ppm.</p>
Xylene	<p>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 5/2024) [xyleen, o-, m-, p-isomeren] Absorbed through skin.</p> <p>TWA 8 hours: 210 mg/m³. STEL 15 minutes: 442 mg/m³. STEL 15 minutes: 100 ppm. TWA 8 hours: 47.5 ppm.</p>
n-Butyl acetate	<p>FOR-2011-12-06-1358 (Norway, 5/2024)</p> <p>STEL 15 minutes: 723 mg/m³. STEL 15 minutes: 150 ppm. TWA 8 hours: 241 mg/m³. TWA 8 hours: 50 ppm.</p>
2-Methoxy-1-methylethyl acetate	<p>FOR-2011-12-06-1358 (Norway, 5/2024) Absorbed through skin.</p> <p>TWA 8 hours: 50 ppm. TWA 8 hours: 270 mg/m³.</p>
Xylene	<p>FOR-2011-12-06-1358 (Norway, 5/2024) [xylen] Absorbed through skin.</p> <p>TWA 8 hours: 25 ppm. TWA 8 hours: 108 mg/m³.</p>
Maleic anhydride	<p>FOR-2011-12-06-1358 (Norway, 5/2024) Sensitiser.</p> <p>TWA 8 hours: 0.2 ppm. TWA 8 hours: 0.8 mg/m³.</p>
n-Butyl acetate	<p>Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024)</p> <p>TWA 8 hours: 240 mg/m³. STEL 15 minutes: 720 mg/m³.</p>
2-Methoxy-1-methylethyl acetate	<p>Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024) Absorbed through skin.</p> <p>TWA 8 hours: 260 mg/m³. STEL 15 minutes: 520 mg/m³.</p>
Xylene	<p>Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024) [xylene – mixed isomers (1,2-, 1,3-, 1,4-)] Absorbed through skin.</p> <p>TWA 8 hours: 100 mg/m³. STEL 15 minutes: 200 mg/m³.</p>
Maleic anhydride	<p>Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024) Absorbed through skin.</p> <p>TWA 8 hours: 0.5 mg/m³. STEL 15 minutes: 1 mg/m³.</p>

SECTION 8: Exposure controls/personal protection

n-Butyl acetate	<p>Portuguese Institute of Quality (Portugal, 11/2014) TWA 8 hours: 150 ppm. STEL 15 minutes: 200 ppm.</p> <p>Decree-Law 24/2012 - Occupational exposure limits for chemical agents (Portugal, 6/2021) STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m³. TWA 8 hours: 50 ppm. TWA 8 hours: 241 mg/m³.</p>
2-Methoxy-1-methylethyl acetate	<p>Decree-Law 24/2012 - Occupational exposure limits for chemical agents (Portugal, 6/2021) Absorbed through skin. STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m³. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m³.</p>
Xylene	<p>Portuguese Institute of Quality (Portugal, 11/2014) [xileno (isómeros o, m & p)] A4. TWA 8 hours: 100 ppm. STEL 15 minutes: 150 ppm.</p> <p>Decree-Law 24/2012 - Occupational exposure limits for chemical agents (Portugal, 6/2021) [xilenos] Absorbed through skin. STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m³. TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m³.</p>
Maleic anhydride	<p>Portuguese Institute of Quality (Portugal, 11/2014) A4. TWA 8 hours: 0.01 mg/m³. Form: Inhalable fraction and vapor.</p>
n-Butyl acetate	<p>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024) VLA 8 hours: 241 mg/m³. VLA 8 hours: 50 ppm. Short term 15 minutes: 723 mg/m³. Short term 15 minutes: 150 ppm.</p>
2-Methoxy-1-methylethyl acetate	<p>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024) Absorbed through skin. VLA 8 hours: 275 mg/m³. VLA 8 hours: 50 ppm. Short term 15 minutes: 550 mg/m³. Short term 15 minutes: 100 ppm.</p>
Xylene	<p>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024) [xilen] Absorbed through skin. VLA 8 hours: 221 mg/m³. VLA 8 hours: 50 ppm. Short term 15 minutes: 442 mg/m³. Short term 15 minutes: 100 ppm.</p>
Maleic anhydride	<p>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024) VLA 8 hours: 1 mg/m³. VLA 8 hours: 0.25 ppm. Short term 15 minutes: 3 mg/m³. Short term 15 minutes: 0.75 ppm.</p>
n-Butyl acetate	<p>Government regulation SR c. 355/2006 (Slovakia, 6/2024) [butylacetáty] Inhalation sensitiser. TWA 8 hours: 241 mg/m³ (Butyl acetates). TWA 8 hours: 50 ppm (Butyl acetates). STEL 15 minutes: 723 mg/m³ (Butyl acetates). STEL 15 minutes: 150 ppm (Butyl acetates).</p>
2-Methoxy-1-methylethyl acetate	<p>Government regulation SR c. 355/2006 (Slovakia, 6/2024) Absorbed through skin , Inhalation sensitiser. TWA 8 hours: 275 mg/m³. TWA 8 hours: 50 ppm.</p>

SECTION 8: Exposure controls/personal protection

Xylene	<p>STEL 15 minutes: 550 mg/m³. STEL 15 minutes: 100 ppm.</p> <p>Government regulation SR c. 355/2006 (Slovakia, 6/2024) [xylén, zmiešané izoméry] Absorbed through skin , Inhalation sensitiser.</p> <p>TWA 8 hours: 221 mg/m³ (xylene, mixed isomers). TWA 8 hours: 50 ppm (xylene, mixed isomers). STEL 15 minutes: 442 mg/m³ (xylene, mixed isomers). STEL 15 minutes: 100 ppm (xylene, mixed isomers).</p>
Maleic anhydride	<p>Government regulation SR c. 355/2006 (Slovakia, 6/2024) Sensitiser , Inhalation sensitiser.</p> <p>TWA 8 hours: 0.41 mg/m³. TWA 8 hours: 0.1 ppm.</p>
n-Butyl acetate	<p>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024)</p> <p>TWA 8 hours: 241 mg/m³. TWA 8 hours: 50 ppm. KTV 15 minutes: 723 mg/m³ 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes]. KTV 15 minutes: 150 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].</p>
2-Methoxy-1-methylethyl acetate	<p>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024) Absorbed through skin.</p> <p>TWA 8 hours: 275 mg/m³. TWA 8 hours: 50 ppm. KTV 15 minutes: 550 mg/m³ 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes]. KTV 15 minutes: 100 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].</p>
Xylene	<p>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024) [ksilen] Absorbed through skin.</p> <p>TWA 8 hours: 221 mg/m³. TWA 8 hours: 50 ppm. KTV 15 minutes: 442 mg/m³ 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes]. KTV 15 minutes: 100 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].</p>
Maleic anhydride	<p>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024)</p> <p>TWA 8 hours: 0.41 mg/m³. TWA 8 hours: 0.1 ppm. KTV 15 minutes: 0.41 mg/m³ 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes]. KTV 15 minutes: 0.1 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].</p>
n-Butyl acetate	<p>National institute of occupational safety and health (Spain, 1/2024)</p> <p>TWA 8 hours: 50 ppm. TWA 8 hours: 241 mg/m³. STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m³.</p>
2-Methoxy-1-methylethyl acetate	<p>National institute of occupational safety and health (Spain, 1/2024) Absorbed through skin.</p> <p>TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m³. STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m³.</p>
Xylene	<p>National institute of occupational safety and health (Spain, 1/2024) [xileno, mezcla isómeros] Absorbed through skin.</p> <p>TWA 8 hours: 50 ppm.</p>

SECTION 8: Exposure controls/personal protection

Maleic anhydride	<p>TWA 8 hours: 221 mg/m³. STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m³.</p> <p>National institute of occupational safety and health (Spain, 1/2024) Inhalation sensitiser , Skin sensitiser. TWA 8 hours: 0.1 ppm. TWA 8 hours: 0.4 mg/m³.</p>
n-Butyl acetate	<p>Work environment authority Regulation 2018:1 (Sweden, 11/2022) [butyl acetate] TWA 8 hours: 50 ppm. TWA 8 hours: 241 mg/m³. STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m³.</p>
2-Methoxy-1-methylethyl acetate	<p>Work environment authority Regulation 2018:1 (Sweden, 11/2022) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m³. STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m³.</p>
Xylene	<p>Work environment authority Regulation 2018:1 (Sweden, 11/2022) [xylene] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m³. STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m³.</p>
Maleic anhydride	<p>Work environment authority Regulation 2018:1 (Sweden, 11/2022) Sensitiser. TWA 8 hours: 0.05 ppm. TWA 8 hours: 0.2 mg/m³. STEL 15 minutes: 0.1 ppm. STEL 15 minutes: 0.4 mg/m³.</p>
n-Butyl acetate	<p>SUVA (Switzerland, 1/2025) TWA 8 hours: 50 ppm. TWA 8 hours: 240 mg/m³. STEL 15 minutes: 150 ppm. STEL 15 minutes: 720 mg/m³.</p>
2-Methoxy-1-methylethyl acetate	<p>SUVA (Switzerland, 1/2025) TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m³. STEL 15 minutes: 50 ppm. STEL 15 minutes: 275 mg/m³.</p>
Xylene	<p>SUVA (Switzerland, 1/2025) [Xylol] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 220 mg/m³. STEL 15 minutes: 100 ppm. STEL 15 minutes: 440 mg/m³.</p>
Maleic anhydride	<p>SUVA (Switzerland, 1/2025) Sensitiser. TWA 8 hours: 0.1 ppm. Form: vapour and aerosols. TWA 8 hours: 0.4 mg/m³. Form: vapour and aerosols. STEL 15 minutes: 0.1 ppm. Form: vapour and aerosols. STEL 15 minutes: 0.4 mg/m³. Form: vapour and aerosols.</p>
n-Butyl acetate	<p>EH40/2005 WELs (United Kingdom (UK), 1/2020) STEL 15 minutes: 966 mg/m³. STEL 15 minutes: 200 ppm. TWA 8 hours: 724 mg/m³. TWA 8 hours: 150 ppm.</p>
2-Methoxy-1-methylethyl acetate	<p>EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin. STEL 15 minutes: 548 mg/m³. TWA 8 hours: 50 ppm. TWA 8 hours: 274 mg/m³. STEL 15 minutes: 100 ppm.</p>

SECTION 8: Exposure controls/personal protection

Xylene	EH40/2005 WELs (United Kingdom (UK), 1/2020) [xylene, o-,m-, p- or mixed isomers] Absorbed through skin. STEL 15 minutes: 441 mg/m ³ . TWA 8 hours: 50 ppm. TWA 8 hours: 220 mg/m ³ . STEL 15 minutes: 100 ppm.
Maleic anhydride	EH40/2005 WELs (United Kingdom (UK), 1/2020) Inhalation sensitiser. STEL 15 minutes: 3 mg/m ³ . TWA 8 hours: 1 mg/m ³ .

Biological exposure indices

Product/ingredient name	Exposure indices
Xylene	VGU BEI (Austria, 9/2020) [Xylole] BEI Fitness: 1000 µg/l, xylene [in blood]. Sampling time: one year. BEI Fitness: 1.5 g/l, methylhippuric acid [in urine]. Sampling time: one year.
No exposure indices known.	
No exposure indices known.	
Xylene	Ordinance on the protection of workers from exposure to hazardous chemicals at work, biological limit values (Annex IV) (Croatia, 12/2023) [ksilen] BEI: 1.5 mg/l, xylene [in blood]. Sampling time: at the end of the work shift. BEI: 14.13 µmol/l, xylene [in blood]. Sampling time: at the end of the work shift. BEI: 0.88 mol/mol creatinine, methylhippuric acid [in urine]. Sampling time: at the end of the work shift. BEI: 1.5 g/g creatinine, methylhippuric acid [in urine]. Sampling time: at the end of the work shift.
No exposure indices known.	
Xylene	Government regulation of Czech Republic Limit Values of Biological Exposure Tests (Czech Republic, 9/2015) [Xyleny] Biological limit values: 820 µmol/mmol creatinine, methylhippuric acid [in urine]. Sampling time: end of the shift. Biological limit values: 1400 mg/g creatinine, methylhippuric acid [in urine]. Sampling time: end of the shift.
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
Xylene	Institute of Occupational Health, Ministry of Social Affairs (Finland, 9/2020) [Ksyleeni] BEI: 5 mmol/l, methylhippuric acid [in urine]. Sampling time: at the end of the work shift.
No exposure indices known.	
Xylene	DFG BEI-values list (Germany, 7/2024) [Xylene (all isomers)] Notes: danger from percutaneous absorption (see p. 211 and p. 228). BEI: 1800 mg/g creatinine, Methylhippuric acids (=toluric acids) (all isomers) [in urine]. Sampling time: end of exposure or end of shift. TRGS 903 - BEI Values (Germany, 10/2024) [Xylole alle Isomeren] BEI: 2000 mg/l, methylhippuric acid [in urine]. Sampling time: end of exposure or end of shift.
No exposure indices known.	

SECTION 8: Exposure controls/personal protection

Xylene	<p>5/2020. (II. 6.) ITM Decree (Hungary, 12/2023) [xilol] BEI: 1500 mg/g creatinine, methylhippuric acid [in urine]. Sampling time: at the end of the shift. BEI: 860 µmol/mmol creatinine, methylhippuric acid [in urine]. Sampling time: at the end of the shift.</p>
No exposure indices known.	
Xylene	<p>NAOSH BGVs (Ireland, 1/2011) [Xylene] BMGV: 1.5 g/g creatinine, methylhippuric acids [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases.</p>
No exposure indices known.	
Xylene	<p>Minister Cabinet Regulations No.325 - BEI (Latvia, 3/2024) [ksiloli (visi izomēri)] BEI: 2000 mg/l, methylhippuric (toluric) acid (all isomers) [in urine]. Sampling time: at the end of the exposure or at the end of the shift.</p>
No exposure indices known.	
Xylene	<p>Portuguese Institute of Quality (Portugal, 11/2014) [Xilenos (graus técnico e comercial)] BEI: 1.5 g/g creatinine, (o, m, p) -methyl-boronic acids [in urine]. Sampling time: end of shift.</p>
Xylene	<p>HG 1218/2006, Annex 2, with subsequent modifications and additions (Romania, 3/2024) [xilen] OBLV: 3 g/l, methylhippuric acid [in urine]. Sampling time: end of shift.</p>
Xylene	<p>Government regulation SR c. 355/2006 (Slovakia, 6/2024) [xylén (všetky izoméry)] BLV: 781 µmol/mmol creatinine, as sum of 2,3,4-methylhippuroic acids [in urine]. Sampling time: at the end of exposure or work shift. BLV: 1334 mg/g creatinine, as sum of 2,3,4-methylhippuroic acids [in urine]. Sampling time: at the end of exposure or work shift. BLV: 10355 µmol/l, as sum of 2,3,4-methylhippuroic acids [in urine]. Sampling time: at the end of exposure or work shift. BLV: 14.6 µmol/l, as xylene [in blood]. Sampling time: at the end of exposure or work shift. BLV: 2000 mg/l, as sum of 2,3,4-methylhippuroic acids [in urine]. Sampling time: at the end of exposure or work shift. BLV: 1.5 mg/l, as xylene [in blood]. Sampling time: at the end of exposure or work shift.</p>
Xylene	<p>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024) [ksilen (vse izomere)] BAT: 2 g/l, methylhippuric acid (all isomers) [in urine]. Sampling time: at the end of the work shift.</p>
Xylene	<p>National institute of occupational safety and health (Spain, 1/2024) [Xilenos] VLB: 1 g/g creatinine, methylhippuric acids [in urine]. Sampling time: end of shift.</p>
No exposure indices known.	
Xylene	<p>SUVA (Switzerland, 1/2025) [Xylol (alle Isomere)] BEI: 2 g/l, methyl hippuric acid [in urine]. Sampling time: immediately after exposure or after working hours.</p>

SECTION 8: Exposure controls/personal protection

Xylene	EH40/2005 BMGVs (United Kingdom (UK), 1/2020) [Xylene, o-, m-, p- or mixed isomers] BGV: 650 mmol/mol creatinine, methyl hippuric acid [in urine]. Sampling time: post shift.
--------	--

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name

n-Butyl acetate

Result

DNEL - General population - Long term - Oral

2 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Oral

2 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

3.4 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Dermal

6 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

7 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Short term - Dermal

11 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

12 mg/m³

Effects: Systemic

DNEL - General population - Long term - Inhalation

35.7 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

48 mg/m³

Effects: Systemic

DNEL - General population - Short term - Inhalation

300 mg/m³

Effects: Local

DNEL - General population - Short term - Inhalation

300 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

300 mg/m³

Effects: Local

SECTION 8: Exposure controls/personal protection

	DNEL - Workers - Short term - Inhalation 600 mg/m ³ <u>Effects</u> : Local
	DNEL - Workers - Short term - Inhalation 600 mg/m ³ <u>Effects</u> : Systemic
2-Methoxy-1-methylethyl acetate	DNEL - General population - Long term - Inhalation 33 mg/m ³ <u>Effects</u> : Local
	DNEL - General population - Long term - Inhalation 33 mg/m ³ <u>Effects</u> : Systemic
	DNEL - General population - Long term - Oral 36 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Inhalation 275 mg/m ³ <u>Effects</u> : Systemic
	DNEL - General population - Long term - Dermal 320 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - Workers - Short term - Inhalation 550 mg/m ³ <u>Effects</u> : Local
	DNEL - Workers - Long term - Dermal 796 mg/kg bw/day <u>Effects</u> : Systemic
Xylene	DNEL - General population - Long term - Oral 5 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Long term - Inhalation 65.3 mg/m ³ <u>Effects</u> : Local
	DNEL - General population - Long term - Inhalation 65.3 mg/m ³ <u>Effects</u> : Systemic
	DNEL - General population - Long term - Dermal 125 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Dermal 212 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Inhalation 221 mg/m ³ <u>Effects</u> : Local
	DNEL - Workers - Long term - Inhalation 221 mg/m ³ <u>Effects</u> : Systemic
	DNEL - General population - Short term - Inhalation 260 mg/m ³

SECTION 8: Exposure controls/personal protection

Effects: Local

DNEL - General population - Short term - Inhalation

260 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Inhalation

442 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

442 mg/m³

Effects: Systemic

4-morpholinecarbaldehyde

DNEL - General population - Long term - Oral

4.17 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

4.17 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

8.93 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Dermal

11.7 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

13.3 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

13.3 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

50.3 mg/m³

Effects: Systemic

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

DNEL - General population - Long term - Oral

0.18 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

0.31 mg/m³

Effects: Systemic

DNEL - General population - Long term - Dermal

0.9 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

1.27 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Dermal

1.8 mg/kg bw/day

Effects: Systemic

Fatty acids, C14-18 and C16-18-unsatd., maleated

DNEL - General population - Long term - Oral

1.5 mg/kg bw/day

Effects: Systemic

SECTION 8: Exposure controls/personal protection

Maleic anhydride

DNEL - General population - Long term - Dermal

1.5 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

3 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

0.05 mg/m³

Effects: Systemic

DNEL - General population - Long term - Oral

0.06 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

0.08 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

0.081 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

0.081 mg/m³

Effects: Systemic

DNEL - General population - Short term - Oral

0.1 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Dermal

0.1 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

0.1 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Short term - Dermal

0.2 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

0.2 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Short term - Inhalation

0.2 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

0.2 mg/m³

Effects: Systemic

PNECs

Not available.

8.2 Exposure controls

Date of issue/*Date of revision*

: 05/03/2026

Date of previous issue

: 26/01/2026

Version : 13

23/38

TEKNODUR COMBI 3430-05 - All variants

Label No : 43918

SECTION 8: Exposure controls/personal protection

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Individual protection measures**
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Recommendations : Wear suitable gloves tested to EN374.
- < 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm
- 1 - 4 hours (breakthrough time): polyvinyl alcohol (PVA) thickness > 0.3 mm or 4H / Silver Shield® gloves.
- > 8 hours (breakthrough time): Viton® thickness > 0.3 mm gloves
- Wash hands before breaks and immediately after handling the product.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
- Filter type: A
- Filter type (spray application): A P
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state	: Liquid.
Colour	: Various
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	:

Ingredient name	°C	°F	Method
n-Butyl acetate	126	258.8	OECD 103
Xylene	136.16	277.1	

Flammability	: Not available.
Lower and upper explosion limit	: Lower: 0.8% (xylene) Upper: 7.6% (n-butyl acetate)
Flash point	: Closed cup: 25°C (77°F)
Auto-ignition temperature	:

Ingredient name	°C	°F	Method
2-Methoxy-1-methylethyl acetate	333	631.4	DIN 51794
n-Butyl acetate	415	779	EU A.15

Decomposition temperature	: Not available.
pH	: Not applicable.
Viscosity	: Not available.
Solubility(ies)	:
	Not available.

Solubility in water	: Not available.
Partition coefficient: n-octanol/ water	: Not applicable.
Vapour pressure	:

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
n-Butyl acetate	11.25096	1.5	DIN EN 13016-2			
Xylene	6.7	0.89				

Relative density	: Not available.
Density	: 1.5 g/cm ³
Vapour density	: Not available.
Particle characteristics	:
Median particle size	: Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties	: Not available.
Oxidising properties	: Not available.

9.2.2 Other safety characteristics

Not applicable.

SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
- 10.5 Incompatible materials** : Reactive or incompatible with the following materials:
oxidising materials
- 10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name

n-Butyl acetate

Result

Rat - Oral - LD50

10760 mg/kg

EU

Rabbit - Dermal - LD50

14112 mg/kg

Rat - Inhalation - LC50 Vapour

0.74 mg/l [4 hours]

2-Methoxy-1-methylethyl acetate

Rat - Oral - LD50

8532 mg/kg

Rabbit - Dermal - LD50

>5 g/kg

Xylene

Rat - Oral - LD50

4300 mg/kg

Toxic effects: Liver - Other changes Kidney, Ureter, and Bladder - Other changes

Rat - Inhalation - LC50 Vapour

21.7 mg/l [4 hours]

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Rat - Oral - LD50

3230 mg/kg

Rat - Dermal - LD50

>3170 mg/kg

Maleic anhydride

Rat - Oral - LD50

400 mg/kg

Rabbit - Dermal - LD50

2620 mg/kg

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Date of issue/*Date of revision*

: 05/03/2026

Date of previous issue

: 26/01/2026

Version : 13

26/38

TEKNODUR COMBI 3430-05 - All variants

Label No : 43918

SECTION 11: Toxicological information

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
TEKNODUR COMBI 3430-05	N/A	29231.5	N/A	292.3	N/A
n-Butyl acetate	10760	14112	N/A	N/A	N/A
2-Methoxy-1-methylethyl acetate	8532	N/A	N/A	N/A	N/A
Xylene	4300	1100	N/A	11	N/A
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	3230	N/A	N/A	N/A	N/A
Maleic anhydride	400	2620	N/A	N/A	N/A

Skin corrosion/irritation

Product/ingredient name

n-Butyl acetate

Result

Rabbit - Skin - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

Xylene

Rat - Skin - Mild irritant

Duration of treatment/exposure: 8 hours

Amount/concentration applied: 60 uL

Rabbit - Skin - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

4-morpholinecarbaldehyde

Rabbit - Skin - Moderate irritant

Amount/concentration applied: 100 %

Rabbit - Skin - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Product/ingredient name

n-Butyl acetate

Result

Rabbit - Eyes - Moderate irritant

Amount/concentration applied: 100 mg

Xylene

Rabbit - Eyes - Mild irritant

Amount/concentration applied: 87 mg

Rabbit - Eyes - Severe irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 5 mg

4-morpholinecarbaldehyde

Rabbit - Eyes - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

Maleic anhydride

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 1 %

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Not available.

SECTION 11: Toxicological information

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name

n-Butyl acetate
2-Methoxy-1-methylethyl acetate
Xylene

Result

STOT SE 3, H336 (Narcotic effects)
STOT SE 3, H336 (Narcotic effects)
STOT SE 3, H335 (Respiratory tract irritation)

Specific target organ toxicity (repeated exposure)

Product/ingredient name

Xylene
Maleic anhydride

Result

STOT RE 2, H373 (oral, inhalation)
STOT RE 1, H372 (respiratory system) (inhalation)

Aspiration hazard

Product/ingredient name

Xylene

Result

ASPIRATION HAZARD - Category 1

Information on likely routes of exposure

Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : May cause an allergic skin reaction.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : Adverse symptoms may include the following:
irritation
redness

SECTION 11: Toxicological information

Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name

n-Butyl acetate

Result

Acute - LC50 - Fresh water

Fish - Fathead minnow - *Pimephales promelas*
Age: 31 to 32 days; Size: 21.6 mm; Weight: 0.175 g
18000 µg/l [96 hours]
Effect: Mortality

Acute - LC50 - Marine water

Crustaceans - Brine shrimp - *Artemia salina*
32 mg/l [48 hours]
Effect: Mortality

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Acute - LC50

OECD [Fish, Acute Toxicity Test]
Fish - *Brachydanio rerio*
0.9 mg/l [96 hours]

EC50

OECD [Alga, Growth Inhibition Test]
Aquatic plants - *Desmodesmodus subspicatus*
1.68 mg/l [72 hours]

Chronic - NOEC

OECD [Daphnia Magna Reproduction Test]
Daphnia - Daphnia
1 mg/l [21 days]

Maleic anhydride

Acute - LC50 - Fresh water

Date of issue/Date of revision : 05/03/2026 **Date of previous issue** : 26/01/2026

Version : 13 29/38

TEKNODUR COMBI 3430-05 - All variants

Label No : 43918

SECTION 12: Ecological information

Fish - Western mosquitofish - *Gambusia affinis* - Adult
230000 µg/l [96 hours]
Effect: Mortality

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Not available.

Conclusion/Summary [Product] : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
n-Butyl acetate	2.3	-	Low
2-Methoxy-1-methylethyl acetate	1.2	-	Low
Xylene	3.12	8.1 to 25.9	Low
4-morpholinecarbaldehyde	-	<1.9 [OECD 305 C]	Low
Maleic anhydride	-2.78	-	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logK _{oc}	K _{oc}
<input checked="" type="checkbox"/> Butyl acetate	1.5	33.2139
2-Methoxy-1-methylethyl acetate	0.36	2.31363
4-morpholinecarbaldehyde	1.6	39.587
12-hydroxy-N-[6-(12-hydroxyoctadecanamido)hexyl]octadecanamide	4.3	20556.9
Maleic anhydride	1.1	11.4841

Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
<input checked="" type="checkbox"/> Butyl acetate	No	No	No	No	No	No	No
2-Methoxy-1-methylethyl acetate	No	No	No	No	No	No	No
Xylene	No	No	No	No	No	No	No
4-morpholinecarbaldehyde	No	No	No	No	No	No	No
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	No	No	No	No	No	No	No
Fatty acids, C14-18 and C16-18-unsatd., maleated	No	No	No	No	No	No	No
12-hydroxy-N-[6-(12-hydroxyoctadecanamido)hexyl]octadecanamide	No	No	No	No	No	No	No
Maleic anhydride	No	No	No	No	No	No	No

Mobility : Not available.

Conclusion/Summary : The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

SECTION 12: Ecological information

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
<input checked="" type="checkbox"/> Butyl acetate	No	N/A	N/A	No	N/A	N/A	N/A
2-Methoxy-1-methylethyl acetate	No	N/A	N/A	No	N/A	N/A	N/A
Xylene	No	N/A	No	Yes	No	N/A	No
4-morpholinecarbaldehyde	No	N/A	No	No	No	N/A	No
Reaction mass of Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	N/A	N/A	N/A	Yes	N/A	N/A	N/A
Fatty acids, C14-18 and C16-18-unsatd., maleated	No	N/A	N/A	No	N/A	N/A	N/A
12-hydroxy-N-[6-(12-hydroxyoctadecanamido)hexyl]octadecanamide	No	N/A	N/A	No	N/A	N/A	N/A
Maleic anhydride	N/A	N/A	N/A	Yes	N/A	N/A	N/A

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
<input checked="" type="checkbox"/> Butyl acetate	No	No	No	No	No	No	No
2-Methoxy-1-methylethyl acetate	No	No	No	No	No	No	No
Xylene	No	No	No	No	No	No	No
4-morpholinecarbaldehyde	No	No	No	No	No	No	No
Reaction mass of Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	No	No	No	No	No	No	No
Fatty acids, C14-18 and C16-18-unsatd., maleated	No	No	No	No	No	No	No
12-hydroxy-N-[6-(12-hydroxyoctadecanamido)hexyl]octadecanamide	No	No	No	No	No	No	No
Maleic anhydride	No	No	No	No	No	No	No

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP] : The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

SECTION 13: Disposal considerations

- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
- Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.
- European waste catalogue (EWC)** : 080111*, 200127*
- Packaging**
- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
- Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3 	3 	3 	3 
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	No.	No.	No.	No.

Additional information

- ADR/RID** : **Viscous liquid exception** This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.
Tunnel code (D/E)
- ADN** : **Viscous liquid exception** This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.
- IMDG** : **Viscous liquid exception** This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.3.2.5.
- 14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
- 14.7 Maritime transport in bulk according to IMO instruments** : Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
TEKNODUR COMBI 3430-05	≥90	3

Labelling :

Other EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Explosive precursors : Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category
P5c

National regulations

Austria

Limitation of the use of organic solvents : Permitted.

Belgium

Book VI carcinogenic agents annex VI.2-1 - VI.2-3

Ingredient name	Status
Styrène	Listed

Czech Republic

Storage code : II

Denmark

Fire class : II-1

Executive Order No. 1795/2015

SECTION 15: Regulatory information

Ingredient name	Annex I Section A	Annex I Section B
titanium dioxide	Listed	-
Ethylbenzene	Listed	-

MAL-code : 3-1

Protection based on MAL : According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:

General: Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

MAL-code: 3-1

Application: When spraying in new* booths if the operator is outside the spray zone. When using scraper or knife, brush, roller, etc, for pre- and post-treatments in cabins or booths of the existing* facility type, if the operator is inside the spray zone. When using scraper or knife, brush, roller, etc. for pre- and post-treatments outside a closed facility, spray booth or spray cabin. During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents.

- Air-supplied half mask and eye protection must be worn.

When spraying in existing* spray booths, if the operator is outside the spray zone.

- Air-supplied full mask and arm protectors must be worn.

During non-atomising spraying in existing* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone.

- Air-supplied full mask must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Air-supplied full mask, coveralls and hood must be worn.

Drying: Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

Polishing: When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

Caution The regulations contain other stipulations in addition to the above.

*See Regulations.

Restrictions on use : Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.

List of undesirable substances : Not listed

SECTION 15: Regulatory information

Carcinogenic waste : Waste containers must be labeled: Contains a substance or substances regulated by Danish working environment legislation on cancer risks.

Finland

France

Social Security Code, Articles L 461-1 to L 461-7 : n-Butyl acetate RG 84
2-Methoxy-1-methylethyl acetate RG 84
Xylene RG 4bis, RG 84
Maleic anhydride RG 66

Reinforced medical surveillance : Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable

Germany

Storage class (TRGS 510) : 3

Hazardous incident ordinance

This product is controlled under the Germany Hazardous Incident Ordinance.

Danger criteria

Category	Reference number
P5c	1.2.5.3

Hazard class for water : 2

Technical instruction on air quality control (TA Luft)

Number [Class]	Description	%
5.2.1	Total dust	74.5
5.2.2 [III]	Dusty inorganic substances	0.014
5.2.5	Organic substances	25.5
5.2.5 [I]	Organic substances	24.8
5.2.7.1.1 [II]	Carcinogenic substances	0.015
5.2.7.1.3	Reproductive toxic substances	0.019

Italy

D.Lgs. 152/06 : Not determined.

Netherlands

Ministry of Social Affairs and Employment (SZW) - Carcinogenic substances and processes, mutagenic or reprotoxic substances

Ingredient name	Carcinogen	Mutagen	Reproductive toxicity - Fertility	Reproductive toxicity - Development	Harmful via breastfeeding
xyleen	-	-	-	Development 2	-

Water Discharge Policy (ABM) : A(2) Toxic for aquatic organisms, may have long-term hazardous effects in aquatic environment. Decontamination effort: A

Norway

Sweden

Flammable liquid class (SRVFS 2005:10) : 2a

Switzerland

VOC content : VOC (w/w): 24.6%

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Date of issue/Date of revision : 05/03/2026 **Date of previous issue** : 26/01/2026 **Version** : 13 **35/38**

TEKNODUR COMBI 3430-05 - All variants

Label No : 43918

SECTION 15: Regulatory information

Not listed.

[UNECE Aarhus Protocol on POPs and Heavy Metals](#)

Not listed.

15.2 Chemical safety assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms :

- ATE = Acute Toxicity Estimate
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = CLP-specific Hazard statement
- N/A = Not available
- PBT = Persistent, Bioaccumulative and Toxic
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- SGG = Segregation Group
- vPvB = Very Persistent and Very Bioaccumulative

[Procedure used to derive the classification according to Regulation \(EC\) No. 1272/2008 \[CLP/GHS\]](#)

Classification	Justification
Flam. Liq. 3, H226 Skin Sens. 1, H317	On basis of test data Calculation method

[Full text of abbreviated H statements](#)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.

[Full text of classifications \[CLP/GHS\]](#)

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Aquatic Chronic 4	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 2	REPRODUCTIVE TOXICITY - Category 2

Date of issue/Date of revision : 05/03/2026 **Date of previous issue** : 26/01/2026 **Version** : 13 **36/38**

TEKNODUR COMBI 3430-05 - All variants

Label No : 43918

SECTION 16: Other information

Resp. Sens. 1	RESPIRATORY SENSITISATION - Category 1
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of issue/ Date of revision : 05/03/2026

Date of previous issue : 26/01/2026

Version : 13

TEKNODUR COMBI 3430-05

All variants

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

