

SAFETY DATA SHEET



TEKNODUR COMBI 3560-09 - All variants

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : TEKNODUR COMBI 3560-09 - All variants

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS : Prod-safe@teknos.com

National contact

Teknos (UK) Limited, 7 Longlands Rd, Bicester, Oxfordshire OX26 5AH, United Kingdom. Tel. +44 (0) 1869 208005.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : NHS: 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to UK CLP/GHS

Flam. Liq. 3, H226

Skin Corr. 1C, H314

Eye Dam. 1, H318

Skin Sens. 1, H317

Aquatic Chronic 2, H411

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 - Flammable liquid and vapour.
H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention : P280 - Wear protective gloves, protective clothing and eye or face protection.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273 - Avoid release to the environment.

SECTION 2: Hazards identification

Response	: P391 - Collect spillage. P304 + P310 - IF INHALED: Immediately call a POISON CENTER or doctor.
Storage	: Not applicable.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Type
Bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane	REACH #: 01-0000015937-58 EC: 412-060-9 CAS: 136210-32-7 Index: 607-350-00-9	≥10 - ≤25	Skin Sens. 1, H317 Aquatic Chronic 3, H412	[1]
Trizinc bis(orthophosphate)	REACH #: 01-2119485044-40 EC: 231-944-3 CAS: 7779-90-0 Index: 030-011-00-6	≤10	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
1,3,3-trimethyl-N-(2-methylpropylidene)-5-[(2-methylpropylidene)amino]-cyclohexanemethylamine tetraethylN,N'-(methylenedicyclohexane-4,1-diyl)bis-dl-aspartate	REACH #: 01-2119978283-28 EC: 259-393-4 CAS: 54914-37-3	≤10	Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317	[1]
	REACH #: 01-0000017556-64 EC: 429-270-1 CAS: 136210-30-5 Index: 607-521-00-8	≤5	Skin Sens. 1, H317 Aquatic Chronic 3, H412	[1]
n-Butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1	≤5	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	[1] [2]
2-Methoxy-1-methylethyl acetate	REACH #: 01-2119475791-29 EC: 203-603-9 CAS: 108-65-6 Index: 607-195-00-7	≤5	Flam. Liq. 3, H226 STOT SE 3, H336	[1] [2]
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate	REACH #: 01-2119491304-40 EC: 915-687-0 CAS: 1065336-91-5	≤1	Skin Sens. 1A, H317 Repr. 2, H361f Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
Xylene	REACH #:	<1	Flam. Liq. 3, H226	[1] [2]

Date of issue/Date of revision : 09/05/2025 **Date of previous issue** : 28/10/2022 **Version** : 4 **2/27**

FEKNODUR COMBI 3560-09 - All variants

Label No : 17797

SECTION 3: Composition/information on ingredients

	01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9		Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 (oral, inhalation) Asp. Tox. 1, H304 Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336	
iso-butanol	REACH #: 01-2119484609-23 EC: 201-148-0 CAS: 78-83-1 Index: 603-108-00-1	≤0.3	Asp. Tox. 1, H304 Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336	[1] [2]
Zinc oxide	REACH #: 01-2119463881-32 EC: 215-222-5 CAS: 1314-13-2 Index: 030-013-00-7	≤0.3	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
Ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≤0.1	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) (oral, inhalation) Asp. Tox. 1, H304 Flam. Liq. 3, H226 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	[1] [2]
cumene	EC: 202-704-5 CAS: 98-82-8 Index: 601-024-00-X	≤0.1	Asp. Tox. 1, H304 Flam. Liq. 3, H226 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	[1] [2]
Phenol	REACH #: 01-2119471329-32 EC: 203-632-7 CAS: 108-95-2 Index: 604-001-00-2	<0.1	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 Muta. 2, H341 STOT RE 2, H373 See Section 16 for the full text of the H statements declared above.	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

- : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

- : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire,

SECTION 4: First aid measures

symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

- Skin contact** : Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

SECTION 5: Firefighting measures

Hazardous combustion products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
sulfur oxides
phosphorus oxides
metal oxide/oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

6.4 Reference to other sections

: See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c E2	5000 tonnes 200 tonnes	50000 tonnes 500 tonnes

7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

<input checked="" type="checkbox"/> Butyl acetate	EH40/2005 WELs (United Kingdom (UK), 1/2020) STEL 15 minutes: 966 mg/m ³ . STEL 15 minutes: 200 ppm. TWA 8 hours: 724 mg/m ³ . TWA 8 hours: 150 ppm.
2-Methoxy-1-methylethyl acetate	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin. STEL 15 minutes: 548 mg/m ³ . TWA 8 hours: 50 ppm. TWA 8 hours: 274 mg/m ³ . STEL 15 minutes: 100 ppm.
Xylene	EH40/2005 WELs (United Kingdom (UK), 1/2020) [xylene, o-,m-, p- or mixed isomers] Absorbed through skin. STEL 15 minutes: 441 mg/m ³ . TWA 8 hours: 50 ppm.

SECTION 8: Exposure controls/personal protection

iso-butanol	TWA 8 hours: 220 mg/m ³ . STEL 15 minutes: 100 ppm. EH40/2005 WELs (United Kingdom (UK), 1/2020) STEL 15 minutes: 231 mg/m ³ . STEL 15 minutes: 75 ppm. TWA 8 hours: 154 mg/m ³ . TWA 8 hours: 50 ppm.
Ethylbenzene	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin. STEL 15 minutes: 552 mg/m ³ . STEL 15 minutes: 125 ppm. TWA 8 hours: 100 ppm. TWA 8 hours: 441 mg/m ³ .
cumene	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin. STEL 15 minutes: 250 mg/m ³ . STEL 15 minutes: 50 ppm. TWA 8 hours: 25 ppm. TWA 8 hours: 125 mg/m ³ .
Phenol	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin. TWA 8 hours: 2 ppm. STEL 15 minutes: 16 mg/m ³ . STEL 15 minutes: 4 ppm. TWA 8 hours: 7.8 mg/m ³ .

Biological exposure indices

Product/ingredient name	Exposure indices
Xylene	EH40/2005 BMGVs (United Kingdom (UK), 1/2020) [Xylene, o-, m-, p- or mixed isomers] BGV: 650 mmol/mol creatinine, methyl hippuric acid [in urine]. Sampling time: post shift.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Result
bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane	DNEL - General population - Short term - Oral 4.2 mg/kg bw/day <u>Effects</u> : Systemic DNEL - General population - Long term - Oral 4.2 mg/kg bw/day <u>Effects</u> : Systemic DNEL - General population - Short term - Dermal 4.2 mg/kg bw/day <u>Effects</u> : Systemic DNEL - General population - Long term - Dermal 4.2 mg/kg bw/day <u>Effects</u> : Systemic DNEL - Workers - Long term - Dermal 11.9 mg/kg bw/day <u>Effects</u> : Systemic

SECTION 8: Exposure controls/personal protection

1,3,3-trimethyl-N-(2-methylpropylidene)-5-[(2-methylpropylidene)amino]-cyclohexanemethylamine

DNEL - General population - Short term - Inhalation
14.5 mg/m³
Effects: Systemic

DNEL - General population - Long term - Inhalation
14.5 mg/m³
Effects: Systemic

DNEL - Workers - Long term - Inhalation
84 mg/m³
Effects: Systemic

DNEL - Workers - Short term - Inhalation
672 mg/m³
Effects: Systemic

DNEL - General population - Long term - Oral
0.3 mg/kg bw/day
Effects: Systemic

DNEL - Workers - Short term - Inhalation
0.073 mg/m³
Effects: Local

DNEL - Workers - Long term - Inhalation
0.073 mg/m³
Effects: Local

tetraethylN,N'-(methylenedicyclohexane-4,1-diyl)bis-dl-aspartate

DNEL - General population - Short term - Oral
1.4 mg/kg bw/day
Effects: Systemic

DNEL - General population - Long term - Oral
1.4 mg/kg bw/day
Effects: Systemic

DNEL - General population - Short term - Dermal
1.4 mg/kg bw/day
Effects: Systemic

DNEL - General population - Long term - Dermal
1.4 mg/kg bw/day
Effects: Systemic

DNEL - Workers - Long term - Dermal
4 mg/kg bw/day
Effects: Systemic

DNEL - General population - Short term - Inhalation
4.8 mg/m³
Effects: Systemic

DNEL - General population - Long term - Inhalation
4.8 mg/m³
Effects: Systemic

DNEL - Workers - Long term - Inhalation
28 mg/m³
Effects: Systemic

DNEL - Workers - Short term - Inhalation
112 mg/m³
Effects: Systemic

n-Butyl acetate

DNEL - General population - Long term - Oral
2 mg/kg bw/day

SECTION 8: Exposure controls/personal protection

Effects: Systemic

DNEL - General population - Short term - Oral

2 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

3.4 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Dermal

6 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

7 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Short term - Dermal

11 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

12 mg/m³

Effects: Systemic

DNEL - General population - Long term - Inhalation

35.7 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

48 mg/m³

Effects: Systemic

DNEL - General population - Short term - Inhalation

300 mg/m³

Effects: Local

DNEL - General population - Short term - Inhalation

300 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

300 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

600 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

600 mg/m³

Effects: Systemic

2-Methoxy-1-methylethyl acetate

DNEL - General population - Long term - Inhalation

33 mg/m³

Effects: Local

DNEL - General population - Long term - Inhalation

33 mg/m³

Effects: Systemic

DNEL - General population - Long term - Oral

36 mg/kg bw/day

Effects: Systemic

SECTION 8: Exposure controls/personal protection

DNEL - Workers - Long term - Inhalation

275 mg/m³

Effects: Systemic

DNEL - General population - Long term - Dermal

320 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Short term - Inhalation

550 mg/m³

Effects: Local

DNEL - Workers - Long term - Dermal

796 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Oral

0.18 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

0.31 mg/m³

Effects: Systemic

DNEL - General population - Long term - Dermal

0.9 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

1.27 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Dermal

1.8 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Oral

5 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

65.3 mg/m³

Effects: Local

DNEL - General population - Long term - Inhalation

65.3 mg/m³

Effects: Systemic

DNEL - General population - Long term - Dermal

125 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

212 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

221 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

221 mg/m³

Effects: Systemic

DNEL - General population - Short term - Inhalation

260 mg/m³

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Xylene

SECTION 8: Exposure controls/personal protection

Effects: Local

DNEL - General population - Short term - Inhalation

260 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Inhalation

442 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

442 mg/m³

Effects: Systemic

iso-butanol

DNEL - General population - Long term - Inhalation

55 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

310 mg/m³

Effects: Local

Ethylbenzene

DMEL - Workers - Long term - Inhalation

442 mg/m³

Effects: Local

DMEL - Workers - Short term - Inhalation

884 mg/m³

Effects: Systemic

DNEL - General population - Long term - Oral

1.6 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

15 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

77 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Dermal

180 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Short term - Inhalation

293 mg/m³

Effects: Local

cumene

DNEL - General population - Long term - Dermal

1.2 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

15.4 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

100 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Inhalation

250 mg/m³

Effects: Local

SECTION 8: Exposure controls/personal protection

Phenol

DNEL - General population - Long term - Oral

5 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

16.6 mg/m³

Effects: Systemic

DNEL - General population - Long term - Inhalation

0.452 mg/m³

Effects: Systemic

DNEL - General population - Long term - Oral

0.5 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

0.5 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

1.23 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

8 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Inhalation

16 mg/m³

Effects: Local

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

- : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

SECTION 8: Exposure controls/personal protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Recommendations : Wear suitable gloves tested to EN374.
- < 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm
- 1 - 4 hours (breakthrough time): polyvinyl alcohol (PVA) thickness > 0.3 mm or 4H / Silver Shield® gloves.
- > 8 hours (breakthrough time): Viton® thickness > 0.3 mm gloves
- Wash hands before breaks and immediately after handling the product.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to British Standard BS EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
- Filter type: A
- Filter type (spray application): A P
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties


Appearance



- Physical state** : Liquid.
- Colour** : Various
- Odour** : Slight
- Odour threshold** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** :

Ingredient name	°C	°F	Method
n-Butyl acetate	126	258.8	OECD 103
2-Methoxy-1-methylethyl acetate	145.8	294.4	OECD 103

- Flammability (solid, gas)** : Not available.
- Upper/lower flammability or explosive limits** : Lower: 1.4% (n-butyl acetate)
Upper: 7.6% (n-butyl acetate)
- Flash point** : Closed cup: 25°C (77°F)
- Auto-ignition temperature** :

SECTION 9: Physical and chemical properties

Ingredient name	°C	°F	Method
 Methoxy-1-methylethyl acetate	333	631.4	DIN 51794
tetraethylN,N'-(methylenedicyclohexane-4,1-diyl)bis-dl-aspartate	375	707	EU A.15


Decomposition temperature : Not available.
pH :  Not applicable.
Viscosity :  Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C): Not available.

Solubility(ies) :
Not available.

Solubility in water : Not available.

Partition coefficient: n-octanol/ water : Not applicable.

Vapour pressure :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
 Butyl acetate	11.25096	1.5	DIN EN 13016-2			
2-Methoxy-1-methylethyl acetate	2.7	0.36	OECD 104			

Relative density : Not available.
Density :  8 g/cm³
Vapour density : Not available.
Explosive properties : Not available.
Oxidising properties : Not available.
Particle characteristics
Median particle size : Not applicable.

9.2 Other information

Not available.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

10.5 Incompatible materials : Reactive or incompatible with the following materials:
oxidising materials

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name

 Butyl acetate

Result

Rat - Oral - LD50

10760 mg/kg

EU

Rabbit - Dermal - LD50

14112 mg/kg

Rat - Inhalation - LC50 Vapour

0.74 mg/l [4 hours]

2-Methoxy-1-methylethyl acetate

Rat - Oral - LD50

8532 mg/kg

Rabbit - Dermal - LD50

>5 g/kg

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Rat - Oral - LD50

3230 mg/kg

Rat - Dermal - LD50

>3170 mg/kg

Xylene

Rat - Oral - LD50

4300 mg/kg

Toxic effects: Liver - Other changes Kidney, Ureter, and Bladder - Other changes

Rat - Inhalation - LC50 Vapour

21.7 mg/l [4 hours]

iso-butanol

Rat - Oral - LD50

2460 mg/kg

Rabbit - Dermal - LD50

3400 mg/kg

Rat - Inhalation - LC50 Vapour

19200 mg/m³ [4 hours]

Ethylbenzene

Rat - Oral - LD50

3500 mg/kg

Rabbit - Dermal - LD50

15400 mg/kg

Rat - Inhalation - LC50 Dusts and mists

29000 mg/l [4 hours]

cumene

Rat - Oral - LD50

1400 mg/kg

Toxic effects: Gastrointestinal - Gastritis

Rat - Inhalation - LC50 Vapour

39000 mg/m³ [4 hours]

Phenol

Rat - Oral - LD50

317 mg/kg

Toxic effects: Behavioral - Convulsions or effect on seizure threshold

Rat - Dermal - LD50

SECTION 11: Toxicological information

669 mg/kg

Toxic effects: Behavioral - Tremor Kidney, Ureter, and Bladder
- Hematuria Skin After topical exposure - Cutaneous sensitization (experimental)

Rabbit - Dermal - LD50

630 mg/kg

Rat - Inhalation - LC50 Vapour

316 mg/m³ [4 hours]

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
n-Butyl acetate	10760	14112	N/A	N/A	N/A
2-Methoxy-1-methylethyl acetate	8532	N/A	N/A	N/A	N/A
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	3230	N/A	N/A	N/A	N/A
Xylene	4300	1100	N/A	11	N/A
iso-butanol	2460	3400	N/A	N/A	N/A
Ethylbenzene	3500	15400	N/A	11	29000
cumene	N/A	N/A	N/A	39	N/A
Phenol	100	630	N/A	3	N/A

Skin corrosion/irritation

Product/ingredient name

n-Butyl acetate

Xylene

Zinc oxide

Ethylbenzene

cumene

Result

Rabbit - Skin - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

Rat - Skin - Mild irritant

Duration of treatment/exposure: 8 hours

Amount/concentration applied: 60 uL

Rabbit - Skin - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

Rabbit - Skin - Moderate irritant

Amount/concentration applied: 100 %

Rabbit - Skin - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

Rabbit - Skin - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 15 mg

Rabbit - Skin - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 10 mg

Rabbit - Skin - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 mg

SECTION 11: Toxicological information

Phenol

Pig - Skin - Severe irritant

Duration of treatment/exposure: 0.5 minutes

Amount/concentration applied: 400 uL

Rabbit - Skin - Mild irritant

Amount/concentration applied: 100 mg


Rabbit - Skin - Severe irritant

Amount/concentration applied: 535 mg

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Product/ingredient name

 bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane

n-Butyl acetate

Xylene

Zinc oxide

Ethylbenzene

cumene

Phenol

Result

Rabbit - Eyes - Mild irritant

Rabbit - Eyes - Moderate irritant

Amount/concentration applied: 100 mg

Rabbit - Eyes - Mild irritant

Amount/concentration applied: 87 mg

Rabbit - Eyes - Severe irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 5 mg

Rabbit - Eyes - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 500 mg

Rabbit - Eyes - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

Rabbit - Eyes - Mild irritant

Amount/concentration applied: 86 mg

Rabbit - Eyes - Mild irritant

Duration of treatment/exposure: 0.5 minutes


Amount/concentration applied: 5 mg

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 5 mg

Conclusion/Summary [Product] : Not available.

Ingredient name

 bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane

Conclusion/Summary

Non-irritating to the eyes.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Not available.

SECTION 11: Toxicological information

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name

☒ Butyl acetate
2-Methoxy-1-methylethyl acetate
Xylene
iso-butanol

cumene

Result

STOT SE 3, H336 (Narcotic effects)
STOT SE 3, H336 (Narcotic effects)
STOT SE 3, H335 (Respiratory tract irritation)
STOT SE 3, H335 (Respiratory tract irritation)
STOT SE 3, H336 (Narcotic effects)
STOT SE 3, H335 (Respiratory tract irritation)

Specific target organ toxicity (repeated exposure)

Product/ingredient name

☒ Xylene
Ethylbenzene
Phenol

Result

STOT RE 2, H373 (oral, inhalation)
STOT RE 2, H373 (hearing organs) (oral, inhalation)
STOT RE 2, H373

Aspiration hazard

Product/ingredient name

☒ Xylene
Ethylbenzene
cumene

Result

ASPIRATION HAZARD - Category 1
ASPIRATION HAZARD - Category 1
ASPIRATION HAZARD - Category 1

Information on likely routes of exposure

Not available.

Potential acute health effects

Eye contact : Causes serious eye damage.
Inhalation : No known significant effects or critical hazards.
Skin contact : Causes severe burns. May cause an allergic skin reaction.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

SECTION 11: Toxicological information

Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name

bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane

Result

Acute - LC50

Fish
66 mg/l [96 hours]

Acute - EC50

Daphnia
88.6 mg/l [48 hours]

Acute - EC50

Algae
113 mg/l [72 hours]

Trizinc bis(orthophosphate)

Acute - EC50

Crustaceans - *Ceriodaphnia dubia*
0.96 mg/l [48 hours]

Acute - EC50

Algae - *Selenastrum capricornutum*
0.32 mg/l [72 hours]

tetraethylN,N'-(methylenedicyclohexane-4,1-diyl)bis-dl-aspartate

Acute - LC50

Fish

SECTION 12: Ecological information

66 mg/l [96 hours]

Acute - EC50

Daphnia

88.6 mg/l [48 hours]

Acute - EC50

Algae

113 mg/l [72 hours]

n-Butyl acetate

Acute - LC50 - Fresh water

Fish - Fathead minnow - *Pimephales promelas*

Age: 31 to 32 days; Size: 21.6 mm; Weight: 0.175 g

18000 µg/l [96 hours]

Effect: Mortality

Acute - LC50 - Marine water

Crustaceans - Brine shrimp - *Artemia salina*

32 mg/l [48 hours]

Effect: Mortality

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Acute - LC50

OECD [Fish, Acute Toxicity Test]

Fish - *Brachydanio rerio*

0.9 mg/l [96 hours]

EC50

OECD [Alga, Growth Inhibition Test]

Aquatic plants - *Desmodesmodus subspicatus*

1.68 mg/l [72 hours]

Chronic - NOEC

OECD [Daphnia Magna Reproduction Test]

Daphnia - Daphnia

1 mg/l [21 days]

iso-butanol

Acute - LC50 - Fresh water

Fish - Rainbow trout, donaldson trout - *Oncorhynchus mykiss*

Weight: 1.67 g

1330000 µg/l [96 hours]

Effect: Mortality

Acute - LC50 - Marine water

Crustaceans - Brine shrimp - *Artemia salina*

600 mg/l [48 hours]

Effect: Mortality

Zinc oxide

Acute - LC50 - Fresh water

Daphnia - Water flea - *Daphnia magna* - Neonate

Age: <24 hours

98 µg/l [48 hours]

Effect: Mortality

Acute - IC50 - Fresh water

Algae - Green algae - *Pseudokirchneriella subcapitata* -

Exponential growth phase

46 µg/l [72 hours]

Effect: Population

Acute - LC50 - Fresh water

US EPA

Fish - Rainbow trout, donaldson trout - *Oncorhynchus mykiss*

Weight: 0.78 g

1.1 ppm [96 hours]

Effect: Mortality

SECTION 12: Ecological information

cumene

Acute - LC50 - Fresh water

Fish - Rainbow trout,donaldson trout - *Oncorhynchus mykiss*
2700 µg/l [96 hours]
Effect: Mortality

Acute - EC50 - Marine water

Crustaceans - Brine shrimp - *Artemia sp.* - Nauplii
Age: 2 to 3
7.4 mg/l [48 hours]
Effect: Intoxication

Phenol

Acute - LC50 - Fresh water

Fish - common carp - *Cyprinus carpio* - Larvae
Size: 8 mm
1.75 µg/l [96 hours]
Effect: Mortality

Acute - LC50 - Marine water

Crustaceans - Opossum shrimp - *Archaeomysis kokuboi* - Juvenile (Fledgling, Hatchling, Weanling)
800 µg/l [48 hours]
Effect: Mortality

Chronic - NOEC - Fresh water

Fish - Rainbow trout,donaldson trout - *Oncorhynchus mykiss*
118 µg/l [90 days]
Effect: Mortality

Acute - EC50 - Fresh water

Algae - Green algae - *Pseudokirchneriella subcapitata*
Age: 4 to 7 days
61.1 µg/l [96 hours]
Effect: Population

Chronic - NOEC - Fresh water

Daphnia - Water flea - *Daphnia magna*
Age: <24 hours
1.5 mg/l [21 days]
Effect: Reproduction

Chronic - NOEC - Marine water

Algae - Neptune's Necklace - *Hormosira banksii* - Gamete
16 µg/l [72 hours]
Effect: Development

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Product/ingredient name

Result

iso-butanol

74% [28 days] - Readily

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
iso-butanol	-	-	Readily

12.3 Bioaccumulative potential

SECTION 12: Ecological information

Product/ingredient name	LogP _{ow}	BCF	Potential
Bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane	5.99	0.25	Low
Trizinc bis(orthophosphate)	-	60960	High
tetraethylN,N'-(methylenedicyclohexane-4,1-diyl)bis-dl-aspartate	5.16	0.25	Low
n-Butyl acetate	2.3	-	Low
2-Methoxy-1-methylethyl acetate	1.2	-	Low
Xylene	3.12	8.1 to 25.9	Low
iso-butanol	1	-	Low
Zinc oxide	-	28960	High
Ethylbenzene	3.6	-	Low
cumene	3.55	35.48	Low
Phenol	1.47	647	High

12.4 Mobility in soil

Soil/water partition coefficient : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane	No	No	No	No	No	No	No
Trizinc bis(orthophosphate)	No	No	No	No	No	No	No
1,3,3-trimethyl-N-(2-methylpropylidene)-5-[(2-methylpropylidene)amino]-cyclohexanemethylamine	No	No	No	No	No	No	No
tetraethylN,N'-(methylenedicyclohexane-4,1-diyl)bis-dl-aspartate	No	No	No	No	No	No	No
n-Butyl acetate	No	No	No	No	No	No	No
2-Methoxy-1-methylethyl acetate	No	No	No	No	No	No	No
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	No	No	No	Yes	No	No	No
Xylene	No	No	No	Yes	No	No	No
iso-butanol	No	No	No	No	No	No	No
Zinc oxide	No	No	No	No	No	No	No
Ethylbenzene	No	No	No	Yes	No	No	No
cumene	No	No	No	No	No	No	No
Phenol	No	No	No	Yes	No	No	No

SECTION 12: Ecological information

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.













European waste catalogue (EWC) : 080111*, 200127*

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN2924	UN2924	UN2924	UN2924
14.2 UN proper shipping name	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (n-butyl acetate, 1,3,3-trimethyl-N-(2-methylpropylidene)-5-[(2-methylpropylidene)amino]cyclohexanemethylamine)	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (n-butyl acetate, 1,3,3-trimethyl-N-(2-methylpropylidene)-5-[(2-methylpropylidene)amino]cyclohexanemethylamine)	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (n-butyl acetate, 1,3,3-trimethyl-N-(2-methylpropylidene)-5-[(2-methylpropylidene)amino]cyclohexanemethylamine)	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (n-butyl acetate, 1,3,3-trimethyl-N-(2-methylpropylidene)-5-[(2-methylpropylidene)amino]cyclohexanemethylamine)
14.3 Transport hazard class(es)	3 (8)   	3 (8)   	3 (8)   	3 (8)   
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.

Additional information

ADR/RID : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
Tunnel code (D/E)

SECTION 14: Transport information

- ADN** : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
- IMDG** : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
- IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture UK (GB)/REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Ozone depleting substances

Not listed.

Prior Informed Consent (PIC)

Not listed.

Persistent Organic Pollutants

Not listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
TEKNODUR COMBI 3560-09	≥90	3

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category
P5c E2

EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

SECTION 15: Regulatory information

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate
GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = GB CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

Classification	Justification
Flam. Liq. 3, H226 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411	On basis of test data Calculation method Calculation method Calculation method Calculation method

Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Date of issue/Date of revision

: 09/05/2025

Date of previous issue

: 28/10/2022

Version : 4

25/27

EKNODUR COMBI 3560-09 - All variants

Label No : 17797

SECTION 16: Other information

Full text of classifications

Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Muta. 2	GERM CELL MUTAGENICITY - Category 2
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of issue/ Date of revision : 09/05/2025

Date of previous issue : 28/10/2022

Version : 4

TEKNODUR COMBI 3560-09

All variants

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

