

SAFETY DATA SHEET



TEKNOFLOOR 100F - All variants

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : TEKNOFLOOR 100F - All variants

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS : Prod-safe@teknos.com

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : Emergency medical information: (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland.
Members of the public Number (8 am-10 pm): +353 (0)1 809 2166
Healthcare professional telephone Number (24hrs): +353 (0)1 809 2566

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226
Skin Irrit. 2, H315
Eye Dam. 1, H318
Skin Sens. 1, H317
Carc. 2, H351
STOT SE 3, H335
STOT RE 2, H373
Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 - Flammable liquid and vapour.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H318 - Causes serious eye damage.
H335 - May cause respiratory irritation.
H351 - Suspected of causing cancer.
H373 - May cause damage to organs through prolonged or repeated exposure.
H412 - Harmful to aquatic life with long lasting effects.

Date of issue/Date of revision : 20/11/2025 **Date of previous issue** : 28/04/2023

Version : 2 **1/25**

TEKNOFLOOR 100F - All variants

Label No : 36672

SECTION 2: Hazards identification

Precautionary statements

Prevention	: P280 - Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 - Do not breathe vapour.
Response	: P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Storage	: P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	: Contains: Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane; Xylene; Solvent naphtha (petroleum), light aromatic and iso-butanol
Supplemental label elements	:
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane	CAS: 25036-25-3	≥25 - ≤50	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317	-	[1]
Xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	≥10 - ≤25	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 (oral, inhalation) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Dermal] = 1100 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
Solvent naphtha (petroleum), light aromatic	REACH #: 01-2119455851-35 EC: 265-199-0 CAS: 64742-95-6 Index: 649-356-00-4	≤8.4	Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2,	-	[1]

SECTION 3: Composition/information on ingredients

iso-butanol	REACH #: 01-2119484609-23 EC: 201-148-0 CAS: 78-83-1 Index: 603-108-00-1	≤5	H411 EUH066 Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336	-	[1] [2]
Ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≤3	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) (oral, inhalation) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
Methylisobutylketone	REACH #: 01-2119473980-30 EC: 203-550-1 CAS: 108-10-1 Index: 606-004-00-4	≤2.7	Flam. Liq. 2, H225 Acute Tox. 4, H332 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H336 EUH066	ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
2-Methoxy-1-methylethyl acetate	REACH #: 01-2119475791-29 EC: 203-603-9 CAS: 108-65-6 Index: 607-195-00-7	≤2.6	Flam. Liq. 3, H226 STOT SE 3, H336	-	[1] [2]
Urea-formaldehyde-polymer	CAS: 68002-18-6	≤3	Aquatic Chronic 4, H413	-	[1]
Cyclohexanone	REACH #: 01-2119453616-35 EC: 203-631-1 CAS: 108-94-1 Index: 606-010-00-7	≤3	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335	ATE [Oral] = 1620 mg/kg ATE [Dermal] = 1100 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	REACH #: 01-2119979085-27 EC: 309-629-8 CAS: 100545-48-0	≤0.3	Skin Sens. 1B, H317 Aquatic Chronic 3, H412	-	[1]
Fatty acids, tall-oil, compds. with oleylamine	REACH #: 01-2119974148-28 EC: 288-315-1 CAS: 85711-55-3	<0.1	Eye Dam. 1, H318 Skin Sens. 1A, H317 STOT RE 2, H373 See Section 16 for the full text of the H statements declared above.	-	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
sulfur oxides
metal oxide/oxides

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

- Small spill** :  Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

SECTION 6: Accidental release measures

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c	5000 tonnes	50000 tonnes

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Xylene	NAOSH (Ireland, 4/2024) [xylene] Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values OELV 8 hours: 50 ppm. OELV 8 hours: 221 mg/m ³ . OELV 15 minutes: 100 ppm. OELV 15 minutes: 442 mg/m ³ .
iso-butanol	NAOSH (Ireland, 4/2024) Notes: Advisory Occupational Exposure Limit Values (OELVs) OELV 8 hours: 150 ppm. OELV 8 hours: 700 mg/m ³ .
Ethylbenzene	NAOSH (Ireland, 4/2024) Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values OELV 8 hours: 100 ppm. OELV 8 hours: 442 mg/m ³ . OELV 15 minutes: 200 ppm. OELV 15 minutes: 884 mg/m ³ .
Methylisobutylketone	NAOSH (Ireland, 4/2024) Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values OELV 8 hours: 20 ppm. OELV 8 hours: 83 mg/m ³ . OELV 15 minutes: 50 ppm. OELV 15 minutes: 208 mg/m ³ .
2-Methoxy-1-methylethyl acetate	NAOSH (Ireland, 4/2024) Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values OELV 8 hours: 50 ppm. OELV 8 hours: 275 mg/m ³ . OELV 15 minutes: 100 ppm. OELV 15 minutes: 550 mg/m ³ .
Cyclohexanone	NAOSH (Ireland, 4/2024) Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values OELV 8 hours: 10 ppm. OELV 8 hours: 40.8 mg/m ³ . OELV 15 minutes: 20 ppm. OELV 15 minutes: 81.6 mg/m ³ .

Biological exposure indices

Product/ingredient name	Exposure indices
Xylene	NAOSH BGVs (Ireland, 1/2011) [Xylene] BMGV: 1.5 g/g creatinine, methylhippuric acids [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases.
Ethylbenzene	NAOSH BGVs (Ireland, 1/2011) BMGV: Semi-quantitative, the biological analyte is an indicator of exposure to the substance but the quantitative interpretation of the measurement is ambiguous. These analytes should be used as a screening test if a quantitative test is not practical; or as a confirmatory test if the quantitative test is not specific and the origin of the determinant is in question., ethylbenzene [in endexhaled air]. Sampling time: not critical. BMGV: 0.7 g/g creatinine [Semi-quantitative, the biological analyte is an indicator of exposure to the substance but the quantitative interpretation of the measurement is ambiguous. These analytes should be used as a screening test if a quantitative test is not practical; or as a confirmatory test if the quantitative test

SECTION 8: Exposure controls/personal protection

Methylisobutylketone	is not specific and the origin of the determinant is in question.], mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: end of shift at end of workweek.
Cyclohexanone	NAOSH BGVs (Ireland, 1/2011) BMGV: 1 mg/l, MIBK [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases. NAOSH BGVs (Ireland, 1/2011) BMGV: 80 mg/l, 1,2-cyclohexanediol [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases. BMGV: 8 mg/l, cyclohexanol [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following:
European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name

Xylene

Result

DNEL - General population - Long term - Oral

5 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

65.3 mg/m³

Effects: Local

DNEL - General population - Long term - Inhalation

65.3 mg/m³

Effects: Systemic

DNEL - General population - Long term - Dermal

125 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

212 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

221 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

221 mg/m³

Effects: Systemic

DNEL - General population - Short term - Inhalation

260 mg/m³

Effects: Local

DNEL - General population - Short term - Inhalation

260 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Inhalation

442 mg/m³

Effects: Local

SECTION 8: Exposure controls/personal protection

Solvent naphtha (petroleum), light aromatic

DNEL - Workers - Short term - Inhalation

442 mg/m³

Effects: Systemic

DNEL - General population - Long term - Inhalation

0.41 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

1.9 mg/m³

Effects: Systemic

DNEL - General population - Long term - Inhalation

178.57 mg/m³

Effects: Local

DNEL - General population - Short term - Inhalation

640 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

837.5 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

1066.67 mg/m³

Effects: Local

DNEL - General population - Short term - Inhalation

1152 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Inhalation

1286.4 mg/m³

Effects: Systemic

iso-butanol

DNEL - General population - Long term - Inhalation

55 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

310 mg/m³

Effects: Local

Ethylbenzene

DMEL - Workers - Long term - Inhalation

442 mg/m³

Effects: Local

DMEL - Workers - Short term - Inhalation

884 mg/m³

Effects: Systemic

DNEL - General population - Long term - Oral

1.6 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

15 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

77 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Dermal

SECTION 8: Exposure controls/personal protection

180 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Short term - Inhalation

293 mg/m³

Effects: Local

DNEL - General population - Long term - Dermal

4.2 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

11.8 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

14.7 mg/m³

Effects: Local

DNEL - General population - Long term - Inhalation

14.7 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

83 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

83 mg/m³

Effects: Systemic

DNEL - General population - Short term - Inhalation

155.2 mg/m³

Effects: Local

DNEL - General population - Short term - Inhalation

155.2 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Inhalation

208 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

208 mg/m³

Effects: Systemic

DNEL - General population - Long term - Oral

4.2 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

33 mg/m³

Effects: Local

DNEL - General population - Long term - Inhalation

33 mg/m³

Effects: Systemic

DNEL - General population - Long term - Oral

36 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

275 mg/m³

Effects: Systemic

Methylisobutylketone

2-Methoxy-1-methylethyl acetate

SECTION 8: Exposure controls/personal protection

DNEL - General population - Long term - Dermal

320 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Short term - Inhalation

550 mg/m³

Effects: Local

DNEL - Workers - Long term - Dermal

796 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Dermal

1 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

1 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Oral

1.5 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Oral

1.5 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

2.55 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Dermal

4 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

4 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Inhalation

5 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

10 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

10 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Inhalation

20 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

20 mg/m³

Effects: Systemic

DNEL - General population - Long term - Inhalation

0.055 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

Cyclohexanone

Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine

SECTION 8: Exposure controls/personal protection

0.308 mg/m³

Effects: Local

Fatty acids, tall-oil, compds. with oleylamine

DNEL - General population - Long term - Oral

0.012 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

0.012 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

0.024 mg/kg bw/day

Effects: Systemic

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

- : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection

- : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations : Wear suitable gloves tested to EN374.

< 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm

> 8 hours (breakthrough time): 4H / Silver Shield® gloves.

Wash hands before breaks and immediately after handling the product.

Body protection

- : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

SECTION 8: Exposure controls/personal protection

- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Filter type: A
Filter type (spray application): A P
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Various
- Odour** : Slight
- Odour threshold** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** :

Ingredient name	°C	°F	Method
iso-butanol	108	226.4	OECD 103
Methylisobutylketone	116.5	241.7	

- Flammability** : Not available.
- Lower and upper explosion limit** : Lower: 0.8% (xylene)
Upper: 7.6% (Solvent naphtha (petroleum), light arom.)
- Flash point** : Closed cup: 25°C (77°F)
- Auto-ignition temperature** :

Ingredient name	°C	°F	Method
Solvent naphtha (petroleum), light aromatic	280 to 470	536 to 878	DIN 51794
2-Methoxy-1-methylethyl acetate	333	631.4	

- Decomposition temperature** : Not available.
- pH** : Not available.
- Viscosity** : Not available.
- Solubility(ies)** :
Not available.

- Solubility in water** : Not available.
- Partition coefficient: n-octanol/ water** : Not applicable.
- Vapour pressure** :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Methylisobutylketone	15.75128	2.1	DIN EN 13016-2			
iso-butanol	<12.00102	<1.6				

SECTION 9: Physical and chemical properties

Relative density	: Not available.
Density	: 1.4 g/cm ³
Vapour density	: Not available.
<u>Particle characteristics</u>	
Median particle size	: Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties	: Not available.
Oxidising properties	: Not available.

9.2.2 Other safety characteristics

Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
10.5 Incompatible materials	: Reactive or incompatible with the following materials: oxidising materials
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name

Xylene

Result

Rat - Oral - LD50

4300 mg/kg

Toxic effects: Liver - Other changes
Kidney, Ureter, and Bladder - Other changes

Rat - Inhalation - LC50 Vapour

21.7 mg/l [4 hours]

Solvent naphtha (petroleum), light aromatic

Rat - Oral - LD50

8400 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity)
Behavioral - Tremor
Lung, Thorax, or Respiration - Other changes

iso-butanol

Rat - Oral - LD50

2460 mg/kg

Rabbit - Dermal - LD50

3400 mg/kg

Rat - Inhalation - LC50 Vapour

19200 mg/m³ [4 hours]

SECTION 11: Toxicological information

Ethylbenzene

Rat - Oral - LD50

3500 mg/kg

Rabbit - Dermal - LD50

15400 mg/kg

Rat - Inhalation - LC50 Dusts and mists

29000 mg/l [4 hours]

Methylisobutylketone

Rat - Oral - LD50

2080 mg/kg

2-Methoxy-1-methylethyl acetate

Rat - Oral - LD50

8532 mg/kg

Rabbit - Dermal - LD50

>5 g/kg

Urea-formaldehyde-polymer

Rat - Oral - LD50

>5 g/kg

Toxic effects: Olfaction - Other changes Behavioral - Somnolence (general depressed activity) Behavioral - Food intake (animal)

Rabbit - Dermal - LD50

>5 g/kg

Toxic effects: Skin After systemic exposure - Dermatitis, other

Cyclohexanone

Rat - Oral - LD50

1800 mg/kg

Rat - Inhalation - LC50 Gas.

8000 ppm [4 hours]

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
TEKNOFLOOR 100F	141378.5	8119.4	N/A	59.5	N/A
Xylene	4300	1100	N/A	11	N/A
Solvent naphtha (petroleum), light aromatic	8400	N/A	N/A	N/A	N/A
iso-butanol	2460	3400	N/A	N/A	N/A
Ethylbenzene	3500	15400	N/A	11	29000
Methylisobutylketone	2080	N/A	N/A	11	N/A
2-Methoxy-1-methylethyl acetate	8532	N/A	N/A	N/A	N/A
Cyclohexanone	1620	1100	N/A	11	N/A

Skin corrosion/irritation

Product/ingredient name

Xylene

Result

Rat - Skin - Mild irritant

Duration of treatment/exposure: 8 hours

Amount/concentration applied: 60 uL

Rabbit - Skin - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

Rabbit - Skin - Moderate irritant

Amount/concentration applied: 100 %

SECTION 11: Toxicological information

Ethylbenzene

Rabbit - Skin - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 15 mg

Methylisobutylketone

Rabbit - Skin - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

Cyclohexanone

Human - Skin - Mild irritant

Duration of treatment/exposure: 48 hours

Amount/concentration applied: 50 %

Rabbit - Skin - Mild irritant

Amount/concentration applied: 500 mg

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Product/ingredient name

Xylene

Result

Rabbit - Eyes - Mild irritant

Amount/concentration applied: 87 mg

Rabbit - Eyes - Severe irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 5 mg

Solvent naphtha (petroleum), light aromatic

Rabbit - Eyes - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 uL

Ethylbenzene

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 500 mg

Methylisobutylketone

Rabbit - Eyes - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 uL

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 40 mg

Urea-formaldehyde-polymer

Rabbit - Eyes - Severe irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 uL

Cyclohexanone

Rabbit - Eyes - Severe irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 250 ug

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 20 mg

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Not available.

SECTION 11: Toxicological information

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] :  Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] :  Not available.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] :  Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name

 Xylene

Solvent naphtha (petroleum), light aromatic

iso-butanol

Methylisobutylketone

2-Methoxy-1-methylethyl acetate

Cyclohexanone

Result

STOT SE 3, H335 (Respiratory tract irritation)

STOT SE 3, H335 (Respiratory tract irritation)

STOT SE 3, H336 (Narcotic effects)

STOT SE 3, H335 (Respiratory tract irritation)

STOT SE 3, H336 (Narcotic effects)

STOT SE 3, H336 (Narcotic effects)

STOT SE 3, H336 (Narcotic effects)

STOT SE 3, H335 (Respiratory tract irritation)

Specific target organ toxicity (repeated exposure)

Product/ingredient name

 Xylene

Ethylbenzene

Fatty acids, tall-oil, compds. with oleylamine

Result

STOT RE 2, H373 (oral, inhalation)

STOT RE 2, H373 (hearing organs) (oral, inhalation)

STOT RE 2, H373

Aspiration hazard

Product/ingredient name

Xylene

Solvent naphtha (petroleum), light aromatic

Ethylbenzene

Result

ASPIRATION HAZARD - Category 1

ASPIRATION HAZARD - Category 1

ASPIRATION HAZARD - Category 1

Information on likely routes of exposure

Not available.

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : May cause respiratory irritation.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness

SECTION 11: Toxicological information

- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

- General** : May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name

Solvent naphtha (petroleum), light aromatic

Result

Acute - LC50

Fish
9.2 mg/l [96 hours]

Acute - EC50

Daphnia
3.2 mg/l [48 hours]

iso-butanol

Acute - LC50 - Fresh water

Fish - Rainbow trout, donaldson trout - *Oncorhynchus mykiss*
Weight: 1.67 g
1330000 µg/l [96 hours]
Effect: Mortality

Acute - LC50 - Marine water

Crustaceans - Brine shrimp - *Artemia salina*
600 mg/l [48 hours]

SECTION 12: Ecological information

Effect: Mortality

Methylisobutylketone

Acute - LC50 - Fresh water

Fish - Fathead minnow - *Pimephales promelas*

Age: 29 days; Size: 21 mm; Weight: 0.141 g

505000 µg/l [96 hours]

Effect: Mortality

Chronic - NOEC - Fresh water

Daphnia - Water flea - *Daphnia magna*

78 mg/l [21 days]

Effect: Behavior

Chronic - NOEC - Fresh water

Fish - Fathead minnow - *Pimephales promelas* - Embryo

Age: <24 hours

168 mg/l [33 days]

Effect: Mortality

Cyclohexanone

Acute - LC50 - Fresh water

Fish - Fathead minnow - *Pimephales promelas*

Age: 30 days; Size: 20.2 mm; Weight: 0.127 g

527000 µg/l [96 hours]

Effect: Mortality

Chronic - EC10 - Fresh water

Algae - Green algae - *Chlamydomonas reinhardtii* -

Exponential growth phase

Age: 7 days

3.56 mg/l [72 hours]

Effect: Population

Acute - EC50 - Fresh water

Algae - Green algae - *Chlamydomonas reinhardtii* -

Exponential growth phase

Age: 7 days

32.9 mg/l [72 hours]

Effect: Population

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Product/ingredient name

iso-butanol

Result

74% [28 days] - Readily

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
iso-butanol	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Xylene	3.12	8.1 to 25.9	Low
Solvent naphtha (petroleum), light aromatic	-	10 to 2500	High
iso-butanol	1	-	Low
Ethylbenzene	3.6	-	Low
Methylisobutylketone	1.9	-	Low
2-Methoxy-1-methylethyl acetate	1.2	-	Low
Cyclohexanone	0.86	-	Low

SECTION 12: Ecological information

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logKoc	Koc
iso-butanol	1.1	12.0246
Ethylbenzene	2.2	170.406
Methylisobutylketone	1.6	40.9047
2-Methoxy-1-methylethyl acetate	0.36	2.31363
Cyclohexanone	1.8	63.2873

Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bis[oxirane	No	No	No	No	No	No	No
Xylene	No	No	No	No	No	No	No
Solvent naphtha (petroleum), light aromatic	No	No	No	No	No	No	No
iso-butanol	No	No	No	No	No	No	No
Ethylbenzene	No	No	No	No	No	No	No
Methylisobutylketone	No	No	No	No	No	No	No
2-Methoxy-1-methylethyl acetate	No	No	No	No	No	No	No
Urea-formaldehyde-polymer	No	No	No	No	No	No	No
Cyclohexanone	No	No	No	No	No	No	No
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	No	No	No	No	No	No	No
Fatty acids, tall-oil, compds. with oleylamine	No	No	No	No	No	No	No

Mobility : Not available.

Conclusion/Summary : The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bis[oxirane	No	N/A	N/A	No	N/A	N/A	N/A
Xylene	No	N/A	No	Yes	No	N/A	No
Solvent naphtha (petroleum), light aromatic	No	N/A	No	No	No	N/A	No
iso-butanol	No	N/A	N/A	No	N/A	N/A	N/A
Ethylbenzene	N/A	N/A	N/A	Yes	N/A	N/A	N/A
Methylisobutylketone	No	N/A	N/A	No	N/A	N/A	N/A
2-Methoxy-1-methylethyl acetate	No	N/A	N/A	No	N/A	N/A	N/A
Urea-formaldehyde-polymer	No	N/A	N/A	No	N/A	N/A	N/A
Cyclohexanone	No	N/A	N/A	No	N/A	N/A	N/A
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	No	N/A	N/A	No	N/A	N/A	N/A
Fatty acids, tall-oil, compds. with oleylamine	N/A	N/A	N/A	Yes	N/A	N/A	N/A

SECTION 12: Ecological information

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bis[oxirane	No	No	No	No	No	No	No
Xylene	No	No	No	No	No	No	No
Solvent naphtha (petroleum), light aromatic	No	No	No	No	No	No	No
iso-butanol	No	No	No	No	No	No	No
Ethylbenzene	No	No	No	No	No	No	No
Methylisobutylketone	No	No	No	No	No	No	No
2-Methoxy-1-methylethyl acetate	No	No	No	No	No	No	No
Urea-formaldehyde-polymer	No	No	No	No	No	No	No
Cyclohexanone	No	No	No	No	No	No	No
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	No	No	No	No	No	No	No
Fatty acids, tall-oil, compds. with oleylamine	No	No	No	No	No	No	No

Conclusion/Summary : The product does not meet the criteria to be considered as a PBT or vPvB.
Regulation (EC) No. 1272/2008 [CLP]

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue (EWC) : 080111*, 200127*

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 13: Disposal considerations

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3 	3 	3 	3 
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	No.	No.	No.	No.

Additional information

ADR/RID : **Viscous liquid exception** This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.
Tunnel code (D/E)

ADN : **Viscous liquid exception** This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.

IMDG : **Viscous liquid exception** This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.3.2.5.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
 TEKNOFLOOR 100F	≥90	3

SECTION 15: Regulatory information

Labelling :

Other EU regulations

Industrial emissions
(integrated pollution
prevention and control) -
Air : Not listed

Industrial emissions
(integrated pollution
prevention and control) -
Water : Not listed

Explosive precursors : Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category

P5c

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Date of issue/Date of revision : 20/11/2025 **Date of previous issue** : 28/04/2023

Version : 2 **23/25**

TEKNOFLOOR 100F - All variants

Label No : 36672

SECTION 16: Other information

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 3, H226	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method
Carc. 2, H351	Calculation method
STOT SE 3, H335	Calculation method
STOT RE 2, H373	Calculation method
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH066	Repeated exposure may cause skin dryness or cracking.

Full text of classifications [CLP/GHS]

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Aquatic Chronic 4	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of issue/ Date of revision : 20/11/2025

Date of previous issue : 28/04/2023

Version : 2

TEKNOFLOOR 100F

All variants

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

