Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Ireland

SAFETY DATA SHEET



TEKNOFLOOR PRIMER 306F-01

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	

: TEKNOFLOOR PRIMER 306F-01

1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use: Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091. e-mail address of person : Prod-safe@teknos.com responsible for this SDS

National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : National Poisons Information Centre: 01 809 2566

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word	Warning	
Hazard statements	H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H411 - Toxic to aquatic life with long lasting effects.	
Precautionary statements		
Prevention	P280 - Wear protective gloves. Wear eye or face protection. P273 - Avoid release to the environment. P261 - Avoid breathing vapour. P264 - Wash thoroughly after handling.	
Response	P391 - Collect spillage.	
Storage	Not applicable.	

SECTION 2: Hazards identification

SECTION 2: Hazards	IC	ientification
Disposal	1	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	-	Bis[4-(2,3-epoxypropoxy)phenyl]propane Oxirane, mono[(C12-14-alkyloxy)methyl]derivs. Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol
Supplemental label elements	:	Contains epoxy constituents. May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Bis[4-(2,3-epoxypropoxy) phenyl]propane	REACH #: 01-2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2	≥50 - ≤75	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5%	[1]
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	REACH #: 01-2119485289-22 EC: 271-846-8 CAS: 68609-97-2 Index: 603-103-00-4	≥10 - ≤25	Skin Irrit. 2, H315 Skin Sens. 1, H317	-	[1]
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	EC: 500-006-8 CAS: 9003-36-5	≤10	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
Benzyl alcohol	REACH #: 01-2119492630-38 EC: 202-859-9 CAS: 100-51-6 Index: 603-057-00-5	≤10	Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Irrit. 2, H319	ATE [Oral] = 1230 mg/kg ATE [Inhalation (dusts and mists)] = 4.2 mg/l	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

Date of issue/Date of revision	: 15/11/2022	Date of previous issue
TEKNOFLOOR PRIMER 306F-01		

: No previous validation

SECTION 4: First aid measures

4.1 Description of first aid measures			
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.		
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.		
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.		
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.		
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.		

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large
	quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.

5.2 Special hazards arising from the substance or mixture

SECTION 5: Firefighting measures

Ŭ		•
Hazards from the substance or mixture	:	In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	-	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

SECTION 7: Handling and storage

•	
Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Seveso Directive - Reporting thresholds

Danger criteria

	Notification and MAPP threshold	Safety report threshold
E2	200 tonne	500 tonne

7.3 Specific end use(s)

Recommendations Industrial sector specific solutions

- : Not available.
- : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name		Exposure limit values
No exposure limit value known		
Recommended monitoring procedures	atmosphere or l of the ventilation protective equip the following: E the assessment limit values and atmospheres - (of exposure to c (Workplace atm for the measure	ontains ingredients with exposure limits, personal, workplace biological monitoring may be required to determine the effectiveness in or other control measures and/or the necessity to use respiratory oment. Reference should be made to monitoring standards, such as suropean Standard EN 689 (Workplace atmospheres - Guidance for t of exposure by inhalation to chemical agents for comparison with measurement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment chemical and biological agents) European Standard EN 482 nospheres - General requirements for the performance of procedures ement of chemical agents) Reference to national guidance methods for the determination of hazardous substances will also be
DNELs/DMELs		

Product/ingredient name	Туре	Exposure	Value	Population	Effects
Bis[4-(2,3-epoxypropoxy)phenyl]	DNEL	Long term Dermal	89.3 µg/kg	General	Systemic
propane			bw/day	population	
	DNEL	Long term Oral	0.5 mg/kg	General	Systemic
			bw/day	population	
	DNEL	Long term Dermal	0.75 mg/	Workers	Systemic
			kg bw/day		
	DNEL	Long term	0.87 mg/m ³	General	Systemic
		Inhalation		population	
	DNEL	Long term	4.93 mg/m ³	Workers	Systemic
Ovirana mana[(C12,14, alkulavu)		Inhalation		Conorol	Sustamia
Oxirane, mono[(C12-14-alkyloxy)	DNEL	Long term Oral	0.5 mg/kg bw/day	General population	Systemic
methyl]derivs.	DNEL	Long term Dermal	0.5 mg/kg	General	Systemic
		Long term Derma	bw/day	population	Oysternic
	DNEL	Long term	0.87 mg/m ³	General	Systemic
		Inhalation	olor mg/m	population	eyetenne
	DNEL	Long term Dermal	1 mg/kg	Workers	Systemic
		5	bw/day		,
	DNEL	Long term	3.6 mg/m ³	Workers	Systemic
		Inhalation			
Formaldehyde, oligomeric reaction	DMEL	Short term Dermal	0.0083 mg/	Workers	Local
products with 1-chloro-			Cm ²		
2,3-epoxypropane and phenol					
	DNEL	Long term Oral	6.25 mg/	General	Systemic
	DUE		kg bw/day	population	
	DNEL	Long term	8.7 mg/m ³	General	Systemic
		Inhalation	20.20 mg/	population	Sustamia
	DNEL	Long term Inhalation	29.39 mg/ m³	Workers	Systemic
	DNEL	Long term Dermal	62.5 mg/	General	Systemic
	DINCE	Long term Derma	kg bw/day	population	Cysternie
	DNEL	Long term Dermal	104.15 mg/	Workers	Systemic
			kg bw/day		- ,
Benzyl alcohol	DNEL	Long term Oral	4 mg/kg	General	Systemic
		U U	bw/day	population	
	DNEL	Long term Dermal	4 mg/kg	General	Systemic
			bw/day	population	
	DNEL	Long term	5.4 mg/m³	General	Systemic
	DUE	Inhalation		population	
	DNEL	Long term Dermal	8 mg/kg	Workers	Systemic
	DNEL	Short term Oral	bw/day	General	Svotomio
	DINEL	Short term Oral	20 mg/kg bw/day	population	Systemic
	DNEL	Short term Dermal	20 mg/kg	General	Systemic
	DINCE	Chort term Derma	bw/day	population	Oysterine
	DNEL	Long term	22 mg/m^3	Workers	Systemic
		Inhalation			_ ,
	DNEL	Short term	27 mg/m³	General	Systemic
		Inhalation		population	-
	DNEL	Short term Dermal	40 mg/kg	Workers	Systemic
			bw/day		
	DNEL	Short term	110 mg/m³	Workers	Systemic
		Inhalation			

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Date of issue/Date of revision TEKNOFLOOR PRIMER 306F-01

SECTION 8: Exposure controls/personal protection

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
	Recommendations : Wear suitable gloves tested to EN374.
	< 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm
	> 8 hours (breakthrough time): 4H / Silver Shield® gloves.
	Wash hands before breaks and immediately after handling the product.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
	Filter type: A
	Filter type (spray application): A P
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance			
Physical state	:	Liquid.	
Colour	:	Various	
Odour	:	Slight	
Odour threshold	:	Not ava	ilable.
Melting point/freezing point	:	Not ava	ilable.
Initial boiling point and	:		
boiling range			

Ingredient name	°C	°F	Method
Benzyl alcohol	205.3	401.5	

Flammability

: Not available.

Date of issue/Date of revision	: 15/11/2022	Date of previous issue	: No previous validation	Version	:1 7	7/15
TEKNOFLOOR PRIMER 306F-01				Label No ::	31540	

SECTION 9: Physical and chemical properties						
Lower and upper explosion limit		: Lower: 1.3% Upper: 13%				
Flash point	: Clos	ed cup: 83°C (181.4°F)			
Auto-ignition temperature	:					
Ingredient name		°C	°F	Method		
Benzyl alcohol		436	816.8			
Decomposition temperature	: Not a	available.	I			
рН	: Not a	applicable.				
Viscosity	: Not a	available.				
Solubility(ies)	:					
Not available.						
Solubility in water	: Not a	available.				
Partition coefficient: n-octano water	/:Nota	applicable.				

Vapour pressure

	Va	Vapour Pressure at 20°C		V	Vapour pressure a		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol	0.62	0.083	EU A.4				
Benzyl alcohol	0.05	0.0067					
Relative density	: Not a	available.					
Density	: 1.1 g	/cm³					
Vapour density	: Not a	available.					
Explosive properties	: Not a	available.					
Oxidising properties	: Not a	available.					
Particle characteristics							
Median particle size	: Not a	applicable.					

SECTION 10: Stability and reactivity

ŝ

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingred	dients.
10.2 Chemical stability	: The product is stable.	
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occ	our.
10.4 Conditions to avoid	: No specific data.	
10.5 Incompatible materials	: No specific data.	
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition prodused should not be produced.	ucts

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure	
Bis[4-(2,3-epoxypropoxy) phenyl]propane	LD50 Dermal	Rabbit	20 g/kg	-	
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	LD50 Oral	Rat	17100 mg/kg	-	
Benzyl alcohol	LC50 Inhalation Dusts and mists	Rat - Male, Female	4200 mg/m ³	4 hours	
	LD50 Dermal	Rabbit	2000 mg/kg	-	
	LD50 Oral	Rat	1230 mg/kg	-	
Conclusion/Summary : Based on available data, the classification criteria are not met.					

Acute toxicity estimates

Route	ATE value
	13401.93 mg/kg 45.76 mg/l

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Bis[4-(2,3-epoxypropoxy)	Eyes - Severe irritant	Rabbit	-	24 hours 2	-
phenyl]propane				mg	
	Skin - Mild irritant	Rabbit	-	500 mg	-
Oxirane, mono[Skin - Moderate irritant	Rabbit	-	24 hours 500	-
(C12-14-alkyloxy)methyl]				uL	
derivs.					
Formaldehyde, oligomeric	Skin - Mild irritant	Rabbit	-	24 hours 500	-
reaction products with				uL	
1-chloro-2,3-epoxypropane					
and phenol					
Benzyl alcohol	Skin - Mild irritant	Man	-	48 hours 16	-
-				mg	
	Skin - Moderate irritant	Pig	-	100 %	-
	Skin - Moderate irritant	Rabbit	-	24 hours 100	-
				mg	

Conclusion/Summary	: Causes skin irritation.
Sensitisation	
Conclusion/Summary	: May cause an allergic skin reaction.
<u>Mutagenicity</u>	
Conclusion/Summary	: Based on available data, the classification criteria are not met.
Carcinogenicity	
Conclusion/Summary	: Based on available data, the classification criteria are not met.
Reproductive toxicity	
Conclusion/Summary	: Based on available data, the classification criteria are not met.
Teratogenicity	
Conclusion/Summary	: Based on available data, the classification criteria are not met.
Specific target organ toxic	<u>ity (single exposure)</u>
Not available.	

Specific target organ toxicity (repeated exposure) Not available.

Aspiration hazard

Not available.

SECTION TE TOXICOI	0	gical information
Information on likely routes of exposure	:	Not available.
Potential acute health effects		
Eye contact	:	Causes serious eye irritation.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	Causes skin irritation. May cause an allergic skin reaction.
Ingestion	:	No known significant effects or critical hazards.
Symptoms related to the phy	<u>sic</u>	cal, chemical and toxicological characteristics
Eye contact		Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	1	No specific data.
Skin contact	:	Adverse symptoms may include the following: irritation redness
Ingestion	1	No specific data.
Delayed and immediate effec	<u>ts</u>	as well as chronic effects from short and long-term exposure
Short term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Long term exposure Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health effe	ect	<u>S</u>
Not available.		
Conclusion/Summary	:	Not available.
General	:	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Reproductive toxicity		No known significant effects or critical hazards.

11.2.1 Endocrine disrupting propertiesNot available.11.2.2 Other informationNot available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Benzyl alcohol	Acute LC50 10000 μg/l Fresh water	Fish - Lepomis macrochirus	96 hours
0	The terms of the second s		·

Conclusion/Summary : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Conclusion/Summary : This product has not been tested for biodegradation.

Date of issue/Date of revision	: 15/11/2022	Date of previous issue	: No previous validation	Version :	1 1	10/15
TEKNOFLOOR PRIMER 306F-01				Label No :3	1540	

SECTION 12: Ecological information

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	3.77	160 to 263	low
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	2.7	-	low
Benzyl alcohol	0.87	-	low

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
European waste catalogue (EWC)	: 080111*, 200127*
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN3082	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin)
14.3 Transport hazard class(es)	9	9	9	9
14.4 Packing group	111	111	111	111
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes.
Additional informa	tion	1	1	1
ADR/RID	or ≤5 kg, p	ct is not regulated as a d rovided the packagings n to 4.1.1.8. de (-)		
ADN		ct is not regulated as a da rovided the packagings n to 4.1.1.8.		
IMDG		ct is not regulated as a de rovided the packagings n to 4.1.1.8.		
ΙΑΤΑ	or ≤5 kg, p	ct is not regulated as a da rovided the packagings n and 5.0.2.8.		
14.6 Special precau user	upright and	within user's premises I secure. Ensure that per f an accident or spillage.	sons transporting the pro	
14.7 Maritime trans bulk according to II instruments	-	nt/applicable due to natur	e of the product.	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)
Annex XIV - List of substances subject to authorisation
Annex XIV
None of the components are listed.
Substances of very high concern
None of the components are listed.
Annex XVII - Restrictions : on the manufacture,

and use of certain dangerous substances, mixtures and articles Date of issue/Date of revision TEKNOFLOOR PRIMER 306F-01

placing on the market

SECTION 15: Regulatory information

Other EU regulations		
Industrial emissions (integrated pollution prevention and control) - Air	:	Not listed
Industrial emissions (integrated pollution prevention and control) - Water	:	Not listed
Ozone depleting substan	<u>ces</u>	<u>(1005/2009/EU)</u>
Not listed.		
Prior Informed Consent (PIC)	<u>(649/2012/EU)</u>

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category

E2

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
	1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative
Procedure used to de	rive the classification according to Regulation (FC) No. 1272/2008 [CI P/GHS]

Classification

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 2, H411	Calculation method
ull text of abbreviated H statements	
Harmful if swallowed.	
H315 Causes skin irritation.	
H317 May cause an allergic skin read	tion.
H319 Causes serious eye irritation.	
H332 Harmful if inhaled.	
H411 Toxic to aquatic life with long la	sting effects.
ull text of classifications [CLP/GHS]	
Acute Tox. 4 ACUTE TOXICITY - Cate	gory 4
	AQUATIC HAZARD - Category 2
Eye Irrit. 2 SERIOUS EYE DAMAGE	/EYE IRRITATION - Category 2
Skin Irrit. 2 SKIN CORROSION/IRRI	
Skin Sens. 1 SKIN SENSITISATION -	Category 1
Date of issue/ Date of : 15/11/2022	
evision	
ate of previous issue : No previous va	lidation
/ersion : 1	
	All variants

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision TEKNOFLOOR PRIMER 306F-01