Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Ireland

SAFETY DATA SHEET



TEKNOL 1881-15 - All variants

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product ic	lentifier
Product nan	ne

: TEKNOL 1881-15 - All variants

1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use: Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091. e-mail address of person : Prod-safe@teknos.com responsible for this SDS

National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number

 Emergency medical information: (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland.
 Members of the public Number (8 am-10 pm): +353 (0)1 809 2166 Healthcare professional telephone Number (24hrs): +353 (0)1 809 2566

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word	Warning	
Hazard statements	H317 - May cause an allergic skin reaction. H412 - Harmful to aquatic life with long lasting effects.	
Precautionary statements		
Prevention	P280 - Wear protective gloves. P273 - Avoid release to the environment. P261 - Avoid breathing vapour.	
Response	₱302 + P352 - IF ON SKIN: Wash with plenty of water. P362 + P364 - Take off contaminated clothing and wash it before reuse	e.
Storage	Not applicable.	

SECTION 2: Hazards identification

SECTION 2. Hazarus	IC	
Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	:	Contains: 3-iodo-2-propynyl-butyl carbamate; 4,5-dichloro-2-octyl-2H-isothiazol- 3-one; 1,2-benzisothiazol-3(2H)-one and 2-methyl-2H-isothiazol-3-one
Supplemental label elements	:	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains biocidal products for dry film and in-can preservation: IPBC and DCOIT and BIT and MIT and OIT and C(M)IT/MIT (3:1). Risk of skin sensitisation.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
inanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≤10	Carc. 2, H351 (inhalation)	-	[1] [*]
2-Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	<1	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	ATE [Oral] = 1200 mg/kg ATE [Inhalation (vapours)] = 3 mg/l	[1] [2]
(Z)-9-Octadecen-1-ol ethoxylated	EC: 500-016-2 CAS: 9004-98-2	≤0.3	Skin Irrit. 2, H315 Aquatic Acute 1, H400	M [Acute] = 1	[1]
3-iodo-2-propynyl-butyl carbamate	EC: 259-627-5 CAS: 55406-53-6 Index: 616-212-00-7	≤0.2	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 400 mg/kg ATE [Inhalation (dusts and mists)] = 0.67 mg/l M [Acute] = 10 M [Chronic] = 1	[1]
4,5-dichloro-2-octyl-2H- isothiazol-3-one	EC: 264-843-8 CAS: 64359-81-5 Index: 613-335-00-8	≤0.022	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 567 mg/kg ATE [Inhalation (dusts and mists)] = 0.16 mg/l Skin Corr. 1, H314: $C \ge 5\%$ Skin Irrit. 2, H315: 0.025% $\le C < 5\%$ Eye Dam. 1, H318:	[1]

				$C \ge 3\%$ Eye Irrit. 2, H319: $0.025\% \le C < 3\%$ Skin Sens. 1, H317: $C \ge 0.0015\%$ M [Acute] = 100 M [Chronic] = 100	
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	≤0.01	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 450 mg/kg ATE [Inhalation (dusts and mists)] = 0.21 mg/l Skin Sens. 1, H317: C $\ge 0.036\%$ M [Acute] = 1 M [Chronic] = 1	[1]
2-methyl-2H-isothiazol- 3-one	EC: 220-239-6 CAS: 2682-20-4 Index: 613-326-00-9	<0.01	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (dusts and mists)] = 0.11 mg/l Skin Sens. 1, H317: C \geq 0.0015% M [Acute] = 10 M [Chronic] = 1	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter \leq 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

SECTION 4: First aid measures

Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/s	<u>symptoms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	:	None known.
5.2 Special hazards arising f	rom	I the substance or mixture
Hazards from the substance or mixture	:	In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

: 05/06/2025 Date of previous issue

SECTION 6: Accidental release measures

	u	
6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Date of issue/Date of revision TEKNOL 1881-15 - All variants : 05/06/2025 Date of previous issue

SECTION 7: Handling and storage

Recommendations Industrial sector specific Not available.Not available.

solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
2-Butoxyethanol	NAOSH (Ireland, 4/2024) Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values OELV 8 hours: 20 ppm. OELV 8 hours: 98 mg/m ³ . OELV 15 minutes: 50 ppm.
	OELV 15 minutes: 246 mg/m ³ .

Biological exposure indices

Product/ingredient name		Exposure indices			
2-Butoxyethanol		NAOSH (Ireland, 1/2011) BMGV: 200 mg/g creatinine, BAA [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases.			
Recommended monitoring procedures	European Stand assessment of e values and mea atmospheres - (of exposure to o (Workplace atm for the measure	Id be made to monitoring standards, such as the following: lard EN 689 (Workplace atmospheres - Guidance for the exposure by inhalation to chemical agents for comparison with limit surement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment chemical and biological agents) European Standard EN 482 ospheres - General requirements for the performance of procedures ment of chemical agents) Reference to national guidance nethods for the determination of hazardous substances will also be			
DNELs/DMELs					
Product/ingredient name		Result DNEL - General population - Long term - Inhalation 28 µg/m ³ Effects: Local			
		DNEL - Workers - Long term - Inhalation 170 μg/m³ <u>Effects</u> : Local			
2-Butoxyethanol		DNEL - General population - Long term - Oral 6.3 mg/kg bw/day <u>Effects</u> : Systemic			
		DNEL - General population - Short term - Oral 26.7 mg/kg bw/day <u>Effects</u> : Systemic			
		DNEL - General population - Long term - Inhalation 59 mg/m ³ <u>Effects</u> : Systemic			
		DNEL - Workers - Long term - Inhalation 98 mg/m³ <u>Effects</u> : Systemic			
		DNEL - General population - Short term - Inhalation			

ous issue : 11/10/2023

	ontrolo	Inoroonal protection
SECTION 8: Exposure of	Jointrois	/personal protection 147 mg/m ³
		<u>Effects</u> : Local
		DNEL - Workers - Short term - Inhalation 246 mg/m³ <u>Effects</u> : Local
		DNEL - General population - Short term - Inhalation 426 mg/m ³ <u>Effects</u> : Systemic
		DNEL - Workers - Short term - Inhalation 1091 mg/m³ <u>Effects</u> : Systemic
(Z)-9-Octadecen-1-ol ethoxylate	d	DNEL - General population - Long term - Oral 2.5 mg/kg bw/day <u>Effects</u> : Systemic
		DNEL - General population - Long term - Inhalation 6.53 mg/m ³ <u>Effects</u> : Systemic
		DNEL - Workers - Long term - Inhalation 37 mg/m ³ Effects: Systemic
		DNEL - General population - Long term - Dermal 125 mg/kg bw/day <u>Effects</u> : Systemic
		DNEL - Workers - Long term - Dermal 350 mg/kg bw/day <u>Effects</u> : Systemic
3-iodo-2-propynyl-butyl carbama	te	DNEL - Workers - Long term - Inhalation 0.023 mg/m ³ <u>Effects</u> : Systemic
		DNEL - Workers - Short term - Inhalation 0.07 mg/m ³ Effects: Systemic
		DNEL - Workers - Short term - Inhalation 1.16 mg/m³ <u>Effects</u> : Local
		DNEL - Workers - Long term - Inhalation 1.16 mg/m³ <u>Effects</u> : Local
		DNEL - Workers - Long term - Dermal 2 mg/kg bw/day <u>Effects</u> : Systemic
1,2-benzisothiazol-3(2H)-one		DNEL - General population - Long term - Dermal 0.345 mg/kg bw/day <u>Effects</u> : Systemic
		DNEL - Workers - Long term - Dermal 0.966 mg/kg bw/day <u>Effects</u> : Systemic
		DNEL - General population - Long term - Inhalation 1.2 mg/m ³ <u>Effects</u> : Systemic
Date of issue/Date of revision	: 05/06/2025	Date of previous issue : 11/10/2023 Version : 5

SECTION 8: Exposure controls/personal protection

DNEL - Workers - Long term - Inhalation 6.81 mg/m³ <u>Effects</u>: Systemic

2-methyl-2H-isothiazol-3-one

DNEL - General population - Long term - Inhalation 0.021 mg/m³ <u>Effects</u>: Local

DNEL - Workers - Long term - Inhalation 0.021 mg/m³ <u>Effects</u>: Local

DNEL - General population - Long term - Oral 0.027 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Short term - Inhalation 0.043 mg/m³ Effects: Local

DNEL - Workers - Short term - Inhalation 0.043 mg/m³ Effects: Local

DNEL - General population - Short term - Oral 0.053 mg/kg bw/day <u>Effects</u>: Systemic

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls	:	ood general ventilation should be sufficient to control worker exposure to airborn ontaminants.			
Individual protection measure	es				
Hygiene measures	:	before eating, smoking and using Appropriate techniques should be Contaminated work clothing shoul	horoughly after handling chemical products, the lavatory and at the end of the working period. used to remove potentially contaminated clothing. Id not be allowed out of the workplace. Wash sing. Ensure that eyewash stations and safety ion location.		
Eye/face protection	:	assessment indicates this is necesigases or dusts. If contact is possi	a approved standard should be used when a risk ssary to avoid exposure to liquid splashes, mists, ible, the following protection should be worn, a higher degree of protection: safety glasses with		
Skin protection					
Hand protection	:	be worn at all times when handling this is necessary. Considering the check during use that the gloves a should be noted that the time to be different for different glove manufa	oves complying with an approved standard should g chemical products if a risk assessment indicates e parameters specified by the glove manufacturer, are still retaining their protective properties. It reakthrough for any glove material may be acturers. In the case of mixtures, consisting of n time of the gloves cannot be accurately		
	Recommendations : Wear suitable gloves tested to EN374.				
	 > 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm 				
		Not recommended	polyvinyl alcohol (PVA) gloves		

Date of issue/Date of revision	: 05/06/2025	Date of previous issue	: 11/10/2023	Version	<mark>:</mark> 5	8/20
TEKNOL 1881-15 - All variants				Label No	1208	325

SECTION 8: Exposure controls/personal protection

•	
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
	Filter type (spray application): A P
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

ŝ,

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties


Appearance	
Physical state	: Liquid.
Colour	: Various
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	:
Ingredient name	2°

Ingredient name		°C	°F	Method	
water		100	212		
Flammability	: No	ot available.	ļ.	ł	
Lower and upper explosion limit		wer: Not applicat			
Flash point	: Cl	osed cup: >100°0	C (>212°F)		
Auto-ignition temperature	: No	ot available.			
Decomposition temperature	: No	ot available.			
рН	: 81	:o 9 [Conc. (% w/	w): 100%]		
Viscosity	: No	ot available.			
Solubility(ies)	:				
Not available.					
Solubility in water	: No	ot available.			
Partition coefficient: n-octanol/ water	: No	ot applicable.			

Vapour pressure

	Va	Vapour Pressure at 20°C			Vapour pressure at 50°C			
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method		
water	17.5	2.3						
Relative density	: Not	available.						
Density	: 1.3	g/cm³						
apour density	: Not	available.						
Particle characteristics								
te of issue/Date of revision	: 05/06/2	2025 Date o	f previous issue	: 11/10/2023		Version : 5	9/20	

TEKNOL 1881-15 - All variants



SECTION 9: Physical and chemical properties Median particle size : Not applicable. 9.2 Other information 9.2.1 Information with regard to physical hazard classes **Explosive properties** : Not available. **Oxidising properties** : Not available. 9.2.2 Other safety characteristics Not applicable. **SECTION 10: Stability and reactivity 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients. **10.2 Chemical stability** : The product is stable. **10.3 Possibility of** : Under normal conditions of storage and use, hazardous reactions will not occur. hazardous reactions 10.4 Conditions to avoid : No specific data. 10.5 Incompatible materials : No specific data.

decomposition products should not be produced.	10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
--	--	--

SECTION 11: Toxicological information . .

I.1 Information on hazard classes as defined Acute toxicity	d in Regulation (EC) No 1272/2008
Product/ingredient name Product/ingredient name Priodo-2-propynyl-butyl carbamate	<mark>Result</mark> Rat - Oral - LD50 400 mg/kg
	Rat - Dermal - LD50 >2000 mg/kg
	Rat - Inhalation - LC50 Dusts and mists 0.763 mg/l [4 hours]
	Rat - Inhalation - LC50 Dusts and mists 0.67 g/m ³ [4 hours]
1,5-dichloro-2-octyl-2H-isothiazol-3-one	Rat - Oral - LD50 1585 mg/kg OECD [Acute Oral Toxicity]
	Rabbit - Dermal - LD50 >652 mg/kg OECD [Acute Dermal Toxicity]
	Rat - Male, Female - Inhalation - LC50 Dusts and mists 0.26 mg/l [4 hours] OECD [Acute Inhalation Toxicity]
1,2-benzisothiazol-3(2H)-one	Rat - Oral - LD50 1020 mg/kg
2-methyl-2H-isothiazol-3-one	Rat - Inhalation - LC50 Dusts and mists 0.11 mg/l [4 hours]

:05/06/2025 Date of previous issue

SECTION 11: Toxicological information

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
FEKNOL 1881-15	N/A	N/A	N/A	470.5	335.7
2-Butoxyethanol	1200	N/A	N/A	3	N/A
3-iodo-2-propynyl-butyl carbamate	400	N/A	N/A	N/A	0.67
4,5-dichloro-2-octyl-2H-isothiazol-3-one	567	N/A	N/A	N/A	0.16
1,2-benzisothiazol-3(2H)-one	450	N/A	N/A	N/A	0.21
2-methyl-2H-isothiazol-3-one	100	300	N/A	N/A	0.11

Product/ingredient name titanium dioxide		Result Human - Skin - Mild irritant
		<u>Duration of treatment/exposure</u> : 72 hours <u>Amount/concentration applied</u> : 300 ug l
2-Butoxyethanol		Rabbit - Skin - Mild irritant Amount/concentration applied: 500 mg
(Z)-9-Octadecen-1-ol ethoxylated		Rabbit - Skin - Moderate irritant Duration of treatment/exposure: 24 hours Amount/concentration applied: 500 mg
1,2-benzisothiazol-3(2H)-one		Human - Skin - Mild irritant Duration of treatment/exposure: 48 hours Amount/concentration applied: 5 %
Conclusion/Summary [Product]	: Not available	ð.
Serious eye damage/eye irritation		
Product/ingredient name		Result
2-Butoxyethanol		Rabbit - Eyes - Moderate irritant Duration of treatment/exposure: 24 hours
		Amount/concentration applied: 100 mg
		Rabbit - Eyes - Severe irritant Amount/concentration applied: 100 mg
(Z)-9-Octadecen-1-ol ethoxylated		Rabbit - Eyes - Moderate irritant Amount/concentration applied: 100 uL
3-iodo-2-propynyl-butyl carbamate		Rabbit - Eyes - Severe irritant
Conclusion/Summary [Product]	: Not available	
Respiratory corrosion/irritation		
Not available.		
Conclusion/Summary [Product]	: Not available	e.
Respiratory or skin sensitization		
Product/ingredient name		Result
iodo-2-propynyl-butyl carbamate		Guinea pig - skin <u>Result</u> : Not sensitizing

TEKNOL 1881-15 - All variants

11/20

SECTION 11: Toxicological information

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Product/ingredient name iodo-2-propynyl-butyl carbamate Result

In vitro - Bacteria Result: Negative

Conclusion/Summary [Product] : Not available.

Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. Not available.

Conclusion/Summary [Product] : Not available.

Reproductive toxicity Product/ingredient name P-iodo-2-propynyl-butyl carbamate

Result

Rabbit - Female - Oral 50 mg/kg [7 days per week] [13 days] <u>Maternal toxicity</u>: Positive <u>Developmental</u>: Negative

Rabbit - Female - Oral 20 mg/kg [7 days per week] [13 days] <u>Maternal toxicity</u>: Negative <u>Developmental</u>: Negative

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure) Not available.

Specific target organ toxicity (repeated exposure)Product/ingredient nameResultImage: Signal content of the second s

STOT RE 1, H372 (larynx)

12/20

Aspiration hazard		
Not available.		
Information on likely routes of	o <mark>f exposure</mark>	
Not available.		
Potential acute health effects		
Eye contact	: No known significant effects or critical hazards.	
Inhalation	: No known significant effects or critical hazards.	
Skin contact	: May cause an allergic skin reaction.	
Ingestion	: No known significant effects or critical hazards.	
Symptoms related to the phy	sical, chemical and toxicological characteristics	
Eye contact	: No specific data.	
Inhalation	: No specific data.	
Date of issue/Date of revision	: 05/06/2025 Date of previous issue : 11/10/2023	Version : 5 12
TEKNOL 1881-15 - All variants		Label No : 1/20825

SECTION 11: Toxicological information

Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
Delayed and immediate effe	ts as well as chronic effects from short and long-term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	<u>ets</u>
Not available.	
Conclusion/Summary [Pro	duct] : Not available.
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

12.1 Toxicity

SECTION 12: Ecological information

Product/ingredient name		Result			
Manium dioxide		Acute - LC50	hog - <i>Fundulus hetere</i> [96 hours]	oclitus	
		Acute - LC50 - Crustaceans - <u>Age</u> : <24 hours 3 mg/l [48 hour <u>Effect</u> : Mortality	Water flea - <i>Ceriodap</i> s 's]	<i>hnia dubia</i> - Nec	nate
2-Butoxyethanol		Acute - LC50 - Fish - Inland si <u>Size</u> : 40 to 100 1250000 μg/l [<u>Effect</u> : Mortality	lverside - <i>Menidia ber</i> 0 mm 96 hours]	yllina	
		Acute - LC50 - Crustaceans - <i>crangon</i> 800000 μg/l [4ξ <u>Effect</u> : Mortality	Common shrimp, san 3 hours]	nd shrimp - <i>Cran</i> g	yon
3-iodo-2-propynyl-butyl carbamate		Acute - LC50 -	- Fresh water		
Date of issue/Date of revision	05/06/2025	Date of previous issue	: 11/10/2023	Version :	5 13/20
TEKNOL 1881-15 - All variants				Label No :1	20825

SECTION 12: Ecological informa	ation
	EU Fish - Trout - <i>Oncorhynchus mykiss</i> 0.067 mg/l [96 hours]
	Acute - NOEC - Fresh water EU
	Fish - Trout - <i>Oncorhynchus mykiss</i> 0.049 mg/l [96 hours]
	Acute - EC50 - Fresh water EU
	Daphnia - Daphnia - <i>Daphnia magna</i> 0.16 mg/l [48 hours]
	Chronic - NOEC - Fresh water EU
	Daphnia - Daphnia - <i>Daphnia Magna</i> 0.05 mg/l [21 days]
	Acute - EC50 - Fresh water EU
	Algae - Algae - <i>Scenedemus subspicatus</i> 0.022 mg/l [72 hours]
4,5-dichloro-2-octyl-2H-isothiazol-3-one	Acute - EC50 - Fresh water Algae - Green algae - <i>Pseudokirchneriella subcapitata</i> 0.003 mg/l [72 hours] <u>Effect</u> : Population
	Acute - EC50 - Fresh water
	Daphnia - Water flea - <i>Daphnia magna</i> 0.001 mg/l [48 hours] <u>Effect</u> : Intoxication
	Acute - LC50 - Fresh water
	US EPA Fish - Rainbow trout,donaldson trout - <i>Oncorhynchus mykiss <u>Weight</u>: 1.2 g 2.7 ppb [96 hours] <u>Effect</u>: Mortality</i>
	Chronic - NOEC
	US EPA Fish - Rainbow trout,donaldson trout - <i>Oncorhynchus mykiss</i> 0.56 ppb [97 days] <u>Effect</u> : Growth
	Chronic - NOEC - Marine water OECD
	Algae - Diatom - <i>Nitzschia pungens</i> 19.789 μg/l [96 hours] <u>Effect</u> : Population
1,2-benzisothiazol-3(2H)-one	Acute - LC50 - Fresh water OECD [Fish, Acute Toxicity Test] Fish - Trout - <i>Onorhynchus Mykiss</i> 1.9 mg/l [96 hours]
	Acute - EC50 OECD 202 [Daphnia sp. Acute Immobilization Test and Reproduction Test] Daphnia - Daphnia - <i>Daphnia Magna</i> 3.7 mg/l [48 hours]

Acute - EC50 - Marine water

Date of issue/Date of revision
TEKNOL 1881-15 - All variants

: 05/06/2025 Date of previous issue

SECTION 12:	Ecological	information	

OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - *Skeletonema Costatum* 0.36 mg/l [72 hours]

Acute - NOEC - Marine water

OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - *Skeletonema Costatum* 0.15 mg/l [72 hours]

2-methyl-2H-isothiazol-3-one

Acute - EC50 - Fresh water

US EPA Daphnia - Water flea - *Daphnia magna* <u>Age</u>: <24 hours 0.18 ppm [48 hours] <u>Effect</u>: Intoxication

Acute - LC50 - Fresh water

US EPA Fish - Rainbow trout,donaldson trout - *Oncorhynchus mykiss* <u>Weight</u>: 0.73 g 0.07 ppm [96 hours] <u>Effect</u>: Mortality

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability	
Product/ingredient name	Result
1,2-benzisothiazol-3(2H)-one	EU
	24% [28 days]

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
了iodo-2-propynyl-butyl carbamate	-	-	Not readily
1,2-benzisothiazol-3(2H)-one	-	-	Inherent

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
P-Butoxyethanol 3-iodo-2-propynyl-butyl	0.81 >1	-	Low Low
carbamate 1,2-benzisothiazol-3(2H)-one	-	3.2	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logKoc	Кос
2-Butoxyethanol	1.83	67.3685
3-iodo-2-propynyl-butyl carbamate	1.13	13.4558
4,5-dichloro-2-octyl-2H-isothiazol-3-one	3.41	2562.01
1,2-benzisothiazol-3(2H)-one	1.86	73.142
2-methyl-2H-isothiazol-3-one	1.74	54.9187

Results of PMT and vPvM assessment

: 05/06/2025 Date of previous issue

SECTION 12: Ecological information

Product/ingredient name	PMT	Р	Μ	т	vPvM	vP	vM
titanium dioxide	No	No	No	No	No	No	No
2-Butoxyethanol	No	No	No	No	No	No	No
(Z)-9-Octadecen-1-ol ethoxylated	No	No	No	No	No	No	No
3-iodo-2-propynyl-butyl carbamate	No	No	No	No	No	No	No
4,5-dichloro-2-octyl-2H- isothiazol-3-one	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
2-methyl-2H-isothiazol-3-one		No	No	No	No	No	No

Mobility

Conclusion/Summary

: Not available.

: The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	Р	В	Т	vPvB	vP	vB	
titanium dioxide	No	No	No	No	No	No	No	
2-Butoxyethanol	No	No	No	No	No	No	No	
(Z)-9-Octadecen-1-ol ethoxylated	No	No	No	No	No	No	No	
3-iodo-2-propynyl-butyl carbamate	No	No	No	No	No	No	No	
4,5-dichloro-2-octyl-2H- isothiazol-3-one	No	No	No	No	No	No	No	
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No	
2-methyl-2H-isothiazol-3-one	No	No	No	No	No	No	No	

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	Р	В	т	vPvB	vP	vB
titanium dioxide	No	No	No	No	No	No	No
2-Butoxyethanol	No	No	No	No	No	No	No
(Z)-9-Octadecen-1-ol ethoxylated	No	No	No	No	No	No	No
3-iodo-2-propynyl-butyl carbamate	No	No	No	No	No	No	No
4,5-dichloro-2-octyl-2H- isothiazol-3-one	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
2-methyl-2H-isothiazol-3-one		No	No	No	No	No	No

Conclusion/Summary : The product does not meet the criteria to be considered as a PBT or vPvB. Regulation (EC) No. 1272/2008 [CLP]

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product]

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

: 05/06/2025 Date of previous issue

SECTION 13: Disposal considerations

13.1 Waste treatment method	s	
<u>Product</u>		
Methods of disposal	:	The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal.
European waste catalogue (EWC)	:	080111*, 200127*
Packaging		
Methods of disposal	:	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	-	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	•			
	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

SECTION 15: Regulatory information

2

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
TEKNOL 1881-15	≥90	3

Labelling

Other EU regulations
Industrial emissions : Not listed (integrated pollution prevention and control) - Air
Industrial emissions : Not listed (integrated pollution prevention and control) - Water
Explosive precursors : Not applicable.
Ozone depleting substances (EU 2024/590)
Not listed.
Prior Informed Consent (PIC) (649/2012/EU) Not listed. Persistent Organic Pollutants
Not listed.
Seveso Directive This product is not controlled under the Seveso Directive.
International regulations
Chemical Weapon Convention List Schedules I, II & III Chemicals
Not listed.
Montreal Protocol
Not listed.
Stockholm Convention on Persistent Organic Pollutants Not listed.
Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Abbreviations and acronyms	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
uoronymo	1272/2008] DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration RRN = REACH Registration Number
	SGG = Segregation Group

Date of issue/Date of revision	: 05/06/2025	Date of previous issue	: 11/10/2023	Version	:5	18/20
TEKNOL 1881-15 - All variants				Label No	12082	25

SECTION 16: Other information

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification	
Skin Sens. 1, H317	Calculation method	
Aquatic Chronic 3, H412	Calculation method	

Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

Acute Tox. 3	ACUTE TOXICITY - Category 2 ACUTE TOXICITY - Category 3
	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Corr. 1	SKIN CORROSION/IRRITATION - Category 1
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
Date of issue/ Date of revision	: 05/06/2025
Date of previous issue	e : 11/10/2023
Version	: 5
	TEKNOL 1881-15 All variants

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision TEKNOL 1881-15 - All variants : 05/06/2025 Date of previous issue