

# SAFETY DATA SHEET



TEKNOL AQUA 1412-01 - All variants

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : TEKNOL AQUA 1412-01 - All variants

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Apply this product only as specified on the label.

### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

**e-mail address of person responsible for this SDS** : Prod-safe@teknos.com

#### National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

**Telephone number** : In an emergency, call 112

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Repr. 1B, H360D  
Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Danger

**Hazard statements** : H360D - May damage the unborn child.  
H411 - Toxic to aquatic life with long lasting effects.

#### Precautionary statements

**Prevention** : P201 - Obtain special instructions before use.  
P280 - Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection.  
P273 - Avoid release to the environment.

**Response** : P391 - Collect spillage.  
P308 + P313 - IF exposed or concerned: Get medical advice or attention.

**Storage** : Not applicable.

**Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Date of issue/Date of revision** : 16/02/2024 **Date of previous issue** : 12/07/2023

**Version** : 1.03 1/23

TEKNOL AQUA 1412-01 - All variants

**Label No** : 76286

## SECTION 2: Hazards identification

<b>Hazardous ingredients</b>	: Contains: Propiconazole
<b>Supplemental label elements</b>	: Contains Propiconazole and 3-iodo-2-propynyl-butyl carbamate. May produce an allergic reaction.
<b>Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles</b>	: <input checked="" type="checkbox"/> Restricted to professional users. As from 1 July 2024, treated articles treated with or incorporating propiconazole shall not be placed on the market for the production of furniture and play structures.

### 2.3 Other hazards

<b>Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII</b>	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
<b>Other hazards which do not result in classification</b>	: None known.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Dipropyleneglycolmethylether	REACH #: 01-2119450011-60 EC: 252-104-2 CAS: 34590-94-8	≤3	Not classified.	-	[2]
Alcohols, C16-18 and C18-unsatd., ethoxylated (8 EO)	REACH #: 01-2119489407-26 EC: 500-236-9 CAS: 68920-66-1	≤3	Skin Irrit. 2, H315 Aquatic Acute 1, H400 Aquatic Chronic 3, H412	M [Acute] = 1	[1]
Propiconazole	EC: 262-104-4 CAS: 60207-90-1 Index: 613-205-00-0	<1	Acute Tox. 4, H302 Skin Sens. 1, H317 Repr. 1B, H360D Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 1517 mg/kg M [Acute] = 1 M [Chronic] = 1	[1]
3-iodo-2-propynyl-butyl carbamate	EC: 259-627-5 CAS: 55406-53-6 Index: 616-212-00-7	≤0.3	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 400 mg/kg ATE [Inhalation (dusts and mists)] = 0.67 mg/l M [Acute] = 10 M [Chronic] = 1	[1]
Tebuconazol	REACH #: 01-0000015329-67 EC: 403-640-2 CAS: 107534-96-3 Index: 603-197-00-7	≤0.3	Acute Tox. 4, H302 Repr. 2, H361d Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 500 mg/kg M [Acute] = 1 M [Chronic] = 10	[1]
Bronopol	EC: 200-143-0 CAS: 52-51-7 Index: 603-085-00-8	≤0.1	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400	ATE [Oral] = 307 mg/kg ATE [Dermal] = 1100 mg/kg M [Acute] = 10	[1]

Date of issue/Date of revision : 16/02/2024 Date of previous issue : 12/07/2023 Version : 1.03 2/23

TEKNOL AQUA 1412-01 - All variants

Label No : 76286

## SECTION 3: Composition/information on ingredients

			See Section 16 for the full text of the H statements declared above.		
--	--	--	--	--	--

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations

### 4.3 Indication of any immediate medical attention and special treatment needed

## SECTION 4: First aid measures

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

## SECTION 6: Accidental release measures

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

#### Seveso Directive - Reporting thresholds

##### Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
E2	200 tonne	500 tonne

### 7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
Dipropyleneglycolmethylether	<b>Regulation on Limit Values - MAC (Austria, 4/2021).</b> <b>[Dipropylene glycol monomethyl ethers (mixture of isomers)]</b> <b>Absorbed through skin.</b> TWA: 50 ppm 8 hours. TWA: 307 mg/m <sup>3</sup> 8 hours. CEIL: 100 ppm, 8 times per shift, 5 minutes. CEIL: 614 mg/m <sup>3</sup> , 8 times per shift, 5 minutes.

## SECTION 8: Exposure controls/personal protection








Dipropyleneglycolmethylether	<p><b>Limit values (Belgium, 5/2021).</b>  <b>[Dipropyleenglycolmonomethylether] Absorbed through skin.</b>  TWA: 50 ppm 8 hours.  TWA: 308 mg/m<sup>3</sup> 8 hours.</p>
Dipropyleneglycolmethylether	<p><b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 6/2021).</b> <b>[(2-Methoxymethyletoxy)propanol] Absorbed through skin.</b>  Limit value 8 hours: 308 mg/m<sup>3</sup> 8 hours.  Limit value 8 hours: 50 ppm 8 hours.</p>
Dipropyleneglycolmethylether	<p><b>Ministry of Economy, Labour and Entrepreneurship ELV/ STELV (Croatia, 1/2021).</b> <b>[(2-methoxymethylethoxy)-propanol] Absorbed through skin.</b>  ELV: 308 mg/m<sup>3</sup> 8 hours.  ELV: 50 ppm 8 hours.</p>
Dipropyleneglycolmethylether	<p><b>Department of labour inspection (Cyprus, 7/2021).</b> <b>Absorbed through skin.</b>  TWA: 50 ppm 8 hours.  TWA: 308 mg/m<sup>3</sup> 8 hours.</p>
Dipropyleneglycolmethylether	<p><b>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 10/2022).</b> <b>[(2-methoxymethylethoxy)-propanol (mixture of isomers)] Absorbed through skin.</b>  TWA: 270 mg/m<sup>3</sup> 8 hours.  TWA: 43.74 ppm 8 hours.  STEL: 550 mg/m<sup>3</sup> 15 minutes.  STEL: 89.1 ppm 15 minutes.</p>
Dipropyleneglycolmethylether	<p><b>Working Environment Authority (Denmark, 6/2022).</b>  <b>[Dipropylenglycolmethylether] Absorbed through skin.</b>  TWA: 50 ppm 8 hours.  TWA: 309 mg/m<sup>3</sup> 8 hours.  STEL: 618 mg/m<sup>3</sup> 15 minutes.  STEL: 100 ppm 15 minutes.</p>
Dipropyleneglycolmethylether	<p><b>Occupational exposure limits, Regulation No. 293 (Estonia, 12/2022).</b> <b>[Dipropylene glycol monomethyl ether] Absorbed through skin.</b>  TWA: 308 mg/m<sup>3</sup> 8 hours.  TWA: 50 ppm 8 hours.</p>
Dipropyleneglycolmethylether	<p><b>EU OEL (Europe, 1/2022).</b> <b>[(2-Methoxymethylethoxy)-propanol] Absorbed through skin. Notes: list of indicative occupational exposure limit values</b>  TWA: 50 ppm 8 hours.  TWA: 308 mg/m<sup>3</sup> 8 hours.</p>
Dipropyleneglycolmethylether	<p><b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021).</b> <b>[(2-Methoxymethylethoxy)propanol] Absorbed through skin.</b>  TWA: 50 ppm 8 hours.  TWA: 310 mg/m<sup>3</sup> 8 hours.</p>
Dipropyleneglycolmethylether	<p><b>Ministry of Labor (France, 10/2022).</b> <b>[(2-methoxymethylethoxy)-propanol] Absorbed through skin. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</b>  TWA: 50 ppm 8 hours.  TWA: 308 mg/m<sup>3</sup> 8 hours.</p>
Dipropyleneglycolmethylether	<p><b>TRGS 900 OEL (Germany, 6/2022).</b> <b>[(2-Methoxymethylethoxy)propanol]</b>  TWA: 310 mg/m<sup>3</sup> 8 hours.  PEAK: 310 mg/m<sup>3</sup> 15 minutes.  TWA: 50 ppm 8 hours.  PEAK: 50 ppm 15 minutes.  <b>DFG MAC-values list (Germany, 7/2022).</b> <b>[Dipropylene glycol monomethyl ether (mixture of isomers)]</b>  TWA: 50 ppm 8 hours.  PEAK: 50 ppm, 4 times per shift, 15 minutes.  TWA: 310 mg/m<sup>3</sup> 8 hours.</p>



## SECTION 8: Exposure controls/personal protection

3-iodo-2-propynyl-butyl carbamate	<p>PEAK: 310 mg/m<sup>3</sup>, 4 times per shift, 15 minutes.  <b>DFG MAC-values list (Germany, 7/2022). Skin sensitiser.</b>  PEAK: 0.116 mg/m<sup>3</sup>, 4 times per shift, 15 minutes.  PEAK: 0.01 ppm, 4 times per shift, 15 minutes.  TWA: 0.058 mg/m<sup>3</sup> 8 hours.  TWA: 0.005 ppm 8 hours.  <b>TRGS 900 OEL (Germany, 6/2022). Skin sensitiser.</b>  PEAK: 0.116 mg/m<sup>3</sup> 15 minutes.  PEAK: 0.01 ppm 15 minutes.  TWA: 0.058 mg/m<sup>3</sup> 8 hours.  TWA: 0.005 ppm 8 hours.</p>
Bronopol	<p><b>DFG MAC-values list (Germany, 7/2022). Absorbed through skin. Skin sensitiser.</b></p>
Dipropyleneglycolmethylether	<p><b>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021). [(2-Methoxymethylethoxy)propanol] Absorbed through skin.</b>  TWA: 100 ppm 8 hours.  TWA: 600 mg/m<sup>3</sup> 8 hours.  STEL: 150 ppm 15 minutes.  STEL: 900 mg/m<sup>3</sup> 15 minutes.</p>
Dipropyleneglycolmethylether	<p><b>5/2020. (II. 6.) ITM Decree (Hungary, 12/2022). [Dipropylene glycol monomethyl ether]</b>  TWA: 308 mg/m<sup>3</sup> 8 hours.  TWA: 50 ppm 8 hours.</p>
Dipropyleneglycolmethylether	<p><b>Ministry of Welfare, List of Exposure Limits (Iceland, 5/2021). [dipropylene glycol methyl ether] Absorbed through skin.</b>  TWA: 300 mg/m<sup>3</sup> 8 hours.  TWA: 50 ppm 8 hours.</p>
Dipropyleneglycolmethylether	<p><b>NAOSH (Ireland, 5/2021). [(2-methoxymethylethoxy)-1-propanol] Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values</b>  OELV-8hr: 50 ppm 8 hours.  OELV-8hr: 308 mg/m<sup>3</sup> 8 hours.</p>
Dipropyleneglycolmethylether	<p><b>Legislative Decree No. 819/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 6/2020). Absorbed through skin.</b>  8 hours: 50 ppm 8 hours.  8 hours: 308 mg/m<sup>3</sup> 8 hours.</p>
Dipropyleneglycolmethylether	<p><b>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 2/2021). [Methoxy propoxy propanols] Absorbed through skin.</b>  TWA: 50 ppm 8 hours.  TWA: 308 mg/m<sup>3</sup> 8 hours.</p>
Dipropyleneglycolmethylether	<p><b>Lithuanian Hygiene Standard HN 23 (Lithuania, 7/2022). Absorbed through skin.</b>  TWA: 308 mg/m<sup>3</sup> 8 hours.  TWA: 50 ppm 8 hours.  STEL: 450 mg/m<sup>3</sup> 15 minutes.  STEL: 75 ppm 15 minutes.</p>
Dipropyleneglycolmethylether	<p><b>Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021). [(2-methoxymethylethoxy)-propanol] Absorbed through skin.</b>  TWA: 50 ppm 8 hours.  TWA: 308 mg/m<sup>3</sup> 8 hours.</p>
Dipropyleneglycolmethylether	<p><b>EU OEL (Europe, 1/2022). [(2-Methoxymethylethoxy)-propanol] Absorbed through skin. Notes: list of indicative occupational exposure limit values</b>  TWA: 50 ppm 8 hours.  TWA: 308 mg/m<sup>3</sup> 8 hours.</p>
Dipropyleneglycolmethylether	<p><b>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 12/2022). [dipropylene glycolmethylether]</b>  OEL, 8-h TWA: 300 mg/m<sup>3</sup> 8 hours.  OEL, 8-h TWA: 48.7 ppm 8 hours.</p>

## SECTION 8: Exposure controls/personal protection

Dipropyleneglycolmethylether	<b>FOR-2011-12-06-1358 (Norway, 12/2022).</b> [Dipropylene glycol methyl ether] Absorbed through skin. Notes: indicative limit value TWA: 50 ppm 8 hours. TWA: 300 mg/m <sup>3</sup> 8 hours.
Dipropyleneglycolmethylether	<b>Regulation of the Minister of Family, Labor and Social Policy of 18 February 2021, regarding the highest permissible concentrations and values of agents harmful to health in the work environment (Journal of Laws 2021, item 325) (Poland, 2/2021).</b> [dipropylene glycol methyl ether] Absorbed through skin. TWA: 240 mg/m <sup>3</sup> 8 hours. STEL: 480 mg/m <sup>3</sup> 15 minutes.
 Dipropyleneglycolmethylether	<b>Portuguese Institute of Quality (Portugal, 11/2014).</b> [2-Metoximetiletoxipropanol] Absorbed through skin. TWA: 100 ppm 8 hours. STEL: 150 ppm 15 minutes.
 Dipropyleneglycolmethylether	<b>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2021).</b> Absorbed through skin. VLA: 308 mg/m <sup>3</sup> 8 hours. VLA: 50 ppm 8 hours.
 Dipropyleneglycolmethylether	<b>Government regulation SR c. 355/2006 (Slovakia, 9/2020).</b> [2-methoxymetyl-ethoxypropanol] Absorbed through skin. TWA: 308 mg/m <sup>3</sup> , (2-methoxymetyl-ethoxypropanol) 8 hours. TWA: 50 ppm, (2-methoxymetyl-ethoxypropanol) 8 hours.
 Dipropyleneglycolmethylether	<b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021).</b> [(2-methoxymethylethoxy)propanol (mixture of isomers)] Absorbed through skin. TWA: 308 mg/m <sup>3</sup> 8 hours. TWA: 50 ppm 8 hours. KTV: 50 ppm, 4 times per shift, 15 minutes. KTV: 308 mg/m <sup>3</sup> , 4 times per shift, 15 minutes.
3-iodo-2-propynyl-butyl carbamate	<b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021).</b> KTV: 0.01 ppm, 4 times per shift, 15 minutes. TWA: 0.005 ppm 8 hours. KTV: 0.116 mg/m <sup>3</sup> , 4 times per shift, 15 minutes. TWA: 0.058 mg/m <sup>3</sup> 8 hours.
 Dipropyleneglycolmethylether	<b>National institute of occupational safety and health (Spain, 4/2022).</b> [Dipropylene glycol methyl ether] Absorbed through skin. TWA: 50 ppm 8 hours. TWA: 308 mg/m <sup>3</sup> 8 hours.
 Dipropyleneglycolmethylether	<b>Work environment authority Regulation 2018:1 (Sweden, 9/2021).</b> [dipropylene glycol monomethyl ether] Absorbed through skin. TWA: 50 ppm 8 hours. TWA: 300 mg/m <sup>3</sup> 8 hours. STEL: 75 ppm 15 minutes. STEL: 450 mg/m <sup>3</sup> 15 minutes.
 Dipropyleneglycolmethylether	<b>SUVA (Switzerland, 1/2023).</b> [Dipropylene glycol methyl ether (mixture of isomers)] STEL: 50 ppm 15 minutes. Form: vapour and aerosols STEL: 300 mg/m <sup>3</sup> 15 minutes. Form: vapour and aerosols TWA: 50 ppm 8 hours. Form: vapour and aerosols TWA: 300 mg/m <sup>3</sup> 8 hours. Form: vapour and aerosols
3-iodo-2-propynyl-butyl carbamate	<b>SUVA (Switzerland, 1/2023).</b> Skin sensitiser. STEL: 0.24 mg/m <sup>3</sup> 15 minutes. Form: vapour and aerosols STEL: 0.02 ppm 15 minutes. Form: vapour and aerosols TWA: 0.01 ppm 8 hours. Form: vapour and aerosols TWA: 0.12 mg/m <sup>3</sup> 8 hours. Form: vapour and aerosols





## SECTION 8: Exposure controls/personal protection

No exposure indices known.

No exposure indices known.

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following:  
 European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
Dipropyleneglycolmethylether	DNEL	Long term Oral	36 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	37.2 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	121 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	283 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	308 mg/m <sup>3</sup>	Workers	Systemic
Alcohols, C16-18 and C18-unsatd., ethoxylated (8 EO)	DNEL	Long term Oral	25 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	87 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	294 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	1250 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	2080 mg/kg bw/day	Workers	Systemic
Propiconazole	DNEL	Long term Oral	0.08 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.14 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.24 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	0.38 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.35 mg/m <sup>3</sup>	Workers	Systemic
3-iodo-2-propynyl-butyl carbamate	DNEL	Long term Inhalation	0.023 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	0.07 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	1.16 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Inhalation	1.16 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Dermal	2 mg/kg bw/day	Workers	Systemic
Bronopol	DNEL	Short term Dermal	4 µg/cm <sup>2</sup>	General population	Local
	DNEL	Long term Dermal	4 µg/cm <sup>2</sup>	General population	Local
	DNEL	Short term Dermal	8 µg/cm <sup>2</sup>	Workers	Local
	DNEL	Long term Dermal	8 µg/cm <sup>2</sup>	Workers	Local
	DNEL	Long term Oral	0.18 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	0.5 mg/kg	General	Systemic

## SECTION 8: Exposure controls/personal protection

	DNEL	Short term Inhalation	bw/day 0.6 mg/m <sup>3</sup>	population General population	Local
	DNEL	Long term Inhalation	0.6 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	0.7 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	1.8 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	2 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	2.1 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	2.5 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Inhalation	2.5 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Inhalation	3.5 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Dermal	6 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	10.5 mg/m <sup>3</sup>	Workers	Systemic

### PNECs

No PNECs available

## 8.2 Exposure controls

### **Appropriate engineering controls**

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

### Individual protection measures

#### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Eye/face protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

### Skin protection

#### **Hand protection**

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations : Wear suitable gloves tested to EN374.

> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm

Not recommended polyvinyl alcohol (PVA) gloves

#### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### **Other skin protection**

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## SECTION 8: Exposure controls/personal protection

- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.  
Filter type (spray application): A P
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : Colourless.
- Odour** : Slight
- Odour threshold** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** :

Ingredient name	°C	°F	Method
water	100	212	
Dipropyleneglycolmethylether	189.6	373.3	EU A.2

- Flammability** : Not available.
- Lower and upper explosion limit** : Lower: 1.1%  
Upper: 14%
- Flash point** : Closed cup: >100°C (>212°F)
- Auto-ignition temperature** :

Ingredient name	°C	°F	Method
Dipropyleneglycolmethylether	207	404.6	EU A.15

- Decomposition temperature** : Not available.
- pH** : 7 to 9
- Viscosity** : Not available.
- Solubility(ies)** :  
Not available.
- Solubility in water** : Not available.
- Partition coefficient: n-octanol/ water** : Not applicable.
- Vapour pressure** :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
water	17.5	2.3				

- Relative density** : Not available.
- Density** : 1 g/cm<sup>3</sup>
- Vapour density** : Not available.
- Explosive properties** : Not available.
- Oxidising properties** : Not available.

## SECTION 9: Physical and chemical properties

### Particle characteristics

Median particle size : Not applicable.

## SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : No specific data.

**10.5 Incompatible materials** : No specific data.

**10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Propiconazole	LC50 Inhalation Dusts and mists	Rat	5.8 mg/l	4 hours
	LD50 Dermal	Rat	>4000 mg/kg	-
	LD50 Oral	Rat	1517 mg/kg	-
3-iodo-2-propynyl-butyl carbamate	LC50 Inhalation Dusts and mists	Rat	0.67 g/m <sup>3</sup>	4 hours
	LC50 Inhalation Dusts and mists	Rat	0.763 mg/l	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
Tebuconazole	LD50 Oral	Rat	400 mg/kg	-
	LC50 Inhalation Vapour	Rat	0.371 g/m <sup>3</sup>	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Dermal	Rat	>5 g/kg	-
Bronopol	LD50 Oral	Rat	3352 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	>0.588 mg/l	4 hours
	LD50 Dermal	Rat	4750 mg/kg	-
	LD50 Oral	Rat	307 mg/kg	-

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

#### Acute toxicity estimates

Route	ATE value
Inhalation (dusts and mists)	223.34 mg/l

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Dipropyleneglycolmethylether	Eyes - Mild irritant	Human	-	8 mg	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
3-iodo-2-propynyl-butyl carbamate	Skin - Mild irritant	Rabbit	-	500 mg	-
	Eyes - Severe irritant	Rabbit	-	-	-
Bronopol	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Moderate irritant	Human	-	10 mg	-

Date of issue/Date of revision : 16/02/2024 Date of previous issue : 12/07/2023

Version : 1.03 13/23

TEKNOL AQUA 1412-01 - All variants

Label No : 76286

## SECTION 11: Toxicological information

	Skin - Moderate irritant	Rabbit	-	80 mg	-
--	--------------------------	--------	---	-------	---

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

**Eyes** : Based on available data, the classification criteria are not met.

### Sensitisation

Product/ingredient name	Route of exposure	Species	Result
Propiconazole	skin	Guinea pig	Sensitising
3-iodo-2-propynyl-butyl carbamate	skin	Guinea pig	Not sensitizing

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

**Skin** : May produce an allergic reaction.

### Mutagenicity

Product/ingredient name	Test	Experiment	Result
Propiconazole	OECD 471 Bacterial Reverse Mutation Test	Subject: Bacteria	Negative
3-iodo-2-propynyl-butyl carbamate	-	Experiment: In vitro Subject: Bacteria	Negative

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Carcinogenicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
Propiconazole	Positive	-	Positive	Mouse	Route of exposure unreported	-
3-iodo-2-propynyl-butyl carbamate	Negative	-	Negative	Rabbit - Female	Oral: 20 mg/kg	13 days; 7 days per week
	Positive	-	Negative	Rabbit - Female	Oral: 50 mg/kg	13 days; 7 days per week

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Teratogenicity

Product/ingredient name	Result	Species	Dose	Exposure
3-iodo-2-propynyl-butyl carbamate	Negative - Oral	Rabbit - Female	50 mg/kg	-

**Conclusion/Summary** : May damage the unborn child.

### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Bronopol	Category 3	-	Respiratory tract irritation

### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
3-iodo-2-propynyl-butyl carbamate	Category 1	-	larynx

### Aspiration hazard

Not available.



## SECTION 11: Toxicological information

**Information on likely routes of exposure** : Not available.

### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards.  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : No known significant effects or critical hazards.  
**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : No specific data.  
**Inhalation** : Adverse symptoms may include the following:  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations  
**Skin contact** : Adverse symptoms may include the following:  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations  
**Ingestion** : Adverse symptoms may include the following:  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

#### Potential chronic health effects

Not available.

**Conclusion/Summary** : Based on available data, the classification criteria are not met.  
**General** : No known significant effects or critical hazards.  
**Carcinogenicity** : No known significant effects or critical hazards.  
**Mutagenicity** : No known significant effects or critical hazards.  
**Reproductive toxicity** : May damage the unborn child.

## 11.2 Information on other hazards

### 11.2.1 Endocrine disrupting properties

Not available.

### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

## SECTION 12: Ecological information

Product/ingredient name	Result	Species	Exposure
Propiconazole	EC50 10.2 mg/l	Daphnia - <i>Daphnia magna</i>	48 hours
	LC50 4.3 mg/l	Fish - <i>Oncorhynchus mykiss</i>	96 hours
3-iodo-2-propynyl-butyl carbamate	Acute EC50 0.022 mg/l Fresh water	Algae - <i>Scenedemus subspicatus</i>	72 hours
	Acute EC50 0.16 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
Tebuconazol	Acute LC50 0.067 mg/l Fresh water	Fish - <i>Oncorhynchus mykiss</i>	96 hours
	Acute NOEC 0.049 mg/l Fresh water	Fish - <i>Oncorhynchus mykiss</i>	96 hours
	Chronic NOEC 0.05 mg/l Fresh water	Daphnia - <i>Daphnia Magna</i>	21 days
	Acute EC50 1.45 ppm Fresh water	Algae - <i>Scenedesmus subspicatus</i>	4 days
	Acute IC50 3200 µg/l Fresh water	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours
	Acute LC50 750 µg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours
Bronopol	Acute LC50 2.37 mg/l Fresh water	Fish - <i>Cyprinus carpio</i> - Fingerling	96 hours
	Chronic IC10 1200 µg/l Fresh water	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours
	Chronic NOEC 0.12 ppm Fresh water	Daphnia - <i>Daphnia magna</i>	21 days
	Chronic NOEC 0.012 ppm	Fish - <i>Oncorhynchus mykiss</i>	83 days
	Acute EC50 0.4 mg/l	Algae	72 hours
	Acute EC50 0.02 ppm Fresh water	Algae - <i>Scenedesmus subspicatus</i>	96 hours
	Acute EC50 1.4 mg/l	Daphnia	48 hours
	Acute LC50 41.2 mg/l	Fish	96 hours
	Acute LC50 11.17 ppm Fresh water	Fish - <i>Lepomis macrochirus</i>	96 hours
	Chronic NOEC 1.94 ppm	Fish - <i>Oncorhynchus mykiss</i>	49 days

**Conclusion/Summary** : Toxic to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

**Conclusion/Summary** : This product has not been tested for biodegradation.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
3-iodo-2-propynyl-butyl carbamate	-	-	Not readily
Bronopol	-	-	Readily

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Dipropyleneglycolmethylether Alcohols, C16-18 and C18-unsatd., ethoxylated (8 EO)	0.004	-	Low
	4.2	-	High
Propiconazole	3.72	-	Low
3-iodo-2-propynyl-butyl carbamate	>1	-	Low
Tebuconazol	3.7	-	Low
Bronopol	0.18	-	Low

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

## SECTION 12: Ecological information

### 12.6 Endocrine disrupting properties

Not available.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**European waste catalogue (EWC)** : 030202

#### European waste catalogue (EWC)





Waste code	Waste designation
03 02 02*	organochlorinated wood preservatives

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spill material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN3082	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Tebuconazole)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Tebuconazole)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Tebuconazole)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Tebuconazole)
14.3 Transport hazard class(es)	9 	9 	9 	9 
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes.

#### Additional information

**ADR/RID** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.  
**Tunnel code (-)**

## SECTION 14: Transport information

- ADN** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
- IMDG** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
- IATA** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in bulk according to IMO instruments** : Not relevant/applicable due to nature of the product.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

###### Annex XIV


None of the components are listed.

###### Substances of very high concern

None of the components are listed.

##### Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
TEKNOL AQUA 1412-01	≥90	3 30
Propiconazole	<1	30

**Labelling** :  Restricted to professional users.  
As from 1 July 2024, treated articles treated with or incorporating propiconazole shall not be placed on the market for the production of furniture and play structures.

#### Other EU regulations

**Industrial emissions (integrated pollution prevention and control) - Air** : Not listed

**Industrial emissions (integrated pollution prevention and control) - Water** : Not listed

**Explosive precursors** : Not applicable.

#### Ozone depleting substances (1005/2009/EU)

Not listed.

#### Prior Informed Consent (PIC) (649/2012/EU)

Annex	Ingredient name	Status
Annex I - Part 1	propiconazole	Listed

#### Persistent Organic Pollutants

Not listed.

#### Seveso Directive

## SECTION 15: Regulatory information

This product is controlled under the Seveso Directive.

### Danger criteria

#### Category

E2

### National regulations

**Biocidal products regulation** : This product is a biocidal product as defined in EU Regulation 528/2012. Its supply and use may be subject to certain requirements or restrictions specified in this regulation.

#### Austria

**VbF class** : Not regulated.

**Limitation of the use of organic solvents** : Permitted.

#### Czech Republic

**Storage code** : IV

#### Denmark

**Product registration number** : 4148556

**Danish fire class** : IV-1

**MAL-code** : 0-1

**Protection based on MAL** : **According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:**

**General:** Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

MAL-code: 0-1

**Application:** When spraying in existing\* spray booths, if the operator is outside the spray zone.

- Arm protectors must be worn.

During non-atomising spraying in existing\* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone.

- Gas filter mask must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Full mask with combined filter, coveralls and hood must be worn.

**Drying:** Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

**Polishing:** When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

## SECTION 15: Regulatory information

**Caution** The regulations contain other stipulations in addition to the above.

\*See Regulations.

**Restrictions on use** : Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.

**List of undesirable substances** : Not listed

### Finland

### France

**Social Security Code, Articles L 461-1 to L 461-7** : Dipropylenglycolmethylether RG 84

**Reinforced medical surveillance** : Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable

### Germany

**Storage class (TRGS 510)** : 6.1C

### Hazardous incident ordinance

This product is controlled under the Germany Hazardous Incident Ordinance.

#### Danger criteria

Category	Reference number
E2	1.3.2

**Hazard class for water** : 3

**Technical instruction on air quality control** : TA-Luft Number 5.2.5: 6.6%  
TA-Luft Class I - Number 5.2.5: 0.6%

**AOX** : The product contains organically bound halogens and can contribute to the AOX value in waste water.

### Italy

**D.Lgs. 152/06** : Not determined.

### Netherlands

**Ministry of Social Affairs and Employment (SZW) - Carcinogenic substances and processes, mutagenic or reprotoxic substances**

Ingredient name	Carcinogen	Mutagen	Reproductive toxicity - Fertility	Reproductive toxicity - Development	Harmful via breastfeeding
propiconazool (ISO)	-	-	-	Development 1B	-
tebuconazool (ISO)	-	-	-	Development 2	-

**Water Discharge Policy (ABM)** : Z(1) Non biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/ reprotoxicity/ bioacumulative potential/ toxicity or persistence). Decontamination effort: Z

### Norway

### Sweden

### Switzerland

**VOC content** : Exempt.

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)



## SECTION 15: Regulatory information

Not listed.

### [UNECE Aarhus Protocol on POPs and Heavy Metals](#)

Not listed.

#### 15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

#### Abbreviations and acronyms

: ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
N/A = Not available  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
SGG = Segregation Group  
vPvB = Very Persistent and Very Bioaccumulative

#### [Procedure used to derive the classification according to Regulation \(EC\) No. 1272/2008 \[CLP/GHS\]](#)

Classification	Justification
Repr. 1B, H360D	Calculation method
Aquatic Chronic 2, H411	Calculation method

#### [Full text of abbreviated H statements](#)

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H360D	May damage the unborn child.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### [Full text of classifications \[CLP/GHS\]](#)

Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Repr. 1B	REPRODUCTIVE TOXICITY - Category 1B
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

**Date of issue/ Date of revision** : 16/02/2024

**Date of previous issue** : 12/07/2023

**Date of issue/Date of revision** : 16/02/2024 **Date of previous issue** : 12/07/2023

**Version** : 1.03 21/23

TEKNOL AQUA 1412-01 - All variants

**Label No** : 76286

## SECTION 16: Other information

Version

: 1.03

TEKNOL AQUA 1412-01

All variants

### Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

*Date of issue*/*Date of revision*

: 16/02/2024

*Date of previous issue*

: 12/07/2023

*Version* : 1.03 22/23

TEKNOL AQUA 1412-01 - All variants

**Label No** : 76286

