Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Malta

# **SAFETY DATA SHEET**



TEKNOLUX AQUA 1429-42 - TS 16047 CLEAR

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### 1.1 Product identifier Product name

: TEKNOLUX AQUA 1429-42 - TS 16047 CLEAR

**1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use**: Paint.

#### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person : Prod-safe@teknos.com

responsible for this SDS

#### **National contact**

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

#### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

 Telephone number
 : Malta Competition and Consumer Affairs Authority (MCCAA): +356 2395 2000

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

#### **Hazard pictograms**



Signal word	: Warning
Hazard statements	<ul> <li>H317 - May cause an allergic skin reaction.</li> <li>H319 - Causes serious eye irritation.</li> <li>H412 - Harmful to aquatic life with long lasting effects.</li> </ul>
Precautionary statements	
Prevention	<ul> <li>P280 - Wear protective gloves. Wear eye or face protection.</li> <li>P273 - Avoid release to the environment.</li> <li>P261 - Avoid breathing vapour.</li> </ul>
Response	<ul> <li>▶302 + P352 - IF ON SKIN: Wash with plenty of water.</li> <li>P362 + P364 - Take off contaminated clothing and wash it before reuse.</li> </ul>
Storage	: Not applicable.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

# **SECTION 2: Hazards identification**

Hazardous ingredients	: Contains: 1,2-benzisothiazol-3(2H)-one and reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)
Supplemental label elements	:
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:
2.3 Other hazards	
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

# **SECTION 3: Composition/information on ingredients**

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
<ul> <li>Propenoic acid, polymer with 2,2-bis(hydroxymethyl)</li> <li>-1,3-propanediol, methyloxirane and oxirane</li> </ul>	CAS: 144086-02-2	≤10	Eye Irrit. 2, H319 Aquatic Chronic 2, H411	-	[1]
2-Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	≤3	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	ATE [Oral] = 1200 mg/kg ATE [Inhalation (vapours)] = 3 mg/l	[1] [2]
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	≤0.01	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 450 mg/kg ATE [Inhalation (dusts and mists)] = $0.21$ mg/l Skin Sens. 1, H317: C $\ge 0.036\%$ M [Acute] = 1 M [Chronic] = 1	[1]
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:1)	EC: 911-418-6 CAS: 55965-84-9 Index: 613-167-00-5	≤0.005	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 53 mg/ kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: $C \ge 0.6\%$ Eye Dam. 1, H318: $C \ge 0.6\%$ Eye Irrit. 2, H319: $0.06\% \le C < 0.6\%$ Skin Sens. 1, H317: $C \ge 0.0015\%$ M [Acute] = 100	[1]
Date of issue/Date of revision	: 15/07/2025 Date	e of previous i	ssue : 20/11/2023	Version : 2	2/18

SECTION 3: Composition/information on ingredients			
		See Section 16 for the full text of the H statements declared above.	M [Chronic] = 100

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

### **SECTION 4: First aid measures**

4.1 Description of first aid r	neasures
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

<u>symptoms</u>
: Adverse symptoms may include the following: pain or irritation watering redness
: No specific data.
: Adverse symptoms may include the following: irritation redness
: No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician: Treat symptomatically. Contact poison treatment specialist immediately if large<br/>quantities have been ingested or inhaled.

Date of issue/Date of revision	: 15/07/2025	Date of previous issue	: 20/11/2023	Version	:2	3/18
TEKNOLUX AQUA 1429-42 - TS	6 16047 CLEAF	र		Label No	1225	574

#### SECTION 4: First aid measures **Specific treatments** : No specific treatment. SECTION 5: Firefighting measures 5.1 Extinguishing media Suitable extinguishing : Use an extinguishing agent suitable for the surrounding fire. media Unsuitable extinguishing : None known. media 5.2 Special hazards arising from the substance or mixture Hazards from the : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water substance or mixture contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. **Hazardous combustion** Decomposition products may include the following materials: 5 products carbon dioxide carbon monoxide 5.3 Advice for firefighters **Special protective actions** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without for fire-fighters suitable training. : Fire-fighters should wear appropriate protective equipment and self-contained **Special protective** breathing apparatus (SCBA) with a full face-piece operated in positive pressure equipment for fire-fighters mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and material for	containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

: 20/11/2023

### **SECTION 6: Accidental release measures**

6.4 Reference to other	
sections	

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

### **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

Recommendations	: Not available.
Industrial sector specific	: Not available.
solutions	

### **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

#### **Occupational exposure limits**

Product/ingredient name	Exposure limit values
₽-Butoxyethanol	EU OEL (Europe, 1/2022) Absorbed through skin. TWA 8 hours: 20 ppm. TWA 8 hours: 98 mg/m <sup>3</sup> . STEL 15 minutes: 50 ppm. STEL 15 minutes: 246 mg/m <sup>3</sup> .

#### **Biological exposure indices**

procedures European Stand assessment of e values and mea atmospheres - 0 of exposure to o (Workplace atm for the measure		Exposure indices	
		Id be made to monitoring standards, such as the following: dard EN 689 (Workplace atmospheres - Guidance for the exposure by inhalation to chemical agents for comparison with limit asurement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment chemical and biological agents) European Standard EN 482 nospheres - General requirements for the performance of procedures ement of chemical agents) Reference to national guidance methods for the determination of hazardous substances will also be	

Date of issue/Date of revision	: 15/07/2025	Date of previous issue	: 20/11/2023	Version	:2	5/18
TEKNOLUX AQUA 1429-42 - T	'S 16047 CLEAF	R		Label No	1225	74

### **SECTION 8: Exposure controls/personal protection**

required.

### DNELs/DMELs

Product/ingredient name Propenoic acid, polymer with 2,2-bis (hydroxymethyl)-1,3-propanediol, methyloxirane and oxirane

#### Result

**DNEL - General population - Long term - Oral** 0.13 mg/kg bw/day <u>Effects</u>: Systemic

**DNEL - General population - Long term - Inhalation** 0.232 mg/m<sup>3</sup> <u>Effects</u>: Systemic

**DNEL - General population - Long term - Dermal** 0.27 mg/kg bw/day <u>Effects</u>: Systemic

**DNEL - Workers - Long term - Dermal** 0.53 mg/kg bw/day <u>Effects</u>: Systemic

**DNEL - Workers - Long term - Inhalation** 0.94 mg/m<sup>3</sup> <u>Effects</u>: Systemic

**DNEL - General population - Long term - Oral** 6.3 mg/kg bw/day <u>Effects</u>: Systemic

**DNEL - General population - Short term - Oral** 26.7 mg/kg bw/day <u>Effects</u>: Systemic

**DNEL - General population - Long term - Inhalation** 59 mg/m<sup>3</sup> <u>Effects</u>: Systemic

DNEL - Workers - Long term - Inhalation 98 mg/m<sup>3</sup> Effects: Systemic

DNEL - General population - Short term - Inhalation 147 mg/m<sup>3</sup> Effects: Local

DNEL - Workers - Short term - Inhalation 246 mg/m<sup>3</sup> Effects: Local

**DNEL - General population - Short term - Inhalation** 426 mg/m<sup>3</sup> <u>Effects</u>: Systemic

DNEL - Workers - Short term - Inhalation 1091 mg/m<sup>3</sup> Effects: Systemic

**DNEL - General population - Long term - Dermal** 0.345 mg/kg bw/day <u>Effects</u>: Systemic

**DNEL - Workers - Long term - Dermal** 0.966 mg/kg bw/day <u>Effects</u>: Systemic

**DNEL - General population - Long term - Inhalation** 1.2 mg/m<sup>3</sup>

Date of issue/Date of revision	: 15/07/2025	Date of previous issue	: 20/11/2023	Version	:2	6/18
TEKNOLUX AQUA 1429-42 -	TS 16047 CLEA	R		Label No	<b>1</b> 22	574

2-Butoxyethanol

1,2-benzisothiazol-3(2H)-one

### **SECTION 8: Exposure controls/personal protection**

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) Effects: Systemic

**DNEL - Workers - Long term - Inhalation** 6.81 mg/m<sup>3</sup> <u>Effects</u>: Systemic

DNEL - General population - Long term - Inhalation 0.02 mg/m<sup>3</sup> Effects: Local

DNEL - Workers - Long term - Inhalation 0.02 mg/m<sup>3</sup> <u>Effects</u>: Local

**DNEL - General population - Short term - Inhalation** 0.04 mg/m<sup>3</sup> <u>Effects</u>: Local

DNEL - Workers - Short term - Inhalation 0.04 mg/m<sup>3</sup> Effects: Local

**DNEL - General population - Long term - Oral** 0.09 mg/kg bw/day <u>Effects</u>: Systemic

**DNEL - General population - Short term - Oral** 0.11 mg/kg bw/day <u>Effects</u>: Systemic

#### **PNECs**

Not available.

8.2 Exposure controls	
Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection meas	<u>ures</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
	Recommendations : Wear suitable gloves tested to EN374.
	> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm
Date of issue/Date of revision	: 15/07/2025 Date of previous issue : 20/11/2023 Version : 2 7/18

# **SECTION 8: Exposure controls/personal protection**

		Not recommended polyvinyl alcohol (PVA) gloves
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
		Filter type (spray application): A P
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

Appearance	
Physical state	: Liquid.
Colour	: Clear.
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	:

Ingredient name	°C	°F	Method
water	100	212	
water	100	212	

Flammability	: Not available.
Lower and upper explosion limit	: Lower: Not applicable. Upper: Not applicable.
Flash point	: Closed cup: >100°C (>212°F)

÷.

### Auto-ignition temperature

Ingredient name	°C	°F	Method
2-Butoxyethanol	230	446	DIN 51794
2-Propenoic acid, polymer with 2,2-bis (hydroxymethyl)-1,3-propanediol, methyloxirane and oxirane	408	766.4	

Decomposition temperature	: Not available.
рН	: 7.6 to 8.3 [Conc. (% w/w): 100%]
Viscosity	: Not available.
Solubility(ies)	:
Not available.	
Solubility in water	: Not available.
Partition coefficient: n-octanol/ water	: Not applicable.
Vapour pressure	:

	Va	apour Pres	sure at 20°C	Va	Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
water	17.5	2.3					
water	17.5	2.3					
Relative density	: Not	available.		<b>I</b>			
Density	: 1 g/	/cm³					
Vapour density	: Not	available.					
Particle characteristics							
Median particle size	: Not	applicable.					
9.2 Other information							
9.2.1 Information with regar	d to physic	cal hazard	classes				
Explosive properties	: Not	available.					
Oxidising properties	: Not	available.					
9.2.2 Other safety character	ristics						
Not applicable.							
SECTION 10: Stabilit	y and re	eactivity	,				
10.1 Reactivity	: No spe	cific test dat	ta related to react	ivity available fo	r this produ	ict or its ingredien	
10.2 Chemical stability	: The pro	oduct is stab	ble				
··,	•• p. •						
10.3 Possibility of hazardous reactions	: Under r	normal conc	litions of storage a	and use, hazard	lous reactic	ns will not occur.	
10.4 Conditions to avoid	: No specific data.						
10.5 Incompatible materials	: No spe	cific data.					
10.6 Hazardous	• Under i	pormal conc	litions of storage :	and use hazard	lous decom	position products	

11.1 Information on hazard classes as defined in Re	gulation (EC) No 1272/2008
---	----------------------------

Acute toxicity Product/ingredient name

1,2-benzisothiazol-3(2H)-one

**Rat - Oral - LD50** 1020 mg/kg

Result

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Rat - Oral - LD50

53 mg/kg <u>Toxic effects</u>: Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration -Respiratory depression

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

: 20/11/2023

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)		
FEKNOLUX AQUA 1429-42	60788.2	N/A	N/A	152.0	N/A		
2-Butoxyethanol	1200	N/A	N/A	3	N/A		
1,2-benzisothiazol-3(2H)-one	450	N/A	N/A	N/A	0.21		
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-	53	50	N/A	0.5	N/A		
3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6] (3:1)							

### Skin corrosion/irritation

Product/ingredient name

2-Butoxyethanol

#### Result

Rabbit - Skin - Mild irritant Amount/concentration applied: 500 mg

1,2-benzisothiazol-3(2H)-one

Human - Skin - Mild irritant Duration of treatment/exposure: 48 hours Amount/concentration applied: 5 %

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) Human - Skin - Severe irritant Amount/concentration applied: 0.01 %

220-238-0] (3.1)

Conclusion/Summary [Product] : Not available.

#### Serious eye damage/eye irritation

Product/ingredient name P-Butoxyethanol

#### Result

**Rabbit - Eyes - Moderate irritant** <u>Duration of treatment/exposure</u>: 24 hours <u>Amount/concentration applied</u>: 100 mg

**Rabbit - Eyes - Severe irritant** <u>Amount/concentration applied</u>: 100 mg

#### Conclusion/Summary [Product] : Not available.

#### **Respiratory corrosion/irritation**

Not available.

Conclusion/Summary [Product] : Not available.

#### **Respiratory or skin sensitization**

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory Conclusion/Summary [Product] : Not available.

#### Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

#### **Carcinogenicity**

Not available.

**Conclusion/Summary [Product]** : Not available.

#### **Reproductive toxicity**

Not available.

Conclusion/Summary [Product] : Not available.

<u>Specific target organ toxicity (single exposure)</u> Not available.

Specific target organ toxicity (repeated exposure) Not available.

Achieve beyond		
Aspiration hazard Not available.		
Information on likely routes Not available.	exposure	
Potential acute health effect		
Eye contact	Causes serious eye irritation.	
Inhalation	No known significant effects or critical hazards.	
Skin contact	May cause an allergic skin reaction.	
Ingestion	No known significant effects or critical hazards.	
•	ical, chemical and toxicological characteristics	
Eye contact	Adverse symptoms may include the following:	
-	pain or irritation	
	watering redness	
Inhalation	No specific data.	
Skin contact	Adverse symptoms may include the following:	
Okin contact	irritation	
	redness	
Ingestion	No specific data.	
Delayed and immediate effe	as well as chronic effects from short and long-term exposure	
<u>Short term exposure</u>		
Potential immediate	Not available.	
effects		
Potential delayed effects	Not available.	
Long term exposure		
Potential immediate effects	Not available.	
Potential delayed effects	Not available.	
Potential chronic health effe		
Not available.	2	
Conclusion/Summary [Pro	ict] : Not available.	
General	Once sensitized, a severe allergic reaction may occur when subsequently expo	osed
	to very low levels.	
Carcinogenicity	No known significant effects or critical hazards.	
Mutagenicity	No known significant effects or critical hazards.	

**Reproductive toxicity** 

: No known significant effects or critical hazards.

#### **11.2 Information on other hazards**

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product]

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

#### 11.2.2 Other information

Not available.

## **SECTION 12: Ecological information**

12.1 Toxicity		
Product/ingredient name 2-Butoxyethanol		Result Acute - LC50 - Marine water Fish - Inland silverside - <i>Menidia beryllina</i> <u>Size</u> : 40 to 100 mm 1250000 μg/l [96 hours] <u>Effect</u> : Mortality
		<b>Acute - LC50 - Marine water</b> Crustaceans - Common shrimp, sand shrimp - <i>Crangon</i> <i>crangon</i> 800000 μg/l [48 hours] <u>Effect</u> : Mortality
1,2-benzisothiazol-3(2H)-one		<b>Acute - LC50 - Fresh water</b> OECD [Fish, Acute Toxicity Test] Fish - Trout - <i>Onorhynchus Mykiss</i> 1.9 mg/l [96 hours]
		<b>Acute - EC50</b> OECD 202 [Daphnia sp. Acute Immobilization Test and Reproduction Test] Daphnia - Daphnia - <i>Daphnia Magna</i> 3.7 mg/l [48 hours]
		<b>Acute - EC50 - Marine water</b> OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - <i>Skeletonema Costatum</i> 0.36 mg/l [72 hours]
		Acute - NOEC - Marine water OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - <i>Skeletonema Costatum</i> 0.15 mg/l [72 hours]
Conclusion/Summary [Product]	: Not available	2.
<b>12.2 Persistence and degradability</b> <b>Product/ingredient name</b> <b>7</b> ,2-benzisothiazol-3(2H)-one		<mark>Result</mark> EU 24% [28 days]
	NI. 6	

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
7,2-benzisothiazol-3(2H)-one	-	-	Inherent

12.3 Bioaccumulative potential

Date of issue/Date of revision	: 15/07/2025	Date of previous issue	: 20/11/2023	Version	:2	12/18
TEKNOLUX AQUA 1429-42 - TS	16047 CLEAF	۲		Label No	1225	74

S	ECTION 12: Ecologi	12: Ecological information			
	Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential	
	Butoxyethanol 1,2-benzisothiazol-3(2H)-one	0.81 -	- 3.2	Low Low	

### 12.4 Mobility in soil

#### Soil/water partition coefficient

Product/ingredient name	logKoc	Кос
Butoxyethanol	1.8	67.3685
1,2-benzisothiazol-3(2H)-one	1.9	73.142

#### Results of PMT and vPvM assessment

Product/ingredient name	PMT	Р	М	Т	vPvM	vP	٧M
Propenoic acid, polymer with 2,2-bis(hydroxymethyl) -1,3-propanediol, methyloxirane and oxirane	No	No	No	No	No	No	No
2-Butoxyethanol	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No
Mobility	: Not av	ailable.					

Conclusion/Summary

: The product does not meet the criteria to be considered as a PMT or vPvM.

# 12.5 Results of PBT and vPvB assessment

# Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	Р	В	т	vPvB	vP	vB
Propenoic acid, polymer with 2,2-bis(hydroxymethyl) -1,3-propanediol, methyloxirane and oxirane	No	N/A	N/A	No	N/A	N/A	N/A
2-Butoxyethanol	No	N/A	N/A	No	N/A	N/A	N/A
1,2-benzisothiazol-3(2H)-one	No	N/A	No	No	No	N/A	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	N/A	N/A	No	N/A	N/A	N/A

#### Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	Р	В	т	vPvB	vP	vB
Propenoic acid, polymer with 2,2-bis(hydroxymethyl) -1,3-propanediol, methyloxirane and oxirane	No	No	No	No	No	No	No
2-Butoxyethanol	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No

: 15/07/2025 Date of previous issue

: 20/11/2023

: The product does not meet the criteria to be considered as a PBT or vPvB. **Conclusion/Summary Regulation (EC) No. 1272/2008** [CLP]

12.6 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** 

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations					
13.1 Waste treatment meth	nods				
Product					
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.				
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.				
European waste catalogue (EWC)	: 080111*				
Packaging					
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.				
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.				

### **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

**14.6 Special precautions for** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

## **SECTION 14: Transport information**

#### 14.7 Maritime transport in bulk according to IMO instruments

: Not relevant/applicable due to nature of the product.

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

#### Annex XIV - List of substances subject to authorisation

#### Annex XIV

None of the components are listed.

#### Substances of very high concern

None of the components are listed.

# Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]		
TEKNOLUX AQUA 1429-42	≥90	3		
Labelling : Other EU regulations				
Industrial emissions : Not listed (integrated pollution prevention and control) - Air				
Industrial emissions : Not listed (integrated pollution prevention and control) - Water				
Explosive precursors       : Not applicable.         Ozone depleting substances (EU 2024/590)         Not listed.				
Prior Informed Consent (PIC) (649/2012/EU) Not listed.				
Persistent Organic Pollutants Not listed.				
Seveso Directive This product is not controlled under the Seveso Directive.				
International regulations Chemical Weapon Convention List Schedules I, II & III Chemicals Not listed.				
Montreal Protocol Not listed.				
Stockholm Convention on Persistent Organic Pollutants Not listed.				
Rotterdam Convention on Prior Informed Consent (PIC) Not listed.				
UNECE Aarhus Protocol on POPs and Heavy Metals Not listed.				

## **SECTION 15: Regulatory information**

# **15.2 Chemical safety** assessment

: This product contains substances for which Chemical Safety Assessments are still required.

## **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
-	1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	LOT statement – CLF-specific hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Sens. 1, H317	Calculation method Calculation method Calculation method

#### Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

#### Full text of classifications [CLP/GHS]

Acute Tox. 2	ACUTE TOXICITY - Category 2	
Acute Tox. 3	ACUTE TOXICITY - Category 3	
Acute Tox. 4	ACUTE TOXICITY - Category 4	
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1	
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1	
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2	
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3	
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1	
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2	
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C	
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2	
Skin Sens. 1	SKIN SENSITISATION - Category 1	
Skin Sens. 1A	SKIN SENSITISATION - Category 1A	
Date of issue/ Date of	: 15/07/2025	
revision		
Date of previous issue	20/11/2023	
Version	: 2	
	TEKNOLUX AQUA 1429-42_TS 16047 CLEAR TS 16047 CLEAR	
Notice to reader		
Date of issue/Date of revision	on : 15/07/2025 Date of previous issue : 20/11/2023	Version : 2 16/18
TEKNOLUX AQUA 142	Label No : 122574	

# **SECTION 16: Other information**

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision: 15/07/2025Date of previous issueTEKNOLUX AQUA 1429-42 - TS 16047 CLEAR