SAFETY DATA SHEET



Label No : 1717958

TEKNOLUX AQUA 1728-52 - NCS S 0502-Y

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : TEKNOLUX AQUA 1728-52 - NCS S 0502-Y

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person : Prod-safe@teknos.com

responsible for this SDS

National contact

Teknos Ireland Limited, 52 Ballymoughan Road, Magherafelt, BT45 6HN, UK. Tel. +44 (0) 2879 301 472.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : NHS: 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word : Warning

Hazard statements: H317 - May cause an allergic skin reaction.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention: P280 - Wear protective gloves.

P273 - Avoid release to the environment.

P261 - Avoid breathing vapour.

Response : P302 + P352 - IF ON SKIN: Wash with plenty of water.

P362 + P364 - Take off contaminated clothing and wash it before reuse.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Date of issue/Date of revision : 27/05/2025 Date of previous issue : 01/12/2023 Version : 2 1/19

SECTION 2: Hazards identification

Hazardous ingredients

: Contains: ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one [EC no. 220-239-6] (3:1)

Supplemental label elements

: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains biocidal products for in-can preservation: C(M)IT/ MIT (3:1).

Annex XVII - Restrictions on the manufacture. placing on the market and use of certain dangerous substances, mixtures and articles

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

: Mixture 3.2 Mixtures

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Manium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥10 - ≤25	Carc. 2, H351 (inhalation)	-	[1] [*]
ethyl phenyl (2,4,6-trimethylbenzoyl) phosphinate	REACH #: 01-2119987994-10 EC: 282-810-6 CAS: 84434-11-7	≤3	Skin Sens. 1B, H317 Aquatic Chronic 2, H411	-	[1]
2-hydroxy- 2-methylpropiophenone	REACH #: 01-2119472306-39 EC: 231-272-0 CAS: 7473-98-5	≤3	Acute Tox. 4, H302 Aquatic Chronic 3, H412	ATE [Oral] = 1694 mg/kg	[1]
4-methylbenzophenone	EC: 205-159-1 CAS: 134-84-9	≤3	STOT RE 2, H373 (oral) Aquatic Chronic 3, H412	-	[1]
Triethylamine	REACH #: 01-2119475467-26 EC: 204-469-4 CAS: 121-44-8 Index: 612-004-00-5	<1	Flam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335	ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (vapours)] = 7.2 mg/l STOT SE 3, H335: C ≥ 1%	[1] [2]
2-Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	<1	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	ATE [Oral] = 1200 mg/kg ATE [Inhalation (vapours)] = 3 mg/l	[1] [2]

Date of issue/Date of revision :01/12/2023 Version : 2 2/19 : 27/05/2025 Date of previous issue Label No : 177958

SECTION 3: Composition/information on ingredients reaction mass of: 5-chloro-EC: 911-418-6 ≤0.012 Acute Tox. 3, H301 ATE [Oral] = 53 mg/[1]2-methyl-4-isothiazolin-CAS: 55965-84-9 Acute Tox. 2, H310 3-one [EC no. 247-500-7] ATE [Dermal] = 50Index: 613-167-00-5 Acute Tox. 2, H330 mg/kg and 2-methyl-2H-isothiazol-Skin Corr. 1C. H314 3-one [EC no. 220-239-6] Eve Dam. 1. H318 ATE [Inhalation (vapours)] = 0.5Skin Sens. 1A, H317 (3:1)Aquatic Acute 1, H400 mq/l Aquatic Chronic 1, Skin Corr. 1C, H410 H314: C ≥ 0.6% **EUH071** Eye Dam. 1, H318: C ≥ 0.6% Eye Irrit. 2, H319: $0.06\% \le C < 0.6\%$ Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter ≤ 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Date of issue/Date of revision : 27/05/2025 .01/12/2023 Version : 2 3/19 Date of previous issue Label No : 177958

SECTION 4: First aid measures

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact : No specific data. Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

> irritation redness

Ingestion : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products

Decomposition products may include the following materials:

carbon dioxide carbon monoxide phosphorus oxides metal oxide/oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Date of issue/Date of revision : 27/05/2025 : 01/12/2023 Version : 2 4/19 Date of previous issue Label No : 1717958

SECTION 6: Accidental release measures

6.3 Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

6.4 Reference to other sections

: See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Date of issue/Date of revision : 27/05/2025 Date of previous issue : 01/12/2023 Version : 2 5/19

Product/ingredient name	Exposure limit values
r iethylamine	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin. STEL 15 minutes: 17 mg/m³. TWA 8 hours: 2 ppm. TWA 8 hours: 8 mg/m³. STEL 15 minutes: 4 ppm.
2-Butoxyethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin. STEL 15 minutes: 50 ppm. TWA 8 hours: 25 ppm. STEL 15 minutes: 246 mg/m³. TWA 8 hours: 123 mg/m³.

Biological exposure indices

Product/ingredient name	Exposure indices
Z -Butoxyethanol	EH40/2005 BMGVs (United Kingdom (UK), 1/2020) BGV: 240 mmol/mol creatinine, butoxyacetic acid [in urine]. Sampling time: post shift.

Recommended monitoring procedures

: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

<u>DNELS/DWELS</u>	
Product/ingredient name	Result
titanium dioxide	DNEL - General population - Long term - Inhalation 28 μg/m³ <u>Effects</u> : Local
	DNEL - Workers - Long term - Inhalation 170 μg/m³ <u>Effects</u> : Local
ethyl phenyl(2,4,6-trimethylbenzoyl) phosphinate	DNEL - General population - Long term - Oral 0.5 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Long term - Dermal 0.5 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Long term - Inhalation 0.87 mg/m³ <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Dermal 1.4 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Inhalation 4.93 mg/m³ <u>Effects</u> : Systemic
2-hydroxy-2-methylpropiophenone	DNEL - General population - Long term - Oral 0.4 mg/kg bw/day <u>Effects</u> : Systemic

Date of issue/Date of revision : 27/05/2025 Date of previous issue : 01/12/2023 Version :2 6/19 Label No : 177958

DNEL - General population - Long term - Dermal

0.5 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Inhalation

0.9 mg/m³ Effects: Systemic

DNEL - Workers - Long term - Dermal

1 mg/kg bw/day Effects: Systemic

DNEL - Workers - Long term - Inhalation

3.5 mg/m³

Effects: Systemic

4-methylbenzophenone DNEL - General population - Long term - Oral

0.05 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Dermal

0.05 mg/kg bw/day Effects: Systemic

DNEL - Workers - Long term - Dermal

0.1 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Long term - Inhalation

0.17 mg/m³ Effects: Systemic

DNEL - Workers - Long term - Inhalation

0.7 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

8.4 mg/m³ Effects: Local

DNEL - Workers - Long term - Inhalation

8.4 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Inhalation

12.6 mg/m³ Effects: Local

DNEL - Workers - Short term - Inhalation

12.6 mg/m³ Effects: Systemic

DNEL - Workers - Long term - Dermal

12.1 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Oral

6.3 mg/kg bw/day Effects: Systemic

DNEL - General population - Short term - Oral

26.7 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Inhalation 59 mg/m³

7/19

Label No : 177958

Date of issue/Date of revision : 27/05/2025 Date of previous issue : 01/12/2023 Version : 2

TEKNOLUX AQUA 1728-52 - NCS S 0502-Y

Triethylamine

2-Butoxyethanol

Effects: Systemic

DNEL - Workers - Long term - Inhalation

98 mg/m³

Effects: Systemic

DNEL - General population - Short term - Inhalation

147 mg/m³ <u>Effects</u>: Local

DNEL - Workers - Short term - Inhalation

246 mg/m³ <u>Effects</u>: Local

DNEL - General population - Short term - Inhalation

426 mg/m³ Effects: Systemic

DNEL - Workers - Short term - Inhalation

1091 mg/m³ Effects: Systemic

DNEL - General population - Long term - Inhalation

0.02 mg/m³ Effects: Local

Effects: Local

DNEL - Workers - Long term - Inhalation 0.02 mg/m³ Effects: Local

DNEL - General population - Short term - Inhalation

0.04 mg/m³ Effects: Local

DNEL - Workers - Short term - Inhalation

0.04 mg/m³ Effects: Local

DNEL - General population - Long term - Oral

0.09 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Short term - Oral

0.11 mg/kg bw/day Effects: Systemic

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

reaction mass of: 5-chloro-2-methyl-

2-methyl-2H-isothiazol-3-one [EC no.

220-239-6] (3:1)

4-isothiazolin-3-one [EC no. 247-500-7] and

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Label No : 177958

Date of issue/Date of revision : 27/05/2025 Date of previous issue : 01/12/2023 Version : 2 8/19

Eve/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists. gases or dusts. If contact is possible, the following protection should be worn. unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations: Wear suitable gloves tested to EN374.

< 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm

> 8 hours (breakthrough time): 4H / Silver Shield® gloves.

Wash hands before breaks and immediately after handling the product.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type (spray application):

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid. Colour White. **Odour** Slight

Odour threshold Not available. Melting point/freezing point Not available.

Initial boiling point and

boiling range

Ingredient name	°C	°F	Method
water value of the state of the	100	212	
2-hydroxy-2-methylpropiophenone	252.1	485.8	OECD 104

Flammability : Not available.

Lower and upper explosion

limit

Lower: Not applicable. Upper: Not applicable.

Closed cup: >100°C (>212°F) Flash point

Auto-ignition temperature

Date of issue/Date of revision • 27/05/2025 .01/12/2023 Version : 2 9/19 Date of previous issue TEKNOLUX AQUA 1728-52 - NCS S 0502-Y Label No : 1717958

SECTION 9: Physical and chemical properties

Ingredient name	°C	°F	Method
ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate	423	793.4	DIN EN 14522

Decomposition temperature : Not available.

7.6 to 8.6 [Conc. (% w/w): 100%] pН

: Not available. **Viscosity**

Solubility(ies)

Not available.

Solubility in water : Not available. Partition coefficient: n-octanol/ : Not applicable.

water

Vapour pressure

	Vapour Pressure at 20°C			Vapour pressure at 50°C			
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
water	17.5	2.3					
2-hydroxy-2-methylpropiophenone	0.00428	0.00057	OECD 104	0.09751	0.013	OECD 104	

Relative density : Not available. : 1.2 g/cm³ **Density** : Not available. Vapour density

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties : Not available. **Oxidising properties** : Not available.

9.2.2 Other safety characteristics

Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

Date of issue/Date of revision Date of previous issue :01/12/2023 Version : 2 10/19 : 27/05/2025 Label No : 177958

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name

2-hydroxy-2-methylpropiophenone

Result

Rat - Oral - LD50

1694 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed

activity) Behavioral - Tremor Liver - Other changes

Rat - Dermal - LD50

6929 mg/kg

Triethylamine Rat - Oral - LD50

460 mg/kg

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no.

220-239-6] (3:1)

Rat - Oral - LD50

53 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration -

Respiratory depression

Conclusion/Summary [Product]: Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
FEKNOLUX AQUA 1728-52	10325.1	34083.9	N/A	240.6	N/A
2-hydroxy-2-methylpropiophenone	1694	6929	N/A	N/A	N/A
Triethylamine	100	300	N/A	7.2	N/A
2-Butoxyethanol	1200	N/A	N/A	3	N/A
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-	53	50	N/A	0.5	N/A
3-one [EC no. 247-500-7] and 2-methyl-2H-					
isothiazol-3-one [EC no. 220-239-6] (3:1)					

Skin corrosion/irritation

Product/ingredient name

titanium dioxide

Result

Human - Skin - Mild irritant

Duration of treatment/exposure: 72 hours Amount/concentration applied: 300 ug I

Triethylamine Rabbit - Skin - Mild irritant

Amount/concentration applied: 365 mg

2-Butoxyethanol Rabbit - Skin - Mild irritant

Amount/concentration applied: 500 mg

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and

2-methyl-2H-isothiazol-3-one [EC no.

220-239-6] (3:1)

Human - Skin - Severe irritant

Amount/concentration applied: 0.01 %

Label No : 177958

Conclusion/Summary [Product]: Not available.

Serious eye damage/eye irritation

Product/ingredient name Result

Date of issue/Date of revision Date of previous issue :01/12/2023 Version : 2 11/19 : 27/05/2025

SECTION 11: Toxicological information

2-Butoxyethanol

Rabbit - Eyes - Moderate irritant

Duration of treatment/exposure: 24 hours Amount/concentration applied: 100 mg

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 100 mg

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product]: Not available.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product]: Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. Not available.

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Not available.

Conclusion/Summary [Product]: Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name Result

riethylamine STOT SE 3, H335 (Respiratory tract irritation)

Specific target organ toxicity (repeated exposure)

Product/ingredient name Result

4-methylbenzophenone STOT RE 2, H373 (oral)

Aspiration hazard

Not available.

Information on likely routes of exposure

Not available.

Potential acute health effects

Date of issue/Date of revision : 01/12/2023 Version : 2 12/19 : 27/05/2025 Date of previous issue Label No : 177958

SECTION 11: Toxicological information

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

Skin contact: May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : No

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

General: Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine

disrupting properties according to the criteria set out in either Regulation (EC)

No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name Result

Manium dioxide Acute - LC50 - Marine water

Fish - Mummichog - Fundulus heteroclitus

>1000000 µg/l [96 hours]

Effect: Mortality

Acute - LC50 - Fresh water

Crustaceans - Water flea - Ceriodaphnia dubia - Neonate

Label No : 1717958

Age: <24 hours 3 mg/l [48 hours] Effect: Mortality

2-Butoxyethanol Acute - LC50 - Marine water

Fish - Inland silverside - Menidia beryllina

<u>Size</u>: 40 to 100 mm 1250000 µg/l [96 hours]

Date of issue/Date of revision : 27/05/2025 Date of previous issue : 01/12/2023 Version : 2 13/19

SECTION 12: Ecological information

Effect: Mortality

Acute - LC50 - Marine water

Crustaceans - Common shrimp, sand shrimp - Crangon

crangon

800000 µg/l [48 hours]

Effect: Mortality

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Not available.

Conclusion/Summary [Product] : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-hydroxy-	1.62	-	Low
2-methylpropiophenone Triethylamine	1.45	<0.5	Low
2-Butoxyethanol	0.81	-	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logKoc	Koc
-hydroxy-2-methylpropiophenone	1.91	80.7076
4-methylbenzophenone	2.81	649.71
Triethylamine	1.88	76.4134
2-Butoxyethanol	1.83	67.3685

Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	Т	vPvM	νP	vM
tranium dioxide	No	No	No	No	No	No	No
ethyl phenyl	No	No	No	No	No	No	No
(2,4,6-trimethylbenzoyl)							
phosphinate							
2-hydroxy-	No	No	No	No	No	No	No
2-methylpropiophenone							
4-methylbenzophenone	No	No	No	No	No	No	No
Triethylamine	No	No	No	No	No	No	No
2-Butoxyethanol	No	No	No	No	No	No	No
reaction mass of: 5-chloro-	No	No	No	No	No	No	No
2-methyl-4-isothiazolin-							
3-one [EC no. 247-500-7]							
and 2-methyl-2H-isothiazol-							
3-one [EC no. 220-239-6] (3:							
1)							

: Not available. **Mobility**

: The product does not meet the criteria to be considered as a PMT or vPvM. **Conclusion/Summary**

12.5 Results of PBT and vPvB assessment Regulation (EC) No. 1907/2006 [REACH]

Version : 2 Date of issue/Date of revision : 27/05/2025 Date of previous issue : 01/12/2023 14/19 Label No : 177958

SECTION 12: Ecological information

Product/ingredient name	PBT	P	В	T	vPvB	vP	vB	
tranium dioxide	No	No	No	No	No	No	No	
ethyl phenyl	No	No	No	No	No	No	No	
(2,4,6-trimethylbenzoyl)								
phosphinate								
2-hydroxy-	No	No	No	No	No	No	No	
2-methylpropiophenone								
4-methylbenzophenone	No	No	No	No	No	No	No	
Triethylamine	No	No	No	No	No	No	No	
2-Butoxyethanol	No	No	No	No	No	No	No	
reaction mass of: 5-chloro-	No	No	No	No	No	No	No	
2-methyl-4-isothiazolin-								
3-one [EC no. 247-500-7]								
and 2-methyl-2H-isothiazol-								
3-one [EC no. 220-239-6] (3:								
1)								

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	Р	В	Т	vPvB	vP	vB
titanium dioxide	No	No	No	No	No	No	No
ethyl phenyl	No	No	No	No	No	No	No
(2,4,6-trimethylbenzoyl)							
phosphinate							. I
2-hydroxy-	No	No	No	No	No	No	No
2-methylpropiophenone							
4-methylbenzophenone	No	No	No	No	No	No	No
Triethylamine	No	No	No	No	No	No	No
2-Butoxyethanol	No	No	No	No	No	No	No
reaction mass of: 5-chloro-	No	No	No	No	No	No	No
2-methyl-4-isothiazolin-							
3-one [EC no. 247-500-7]							
and 2-methyl-2H-isothiazol-							
3-one [EC no. 220-239-6] (3:							
1)							

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP] : The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product]

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

European waste catalogue (EWC)

: 080112

 Date of issue/Date of revision
 : 27/05/2025
 Date of previous issue
 : 01/12/2023
 Version
 : 2
 15/19

 TEKNOLUX AQUA 1728-52 - NCS S 0502-Y
 Label No : 1 7958
 Label No : 1 7958

SECTION 13: Disposal considerations

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
TEKNOLUX AQUA 1728-52	≥90	3

Labelling

Other EU regulations

Industrial emissions (integrated pollution

: Not listed

prevention and control) -Air

Date of issue/Date of revision : 27/05/2025 Date of previous issue

TEKNOLUX AQUA 1728-52 - NCS S 0502-Y

: 01/12/2023

Version : 2

16/19

Label No : 177958

SECTION 15: Regulatory information

: Not listed **Industrial emissions**

(integrated pollution prevention and control) -

Water

Explosive precursors : Not applicable. Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety

assessment

: This product contains substances for which Chemical Safety Assessments are still

required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/20081

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent. Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Sens. 1, H317 Aquatic Chronic 3, H412	Calculation method Calculation method

Full text of abbreviated H statements

Date of issue/Date of revision .01/12/2023 Version : 2 17/19 : 27/05/2025 Date of previous issue Label No : 177958

SECTION 16: Other information

H 225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

Cute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Skin Corr. 1A	SKIN CORROSION/IRRITATION - Category 1A
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of issue/ Date of : 27/05/2025

revision

Date of previous issue : 01/12/2023

Version : 2

TEKNOLUX AQUA 1728-52 NCS S 0502-Y NCS S 0502-Y

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision : 27/05/2025 Date of previous issue : 01/12/2023 Version : 2 18/19

TEKNOLUX AQUA 1728-52 - NCS S 0502-Y

Label No : 177958

: 01/12/2023 Version :2 Date of issue/Date of revision : 27/05/2025 Date of previous issue 19/19 **Label No** : 777958