Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Ireland

# SAFETY DATA SHEET



**TEKNOLUX AQUA 1728-53 - TS 21381 BLACK** 

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### 1.1 Product identifier **Product name**

: TEKNOLUX AQUA 1728-53 - TS 21381 BLACK

1.2 Relevant identified uses of the substance or mixture and uses advised against **Product use** : Paint.

#### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091. e-mail address of person : Prod-safe@teknos.com responsible for this SDS

#### **National contact**

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

#### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

: National Poisons Information Centre: 01 809 2566 **Telephone number** 

# SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements	
Hazard pictograms	
Signal word	: 🕅 arning
Hazard statements	<ul> <li>         F315 - Causes skin irritation.         H317 - May cause an allergic skin reaction.         H319 - Causes serious eye irritation.         H335 - May cause respiratory irritation.         H412 - Harmful to aquatic life with long lasting effects.     </li> </ul>
Precautionary statements	
Prevention	<ul> <li>▶ 280 - Wear protective gloves. Wear eye or face protection.</li> <li>▶ 273 - Avoid release to the environment.</li> <li>▶ 261 - Avoid breathing vapour.</li> </ul>
Response	: ₱304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.
Date of issue/Date of revision	: 04/12/2023 Date of previous issue : 02/08/2023 Version : 1.01 1/15

TEKNOLUX AQUA 1728-53 - TS 21381 BLACK

<b>SECTION 2: Hazards</b>	ic	lentification
Storage	1	P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	-	Contains: ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate; Triethylamine and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)
Supplemental label elements	:	
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do	:	None known.

not result in classification

# **SECTION 3: Composition/information on ingredients**

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
€thyl phenyl (2,4,6-trimethylbenzoyl) phosphinate	REACH #: 01-2119987994-10 EC: 282-810-6 CAS: 84434-11-7	≤3	Skin Sens. 1B, H317 Aquatic Chronic 2, H411	-	[1]
2-hydroxy- 2-methylpropiophenone	REACH #: 01-2119472306-39 EC: 231-272-0 CAS: 7473-98-5	≤3	Acute Tox. 4, H302 Aquatic Chronic 3, H412	ATE [Oral] = 1694 mg/kg	[1]
4-methylbenzophenone	EC: 205-159-1 CAS: 134-84-9	≤3	STOT RE 2, H373 (oral) Aquatic Chronic 3, H412	-	[1]
Triethylamine	REACH #: 01-2119475467-26 EC: 204-469-4 CAS: 121-44-8 Index: 612-004-00-5	<3	Flam. Liq. 2, H225 Acute Tox. 4, H302 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335	ATE [Oral] = 460 mg/kg ATE [Dermal] = 300  mg/kg ATE [Inhalation (vapours)] = 3 mg/l STOT SE 3, H335: $C \ge 1\%$	[1] [2]
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:1)	CAS: 55965-84-9 Index: 613-167-00-5	≤0.01	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 53 mg/ kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: C $\geq$ 0.6%	[1]
Date of issue/Date of revision		e of previous is	sue : 02/08/2023	Version :1.01	
TEKNOLUX AQUA 1728-53	- TS 21381 BLACK			Label No :7484	17

# SECTION 3: Composition/information on ingredients

EUH071	Eye Dam. 1, H318: C ≥ 0.6% Eye Irrit. 2, H319: 0.06% ≤ C < 0.6% Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100
See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

# **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed <u>Over-exposure signs/symptoms</u>

#### SECTION 4: First aid measures Eve contact : Adverse symptoms may include the following: pain or irritation watering redness Inhalation : Adverse symptoms may include the following: respiratory tract irritation coughing Skin contact : Adverse symptoms may include the following: irritation redness Ingestion : No specific data. 4.3 Indication of any immediate medical attention and special treatment needed Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

#### SECTION 5: Firefighting measures 5.1 Extinguishing media Suitable extinguishing : Use an extinguishing agent suitable for the surrounding fire. media **Unsuitable extinguishing** : None known. media 5.2 Special hazards arising from the substance or mixture Hazards from the : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water substance or mixture contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. Decomposition products may include the following materials: **Hazardous combustion** carbon dioxide products carbon monoxide nitrogen oxides phosphorus oxides metal oxide/oxides 5.3 Advice for firefighters **Special protective actions** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without for fire-fighters suitable training. Fire-fighters should wear appropriate protective equipment and self-contained **Special protective** equipment for fire-fighters breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

# SECTION 6: Accidental release measures

6.1 Personal precautions, prot	ective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

# **SECTION 6: Accidental release measures**

6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and materia	for containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

### SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

Protective measures	: Fut on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)
Recommendations
Industrial sector specific solutions

- : Not available.
- : Not available.

# **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
	NAOSH (Ireland, 5/2021). Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values OELV-8hr: 2 ppm 8 hours. OELV-8hr: 8.4 mg/m <sup>3</sup> 8 hours. OELV-15min: 3 ppm 15 minutes. OELV-15min: 12.6 mg/m <sup>3</sup> 15 minutes.

#### **Biological exposure indices**

Product/ingredient name No exposure indices known.		Exposure indices	
Recommended monitoring procedures	European Stand assessment of e values and mea atmospheres - ( of exposure to c (Workplace atm for the measure	Id be made to monitoring standards, such as the following: lard EN 689 (Workplace atmospheres - Guidance for the exposure by inhalation to chemical agents for comparison with limit surement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment chemical and biological agents) European Standard EN 482 ospheres - General requirements for the performance of procedures ment of chemical agents) Reference to national guidance nethods for the determination of hazardous substances will also be	

#### **DNELs/DMELs**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
thyl phenyl(2,4,6-trimethylbenzoyl)	DNEL	Long term Oral	0.5 mg/kg	General	Systemic
phosphinate		_	bw/day	population	-
	DNEL	Long term Dermal	0.5 mg/kg	General	Systemic
		Ū.	bw/day	population	
	DNEL	Long term	0.87 mg/m <sup>3</sup>		Systemic
		Inhalation	Ũ	population	5
	DNEL	Long term Dermal	1.4 mg/kg	Workers	Systemic
		5	bw/day		5
	DNEL	Long term	4.93 mg/m <sup>3</sup>	Workers	Systemic
		Inhalation	J.		,
2-hydroxy-2-methylpropiophenone	DNEL	Long term Dermal	1 mg/kg	Workers	Systemic
, , , , , , , , , , , , , , , , , , , ,		5	bw/day		,
	DNEL	Long term Oral	0.4 mg/kg	General	Systemic
		5	bw/day	population	,
	DNEL	Long term Dermal	0.5 mg/kg	General	Systemic
			bw/day	population	-,
	DNEL	Long term	0.9 mg/m <sup>3</sup>	General	Systemic
		Inhalation	<b>J</b>	population	,
	DNEL	Long term	3.5 mg/m <sup>3</sup>	Workers	Systemic
		Inhalation	<u>-</u>		-,
4-methylbenzophenone	DNEL	Long term Oral	0.05 mg/	General	Systemic
, , , , , , , , , , , , , , , , , , ,		5	kg bw/day	population	,
	DNEL	Long term Dermal	0.05 mg/	General	Systemic
			kg bw/day	population	-,
	DNEL	Long term Dermal	0.1 mg/kg	Workers	Systemic
			bw/day		-,
	DNEL	Long term	0.17 mg/m <sup>3</sup>	General	Systemic
		Inhalation		population	-,
	DNEL	Long term	0.7 mg/m <sup>3</sup>	Workers	Systemic
		Inhalation	- <b>J</b>		,
Triethylamine	DNEL	Long term	8.4 mg/m <sup>3</sup>	Workers	Local
<b>,</b>	<b>_</b>	Inhalation			
e of issue/Date of revision : 04/1	2/2023	Date of previous issue	: 02/08/20	123	ersion : 1.01 6/1

TEKNOLUX AQUA 1728-53 - TS 21381 BLACK

	DNEL	Long term	8.4 mg/m <sup>3</sup>	Workers	Systemic
		Inhalation	10.1		Que terre i
	DNEL	Long term Dermal	12.1 mg/ kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	12.6 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	12.6 mg/m <sup>3</sup>	Workers	Systemic
action mass of: 5-chloro-2-methyl-	DNEL	Long term	0.02 mg/m <sup>3</sup>	General	Local
isothiazolin-3-one [EC no. 47-500-7] and 2-methyl-2H- othiazol-3-one [EC no. 220-239-6] 1:1)		Inhalation		population	
	DNEL	Long term Inhalation	0.02 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	0.04 mg/m <sup>3</sup>	General population	Local
	DNEL	Short term Inhalation	0.04 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Oral	0.09 mg/ kg bw/day	General population	Systemic
	DNEL	Short term Oral	0.11 mg/ kg bw/day	General population	Systemic

#### **PNECs**

No PNECs available

8.2 Exposure controls	
Appropriate engineering controls	: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Individual protection meas	<u>sures</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
	Recommendations : Wear suitable gloves tested to EN374.
	< 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm
	> 8 hours (breakthrough time): $4H$ / Silver Shield® gloves.
	Wash hands before breaks and immediately after handling the product.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Date of issue/Date of revision	:04/12/2023	Date of previous issue	: 02/08/2023	Version	:1.01
TEKNOLUX AQUA 1728-53 - TS 2	1381 BLACK	< colored and set of the set of t		Label No	<b>7</b> 4847

7/15

# **SECTION 8: Exposure controls/personal protection**

Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
	Filter type (spray application): A P
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Colour	: Black.
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	:

Ingredient name	°C	°F	Method	
<b>F</b> riethylamine	89.3	192.7		
water	100	212		

Flammability	: 1
Lower and upper explosion limit	:

Not available.

: Lower: Not applicable. Upper: Not applicable.

: Closed cup: >100°C (>212°F)

Flash point Auto-ignition temperature

Ingredient name	°C	°F	Method
Propanol, 1-(2-butoxy-1-methylethoxy)	194	381.2	EU A.15
Triethylamine	249	480.2	

Decomposition temperature	: Not available.
рН	: 7.2 to 8.2 [Conc. (% w/w): 100%]
Viscosity	: Not available.
Solubility(ies)	:
Not available.	
Solubility in water	: Not available.
Partition coefficient: n-octanol/	: Not applicable.

2

ŝ,

# water

#### Vapour pressure

	Va	Vapour Pressure at 20°C		Va	Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
<b>F</b> iethylamine	54.00459	7.2					
water	17.5	2.3					

Relative density

: Not available.

# **SECTION 9: Physical and chemical properties**

Density	: 1.1 g/cm <sup>3</sup>
Vapour density	: Not available.
Explosive properties	: Not available.
Oxidising properties	: Not available.
Particle characteristics	
Median particle size	: Not applicable.

SECTION 10: Stability and reactivity						
10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredier	ıts.				
10.2 Chemical stability	The product is stable.					
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.					
10.4 Conditions to avoid	No specific data.					
10.5 Incompatible materials	No specific data.					
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.	;				

# **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-hydroxy-	LD50 Dermal	Rat	6929 mg/kg	-
2-methylpropiophenone	LD50 Oral	Rat	1694 mg/kg	-
Triethylamine	LD50 Oral	Rat	460 mg/kg	-
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	LD50 Oral	Rat	53 mg/kg	-

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Acute toxicity estimates

Route	ATE value
Øral	30051.04 mg/kg
Dermal	27044.33 mg/kg
Inhalation (vapours)	270.44 mg/l

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Friethylamine reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	Skin - Mild irritant Skin - Severe irritant	Rabbit Human	-	365 mg 0.01 %	-

# Conclusion/Summary

: Causes skin irritation.

Sensitisation

#### **SECTION 11: Toxicological information** : May cause an allergic skin reaction. **Conclusion/Summary**

Mutagenicity	
<b>Conclusion/Summary</b>	: Based on available data, the classification criteria are not met.
<b>Carcinogenicity</b>	
<b>Conclusion/Summary</b>	: Based on available data, the classification criteria are not met.
Reproductive toxicity	
<b>Conclusion/Summary</b>	: Based on available data, the classification criteria are not met.
<b>Teratogenicity</b>	
<b>Conclusion/Summary</b>	: Based on available data, the classification criteria are not met.

#### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
<b>I</b> ∕riethylamine	Category 3	-	Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
✓methylbenzophenone	Category 2	oral	-

#### **Aspiration hazard**

Not available.

Information on likely routes	: Not available.
of exposure	

#### Potential acute health effects

Eye contact	: Causes serious eye irritation.
Inhalation	: May cause respiratory irritation.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure Short term exposure **Potential immediate** : Not available. effects Potential delayed effects : Not available. Long term exposure **Potential immediate** : Not available. effects **Potential delayed effects** : Not available. **Potential chronic health effects** Date of issue/Date of revision : 04/12/2023 Date of previous issue :02/08/2023

# **SECTION 11: Toxicological information**

Not available.

Conclusion/Summary	: Not available.
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: 📈 known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

### **11.2 Information on other hazards 11.2.1 Endocrine disrupting properties** Not available.

#### 11.2.2 Other information

Not available.

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

**Conclusion/Summary** : Harmful to aquatic life with long lasting effects.

#### 12.2 Persistence and degradability

**Conclusion/Summary** : This product has not been tested for biodegradation.

#### **12.3 Bioaccumulative potential**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
P-hydroxy- 2-methylpropiophenone	1.62	-	Low
Triethylamine	1.45	<0.5	Low

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### 12.6 Endocrine disrupting properties

Not available.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

<u>Product</u> Methods of disposal	: The generation of waste should be avoided or minimise Disposal of this product, solutions and any by-products with the requirements of environmental protection and any regional local authority requirements. Dispose of s products via a licensed waste disposal contractor. Wa untreated to the sewer unless fully compliant with the re with jurisdiction.	should at all times comply waste disposal legislation and surplus and non-recyclable ste should not be disposed of
Hazardous waste	: The classification of the product may meet the criteria f	for a hazardous waste.
Date of issue/Date of revision	: 04/12/2023 Date of previous issue : 02/08/2023	Version : 1.01 11/15
TEKNOLUX AQUA 1728-53	- TS 21381 BLACK	Label No :74847

# **SECTION 13: Disposal considerations**

European waste catalogue (EWC)	: 080111*
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	9006	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	-	-
14.3 Transport hazard class(es)	-	9	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	Yes.	No.	No.

#### **Additional information**

•	n	N
	ப	

: The product is only regulated as a dangerous good when transported in tank vessels.

**14.6 Special precautions for** : **Transport within user's premises:** always transport in closed containers that are user upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in : Not relevant/applicable due to nature of the product.

#### bulk according to IMO instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

#### **Annex XIV**

Date of issue/Date of revision

None of the components are listed.

#### Substances of very high concern

None of the components are listed.

#### Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
FEKNOLUX AQUA 1728-53	≥90	3

:04/12/2023

:02/08/2023

# **SECTION 15: Regulatory information**

CECTION 10. Regula	iony mitormation
Labelling	:
Other EU regulations	
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed
Explosive precursors	: Not applicable.
Ozone depleting substance	e <u>s (1005/2009/EU)</u>
Not listed.	
Prior Informed Consent (PI Not listed.	<u>C) (649/2012/EU)</u>
Persistent Organic Pollutar Not listed.	<u>nts</u>
Seveso Directive	
This product is not controlled	under the Seveso Directive.
International regulations	
Chemical Weapon Convention	on List Schedules I, II & III Chemicals
Montreal Protocol Not listed.	
Stockholm Convention on P Not listed.	ersistent Organic Pollutants
Rotterdam Convention on P Not listed.	rior Informed Consent (PIC)
UNECE Aarhus Protocol on	POPs and Heavy Metals

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

- **15.2 Chemical safety** assessment
- : This product contains substances for which Chemical Safety Assessments are still required.

# **SECTION 16: Other information**

Indicates information	n that has changed from previously issued version.
Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative
Procedure used to der	ive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

:02/08/2023

	Classification	Justification	
Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 3, H412		Calculation method Calculation method Calculation method Calculation method Calculation method	
	abbreviated H statements		
H225	Highly flammable liquid and vapour.		
H301	Toxic if swallowed.		
H302	Harmful if swallowed.		
H310	Fatal in contact with skin.		
1311	Toxic in contact with skin.		
1314	Causes severe skin burns and eye damage.		
1315	Causes skin irritation.		
1317	May cause an allergic skin reaction.		
1318	Causes serious eye damage.		
1319	Causes serious eye irritation.		
330	Fatal if inhaled.		
331	Toxic if inhaled.		
1335	May cause respiratory irritation.		
1373	May cause damage to organs through prolonged or repeated exposure.		
-1400	Very toxic to aquatic life		

- H400 Very toxic to aquatic life.H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH071 Corrosive to the respiratory tract.

#### Full text of classifications [CLP/GHS]

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Skin Corr. 1A	SKIN CORROSION/IRRITATION - Category 1A
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
Date of issue/ Date o	f : 04/12/2023

revision		
Date of previous issue	: 02/08/2023	
Version	: 1.01	
	TEKNOLUX AQUA 1728-53 TS 21381 BLACK	TS 21381 BLACK

#### Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision: 04/12/2023Date of previous issueTEKNOLUX AQUA 1728-53 - TS 21381 BLACK