## SAFETY DATA SHEET



TEKNOLUX AQUA 1728-62 - BEIGE 13

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : TEKNOLUX AQUA 1728-62 - BEIGE 13

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS

: Prod-safe@teknos.com

1.4 Emergency telephone number

**National advisory body/Poison Centre** 

Telephone number : In an emergency, call 112

#### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Product definition**: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

Hazard pictograms



Signal word : Warning

**Hazard statements** : H317 - May cause an allergic skin reaction.

H412 - Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

**Prevention**: P280 - Wear protective gloves.

P273 - Avoid release to the environment.

P261 - Avoid breathing vapour.

Response : P302 + P352 - IF ON SKIN: Wash with plenty of water.

P362 + P364 - Take off contaminated clothing and wash it before reuse.

Storage : Not applicable.

**Disposal** : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Hazardous ingredients : Contains: 2-Propenoic acid, reaction products with dipentaerythritol; ethyl phenyl

(2,4,6-trimethylbenzoyl)phosphinate; 2-methyl-2H-isothiazol-3-one and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-

Label No : 1/37054

2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Date of issue/Date of revision: 03/12/2025Date of previous issue: 04/02/2025Version: 21/25

### **SECTION 2: Hazards identification**

Supplemental label elements

: Contains biocidal products for in-can preservation: BIT and MIT and C(M)IT/MIT (3: 1) and Bronopol and OIT.

**Annex XVII - Restrictions** on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

#### 2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a

Other hazards which do not result in classification : None known.

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Z-Propenoic acid, reaction products with dipentaerythritol	REACH #: 01-2119980666-22 CAS: 1384855-91-7	≤3	Eye Irrit. 2, H319 Skin Sens. 1A, H317 Aquatic Chronic 3, H412	-	[1]
2-Butoxyethanol	EC: 260-252-4 CAS: 56539-66-3	≤3	Eye Irrit. 2, H319	-	[1]
ethyl phenyl (2,4,6-trimethylbenzoyl) phosphinate	REACH #: 01-2119987994-10 EC: 282-810-6 CAS: 84434-11-7	≤3	Skin Sens. 1B, H317 Aquatic Chronic 2, H411	-	[1]
Triethylamine	REACH #: 01-2119475467-26 EC: 204-469-4 CAS: 121-44-8 Index: 612-004-00-5	≤0.3	Flam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335	ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (vapours)] = 7.2 mg/l STOT SE 3, H335: C≥1%	[1] [2]
2-methyl-2H-isothiazol- 3-one	EC: 220-239-6 CAS: 2682-20-4 Index: 613-326-00-9	<0.0015	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (dusts and mists)] = 0.11 mg/l Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 10 M [Chronic] = 1	[1]
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6]	EC: 911-418-6 CAS: 55965-84-9 Index: 613-167-00-5	<0.0015	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318	ATE [Oral] = 53 mg/ kg ATE [Dermal] = 50 mg/kg ATE [Inhalation	[1]

: 04/02/2025 2/25 Date of issue/Date of revision : 03/12/2025 Date of previous issue Version :2 Label No : 1/37054

#### SECTION 3: Composition/information on ingredients Skin Sens. 1A, H317 (vapours)] = 0.5Aguatic Acute 1, H400 mg/l Aquatic Chronic 1, Skin Corr. 1C, H410 H314: C ≥ 0.6% **EUH071** Eye Dam. 1, H318: C ≥ 0.6% Eye Irrit. 2, H319: $0.06\% \le C < 0.6\%$ Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100 See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### **Type**

- 11 Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

#### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

**Eye contact** 

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear aloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

**Eye contact** : No specific data. Inhalation : No specific data.

Date of issue/Date of revision : 03/12/2025 : 04/02/2025 Version : 2 3/25 Date of previous issue Label No : 1/37054

#### **SECTION 4: First aid measures**

Skin contact

: Adverse symptoms may include the following:

irritation redness

No specific data. Ingestion

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

5.2 Special hazards arising from the substance or mixture

### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** media

: None known.

Hazards from the substance or mixture

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous combustion** products

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide phosphorus oxides metal oxide/oxides

#### 5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective** equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

#### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

#### 6.3 Methods and material for containment and cleaning up

Date of issue/Date of revision · 04/02/2025 Version : 2 4/25 : 03/12/2025 Date of previous issue Label No : 1/37054

#### **SECTION 6: Accidental release measures**

#### **Small spill**

#### Large spill

# : Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

## 6.4 Reference to other sections

See Section 1 for emergency contact information.
 See Section 8 for information on appropriate personal protective equipment.
 See Section 13 for additional waste treatment information.

## **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

## Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. See Section 10 for incompatible materials before handling or use.

#### 7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

## **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

**Occupational exposure limits** 

Date of issue/Date of revision : 03/12/2025 Date of previous issue : 04/02/2025 Version : 2 5/25

Product/ingredient name   Exposure limit values
TWA 8 hours: 2 ppm. TWA 8 hours: 8.4 mg/m³. PEAK 15 minutes: 3 ppm 4 times per shift. PEAK 15 minutes: 12.6 mg/m³ 4 times per shift. PEAK 15 minutes: 12.6 mg/m³ 4 times per shift. PEAK 15 minutes: 12.6 mg/m³ 4 times per shift. PEAK 15 minutes: 12.6 mg/m³ 4 times per shift. PEAK 15 minutes: 12.6 mg/m³ 4 times per shift. PEAK 15 minutes: 12.6 mg/m³ 4 times per shift. PEAK 15 minutes: 12.6 mg/m³ 4 times per shift. PEAK 15 minutes: 12.6 mg/m³ 4 times per shift. PEAK 15 minutes: 12.6 mg/m³ 4 times per shift. PEAK 15 minutes: 10.6 mg/m³ 4 times per shift. PEAK 15 minutes: 0.0 mg/m³ 4 times per shift. PEAK 15 minutes: 0.05 mg/m³ 4 times per shift. PEAK 15 minutes: 0.05 mg/m³ 4 times per shift. PEAK 15 minutes: 0.05 mg/m³ 4 times per shift. PEAK 15 minutes: 0.05 mg/m³. Regulation on Limit Values - MAC (Austria, 12/2024) [5-Chidologo mg/m³]. PEAK 15 minutes: 0.05 mg/m³. PEAK 15 minutes: 0.05 mg/m³. Limit values (Beigium, 12/2023) Absorbed through skin. TWA 8 hours: 0.5 ppm. TWA 8 hour
Regulation on Limit Values - MAC (Austria, 12/2024) [5-Chi 2-methyl-2,3-dihydroisothiazol-3-on und 2-Methyl-2,3-dihydroisothiazol-3-on und 2-Methyl-2,3-dihydroisothiazol-3-on (Gemisch im Verhältnis 3:1)] Skin sensitiser.  TWA 8 hours: 0.05 mg/m³.  Regulation on Limit Values - MAC (Austria, 12/2024) [5-Chi 2-methyl-2-3-dihydroisothiazol-3-on und 2-Methyl-2,3-dihydroisothiazol-3-on und 2-Methyl-2,3-dihydroisothiazol-3-on und 2-Methyl-2,3-dihydroisothiazol-3-on (Gemisch im Verhältnis 3:1)] Skin sensitiser.  TWA 8 hours: 0.05 mg/m³.  TWA 8 hours: 0.05 mg/m³.  Limit values (Belgium, 12/2023) Absorbed through skin.  TWA 8 hours: 0.07 mg/m³.  STEL 15 minutes: 1 ppm.  STEL 15 minutes: 4.14 mg/m³.  Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024) Absorbed through skin.  Limit value 15 minutes: 12.6 mg/m³.  Limit value 15 minutes: 3 ppm.  Limit value 8 hours: 2 ppm.  Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annes (Croatia, 12/2023) Absorbed through skin.  STELV 15 minutes: 12.6 mg/m³.  STELV 15 minutes: 3 ppm.
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)  Priethylamine  Regulation on Limit Values - MAC (Austria, 12/2024) [5-Chl 2-methyl-2,3-dihydroisothiazol-3-on und 2-Methyl-2,3-dihydroisothiazol-3-on und 2-Methyl-2,3-dihydroisothiazol-3-on (Gemisch im Verhältnis 3:1)] Skin sensitiser.  TWA 8 hours: 0.05 mg/m³.  Limit values (Belgium, 12/2023) Absorbed through skin.  TWA 8 hours: 2.07 mg/m³.  STEL 15 minutes: 4.14 mg/m³.  Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024) Absorbed through skin.  Limit value 15 minutes: 12.6 mg/m³.  Limit value 15 minutes: 3 ppm.  Limit value 8 hours: 2 ppm.  Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Anne (Croatia, 12/2023) Absorbed through skin.  STELV 15 minutes: 12.6 mg/m³.  STELV 15 minutes: 12.6 mg/m³.
TWA 8 hours: 0.5 ppm. TWA 8 hours: 2.07 mg/m³. STEL 15 minutes: 1 ppm. STEL 15 minutes: 4.14 mg/m³.  Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024) Absorbed through skin. Limit value 15 minutes: 12.6 mg/m³. Limit value 8 hours: 8.4 mg/m³. Limit value 8 hours: 3 ppm. Limit value 8 hours: 2 ppm.  Priethylamine  Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Anne (Croatia, 12/2023) Absorbed through skin. STELV 15 minutes: 12.6 mg/m³. STELV 15 minutes: 3 ppm.
Health - Ordinance No 13/2003. (Bulgaria, 4/2024) Absorbed through skin.  Limit value 15 minutes: 12.6 mg/m³.  Limit value 8 hours: 8.4 mg/m³.  Limit value 15 minutes: 3 ppm.  Limit value 8 hours: 2 ppm.  Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Anne (Croatia, 12/2023) Absorbed through skin.  STELV 15 minutes: 3 ppm.
hazardous chemicals at work, exposure limit values (Anne (Croatia, 12/2023) Absorbed through skin.  STELV 15 minutes: 3 ppm.
ELV 8 hours: 8.4 mg/m³. ELV 8 hours: 2 ppm.
Department of labour inspection (Cyprus, 7/2021) Absorbed through skin.  STEL 15 minutes: 3 ppm.  STEL 15 minutes: 12.6 mg/m³.  TWA 8 hours: 2 ppm.  TWA 8 hours: 8.4 mg/m³.
Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 12/2023)  STEL 15 minutes: 200 mg/m³.  TWA 8 hours: 100 mg/m³.  TWA 8 hours: 20.36 ppm.  STEL 15 minutes: 40.72 ppm.
Triethylamine  Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 12/2023) Absorbed through skin.  TWA 8 hours: 8 mg/m³.  TWA 8 hours: 1.9 ppm.  STEL 15 minutes: 12 mg/m³.  STEL 15 minutes: 2.85 ppm.
Working Environment Authority (Denmark, 12/2024) Absorbed through skin.  TWA 8 hours: 1 ppm.  TWA 8 hours: 4.1 mg/m³.  STEL 15 minutes: 12.6 mg/m³.  STEL 15 minutes: 3 ppm.

 Date of issue/Date of revision
 : 03/12/2025
 Date of previous issue
 : 04/02/2025
 Version
 : 2
 6/25

 TEKNOLUX AQUA 1728-62 - BEIGE 13
 Label No : 1/37054

riethylamine Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024) Absorbed through skin, Sensitiser. TWA 8 hours: 8.4 mg/m<sup>3</sup>. TWA 8 hours: 2 ppm. STEL 15 minutes: 12.6 mg/m<sup>3</sup>. STEL 15 minutes: 3 ppm. riethylamine EU OEL (Europe, 1/2022) Absorbed through skin. TWA 8 hours: 2 ppm. TWA 8 hours: 8.4 mg/m<sup>3</sup>.

**T**riethylamine Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021) Absorbed through skin.

STEL 15 minutes: 1 ppm. STEL 15 minutes: 4.2 mg/m3.

STEL 15 minutes: 3 ppm. STEL 15 minutes: 12.6 mg/m3.

riethylamine Ministry of Labor (France, 6/2024) Absorbed through skin.

STEL 15 minutes: 3 ppm. Notes: Binding regulatory limit values

(article R. 4412-149 of the Labor Code)

STEL 15 minutes: 12.6 mg/m³. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)

TWA 8 hours: 4.2 mg/m³. Notes: Binding regulatory limit values

(article R. 4412-149 of the Labor Code)

TWA 8 hours: 1 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)

TRGS 900 OEL (Germany, 6/2024) Absorbed through skin.

TWA 8 hours: 4.2 mg/m<sup>3</sup>. PEAK 15 minutes: 8.4 mg/m<sup>3</sup>. TWA 8 hours: 1 ppm.

PEAK 15 minutes: 2 ppm.

DFG MAC-values list (Germany, 7/2024) Develop D.

TWA 8 hours: 1 ml/m3.

PEAK 15 minutes: 2 ppm 4 times per shift [Interval: 1 hour].

TWA 8 hours: 4.2 mg/m<sup>3</sup>.

PEAK 15 minutes: 8.4 mg/m<sup>3</sup> 4 times per shift [Interval: 1 hour]. PEAK 15 minutes: 2 ml/m<sup>3</sup> 4 times per shift [Interval: 1 hour].

2-methyl-2H-isothiazol-3-one DFG MAC-values list (Germany, 7/2024) Skin sensitiser.

> Presidential Decree 307/1986: Occupational exposure limit values (Greece, 8/2024) Absorbed through skin.

TWA 8 hours: 10 ppm. TWA 8 hours: 40 mg/m<sup>3</sup>. STEL 15 minutes: 15 ppm. STEL 15 minutes: 60 mg/m<sup>3</sup>.

**T**riethylamine 5/2020. (II. 6.) ITM Decree (Hungary, 1/2025) Absorbed through

TWA 8 hours: 8.4 mg/m<sup>3</sup>. PEAK 15 minutes: 12.6 mg/m<sup>3</sup>. PEAK 15 minutes: 3 ppm. TWA 8 hours: 2 ppm.

riethylamine Ministry of Welfare, List of Exposure Limits (Iceland, 11/2024)

Absorbed through skin.

STEL 15 minutes: 12.6 mg/m<sup>3</sup>. STEL 15 minutes: 3 ppm. TWA 8 hours: 8.4 mg/m<sup>3</sup>. TWA 8 hours: 2 ppm.

riethylamine NAOSH (Ireland, 4/2024) Absorbed through skin. Notes: EU

derived Occupational Exposure Limit Values

OELV 8 hours: 2 ppm. OELV 8 hours: 8.4 mg/m<sup>3</sup>. OELV 15 minutes: 3 ppm. OELV 15 minutes: 12.6 mg/m<sup>3</sup>.

Date of issue/Date of revision : 04/02/2025 Version : 2 7/25 : 03/12/2025 Date of previous issue Label No : 1/37054

TEKNOLUX AQUA 1728-62 - BEIGE 13

**T**riethylamine

**T**riethylamine

**T**riethylamine

Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 9/2024)

Absorbed through skin. Limit value 8 hours: 2 ppm. Limit value 8 hours: 8.4 mg/m<sup>3</sup>. Short Term 15 minutes: 3 ppm. Short Term 15 minutes: 12.6 mg/m<sup>3</sup>.

riethylamine

Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024)

STEL 15 minutes: 3 ppm. TWA 8 hours: 8.4 mg/m<sup>3</sup>. STEL 15 minutes: 12.6 mg/m<sup>3</sup>.

TWA 8 hours: 2 ppm.

riethylamine

Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024)

Absorbed through skin. TWA 8 hours: 8.4 mg/m<sup>3</sup>. TWA 8 hours: 2 ppm.

STEL 15 minutes: 12.6 mg/m<sup>3</sup>. STEL 15 minutes: 3 ppm.

riethylamine

Grand-Duchy Regulation 2016. Chemical agents. Annex I

(Luxembourg, 3/2021) Absorbed through skin.

TWA 8 hours: 2 ppm. TWA 8 hours: 8.4 mg/m<sup>3</sup>. STEL 15 minutes: 3 ppm. STEL 15 minutes: 12.6 mg/m<sup>3</sup>.

**T**riethylamine

EU OEL (Europe, 1/2022) Absorbed through skin.

TWA 8 hours: 2 ppm. TWA 8 hours: 8.4 mg/m<sup>3</sup>. STEL 15 minutes: 3 ppm. STEL 15 minutes: 12.6 mg/m<sup>3</sup>.

riethylamine

Ministry of Social Affairs and Employment, Legal limit values

(Netherlands, 5/2024) Absorbed through skin.

TWA 8 hours: 4.2 mg/m<sup>3</sup>. STEL 15 minutes: 12.6 mg/m<sup>3</sup>. STEL 15 minutes: 3 ppm. TWA 8 hours: 1 ppm.

**T**riethylamine

FOR-2011-12-06-1358 (Norway, 5/2024) Absorbed through skin.

TWA 8 hours: 2 ppm. TWA 8 hours: 8 mg/m<sup>3</sup>.

riethylamine

Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland,

7/2024) Absorbed through skin. TWA 8 hours: 3 mg/m<sup>3</sup>. STEL 15 minutes: 9 mg/m<sup>3</sup>.

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024) Absorbed through skin.

TWA 8 hours: 0.2 mg/m<sup>3</sup>. STEL 15 minutes: 0.4 mg/m<sup>3</sup>.

**T**riethylamine

Portuguese Institute of Quality (Portugal, 11/2014) A4.

Absorbed through skin. TWA 8 hours: 1 ppm. STEL 15 minutes: 3 ppm.

Decree-Law 24/2012 - Occupational exposure limits for chemical agents (Portugal, 6/2021) Absorbed through skin.

STEL 15 minutes: 3 ppm. STEL 15 minutes: 12.6 mg/m<sup>3</sup>.

TWA 8 hours: 2 ppm.

Date of issue/Date of revision : 04/02/2025 Version : 2 8/25 : 03/12/2025 Date of previous issue Label No : 1/37054

TWA 8 hours: 8.4 mg/m<sup>3</sup>. riethylamine HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024) Absorbed through skin. VLA 8 hours: 8.4 mg/m<sup>3</sup>. VLA 8 hours: 2 ppm. Short term 15 minutes: 12.6 mg/m<sup>3</sup>. Short term 15 minutes: 3 ppm. riethylamine Government regulation SR c. 355/2006 (Slovakia, 6/2024) Absorbed through skin, Inhalation sensitiser. TWA 8 hours: 8.4 ma/m<sup>3</sup>. TWA 8 hours: 2 ppm. STEL 15 minutes: 12.6 mg/m<sup>3</sup>. STEL 15 minutes: 3 ppm. **T**riethylamine Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024) Absorbed through skin. TWA 8 hours: 8.4 mg/m<sup>3</sup>. TWA 8 hours: 2 ppm. KTV 15 minutes: 12.6 mg/m<sup>3</sup> 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes]. KTV 15 minutes: 3 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes]. riethylamine National institute of occupational safety and health (Spain, 1/2024) Absorbed through skin. TWA 8 hours: 2 ppm. TWA 8 hours: 8.4 mg/m<sup>3</sup>. STEL 15 minutes: 3 ppm. STEL 15 minutes: 12.6 mg/m<sup>3</sup>. **T**riethylamine Work environment authority Regulation 2018:1 (Sweden, 11/2022) Absorbed through skin. TWA 8 hours: 1 ppm. TWA 8 hours: 4.2 mg/m<sup>3</sup>. STEL 15 minutes: 3 ppm. STEL 15 minutes: 12.6 mg/m<sup>3</sup>. riethylamine SUVA (Switzerland, 1/2025) TWA 8 hours: 1 ppm. TWA 8 hours: 4.2 mg/m<sup>3</sup>. STEL 15 minutes: 2 ppm. STEL 15 minutes: 8.4 mg/m<sup>3</sup>. SUVA (Switzerland, 1/2025) Sensitiser. reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and STEL 15 minutes: 0.4 mg/m<sup>3</sup>. Form: Inhalable fraction. 2-methyl-2H-isothiazol-3-one [EC no. TWA 8 hours: 0.2 mg/m<sup>3</sup>. Form: Inhalable fraction. 220-239-6] (3:1) riethylamine EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin. STEL 15 minutes: 17 mg/m<sup>3</sup>. TWA 8 hours: 2 ppm. TWA 8 hours: 8 mg/m<sup>3</sup>. STEL 15 minutes: 4 ppm.

#### **Biological exposure indices**

Product/ingredient name	Exposure indices
No exposure indices known.	

 Date of issue/Date of revision
 : 03/12/2025
 Date of previous issue
 : 04/02/2025
 Version
 : 2
 9/25

 TEKNOLUX AQUA 1728-62 - BEIGE 13
 Label No : ₹37054

## SECTION 8: Exposure controls/personal protection No exposure indices known. No exposure indices known.

## Recommended monitoring procedures

No exposure indices known.

: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

Product/ingredient name

2-Butoxyethanol

#### Result

DNEL - General population - Long term - Oral

2.5 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Dermal

3.1 mg/kg bw/day Effects: Systemic

**DNEL - Workers - Long term - Dermal** 

6.25 mg/kg bw/day Effects: Systemic

**DNEL - General population - Long term - Inhalation** 40 mg/m<sup>3</sup>

Date of issue/Date of revision : 03/12/2025 Date of previous issue : 04/02/2025 Version : 2 10/25

TEKNOLUX AQUA 1728-62 - BEIGE 13

**Label No** : 1/37054

Effects: Systemic

**DNEL - Workers - Long term - Inhalation** 

80 mg/m<sup>3</sup>

Effects: Systemic

ethyl phenyl(2,4,6-trimethylbenzoyl) phosphinate

Triethylamine

**DNEL - General population - Long term - Oral** 0.5 mg/kg bw/day

Effects: Systemic

**DNEL - General population - Long term - Dermal** 

0.5 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Inhalation

0.87 mg/m³ Effects: Systemic

**DNEL - Workers - Long term - Dermal** 

1.4 mg/kg bw/day Effects: Systemic

**DNEL - Workers - Long term - Inhalation** 

4.93 mg/m³ Effects: Systemic

**DNEL - Workers - Long term - Inhalation** 

8.4 mg/m³ Effects: Local

**DNEL - Workers - Long term - Inhalation** 

8.4 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Short term - Inhalation** 

12.6 mg/m³ Effects: Local

**DNEL - Workers - Short term - Inhalation** 

12.6 mg/m³ Effects: Systemic

**DNEL - Workers - Long term - Dermal** 

12.1 mg/kg bw/day Effects: Systemic

**DNEL - General population - Long term - Inhalation** 

0.021 mg/m³ Effects: Local

**DNEL - Workers - Long term - Inhalation** 

0.021 mg/m³ Effects: Local

DNEL - General population - Long term - Oral

0.027 mg/kg bw/day Effects: Systemic

DNEL - General population - Short term - Inhalation

0.043 mg/m³ Effects: Local

**DNEL - Workers - Short term - Inhalation** 

0.043 mg/m<sup>3</sup>

Date of issue/Date of revision : 03/12/2025 Date of previous issue : 04/02/2025 Version : 2 11/25

TEKNOLUX AQUA 1728-62 - BEIGE 13

2-methyl-2H-isothiazol-3-one

Label No : 1/37054

Effects: Local

DNEL - General population - Short term - Oral

0.053 mg/kg bw/day Effects: Systemic

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

DNEL - General population - Long term - Inhalation

0.02 ma/m<sup>3</sup> Effects: Local

**DNEL - Workers - Long term - Inhalation** 

0.02 mg/m<sup>3</sup> Effects: Local

DNEL - General population - Short term - Inhalation

0.04 mg/m<sup>3</sup> Effects: Local

**DNEL - Workers - Short term - Inhalation** 

0.04 mg/m<sup>3</sup> Effects: Local

DNEL - General population - Long term - Oral

0.09 mg/kg bw/day Effects: Systemic

DNEL - General population - Short term - Oral

0.11 mg/kg bw/day Effects: Systemic

#### **PNECs**

Not available.

#### 8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### Individual protection measures

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** 

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists. gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

### **Skin protection Hand protection**

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of

several substances, the protection time of the gloves cannot be accurately

estimated.

Recommendations: Wear suitable gloves tested to EN374.

< 1 hour (breakthrough time):

Nitrile gloves. thickness > 0.3 mm

Date of issue/Date of revision : 04/02/2025 : 03/12/2025 Date of previous issue TEKNOLUX AQUA 1728-62 - BEIGE 13

Version : 2 Label No : 1/37054

12/25

1 - 4 hours (breakthrough time): 4H / Silver Shield® gloves.

Personal protective equipment for the body should be selected based on the task **Body protection** being performed and the risks involved and should be approved by a specialist

before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

: Based on the hazard and potential for exposure, select a respirator that meets the Respiratory protection

appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important

aspects of use.

Filter type (spray application):

**Environmental exposure** 

controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

#### **Appearance**

**Physical state** : Liquid. Colour Beige. **Odour** : Slight

**Odour threshold** Not available. Melting point/freezing point : Not available.

Initial boiling point and

boiling range

Ingredient name	°C	°F	Method
water	100	212	
2-Butoxyethanol	173	343.4	

**Flammability** : Not available.

Lower and upper explosion Lower: Not applicable. Upper: Not applicable. limit

Flash point : Closed cup: >100°C (>212°F)

**Auto-ignition temperature** 

Ingredient name	°C	°F	Method
2-Butoxyethanol	395	743	
ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate	423	793.4	DIN EN 14522

**Decomposition temperature** : Not available.

: 7.5 to 8.5 [Conc. (% w/w): 100%] Ha

**Viscosity** Not available.

Solubility(ies)

Not available.

: Not available. Solubility in water Partition coefficient: n-octanol/ : Not applicable.

water

Vapour pressure

Version : 2 Date of issue/Date of revision · 04/02/2025 13/25 : 03/12/2025 Date of previous issue Label No : 1/37054

## SECTION 9: Physical and chemical properties

	Vapour Pressure at 20°C			Vapour pressure at 50°C			
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
water	17.5	2.3					
2-Butoxyethanol	0.35	0.047					

**Relative density** : Not available. **Density** : 1.1 g/cm<sup>3</sup> Vapour density : Not available.

**Particle characteristics** 

Median particle size : Not applicable.

#### 9.2 Other information

9.2.1 Information with regard to physical hazard classes

**Explosive properties** : Not available. **Oxidising properties** : Not available.

9.2.2 Other safety characteristics

Not applicable.

### SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute toxicity** 

Product/ingredient name Result

**T**riethylamine Rat - Oral - LD50

460 mg/kg

2-methyl-2H-isothiazol-3-one Rat - Inhalation - LC50 Dusts and mists

0.11 mg/l [4 hours]

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and

2-methyl-2H-isothiazol-3-one [EC no.

220-239-6] (3:1)

Rat - Oral - LD50

53 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration -

Respiratory depression

**Conclusion/Summary [Product]**: Not available.

**Acute toxicity estimates** 

Date of issue/Date of revision : 04/02/2025 Version : 2 14/25 : 03/12/2025 Date of previous issue Label No : 1/37054

## **SECTION 11: Toxicological information**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
FEKNOLUX AQUA 1728-62	45344.5	136033.6	N/A	3264.8	N/A
Triethylamine	100	300	N/A	7.2	N/A
2-methyl-2H-isothiazol-3-one	100	300	N/A	N/A	0.11
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	53	50	N/A	0.5	N/A

#### Skin corrosion/irritation

Product/ingredient name

riethylamine

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Result

Rabbit - Skin - Mild irritant

Amount/concentration applied: 365 mg

Human - Skin - Severe irritant Amount/concentration applied: 0.01 %

Conclusion/Summary [Product] : Not available.

#### Serious eye damage/eye irritation

Not available.

**Conclusion/Summary [Product]**: Not available.

#### **Respiratory corrosion/irritation**

Not available.

Conclusion/Summary [Product] : Not available.

#### **Respiratory or skin sensitization**

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

**Conclusion/Summary [Product]**: Not available.

#### Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

#### Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

#### **Reproductive toxicity**

Not available.

Date of issue/Date of revision : 03/12/2025 : 04/02/2025 Version : 2 15/25 Date of previous issue Label No : 1/37054

### SECTION 11: Toxicological information

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name Result

Triethylamine STOT SE 3, H335 (Respiratory tract irritation)

Specific target organ toxicity (repeated exposure)

Not available.

**Aspiration hazard** 

Not available.

Information on likely routes of exposure

Not available.

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact**: May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion**: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

**Long term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

**Conclusion/Summary [Product]**: Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]**: The product does not meet the criteria to be considered as having endocrine

disrupting properties according to the criteria set out in either Regulation (EC)

Label No : 1/37054

No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

Date of issue/Date of revision: 03/12/2025Date of previous issue: 04/02/2025Version: 216/25

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### Product/ingredient name

2-methyl-2H-isothiazol-3-one

#### **Result**

Acute - EC50 - Fresh water

**US EPA** 

Daphnia - Water flea - Daphnia magna

Age: <24 hours 0.18 ppm [48 hours] Effect: Intoxication

Acute - LC50 - Fresh water

US EPA

Fish - Rainbow trout, donaldson trout - Oncorhynchus mykiss

Weight: 0.73 g 0.07 ppm [96 hours] Effect: Mortality

**Conclusion/Summary [Product]**: Not available.

#### 12.2 Persistence and degradability

Not available.

Conclusion/Summary [Product] : Not available.

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
riethylamine	1.45	<0.5 [OECD 305 C]	Low

#### 12.4 Mobility in soil

#### Soil/water partition coefficient

Product/ingredient name	logKoc	Koc
Z-Butoxyethanol Triethylamine 2-methyl-2H-isothiazol-3-one	1.2 1.9 1.7	17.4169 76.4134 54.9187

#### Results of PMT and vPvM assessment

Product/ingredient name	PMT	Р	M	Т	vPvM	νP	vM
2-Propenoic acid, reaction products with dipentaerythritol	No	No	No	No	No	No	No
2-Butoxyethanol	No	No	No	No	No	No	No
ethyl phenyl (2,4,6-trimethylbenzoyl) phosphinate	No	No	No	No	No	No	No
Triethylamine	No	No	No	No	No	No	No
2-methyl-2H-isothiazol-3-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No

Mobility : Not available.

**Conclusion/Summary** : The product does not meet the criteria to be considered as a PMT or vPvM.

## 12.5 Results of PBT and vPvB assessment Regulation (EC) No. 1907/2006 [REACH]

 Date of issue/Date of revision
 : 03/12/2025
 Date of previous issue
 : 04/02/2025
 Version
 : 2
 17/25

 TEKNOLUX AQUA 1728-62 - BEIGE 13
 Label No : 1/37054

## **SECTION 12: Ecological information**

Product/ingredient name	PBT	P	В	T	vPvB	vP	vB
Propenoic acid, reaction products with dipentaerythritol	No	N/A	N/A	No	N/A	N/A	N/A
2-Butoxyethanol	No	N/A	N/A	No	N/A	N/A	N/A
ethyl phenyl (2,4,6-trimethylbenzoyl) phosphinate	No	N/A	N/A	No	N/A	N/A	N/A
Triethylamine	No	N/A	No	No	No	N/A	No
2-methyl-2H-isothiazol-3-one	No	N/A	N/A	No	N/A	N/A	N/A
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	N/A	N/A	No	N/A	N/A	N/A

#### Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	Р	В	Т	vPvB	vP	vB
2-Propenoic acid, reaction products with dipentaerythritol	No	No	No	No	No	No	No
2-Butoxyethanol	No	No	No	No	No	No	No
ethyl phenyl	No	No	No	No	No	No	No
(2,4,6-trimethylbenzoyl)							
phosphinate							
Triethylamine	No	No	No	No	No	No	No
2-methyl-2H-isothiazol-3-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro-	No	No	No	No	No	No	No
2-methyl-4-isothiazolin-							
3-one [EC no. 247-500-7]							
and 2-methyl-2H-isothiazol-							
3-one [EC no. 220-239-6] (3:							
1)							

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP] : The product does not meet the criteria to be considered as a PBT or vPvB.

#### 12.6 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** 

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

**Product** 

**Methods of disposal** 

: Avoid release to the environment. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Dispose of contents and container in accordance with all local, regional, national and international regulations.

: The classification of the product may meet the criteria for a hazardous waste.

Hazardous waste European waste

: 080112

catalogue (EWC)

**Packaging** 

 Date of issue/Date of revision
 : 03/12/2025
 Date of previous issue
 : 04/02/2025
 Version
 : 2
 18/25

 TEKNOLUX AQUA 1728-62 - BEIGE 13
 Label No : \$\frac{1}{3}\$7054

## **SECTION 13: Disposal considerations**

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** 

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

14.6 Special precautions for

: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not relevant/applicable due to nature of the product.

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed.

Substances of very high concern

None of the components are listed.

## Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
TEKNOLUX AQUA 1728-62	≥90	3

Labelling

**Synthetic polymer microparticles - Designation 78** 

Generic identity of polymer(s)

: 3901 - Polymers of ethylene., 3906 - Acrylic polymers.

Total percentage of synthetic polymer microparticles

**4**.4%

Date of issue/Date of revision : 03/12/2025 Date of previous issue : 04/02/2025 Version : 2 19/25

Label No : 1/37054

## **SECTION 15: Regulatory information**

The synthetic polymer microparticles supplied is subject to conditions laid down by entry 78 of Annex XVII to Regulation (EC) No 1907/2006 of the European Parliament and of the Council.

#### Other EU regulations

Industrial emissions

(integrated pollution prevention and control) -

Air

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Water

Explosive precursors : Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

**Persistent Organic Pollutants** 

Not listed.

**Seveso Directive** 

This product is not controlled under the Seveso Directive.

**National regulations** 

**Austria** 

Limitation of the use of

: Permitted.

: Not listed

organic solvents

**Belgium** 

Book VI carcinogenic agents annex VI.2-1 - VI.2-3

Ingredient name	Status
<b>M</b> oirs de charbon	Listed

**Czech Republic** 

Storage code : IV

**Denmark** 

Fire class : IV-1 Executive Order No. 1795/2015

Ingredient name	Annex I Section A	Annex I Section B
Manium dioxide	Listed	-
carbon black respirable	Listed	_

MAL-code : 2-5

**Protection based on MAL** 

According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:

**General:** Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

Label No : 1/37054

Date of issue/Date of revision: 03/12/2025Date of previous issue: 04/02/2025Version: 220/25

## SECTION 15: Regulatory information

MAL-code: 2-5

Application: When using scraper or knife, brush, roller etc. for pre- and posttreatments in a spray booth where the operator is outside the spray zone and when working in similar new\* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. When spraying in new\* booths and cabins with non-atomizing guns.

Protective clothing must be worn.

When using scraper or knife, brush, roller, etc, for pre- and post-treatments in cabins or booths of the existing\* facility type, if the operator is inside the spray zone. When using scraper or knife, brush, roller, etc. for pre- and post-treatments outside a closed facility, spray booth or spray cabin.

- Gas filter mask and protective clothing must be worn.

When spraying in existing\* spray booths, if the operator is outside the spray zone.

- Air-supplied full mask and protective clothing must be worn.

During non-atomising spraying in existing\* facilities of the combined-cabin, spraycabin and spray-booth type where the operator is working inside the spray zone. During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents.

- Air-supplied half mask, protective clothing and eye protection must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Air-supplied full mask, protective clothing and hood must be worn.

Drying: Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

**Polishing:** When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

**Caution** The regulations contain other stipulations in addition to the above.

\*See Regulations.

Restrictions on use

: Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.

List of undesirable substances

: Not listed

Carcinogenic waste

: Waste containers must be labeled: Contains a substance or substances regulated by Danish working environment legislation on cancer risks.

**Finland France** 

Social Security Code, Articles L 461-1 to L 461-7 : Triethylamine RG 49, RG 49bis

Reinforced medical surveillance

: Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable

**Germany** 

Storage class (TRGS 510) : 10 **Hazardous incident ordinance** 

Date of issue/Date of revision · 04/02/2025 Version : 2 21/25 : 03/12/2025 Date of previous issue Label No : 1/37054

## **SECTION 15: Regulatory information**

This product is not controlled under the Germany Hazardous Incident Ordinance.

**Hazard class for water** : 2

Technical instruction on air quality control (TA Luft)

Number [Class]	Description	%
5.2.1	Total dust	31.8
5.2.5	Organic substances	9
5.2.5 [I]	Organic substances	1.6

**AOX** 

: The product contains organically bound halogens and can contribute to the AOX value in waste water.

Italy

D.Lgs. 152/06 : Not determined.

**Netherlands** 

Ministry of Social Affairs and Employment (SZW) - Carcinogenic substances and processes, mutagenic or reprotoxic substances

Ingredient name	Carcinogen	Mutagen	Reproductive toxicity - Fertility	Reproductive toxicity - Development	Harmful via breastfeeding
ethanol (complexe) aardolie- en steenkoolderivaten EG nrs. beginnend met 232, 263, 265-275, 277, 278, 283-285, 287, 289, 291-298, 300, 302, 305-310	Listed Listed	-	Fertility 1A	Development 1A	Listed -

**Water Discharge Policy** 

(ABM)

: Z(1) Non biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/ reprotoxicity/ bioacumulative potential/ toxicity or persistence). Decontamination effort: Z

**Norway** 

**Sweden** 

**Switzerland** 

**VOC** content : Exempt.

**International regulations** 

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

**Montreal Protocol** 

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

**Rotterdam Convention on Prior Informed Consent (PIC)** 

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

Date of issue/Date of revision : 03/12/2025 : 04/02/2025 Version : 2 22/25 Date of previous issue Label No : 1/37054

#### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

**Abbreviations and** acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Sens. 1, H317 Aquatic Chronic 3, H412	Calculation method Calculation method

#### Full text of abbreviated H statements

<b>⊮</b> 225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

#### Full text of classifications [CLP/GHS]

Cute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Skin Corr. 1A	SKIN CORROSION/IRRITATION - Category 1A
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
1	

Date of issue/ Date of

revision

: 03/12/2025

Date of previous issue : 04/02/2025

Version : 2

**Notice to reader** 

Date of issue/Date of revision : 03/12/2025 : 04/02/2025 Version : 2 23/25 Date of previous issue Label No : 1/37054

### **SECTION 16: Other information**

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision: 03/12/2025Date of previous issue: 04/02/2025Version: 224/25

Date of issue/Date of revision: 03/12/2025Date of previous issue: 04/02/2025Version: 225/25

**Label No** : 1/37054