# **SAFETY DATA SHEET**



### TEKNOLUX AQUA TOPCOAT 1908-15 - All variants

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : TEKNOLUX AQUA TOPCOAT 1908-15 - All variants

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS

: Prod-safe@teknos.com

**National contact** 

Teknos Ireland Limited, 52 Ballymoughan Road, Magherafelt, BT45 6HN, UK. Tel. +44 (0) 2879 301 472.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : NHS: 111

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

**Product definition**: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word : Warning

**Hazard statements** : H317 - May cause an allergic skin reaction.

**Precautionary statements** 

Prevention : P280 - Wear protective gloves.

P261 - Avoid breathing vapour.

Response : P302 + P352 - IF ON SKIN: Wash with plenty of water.

P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P362 + P364 - Take off contaminated clothing and wash it before reuse.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

**Hazardous ingredients** : Contains: 2-Propenoic acid, reaction products with dipentaerythritol; Phosphine

oxide, phenylbis(2,4,6-trimethylbenzoyl)-; Propylidynetrimethanol, ethoxylated,

Label No : 98563

esters with acrylic acid and 1,2-benzisothiazol-3(2H)-one

Date of issue/Date of revision : 13/05/2025 Date of previous issue : 09/01/2024 Version : 1.01 1/21

### **SECTION 2: Hazards identification**

Supplemental label elements

**Annex XVII - Restrictions** on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles



#### 2.3 Other hazards

**Product meets the criteria** for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Crylated Polyurethane	-	≤5	Aquatic Chronic 3, H412	-	[1]
2-Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	≤3	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	ATE [Oral] = 1200 mg/kg ATE [Inhalation (vapours)] = 3 mg/l	[1] [2]
2-Propenoic acid, reaction products with dipentaerythritol	REACH #: 01-2119980666-22 CAS: 1384855-91-7	≤3	Eye Irrit. 2, H319 Skin Sens. 1A, H317 Aquatic Chronic 3, H412	-	[1]
hydroxycyclohexyl phenyl ketone	REACH #: 01-2119457404-40 EC: 213-426-9 CAS: 947-19-3	≤3	Aquatic Chronic 3, H412	-	[1]
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	REACH #: 01-2119489401-38 EC: 423-340-5 CAS: 162881-26-7 Index: 015-189-00-5	≤0.3	Skin Sens. 1A, H317 Aquatic Chronic 4, H413	-	[1]
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	REACH #: 01-2119489900-30 EC: 500-066-5 CAS: 28961-43-5	≤0.3	Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412	-	[1]
Triethylamine	REACH #: 01-2119475467-26 EC: 204-469-4 CAS: 121-44-8 Index: 612-004-00-5	≤0.3	Flam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335	ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (vapours)] = 7.2 mg/l STOT SE 3, H335: C ≥ 1%	[1] [2]
1,2-benzisothiazol-3(2H)-	EC: 220-120-9	<0.036	Acute Tox. 4, H302	ATE [Oral] = 450	[1]

: 09/01/2024 Date of issue/Date of revision : 13/05/2025 Date of previous issue Version : 1.01 2/21 Label No : 98563

# **SECTION 3: Composition/information on ingredients**

-			<u> </u>		
one	CAS: 2634-33-5 Index: 613-088-00-6		Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	mg/kg ATE [Inhalation (dusts and mists)] = 0.21 mg/l Skin Sens. 1, H317: C ≥ 0.036% M [Acute] = 1 M [Chronic] = 1	
sodium pyrithione	EC: 223-296-5 CAS: 3811-73-2	<0.1	Acute Tox. 4, H302 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 2, H411 EUH070	ATE [Oral] = 500 mg/kg ATE [Dermal] = 790 mg/kg ATE [Inhalation (dusts and mists)] = 0.5 mg/l M [Acute] = 100	[1]
2-methyl-2H-isothiazol- 3-one	EC: 220-239-6 CAS: 2682-20-4 Index: 613-326-00-9	<0.0015	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071  See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (dusts and mists)] = 0.11 mg/l Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 10 M [Chronic] = 1	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

#### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

**Eye contact** 

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Date of issue/Date of revision : 13/05/2025 . 09/01/2024 Version : 1.01 3/21 Date of previous issue **Label No** : 98563

#### **SECTION 4: First aid measures**

#### Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### **Protection of first-aiders**

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear aloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

**Eye contact** : No specific data. Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

> irritation redness

Ingestion : No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

: No specific treatment. **Specific treatments** 

### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** 

media

: None known.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst.

**Hazardous combustion** products

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide metal oxide/oxides

#### 5.3 Advice for firefighters

**Special protective actions** for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective** equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Version : 1.01 4/21 Date of issue/Date of revision . 09/01/2024 : 13/05/2025 Date of previous issue Label No : 98563

#### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

#### **6.2 Environmental** precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### 6.3 Methods and material for containment and cleaning up

#### **Small spill**

: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

#### Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

#### 6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

### SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

#### **Protective measures**

: Fut on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

#### **Advice on general** occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### 7.3 Specific end use(s)

solutions

Recommendations : Not available. **Industrial sector specific** : Not available.

Version : 1.01 5/21 Date of issue/Date of revision : 13/05/2025 Date of previous issue . 09/01/2024

TEKNOLUX AQUA TOPCOAT 1908-15 - All variants

Label No : 98563

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

#### **Occupational exposure limits**

Product/ingredient name	Exposure limit values
Z-Butoxyethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin.  STEL 15 minutes: 50 ppm.  TWA 8 hours: 25 ppm.  STEL 15 minutes: 246 mg/m³.  TWA 8 hours: 123 mg/m³.
Triethylamine	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin.  STEL 15 minutes: 17 mg/m³.  TWA 8 hours: 2 ppm.  TWA 8 hours: 8 mg/m³.  STEL 15 minutes: 4 ppm.

#### **Biological exposure indices**

Product/ingredient name	Exposure indices
<b>2</b> -Butoxyethanol	EH40/2005 BMGVs (United Kingdom (UK), 1/2020) BGV: 240 mmol/mol creatinine, butoxyacetic acid [in urine]. Sampling time: post shift.

# Recommended monitoring procedures

: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

Product/ingredient name

2-Butoxyethanol

#### Result

DNEL - General population - Long term - Oral

6.3 mg/kg bw/day Effects: Systemic

DNEL - General population - Short term - Oral

26.7 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Long term - Inhalation

59 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Long term - Inhalation** 

98 mg/m<sup>3</sup>

Effects: Systemic

DNEL - General population - Short term - Inhalation

147 mg/m³ <u>Effects</u>: Local

**DNEL - Workers - Short term - Inhalation** 

246 mg/m³ <u>Effects</u>: Local

DNEL - General population - Short term - Inhalation

Date of issue/Date of revision: 13/05/2025Date of previous issue: 09/01/2024Version: 1.016/21TEKNOLUX AQUA TOPCOAT 1908-15 - All variantsLabel No : 98563

426 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Short term - Inhalation** 

1091 mg/m³ Effects: Systemic

hydroxycyclohexyl phenyl ketone

Phosphine oxide, phenylbis

(2,4,6-trimethylbenzoyl)-

DNEL - General population - Long term - Oral

0.694 mg/kg bw/day Effects: Systemic

**DNEL - General population - Long term - Dermal** 

0.694 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Inhalation

1.21 mg/m³ Effects: Systemic

**DNEL - Workers - Long term - Dermal** 

1.94 mg/kg bw/day Effects: Systemic

**DNEL - Workers - Long term - Inhalation** 

6.8 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Long term - Inhalation** 

21 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Short term - Inhalation** 

21 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Long term - Dermal** 

3.3 mg/kg

Effects: Systemic

**DNEL - Workers - Short term - Dermal** 

3.3 mg/kg

Effects: Systemic

DNEL - General population - Consumers - Long term -

Inhalation 5.2 mg/m<sup>3</sup>

Effects: Systemic

DNEL - General population - Consumers - Long term -

Dermal

1.5 mg/kg

Effects: Systemic

DNEL - General population - Consumers - Long term - Oral

1.5 mg/kg

Effects: Systemic

DNEL - General population - Short term - Oral

1.67 ng/kg bw/day Effects: Systemic

DNEL - General population - Long term - Oral

1.5 mg/kg bw/day <u>Effects</u>: Systemic

**DNEL - General population - Long term - Dermal** 

Date of issue/Date of revision

: 13/05/2025 Date of previous issue

: 09/01/2024

Version : 1.01 7/21

TEKNOLUX AQUA TOPCOAT 1908-15 - All variants

Label No : 98563

1.5 mg/kg bw/day Effects: Systemic

#### DNEL - General population - Short term - Dermal

1.67 mg/kg bw/day Effects: Systemic

### **DNEL - General population - Short term - Inhalation**

1.93 mg/m³ Effects: Systemic

#### DNEL - General population - Long term - Inhalation

1.93 mg/m³ Effects: Systemic

#### **DNEL - Workers - Long term - Dermal**

3 mg/kg bw/day Effects: Systemic

#### **DNEL - Workers - Short term - Dermal**

3.33 mg/kg bw/day Effects: Systemic

#### **DNEL - Workers - Short term - Inhalation**

7.84 mg/m³ Effects: Systemic

#### **DNEL - Workers - Long term - Inhalation**

7.84 mg/m³ Effects: Systemic

Propylidynetrimethanol, ethoxylated, esters with acrylic acid

#### **DNEL - Workers - Long term - Dermal**

10.5 mg/kg bw/day Effects: Systemic

#### **DNEL - Workers - Long term - Inhalation**

37 mg/m³ Effects: Systemic

Triethylamine

#### **DNEL - Workers - Long term - Inhalation**

8.4 mg/m³ Effects: Local

#### **DNEL - Workers - Long term - Inhalation**

8.4 mg/m<sup>3</sup>

Effects: Systemic

#### **DNEL - Workers - Short term - Inhalation**

12.6 mg/m³ Effects: Local

#### DNEL - Workers - Short term - Inhalation

12.6 mg/m³
<u>Effects</u>: Systemic

#### DNEL - Workers - Long term - Dermal

12.1 mg/kg bw/day Effects: Systemic

1,2-benzisothiazol-3(2H)-one

### DNEL - General population - Long term - Dermal

0.345 mg/kg bw/day <u>Effects</u>: Systemic

#### **DNEL - Workers - Long term - Dermal**

0.966 mg/kg bw/day Effects: Systemic

**Date of issue/Date of revision** : 13/05/2025 **Date of TEKNOLUX AQUA TOPCOAT** 1908-15 - All variants

: 13/05/2025 Date of previous issue

: 09/01/2024

Version : 1.01 8/21

**Label No** : 98563

DNEL - General population - Long term - Inhalation

1.2 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Long term - Inhalation** 

6.81 mg/m³ Effects: Systemic

2-methyl-2H-isothiazol-3-one

DNEL - General population - Long term - Inhalation

0.021 mg/m³ Effects: Local

**DNEL - Workers - Long term - Inhalation** 

0.021 mg/m³ Effects: Local

DNEL - General population - Long term - Oral

0.027 mg/kg bw/day Effects: Systemic

DNEL - General population - Short term - Inhalation

0.043 mg/m³ Effects: Local

**DNEL - Workers - Short term - Inhalation** 

0.043 mg/m³ Effects: Local

DNEL - General population - Short term - Oral

0.053 mg/kg bw/day Effects: Systemic

#### **PNECs**

Not available.

#### 8.2 Exposure controls

Appropriate engineering controls

: Sood general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### Individual protection measures

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** 

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

# Skin protection

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations: Wear suitable gloves tested to EN374.

Date of issue/Date of revision

: 13/05/2025 Date of previous issue

**Label No** : **9**8563

> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm polyvinyl alcohol (PVA) gloves Not recommended

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type (spray application):

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

#### **Appearance**

**Physical state** : Liquid. Colour : Various **Odour** : Slight

Not available. **Odour threshold** Melting point/freezing point : Not available.

Initial boiling point and

boiling range

Ingredient name	°C	°F	Method
water varieties and the second	100	212	
2-Butoxyethanol	171 to 171.5	339.8 to 340.7	IP 123-93

Lower: 2.6% (propane-1,2-diol)

**Flammability** : Not available.

Lower and upper explosion

Upper: 12.6% (propane-1,2-diol) limit

: Closed cup: >100°C (>212°F) Flash point

**Auto-ignition temperature** 

Ingredient name	°C	°F	Method
Butoxyethanol	230	446	DIN 51794
Propylene glycol	371	699.8	

**Decomposition temperature** : Not available.

pН : 7.5 to 8.5 [Conc. (% w/w): 100%]

**Viscosity** Not available.

Solubility(ies)

Not available.

Solubility in water : Not available. Partition coefficient: n-octanol/ : Not applicable.

water

Vapour pressure

Version : 1.01 10/21 Date of issue/Date of revision : 13/05/2025 . 09/01/2024 Date of previous issue Label No: 98563

### SECTION 9: Physical and chemical properties

	Vapour Pressure at 20°C			Va	oour pressu	re at 50°C
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
water	17.5	2.3				
2-Butoxyethanol	0.75006	0.1				

**Relative density** : Not available. : 1.1 g/cm<sup>3</sup> **Density** : Not available. Vapour density

**Particle characteristics** 

Median particle size : Not applicable.

#### 9.2 Other information

9.2.1 Information with regard to physical hazard classes

**Explosive properties** : Not available. : Not available. **Oxidising properties** 

9.2.2 Other safety characteristics

Not applicable.

# **SECTION 10: Stability and reactivity**

: No specific test data related to reactivity available for this product or its ingredients. 10.1 Reactivity

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Product/ingredient name Result

Phosphine oxide, phenylbis Rat - Oral - LD50 (2,4,6-trimethylbenzoyl)->2000 mg/kg

**OECD** [Acute Oral Toxicity]

Propylidynetrimethanol, ethoxylated, esters Rabbit - Dermal - LD50

with acrylic acid >13 g/kg

Triethylamine Rat - Oral - LD50

460 mg/kg

1,2-benzisothiazol-3(2H)-one Rat - Oral - LD50

1020 mg/kg

2-methyl-2H-isothiazol-3-one Rat - Inhalation - LC50 Dusts and mists

0.11 mg/l [4 hours]

**Conclusion/Summary [Product]**: Not available.

Date of issue/Date of revision : 13/05/2025 . 09/01/2024 Version : 1.01 11/21 Date of previous issue Label No : 98563

### **SECTION 11: Toxicological information**

#### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
FEKNOLUX AQUA TOPCOAT 1908-15	25380.7	177514.8	N/A	108.3	N/A
2-Butoxyethanol	1200	N/A	N/A	3	N/A
Triethylamine	100	300	N/A	7.2	N/A
1,2-benzisothiazol-3(2H)-one	450	N/A	N/A	N/A	0.21
sodium pyrithione	500	790	N/A	N/A	0.5
2-methyl-2H-isothiazol-3-one	100	300	N/A	N/A	0.11

Result

**Skin corrosion/irritation** 

Product/ingredient name

2-Butoxyethanol Rabbit - Skin - Mild irritant

Amount/concentration applied: 500 mg

Propylidynetrimethanol, ethoxylated, esters

with acrylic acid

Rabbit - Skin - Moderate irritant Amount/concentration applied: 500 mg

Triethylamine Rabbit - Skin - Mild irritant

Amount/concentration applied: 365 mg

1,2-benzisothiazol-3(2H)-one Human - Skin - Mild irritant

> Duration of treatment/exposure: 48 hours Amount/concentration applied: 5 %

**Conclusion/Summary [Product]**: Not available.

Serious eye damage/eye irritation

Product/ingredient name

Result

Rabbit - Eyes - Moderate irritant

Duration of treatment/exposure: 24 hours Amount/concentration applied: 100 mg

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 100 mg

Propylidynetrimethanol, ethoxylated, esters

with acrylic acid

2-Butoxyethanol

Rabbit - Eyes - Moderate irritant

Amount/concentration applied: 100 mg

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Product/ingredient name Result

Guinea pig - skin Phosphine oxide, phenylbis

(2,4,6-trimethylbenzoyl)-OECD [Skin Sensitization]

Result: Sensitising

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Date of issue/Date of revision : 13/05/2025 Date of previous issue : 09/01/2024

TEKNOLUX AQUA TOPCOAT 1908-15 - All variants

Version : 1.01 12/21

**Label No** : 98563

### **SECTION 11: Toxicological information**

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Product/ingredient name

Phosphine oxide, phenylbis
(2,4,6-trimethylbenzoyl)
Result

Result: Negative

**Conclusion/Summary [Product]**: Not available.

**Carcinogenicity** 

Not available.

**Conclusion/Summary [Product]**: Not available.

Ingredient name Conclusion/Summary

Phosphine oxide, phenylbis
(2,4,6-trimethylbenzoyl)
Conclusion/Summary

No results available.

**Reproductive toxicity** 

Not available.

**Conclusion/Summary [Product]**: Not available.

**Specific target organ toxicity (single exposure)** 

Product/ingredient name Result

riethylamine STOT SE 3, H335 (Respiratory tract irritation)

Specific target organ toxicity (repeated exposure)

Product/ingredient name Result

sodium pyrithione STOT RE 1, H372

**Aspiration hazard** 

Not available.

Information on likely routes of exposure

Not available.

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact**: May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

**Long term exposure** 

Date of issue/Date of revision: 13/05/2025Date of previous issue: 09/01/2024Version: 1.0113/21

Label No : 98563

### **SECTION 11: Toxicological information**

Potential immediate

effects

: Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

**Conclusion/Summary [Product]** : Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

: No known significant effects or critical hazards. Carcinogenicity Mutagenicity : No known significant effects or critical hazards. : No known significant effects or critical hazards. Reproductive toxicity

#### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** 

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

#### 11.2.2 Other information

Not available.

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### Product/ingredient name

2-Butoxyethanol

#### Result

#### Acute - LC50 - Marine water

Fish - Inland silverside - Menidia beryllina

Size: 40 to 100 mm 1250000 µg/l [96 hours]

Effect: Mortality

#### Acute - LC50 - Marine water

Crustaceans - Common shrimp, sand shrimp - Crangon

crangon

800000 µg/l [48 hours]

Effect: Mortality

#### Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-

#### Acute - LC50

OECD [Fish. Acute Toxicity Test]

Fish - Brachydanio rerio >0.09 mg/l [96 hours]

#### Acute - EC50

Daphnia sp. Acute Immobilization Test and Reproduction Test Daphnia - Daphnia magna

Label No : 98563

>1.175 mg/l [48 hours]

#### EC50

Alga, Growth Inhibition Test

Aquatic plants - Desmodesmus subspicatus

≥0.26 mg/l [72 hours]

#### **NOEC - Fresh water**

OECD [Daphnia Magna Reproduction Test]

Daphnia - Daphnia magna ≥0.008 mg/l [21 days]

#### 1,2-benzisothiazol-3(2H)-one

Acute - LC50 - Fresh water

OECD [Fish. Acute Toxicity Test] Fish - Trout - Onorhynchus Mykiss

1.9 mg/l [96 hours]

Date of issue/Date of revision : 13/05/2025 Date of previous issue . 09/01/2024 Version : 1.01 14/21

### **SECTION 12: Ecological information**

Acute - EC50

OECD 202 [Daphnia sp. Acute Immobilization Test and

Reproduction Test]

Daphnia - Daphnia - Daphnia Magna

3.7 mg/l [48 hours]

Acute - EC50 - Marine water

OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - Skeletonema Costatum

0.36 mg/l [72 hours]

Acute - NOEC - Marine water

OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - Skeletonema Costatum

0.15 mg/l [72 hours]

2-methyl-2H-isothiazol-3-one

Acute - EC50 - Fresh water

**US EPA** 

Daphnia - Water flea - Daphnia magna

Age: <24 hours 0.18 ppm [48 hours] Effect: Intoxication

Acute - LC50 - Fresh water

**US EPA** 

Fish - Rainbow trout, donaldson trout - Oncorhynchus mykiss

Weight: 0.73 g 0.07 ppm [96 hours] Effect: Mortality

Conclusion/Summary [Product] : Mot available.

12.2 Persistence and degradability

**Product/ingredient name** Result 1,2-benzisothiazol-3(2H)-one EU

24% [28 days]

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	-	-	Not readily
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	-	-	Readily
1,2-benzisothiazol-3(2H)-one	-	-	Inherent

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-Butoxyethanol	0.81	-	Low
hydroxycyclohexyl phenyl ketone	2.81	4 to 12	Low
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	5.77	<5	Low
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	2.89	-	Low
Triethylamine 1,2-benzisothiazol-3(2H)-one	1.45	<0.5 3.2	Low Low

Date of issue/Date of revision : 13/05/2025 Date of previous issue : 09/01/2024 Version : 1.01 15/21 **Label No** : 98563

# **SECTION 12: Ecological information**

### 12.4 Mobility in soil

### Soil/water partition coefficient

Product/ingredient name	logKoc	Koc
<b>2</b> -Butoxyethanol	1.83	67.3685
hydroxycyclohexyl phenyl ketone	2.12	131.578
Phosphine oxide, phenylbis	5.04	108908
(2,4,6-trimethylbenzoyl)-		
Triethylamine	1.88	76.4134
1,2-benzisothiazol-3(2H)-one	1.86	73.142
sodium pyrithione	1.67	46.4942
2-methyl-2H-isothiazol-3-one	1.74	54.9187

### Results of PMT and vPvM assessment

Product/ingredient name	PMT	Р	M	Т	vPvM	vP	vM
Crylated Polyurethane	No	No	No	No	No	No	No
2-Butoxyethanol	No	No	No	No	No	No	No
2-Propenoic acid, reaction products with dipentaerythritol	No	No	No	No	No	No	No
hydroxycyclohexyl phenyl ketone	No	No	No	No	No	No	No
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	No	No	No	No	No	No	No
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	No	No	No	No	No	No	No
Triethylamine	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
sodium pyrithione	No	No	No	No	No	No	No
2-methyl-2H-isothiazol-3-one	No	No	No	No	No	No	No

Mobility

: Not available.

**Conclusion/Summary** 

: The product does not meet the criteria to be considered as a PMT or vPvM.

### 12.5 Results of PBT and vPvB assessment Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	Р	В	T	vPvB	νP	vB
Acrylated Polyurethane	No	No	No	No	No	No	No
2-Butoxyethanol	No	No	No	No	No	No	No
2-Propenoic acid, reaction products with dipentaerythritol	No	No	No	No	No	No	No
hydroxycyclohexyl phenyl ketone	No	No	No	No	No	No	No
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	No	No	No	No	No	No	No
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	No	No	No	No	No	No	No
Triethylamine	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
sodium pyrithione	No	No	No	No	No	No	No
2-methyl-2H-isothiazol-3-one	No	No	No	No	No	No	No

Regulation (EC) No. 1272/2008 [CLP]

Date of issue/Date of revision Version : 1.01 16/21 : 13/05/2025 Date of previous issue : 09/01/2024 Label No : 98563

### **SECTION 12: Ecological information**

Product/ingredient name	PBT	P	В	T	vPvB	νP	vB	
Acrylated Polyurethane	No	No	No	No	No	No	No	
2-Butoxyethanol	No	No	No	No	No	No	No	
2-Propenoic acid, reaction products with dipentaerythritol	No	No	No	No	No	No	No	
hydroxycyclohexyl phenyl ketone	No	No	No	No	No	No	No	
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	No	No	No	No	No	No	No	
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	No	No	No	No	No	No	No	
Triethylamine	No	No	No	No	No	No	No	
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No	
sodium pyrithione	No	No	No	No	No	No	No	
2-methyl-2H-isothiazol-3-one	No	No	No	No	No	No	No	

**Conclusion/Summary Regulation (EC) No. 1272/2008** [CLP]

: The product does not meet the criteria to be considered as a PBT or vPvB.

#### 12.6 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** 

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### **Product**

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**European waste** catalogue (EWC) : 08.01.19

**Packaging** 

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** 

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Date of issue/Date of revision : 13/05/2025 Date of previous issue . 09/01/2024 Version : 1.01 17/21 Label No : 98563

### **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	9006	Mot regulated.	Not regulated.
14.2 UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.		
14.3 Transport hazard class(es)	-	9		
14.4 Packing group	-	-		
14.5 Environmental hazards	No.	Yes.	₩o.	No.

#### **Additional information**

**ADN** 

: The product is only regulated as a dangerous good when transported in tank vessels.

**IATA** 

: The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user

: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not relevant/applicable due to nature of the product.

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed.

Substances of very high concern

None of the components are listed.

#### Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
FEKNOLUX AQUA TOPCOAT 1908-15	≥90	3

Labelling

Other EU regulations

**Industrial emissions** : Not listed

(integrated pollution prevention and control) -

Air

**Industrial emissions** : Not listed (integrated pollution

prevention and control) -

Water

Date of issue/Date of revision : 13/05/2025 . 09/01/2024 Version : 1.01 18/21 Date of previous issue Label No : 98563

### **SECTION 15: Regulatory information**

Explosive precursors : Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

**Persistent Organic Pollutants** 

Not listed.

**Seveso Directive** 

This product is not controlled under the Seveso Directive.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

**Montreal Protocol** 

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

**Rotterdam Convention on Prior Informed Consent (PIC)** 

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

#### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

**Abbreviations and** 

s and : ATE = Acute Toxicity Estimate

acronyms CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification		
Skin Sens. 1, H317	Calculation method		

#### Full text of abbreviated H statements

<b>⊬</b> 225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.

Date of issue/Date of revision : 13/05/2025 Date of previous issue : 09/01/2024 Version : 1.01 19/21

Label No : 98563

### **SECTION 16: Other information**

H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH070	Toxic by eye contact.
EUH071	Corrosive to the respiratory tract.

#### Full text of classifications [CLP/GHS]

Cute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Aquatic Chronic 4	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Skin Corr. 1A	SKIN CORROSION/IRRITATION - Category 1A
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of issue/ Date of : 13/05/2025

revision

Date of previous issue : 09/01/2024

Version : 1.01

#### **Notice to reader**

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision : 13/05/2025 Date of previous issue : 09/01/2024 Version : 1.01 20/21 **Label No** : 98563

: 09/01/2024 Version : 1.01 21/21 Date of issue/Date of revision : 13/05/2025 Date of previous issue **Label No :98**563