

# SAFETY DATA SHEET



TEKNOPOX AQUA COMBI 0360-04 - All variants

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : TEKNOPOX AQUA COMBI 0360-04 - All variants

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Paint.

### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

**e-mail address of person responsible for this SDS** : Prod-safe@teknos.com

#### National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

**Telephone number** : In an emergency, call 112

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315  
Eye Irrit. 2, H319  
Skin Sens. 1, H317  
Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Warning

**Hazard statements** : H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H412 - Harmful to aquatic life with long lasting effects.


#### Precautionary statements

**Prevention** : P280 - Wear protective gloves. Wear eye or face protection.  
P273 - Avoid release to the environment.  
P261 - Avoid breathing vapour.  
P264 - Wash thoroughly after handling.

**Response** : P362 + P364 - Take off contaminated clothing and wash it before reuse.

**Storage** : Not applicable.

## SECTION 2: Hazards identification


<b>Disposal</b>	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
<b>Hazardous ingredients</b>	:  Contains: 3-aminomethyl-3,5,5-trimethylcyclohexylamine; m-Xylene- $\alpha,\alpha'$ -diamine and 2,4,7,9-tetramethyl-5-decyne-4,7-diol
<b>Supplemental label elements</b>	: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
<b>Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles</b>	:

### 2.3 Other hazards

<b>Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII</b>	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
<b>Other hazards which do not result in classification</b>	: None known.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
 Aliphatic polyamine	-	≤10	Aquatic Chronic 2, H411	-	[1]
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≤5	Carc. 2, H351 (inhalation)	-	[1] [*]
1-Methoxy 2-propanol	REACH #: 01-2119457435-35 EC: 203-539-1 CAS: 107-98-2 Index: 603-064-00-3	≤3	Flam. Liq. 3, H226 STOT SE 3, H336	-	[1] [2]
3-aminomethyl-3,5,5-trimethylcyclohexylamine	REACH #: 01-2119514687-32 EC: 220-666-8 CAS: 2855-13-2 Index: 612-067-00-9	<3	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317	ATE [Oral] = 1030 mg/kg Skin Sens. 1, H317: C ≥ 0.001%	[1]
m-Xylene- $\alpha,\alpha'$ -diamine	REACH #: 01-2119480150-50 EC: 216-032-5 CAS: 1477-55-0	<1	Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412 EUH071	ATE [Oral] = 930 mg/kg ATE [Inhalation (gases)] = 4500 ppm	[1]
2,4,7,9-tetramethyl-5-decyne-4,7-diol	REACH #: 01-2119954390-39 EC: 204-809-1 CAS: 126-86-3	≤0.3	Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 3, H412	-	[1]
C16-18-(even numbered, saturated and unsaturated)-	REACH #: 01-2119473797-19	≤0.053	Acute Tox. 4, H302 Skin Corr. 1B, H314	ATE [Oral] = 500 mg/kg	[1]

## SECTION 3: Composition/information on ingredients

alkylamines	CAS: 1213789-63-9	Eye Dam. 1, H318 STOT SE 3, H335 STOT RE 2, H373 (oral) Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 <b>See Section 16 for the full text of the H statements declared above.</b>	M [Acute] = 10 M [Chronic] = 10
-------------	-------------------	--	------------------------------------

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[\*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter  $\leq 10 \mu\text{m}$  not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

## SECTION 4: First aid measures

Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.

### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides

### 5.3 Advice for firefighters

Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
--

### 6.3 Methods and material for containment and cleaning up

## SECTION 6: Accidental release measures

- Small spill** : Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

## SECTION 8: Exposure controls/personal protection

Product/ingredient name	Exposure limit values
1-Methoxy 2-propanol	<b>Regulation on Limit Values - MAC (Austria, 4/2021)</b> Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 187 mg/m <sup>3</sup> . CEIL: 50 ppm. CEIL: 187 mg/m <sup>3</sup> .
m-Xylene-α,α'-diamine	<b>Regulation on Limit Values - MAC (Austria, 4/2021)</b> TWA 8 hours: 0.1 mg/m <sup>3</sup> . CEIL: 0.1 mg/m <sup>3</sup> .
1-Methoxy 2-propanol	<b>Limit values (Belgium, 12/2023)</b> Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 184 mg/m <sup>3</sup> . STEL 15 minutes: 100 ppm. STEL 15 minutes: 369 mg/m <sup>3</sup> .
m-Xylene-α,α'-diamine	<b>Limit values (Belgium, 12/2023)</b> Absorbed through skin. Limit value - M: 0.1 mg/m <sup>3</sup> .
1-Methoxy 2-propanol	<b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024)</b> Absorbed through skin. Limit value 8 hours: 375 mg/m <sup>3</sup> . Limit value 15 minutes: 568 mg/m <sup>3</sup> . Limit value 15 minutes: 150 ppm. Limit value 8 hours: 100 ppm.
1-Methoxy 2-propanol	<b>Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023)</b> STELV 15 minutes: 568 mg/m <sup>3</sup> . STELV 15 minutes: 150 ppm. ELV 8 hours: 375 mg/m <sup>3</sup> . ELV 8 hours: 100 ppm.
1-Methoxy 2-propanol	<b>Department of labour inspection (Cyprus, 7/2021)</b> Absorbed through skin. STEL 15 minutes: 150 ppm. STEL 15 minutes: 568 mg/m <sup>3</sup> . TWA 8 hours: 100 ppm. TWA 8 hours: 375 mg/m <sup>3</sup> .
1-Methoxy 2-propanol	<b>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 12/2023)</b> Absorbed through skin. TWA 8 hours: 270 mg/m <sup>3</sup> . TWA 8 hours: 72.09 ppm. STEL 15 minutes: 550 mg/m <sup>3</sup> . STEL 15 minutes: 146.84 ppm.
1-Methoxy 2-propanol	<b>Working Environment Authority (Denmark, 3/2024) [1-methoxy-2-propanol]</b> Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 185 mg/m <sup>3</sup> . STEL 15 minutes: 568 mg/m <sup>3</sup> . STEL 15 minutes: 150 ppm.
m-Xylene-α,α'-diamine	<b>Working Environment Authority (Denmark, 3/2024)</b> Absorbed through skin. CEIL: 0.02 ppm. CEIL: 0.1 mg/m <sup>3</sup> .
1-Methoxy 2-propanol	<b>Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024)</b> Absorbed through skin , Sensitiser. TWA 8 hours: 375 mg/m <sup>3</sup> . TWA 8 hours: 100 ppm. STEL 15 minutes: 568 mg/m <sup>3</sup> . STEL 15 minutes: 150 ppm.

## SECTION 8: Exposure controls/personal protection

1-Methoxy 2-propanol	<p><b>EU OEL (Europe, 1/2022)</b> Absorbed through skin.  TWA 8 hours: 100 ppm.  TWA 8 hours: 375 mg/m<sup>3</sup>.  STEL 15 minutes: 150 ppm.  STEL 15 minutes: 568 mg/m<sup>3</sup>.</p>
1-Methoxy 2-propanol	<p><b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021)</b> Absorbed through skin.  TWA 8 hours: 100 ppm.  TWA 8 hours: 370 mg/m<sup>3</sup>.  STEL 15 minutes: 150 ppm.  STEL 15 minutes: 560 mg/m<sup>3</sup>.</p>
1-Methoxy 2-propanol	<p><b>Ministry of Labor (France, 6/2024)</b> Absorbed through skin.  TWA 8 hours: 50 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)  TWA 8 hours: 188 mg/m<sup>3</sup>. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)  STEL 15 minutes: 375 mg/m<sup>3</sup>. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)  STEL 15 minutes: 100 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</p>
m-Xylene-α,α'-diamine	<p><b>Ministry of Labor (France, 6/2024)</b>  STEL 15 minutes: 0.1 mg/m<sup>3</sup>. Notes: Permissible limit values (circulars)</p>
1-Methoxy 2-propanol	<p><b>TRGS 900 OEL (Germany, 6/2024)</b>  TWA 8 hours: 370 mg/m<sup>3</sup>.  PEAK 15 minutes: 740 mg/m<sup>3</sup>.  TWA 8 hours: 100 ppm.  PEAK 15 minutes: 200 ppm.</p>
	<p><b>DFG MAC-values list (Germany, 7/2023)</b> Develop C.  TWA 8 hours: 100 ppm.  PEAK 15 minutes: 200 ppm 4 times per shift [Interval: 1 hour].  TWA 8 hours: 370 mg/m<sup>3</sup>.  PEAK 15 minutes: 740 mg/m<sup>3</sup> 4 times per shift [Interval: 1 hour].</p>
3-aminomethyl-3,5,5-trimethylcyclohexylamine	<p><b>DFG MAC-values list (Germany, 7/2023)</b> Skin sensitiser.</p>
m-Xylene-α,α'-diamine	<p><b>DFG MAC-values list (Germany, 7/2023)</b> Skin sensitiser.</p>
1-Methoxy 2-propanol	<p><b>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021)</b> Absorbed through skin.  TWA 8 hours: 100 ppm.  TWA 8 hours: 360 mg/m<sup>3</sup>.  STEL 15 minutes: 300 ppm.  STEL 15 minutes: 1080 mg/m<sup>3</sup>.</p>
1-Methoxy 2-propanol	<p><b>5/2020. (II. 6.) ITM Decree (Hungary, 12/2023)</b> Absorbed through skin.  TWA 8 hours: 375 mg/m<sup>3</sup>.  PEAK 15 minutes: 568 mg/m<sup>3</sup>.  PEAK 15 minutes: 150 ppm.  TWA 8 hours: 100 ppm.</p>
1-Methoxy 2-propanol	<p><b>Ministry of Welfare, List of Exposure Limits (Iceland, 11/2023)</b>  Absorbed through skin.  STEL 15 minutes: 568 mg/m<sup>3</sup>.  STEL 15 minutes: 150 ppm.  TWA 8 hours: 185 mg/m<sup>3</sup>.  TWA 8 hours: 50 ppm.</p>
m-Xylene-α,α'-diamine	<p><b>Ministry of Welfare, List of Exposure Limits (Iceland, 11/2023)</b>  Absorbed through skin.  STEL 15 minutes: 0.1 mg/m<sup>3</sup>.  STEL 15 minutes: 0.02 ppm.</p>

## SECTION 8: Exposure controls/personal protection

1-Methoxy 2-propanol	<p><b>NAOSH (Ireland, 4/2024)</b> Notes: EU derived Occupational Exposure Limit Values</p> <p>OELV 8 hours: 100 ppm. OELV 8 hours: 375 mg/m<sup>3</sup>. OELV 15 minutes: 150 ppm. OELV 15 minutes: 568 mg/m<sup>3</sup>.</p>
m-Xylene-α,α'-diamine	<p><b>NAOSH (Ireland, 4/2024)</b> Notes: Advisory Occupational Exposure Limit Values (OELVs)</p> <p>OELV 8 hours: 0.1 mg/m<sup>3</sup>.</p>
1-Methoxy 2-propanol	<p><b>Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 6/2020)</b></p> <p>Absorbed through skin.</p> <p>Limit value 8 hours: 100 ppm. Limit value 8 hours: 375 mg/m<sup>3</sup>. Short Term 15 minutes: 150 ppm. Short Term 15 minutes: 568 mg/m<sup>3</sup>.</p>
1-Methoxy 2-propanol	<p><b>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024)</b></p> <p>Absorbed through skin.</p> <p>TWA 8 hours: 100 ppm. STEL 15 minutes: 568 mg/m<sup>3</sup>. TWA 8 hours: 375 mg/m<sup>3</sup>. STEL 15 minutes: 150 ppm.</p>
3-aminomethyl-3,5,5-trimethylcyclohexylamine	<p><b>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024)</b></p> <p><b>[Amīni, alifātiskie]</b></p> <p>TWA 8 hours: 1 mg/m<sup>3</sup>.</p>
1-Methoxy 2-propanol	<p><b>Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024)</b></p> <p>Absorbed through skin.</p> <p>TWA 8 hours: 190 mg/m<sup>3</sup>. TWA 8 hours: 50 ppm. STEL 15 minutes: 300 mg/m<sup>3</sup>. STEL 15 minutes: 75 ppm.</p>
1-Methoxy 2-propanol	<p><b>Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021)</b> Absorbed through skin.</p> <p>TWA 8 hours: 100 ppm. TWA 8 hours: 375 mg/m<sup>3</sup>. STEL 15 minutes: 150 ppm. STEL 15 minutes: 568 mg/m<sup>3</sup>.</p>
1-Methoxy 2-propanol	<p><b>EU OEL (Europe, 1/2022)</b> Absorbed through skin.</p> <p>TWA 8 hours: 100 ppm. TWA 8 hours: 375 mg/m<sup>3</sup>. STEL 15 minutes: 150 ppm. STEL 15 minutes: 568 mg/m<sup>3</sup>.</p>
1-Methoxy 2-propanol	<p><b>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 5/2024)</b> Absorbed through skin.</p> <p>TWA 8 hours: 375 mg/m<sup>3</sup>. STEL 15 minutes: 563 mg/m<sup>3</sup>. TWA 8 hours: 100 ppm. STEL 15 minutes: 150 ppm.</p>
1-Methoxy 2-propanol	<p><b>FOR-2011-12-06-1358 (Norway, 12/2022)</b> Absorbed through skin.</p> <p>TWA 8 hours: 50 ppm. TWA 8 hours: 180 mg/m<sup>3</sup>.</p>
m-Xylene-α,α'-diamine	<p><b>FOR-2011-12-06-1358 (Norway, 12/2022)</b></p> <p>CEIL: 0.1 mg/m<sup>3</sup>.</p>
1-Methoxy 2-propanol	<p><b>Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 8/2023)</b> Absorbed through skin.</p> <p>TWA 8 hours: 180 mg/m<sup>3</sup>. STEL 15 minutes: 360 mg/m<sup>3</sup>.</p>

## SECTION 8: Exposure controls/personal protection

1-Methoxy 2-propanol	Portuguese Institute of Quality (Portugal, 11/2014) A4. TWA 8 hours: 50 ppm. STEL 15 minutes: 100 ppm.
m-Xylene- $\alpha,\alpha'$ -diamine	Portuguese Institute of Quality (Portugal, 11/2014) Absorbed through skin. CEIL: 0.1 mg/m <sup>3</sup> .
1-Methoxy 2-propanol	HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024) Absorbed through skin. VLA 8 hours: 375 mg/m <sup>3</sup> . VLA 8 hours: 100 ppm. Short term 15 minutes: 568 mg/m <sup>3</sup> . Short term 15 minutes: 150 ppm.
1-Methoxy 2-propanol	Government regulation SR c. 355/2006 (Slovakia, 7/2024) Absorbed through skin , Inhalation sensitiser. TWA 8 hours: 375 mg/m <sup>3</sup> . TWA 8 hours: 100 ppm. STEL 15 minutes: 568 mg/m <sup>3</sup> . STEL 15 minutes: 150 ppm.
1-Methoxy 2-propanol	Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024) Absorbed through skin. TWA 8 hours: 375 mg/m <sup>3</sup> . TWA 8 hours: 100 ppm. KTV 15 minutes: 568 mg/m <sup>3</sup> 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes]. KTV 15 minutes: 150 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].
1-Methoxy 2-propanol	National institute of occupational safety and health (Spain, 1/2024) Absorbed through skin. TWA 8 hours: 100 ppm. TWA 8 hours: 375 mg/m <sup>3</sup> . STEL 15 minutes: 150 ppm. STEL 15 minutes: 568 mg/m <sup>3</sup> .
1-Methoxy 2-propanol	Work environment authority Regulation 2018:1 (Sweden, 11/2022) Absorbed through skin. STEL 15 minutes: 150 ppm. STEL 15 minutes: 568 mg/m <sup>3</sup> . TWA 8 hours: 190 mg/m <sup>3</sup> . TWA 8 hours: 50 ppm.
1-Methoxy 2-propanol	SUVA (Switzerland, 1/2024) TWA 8 hours: 100 ppm. TWA 8 hours: 360 mg/m <sup>3</sup> . STEL 15 minutes: 200 ppm. STEL 15 minutes: 720 mg/m <sup>3</sup> .
m-Xylene- $\alpha,\alpha'$ -diamine	SUVA (Switzerland, 1/2024) Absorbed through skin , Sensitiser. TWA 8 hours: 0.1 mg/m <sup>3</sup> .
1-Methoxy 2-propanol	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin. STEL 15 minutes: 560 mg/m <sup>3</sup> . STEL 15 minutes: 150 ppm. TWA 8 hours: 375 mg/m <sup>3</sup> . TWA 8 hours: 100 ppm.

### [Biological exposure indices](#)

## SECTION 8: Exposure controls/personal protection

Product/ingredient name	Exposure indices
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
☑Methoxy 2-propanol	<b>DFG BEI-values list (Germany, 7/2023)</b> BEI: 15 mg/l, propylene glycol 1-methyl ether [in urine]. Sampling time: end of exposure or end of shift. <b>TRGS 903 - BEI Values (Germany, 2/2024)</b> BEI: 15 mg/l, 1-methoxypropan-2-ol [in urine]. Sampling time: end of exposure or end of shift.
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
☑Methoxy 2-propanol	<b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024)</b> BAT: 15 mg/l, 1-methoxypropan-2-ol [in urine]. Sampling time: at the end of the work shift.
No exposure indices known.	
No exposure indices known.	
☑Methoxy 2-propanol	<b>SUVA (Switzerland, 1/2024)</b> BEI: 20 mg/l, 1-methoxypropanol-2 [in urine]. Sampling time: immediately after exposure or after working hours. BEI: 221.9 µmol/l, 1-methoxypropanol-2 [in urine]. Sampling time: immediately after exposure or after working hours.
No exposure indices known.	

## SECTION 8: Exposure controls/personal protection

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs/DMELs

#### Product/ingredient name

Titanium dioxide

#### Result

**DNEL - General population - Long term - Inhalation**

28 µg/m<sup>3</sup>

Effects: Local

**DNEL - Workers - Long term - Inhalation**

170 µg/m<sup>3</sup>

Effects: Local

1-Methoxy 2-propanol

**DNEL - General population - Long term - Oral**

33 mg/kg bw/day

Effects: Systemic

**DNEL - General population - Long term - Inhalation**

43.9 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - General population - Long term - Dermal**

78 mg/kg bw/day

Effects: Systemic

**DNEL - Workers - Long term - Dermal**

183 mg/kg bw/day

Effects: Systemic

**DNEL - Workers - Long term - Inhalation**

369 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Short term - Inhalation**

553.5 mg/m<sup>3</sup>

Effects: Local

**DNEL - Workers - Short term - Inhalation**

553.5 mg/m<sup>3</sup>

Effects: Systemic

3-aminomethyl-  
3,5,5-trimethylcyclohexylamine

**DNEL - Workers - Short term - Inhalation**

0.073 mg/m<sup>3</sup>

Effects: Local

**DNEL - Workers - Long term - Inhalation**

0.073 mg/m<sup>3</sup>

Effects: Local

**DNEL - General population - Long term - Oral**

0.3 mg/kg bw/day

Effects: Systemic

**DNEL - General population - Short term - Oral**

0.3 mg/kg bw/day

Effects: Systemic

m-Xylene-α,α'-diamine

**DNEL - Workers - Long term - Inhalation**

## SECTION 8: Exposure controls/personal protection

0.2 mg/m<sup>3</sup>  
Effects: Local

### **DNEL - Workers - Long term - Dermal**

0.33 mg/kg bw/day  
Effects: Systemic

### **DNEL - Workers - Long term - Inhalation**

1.2 mg/m<sup>3</sup>  
Effects: Systemic

2,4,7,9-tetramethyl-5-decyne-4,7-diol

### **DNEL - General population - Long term - Oral**

0.29 mg/kg bw/day  
Effects: Systemic

### **DNEL - General population - Long term - Dermal**

0.29 mg/kg bw/day  
Effects: Systemic

### **DNEL - General population - Long term - Inhalation**

0.505 mg/m<sup>3</sup>  
Effects: Systemic

### **DNEL - Workers - Long term - Dermal**

0.812 mg/kg bw/day  
Effects: Systemic

### **DNEL - Workers - Long term - Inhalation**

2.86 mg/m<sup>3</sup>  
Effects: Systemic

C16-18-(even numbered, saturated and unsaturated)-alkylamines

### **DNEL - General population - Long term - Inhalation**

0.035 mg/m<sup>3</sup>  
Effects: Systemic

### **DNEL - General population - Long term - Oral**

40 µg/kg bw/day  
Effects: Systemic

### **DNEL - Workers - Long term - Inhalation**

0.38 mg/m<sup>3</sup>  
Effects: Systemic

### **DNEL - Workers - Short term - Inhalation**

1 mg/m<sup>3</sup>  
Effects: Local

### **DNEL - Workers - Long term - Inhalation**

1 mg/m<sup>3</sup>  
Effects: Local

### **PNECs**

Not available.

## **8.2 Exposure controls**

### **Appropriate engineering controls**

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

### **Individual protection measures**

## SECTION 8: Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Recommendations : Wear suitable gloves tested to EN374.
- > 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm
- Not recommended polyvinyl alcohol (PVA) gloves
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
- Filter type (spray application): A P
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : Various
- Odour** : Slight
- Odour threshold** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** :

Ingredient name	°C	°F	Method
Water	100	212	
1-Methoxy 2-propanol	120.17	248.3	OECD 103

- Flammability** : Not available.
- Lower and upper explosion limit** : Lower: Not applicable.  
Upper: Not applicable.

## SECTION 9: Physical and chemical properties

**Flash point** : Closed cup: >100°C (>212°F)

**Auto-ignition temperature** :

Ingredient name	°C	°F	Method
1-Methoxy 2-propanol	270	518	
2,2,4-trimethylpentane-1,3-diol isobutyrate	393	739.4	

**Decomposition temperature** : Not available.

**pH** : 9 to 11 [Conc. (% w/w): 100%]

**Viscosity** : Not available.

**Solubility(ies)** :

Not available.

**Solubility in water** : Not available.

**Partition coefficient: n-octanol/ water** : Not applicable.

**Vapour pressure** :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Water	17.5	2.3				
1-Methoxy 2-propanol	8.5	1.1				

**Relative density** : Not available.

**Density** : 1.2 g/cm<sup>3</sup>

**Vapour density** : Not available.

### Particle characteristics

**Median particle size** : Not applicable.

## 9.2 Other information

### 9.2.1 Information with regard to physical hazard classes

**Explosive properties** : Not available.

**Oxidising properties** : Not available.

### 9.2.2 Other safety characteristics

Not applicable.

## SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : No specific data.

**10.5 Incompatible materials** : No specific data.

**10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Product/ingredient name

1-Methoxy 2-propanol

##### Result

###### Rabbit - Dermal - LD50

13 g/kg

###### Rat - Oral - LD50

6600 mg/kg

Toxic effects: Brain and Coverings - Other degenerative changes Behavioral - General anesthetic Lung, Thorax, or Respiration - Dyspnea

m-Xylene- $\alpha,\alpha'$ -diamine

###### Rat - Oral - LD50

930 mg/kg

###### Rabbit - Dermal - LD50

2 g/kg

###### Rat - Inhalation - LC50 Gas.

700 ppm [1 hours]

Toxic effects: Eye - Lacrimation Lung, Thorax, or Respiration - Respiratory depression

**Conclusion/Summary [Product]** : Not available.

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
EKNOPOX AQUA COMBI 0360-04	96126.0	N/A	N/A	N/A	N/A
1-Methoxy 2-propanol	6600	13000	N/A	N/A	N/A
3-aminomethyl-3,5,5-trimethylcyclohexylamine	1030	N/A	N/A	N/A	N/A
m-Xylene- $\alpha,\alpha'$ -diamine	930	N/A	4500	N/A	N/A
C16-18-(even numbered, saturated and unsaturated)-alkylamines	500	N/A	N/A	N/A	N/A

#### Skin corrosion/irritation

##### Product/ingredient name

Titanium dioxide

##### Result

###### Human - Skin - Mild irritant

Duration of treatment/exposure: 72 hours

Amount/concentration applied: 300 ug l

1-Methoxy 2-propanol

###### Rabbit - Skin - Mild irritant

Amount/concentration applied: 500 mg

m-Xylene- $\alpha,\alpha'$ -diamine

###### Rabbit - Skin - Severe irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 750 ug

2,4,7,9-tetramethyl-5-decyne-4,7-diol

###### Rabbit - Skin - Mild irritant

Amount/concentration applied: 0.5 gm

**Conclusion/Summary [Product]** : Not available.

#### Serious eye damage/eye irritation

##### Product/ingredient name

##### Result

## SECTION 11: Toxicological information

1-Methoxy 2-propanol

**Rabbit - Eyes - Mild irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

m-Xylene- $\alpha,\alpha'$ -diamine

**Rabbit - Eyes - Severe irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 50 ug

2,4,7,9-tetramethyl-5-decyne-4,7-diol

**Rabbit - Eyes - Severe irritant**

Amount/concentration applied: 0.1 MI

**Conclusion/Summary [Product]** : Not available.

### Respiratory corrosion/irritation

Not available.

**Conclusion/Summary [Product]** : Not available.

### Respiratory or skin sensitization

Not available.

### Skin

**Conclusion/Summary [Product]** : Not available.

### Respiratory

**Conclusion/Summary [Product]** : Not available.

### Germ cell mutagenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

Not available.

**Conclusion/Summary [Product]** : Not available.

### Reproductive toxicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Specific target organ toxicity (single exposure)

#### **Product/ingredient name**

1-Methoxy 2-propanol  
C16-18-(even numbered, saturated and unsaturated)-alkylamines

#### **Result**

STOT SE 3, H336 (Narcotic effects)  
STOT SE 3, H335 (Respiratory tract irritation)

### Specific target organ toxicity (repeated exposure)

#### **Product/ingredient name**

C16-18-(even numbered, saturated and unsaturated)-alkylamines

#### **Result**

STOT RE 2, H373 (oral)

## SECTION 11: Toxicological information

### Aspiration hazard

#### Product/ingredient name

C16-18-(even numbered, saturated and unsaturated)-alkylamines

#### Result

ASPIRATION HAZARD - Category 1

### Information on likely routes of exposure

Not available.

### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.


**Conclusion/Summary [Product]** : Not available.

- General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

## 11.2 Information on other hazards

### 11.2.1 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** :  The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product/ingredient name

Titanium dioxide

#### Result

##### Acute - LC50 - Marine water

Fish - Mummichog - *Fundulus heteroclitus*

>1000000 µg/l [96 hours]

Effect: Mortality

##### Acute - LC50 - Fresh water

Crustaceans - Water flea - *Ceriodaphnia dubia* - Neonate

Age: <24 hours

3 mg/l [48 hours]

Effect: Mortality

2,4,7,9-tetramethyl-5-decyne-4,7-diol

##### LC50

Fish - *Cyprinus carpio*

42 mg/l [96 hours]

##### EC50

Daphnia - *Daphnia magna*

91 mg/l [48 hours]

C16-18-(even numbered, saturated and unsaturated)-alkylamines

##### Acute - LC50

Fish

4.21 mg/l [96 hours]

##### Acute - EC50

Daphnia

0.98 mg/l [48 hours]

##### Acute - EC50

Algae

0.46 mg/l [72 hours]

Conclusion/Summary [Product] : Not available.

### 12.2 Persistence and degradability

Not available.

Conclusion/Summary [Product] : Not available.

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
1-Methoxy 2-propanol	<1	-	Low
3-aminomethyl-	0.99	-	Low
3,5,5-trimethylcyclohexylamine			
m-Xylene-α,α'-diamine	0.18	2.69	Low

### 12.4 Mobility in soil

#### Soil/water partition coefficient

Product/ingredient name	logK <sub>oc</sub>	K <sub>oc</sub>
1-Methoxy 2-propanol	1.02	10.447
3-aminomethyl-	1.99	98.3852
3,5,5-trimethylcyclohexylamine		
m-Xylene-α,α'-diamine	1.67	46.5812
2,4,7,9-tetramethyl-5-decyne-4,7-diol	1.92	83.8929

#### Results of PMT and vPvM assessment

## SECTION 12: Ecological information

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
Aliphatic polyamine	No	No	No	No	No	No	No
titanium dioxide	No	No	No	No	No	No	No
1-Methoxy 2-propanol	No	No	No	No	No	No	No
3-aminomethyl-	No	No	No	No	No	No	No
3,5,5-trimethylcyclohexylamine							
m-Xylene- $\alpha,\alpha'$ -diamine	No	No	No	No	No	No	No
2,4,7,9-tetramethyl-	No	No	No	No	No	No	No
5-decyne-4,7-diol							
C16-18-(even numbered, saturated and unsaturated)-alkylamines	No	No	No	No	No	No	No

**Mobility** : Not available.

**Conclusion/Summary** : The product does not meet the criteria to be considered as a PMT or vPvM.

### 12.5 Results of PBT and vPvB assessment

#### Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Aliphatic polyamine	No	No	No	No	No	No	No
titanium dioxide	No	No	No	No	No	No	No
1-Methoxy 2-propanol	No	No	No	No	No	No	No
3-aminomethyl-	No	No	No	No	No	No	No
3,5,5-trimethylcyclohexylamine							
m-Xylene- $\alpha,\alpha'$ -diamine	No	No	No	No	No	No	No
2,4,7,9-tetramethyl-	No	No	No	No	No	No	No
5-decyne-4,7-diol							
C16-18-(even numbered, saturated and unsaturated)-alkylamines	No	No	No	No	No	No	No

#### Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Aliphatic polyamine	No	No	No	No	No	No	No
titanium dioxide	No	No	No	No	No	No	No
1-Methoxy 2-propanol	No	No	No	No	No	No	No
3-aminomethyl-	No	No	No	No	No	No	No
3,5,5-trimethylcyclohexylamine							
m-Xylene- $\alpha,\alpha'$ -diamine	No	No	No	No	No	No	No
2,4,7,9-tetramethyl-	No	No	No	No	No	No	No
5-decyne-4,7-diol							
C16-18-(even numbered, saturated and unsaturated)-alkylamines	No	No	No	No	No	No	No

**Conclusion/Summary** : The product does not meet the criteria to be considered as a PBT or vPvB.

#### Regulation (EC) No. 1272/2008 [CLP]

### 12.6 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**European waste catalogue (EWC)** : 080111\*, 200127\*

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in bulk according to IMO instruments** : Not relevant/applicable due to nature of the product.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

##### Annex XIV

None of the components are listed.

##### Substances of very high concern

None of the components are listed.

##### Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

## SECTION 15: Regulatory information

Product/ingredient name	%	Designation [Usage]
TEKNOPOX AQUA COMBI 0360-04	≥90	3

Labelling :

### Other EU regulations

Industrial emissions  
(integrated pollution  
prevention and control) -  
Air : Not listed

Industrial emissions  
(integrated pollution  
prevention and control) -  
Water : Not listed

Explosive precursors : Not applicable.

### Ozone depleting substances (EU 2024/590)

Not listed.

### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

### Persistent Organic Pollutants

Not listed.

### Seveso Directive

This product is not controlled under the Seveso Directive.

### National regulations

#### Austria

Limitation of the use of  
organic solvents : Permitted.

#### Belgium

#### Book VI carcinogenic agents annex VI.2-1 - VI.2-3

Ingredient name	Status
Noirs de charbon	Listed
Noirs de charbon	Listed

### Czech Republic

Storage code : IV

### Denmark

Fire class : W-1

### Executive Order No. 1795/2015

Ingredient name	Annex I Section A	Annex I Section B
Titanium dioxide	Listed	-
carbon black respirable	Listed	-
Carbon black	Listed	-

MAL-code : 5-5

Protection based on MAL : According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:

**General:** Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

## SECTION 15: Regulatory information

MAL-code: 5-5

**Application:** When using scraper or knife, brush, roller etc. for pre- and post-treatments in a spray booth where the operator is outside the spray zone and when working in similar new\* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. When spraying in new\* booths and cabins with non-atomizing guns.

- Protective clothing must be worn.

During non-atomising spraying in existing\* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. When spraying in existing\* spray booths, if the operator is outside the spray zone. When using scraper or knife, brush, roller, etc. for pre- and post-treatments in cabins or booths of the existing\* facility type, if the operator is inside the spray zone. When using scraper or knife, brush, roller, etc. for pre- and post-treatments outside a closed facility, spray booth or spray cabin. During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents.

- Air-supplied full mask and protective clothing must be worn.

When spraying in new\* booths if the operator is outside the spray zone.

- Air-supplied full mask must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.


- Air-supplied full mask, protective clothing and hood must be worn.

**Drying:** Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc. must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

**Polishing:** When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.


**Caution** The regulations contain other stipulations in addition to the above.

\*See Regulations.

<b>Restrictions on use</b>	:	Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.
<b>List of undesirable substances</b>	:	Not listed
<b>Carcinogenic waste</b>	:	Waste containers must be labeled: Contains a substance or substances regulated by Danish working environment legislation on cancer risks.
<b>Epoxy/Isocyanate</b>	:	 The product is covered by the rules for epoxy resins and isocyanates in Executive Order no. 1793 of 18/12/2015 on working with substances and materials (chemical agents). Pay attention to the rules, for example: the user of the product must have undergone special training and waste must be labelled. This requirement is in addition to the training requirement described in the REACH regulation, Annex XVII, entry 74 (COMMISSION REGULATION (EU) 2020/1149).

[Finland](#)

[France](#)

<b>Social Security Code, Articles L 461-1 to L 461-7</b>	:	 Methoxy 2-propanol 3-aminomethyl-3,5,5-trimethylcyclohexylamine	RG 84 RG 49bis
--	---	--	-------------------

## SECTION 15: Regulatory information

**Reinforced medical surveillance** : Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable

### Germany

**Storage class (TRGS 510)** : 10

### Hazardous incident ordinance

This product is not controlled under the Germany Hazardous Incident Ordinance.

**Hazard class for water** : 2

### Technical instruction on air quality control (TA Luft)

Number [Class]	Description	%
5.2.1	Total dust	36.5
5.2.5	Organic substances	10.1
5.2.5 [I]	Organic substances	3.4
5.2.7.1.3	Reproductive toxic substances	0.029

**AOX** : The product contains organically bound halogens and can contribute to the AOX value in waste water.

### Italy

**D.Lgs. 152/06** : Not determined.

### Netherlands

**Water Discharge Policy (ABM)** : A(3) Hazardous for aquatic organisms, may have long-term hazardous effects in aquatic environment. Decontamination effort: A

### Norway

### Sweden

**Epoxy/Isocyanate** : The product is covered by the specific rules for epoxy resins and isocyanates, allergenic chemical products in provision AFS 2011:19 Chemical Hazards in the Working Environment. Pay attention to that handling the product requires certificate of undergone necessary training and can require medical examination. Waste must be labelled with named substance and as Hazardous waste. This requirement is in addition to the training requirement described in the REACH regulation, Annex XVII, entry 74 (COMMISSION REGULATION (EU) 2020/1149).

### Switzerland

**VOC content** : Exempt.

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

**15.2 Chemical safety assessment** : This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

Indicates information that has changed from previously issued version.

### Abbreviations and acronyms

: ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
N/A = Not available  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
SGG = Segregation Group  
vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 3, H412	Calculation method

### Full text of abbreviated H statements

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

### Full text of classifications [CLP/GHS]

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of issue/ Date of revision : 30/05/2025

Date of previous issue : 17/10/2022

Version : 8

Date of issue/Date of revision : 30/05/2025 Date of previous issue : 17/10/2022

Version : 8 24/26

EKNOPOX AQUA COMBI 0360-04 - All variants

Label No : 20599

## SECTION 16: Other information

TEKNOPOX AQUA COMBI 0360-04

All variants

### Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

