SAFETY DATA SHEET



TEKNOPOX AQUA COMBI 0360-04 - All variants

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

: TEKNOPOX AQUA COMBI 0360-04 - All variants **Product name**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS

: Prod-safe@teknos.com

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : Emergency medical information: (seven days) contact National Poisons Information

Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland.

Members of the public Number (8 am-10 pm): +353 (0)1 809 2166 Healthcare professional telephone Number (24hrs): +353 (0)1 809 2566

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315 Eve Irrit. 2. H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word : Warning

Hazard statements H315 - Causes skin irritation.

> H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : P280 - Wear protective gloves. Wear eye or face protection.

P273 - Avoid release to the environment.

P261 - Avoid breathing vapour.

P264 - Wash thoroughly after handling.

Response : P362 + P364 - Take off contaminated clothing and wash it before reuse.

Storage Not applicable.

Date of issue/Date of revision : 17/11/2025 Date of previous issue . 30/05/2025 Version : 4 1/18 Label No : 1/36136

SECTION 2: Hazards identification

Disposal

: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous ingredients

: Contains: 3-aminomethyl-3,5,5-trimethylcyclohexylamine; m-Xylene-α,α'-diamine

Supplemental label

and 2,4,7,9-tetramethyl-5-decyne-4,7-diol

elements

Annex XVII - Restrictions on the manufacture,

placing on the market and use of certain dangerous substances, mixtures and

articles

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Aliphatic polyamine	-	≤10	Aquatic Chronic 2, H411	-	[1]
1-Methoxy 2-propanol	REACH #: 01-2119457435-35 EC: 203-539-1 CAS: 107-98-2 Index: 603-064-00-3	≤3	Flam. Liq. 3, H226 STOT SE 3, H336	-	[1] [2]
3-aminomethyl- 3,5,5-trimethylcyclohexylamine	REACH #: 01-2119514687-32 EC: 220-666-8 CAS: 2855-13-2 Index: 612-067-00-9	<3	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317	ATE [Oral] = 1030 mg/kg Skin Sens. 1, H317: C ≥ 0.001%	[1]
m-Xylene-α,α'-diamine	REACH #: 01-2119480150-50 EC: 216-032-5 CAS: 1477-55-0	<1	Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412 EUH071	ATE [Oral] = 930 mg/kg ATE [Inhalation (gases)] = 4500 ppm	[1] [2]
2,4,7,9-tetramethyl- 5-decyne-4,7-diol	REACH #: 01-2119954390-39 EC: 204-809-1 CAS: 126-86-3	≤0.3	Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 3, H412	-	[1]
C16-18-(even numbered, saturated and unsaturated)-alkylamines	REACH #: 01-2119473797-19 CAS: 1213789-63-9	≤0.053	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 STOT RE 2, H373 (oral) Asp. Tox. 1, H304	ATE [Oral] = 500 mg/kg M [Acute] = 10 M [Chronic] = 10	[1]

Date of issue/Date of revision : 17/11/2025 Date of previous issue : 30/05/2025 Version: 4 2/18 Label No : 1/36136

SECTION 3: Composition/information on ingredients Aquatic Acute 1, H400 Aquatic Chronic 1, H410 See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

Date of issue/Date of revision: 17/11/2025Date of previous issue: 30/05/2025Version: 43/18TEKNOPOX AQUA COMBI 0360-04 - All variantsLabel No : ₹36136

SECTION 4: First aid measures

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

: No specific treatment. **Specific treatments**

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Date of issue/Date of revision · 17/11/2025 . 30/05/2025 Version: 4 4/18 Date of previous issue Label No : 1/36136

SECTION 6: Accidental release measures

Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

6.4 Reference to other sections

: See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
1-Methoxy 2-propanol	NAOSH (Ireland, 4/2024) Notes: EU derived Occupational Exposure Limit Values OELV 8 hours: 100 ppm. OELV 8 hours: 375 mg/m³. OELV 15 minutes: 150 ppm. OELV 15 minutes: 568 mg/m³.
m-Xylene-α,α'-diamine	NAOSH (Ireland, 4/2024) Notes: Advisory Occupational Exposure Limit Values (OELVs) OELV 8 hours: 0.1 mg/m³.

Date of issue/Date of revision: 17/11/2025Date of previous issue: 30/05/2025Version: 45/18TEKNOPOX AQUA COMBI 0360-04 - All variantsLabel No : ₹36136

SECTION 8: Exposure controls/personal protection

Biological exposure indices

Product/ingredient name	Exposure indices
No exposure indices known.	

Recommended monitoring procedures

: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name

1-Methoxy 2-propanol

Result

DNEL - General population - Long term - Oral

33 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Inhalation

43.9 mg/m³ Effects: Systemic

DNEL - General population - Long term - Dermal

78 mg/kg bw/day Effects: Systemic

DNEL - Workers - Long term - Dermal

183 mg/kg bw/day Effects: Systemic

DNEL - Workers - Long term - Inhalation

369 mg/m³ Effects: Systemic

DNEL - Workers - Short term - Inhalation

553.5 ma/m3 Effects: Local

DNEL - Workers - Short term - Inhalation

553.5 ma/m3 Effects: Systemic

DNEL - Workers - Short term - Inhalation

0.073 mg/m³ Effects: Local

DNEL - Workers - Long term - Inhalation

0.073 mg/m³ Effects: Local

DNEL - General population - Long term - Oral

0.3 mg/kg bw/day Effects: Systemic

DNEL - General population - Short term - Oral

0.3 mg/kg bw/day Effects: Systemic

DNEL - Workers - Long term - Inhalation

0.2 mg/m³ Effects: Local

m-Xylene-α,α'-diamine

3-aminomethyl-

3,5,5-trimethylcyclohexylamine

Date of issue/Date of revision : 17/11/2025 Date of previous issue . 30/05/2025 Version: 4 6/18 Label No : 1/36136

SECTION 8: Exposure controls/personal protection

DNEL - Workers - Long term - Dermal

0.33 mg/kg bw/day Effects: Systemic

DNEL - Workers - Long term - Inhalation

1.2 mg/m³

Effects: Systemic

2,4,7,9-tetramethyl-5-decyne-4,7-diol

DNEL - General population - Long term - Oral

0.29 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Dermal

0.29 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Inhalation

0.505 mg/m³ Effects: Systemic

DNEL - Workers - Long term - Dermal

0.812 mg/kg bw/day Effects: Systemic

DNEL - Workers - Long term - Inhalation

2.86 mg/m3 Effects: Systemic

C16-18-(even numbered, saturated and unsaturated)-alkylamines

DNEL - General population - Long term - Inhalation

0.035 mg/m³ Effects: Systemic

DNEL - General population - Long term - Oral

40 µg/kg bw/day Effects: Systemic

DNEL - Workers - Long term - Inhalation

0.38 mg/m³ Effects: Systemic

DNEL - Workers - Short term - Inhalation

1 ma/m³ Effects: Local

DNEL - Workers - Long term - Inhalation

1 ma/m³ Effects: Local

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Version : 4 Date of issue/Date of revision : 17/11/2025 Date of previous issue : 30/05/2025 7/18 Label No : 1/36136

SECTION 8: Exposure controls/personal protection

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists. gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer. check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations: Wear suitable gloves tested to EN374.

> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm polyvinyl alcohol (PVA) gloves Not recommended

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type (spray application):

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid. Colour Various **Odour** Slight **Odour threshold** Not available.

Melting point/freezing point Initial boiling point and

boiling range

Not available.

Ingredient name °C °F **Method** 100 water 212 1-Methoxy 2-propanol 120.17 248.3 **OECD 103**

Flammability : Not available.

Lower and upper explosion : Lower: Not applicable.

limit

Upper: Not applicable.

Closed cup: >100°C (>212°F) Flash point

Auto-ignition temperature

Date of issue/Date of revision : 17/11/2025 . 30/05/2025 Version: 4 8/18 Date of previous issue Label No : 1/36136

SECTION 9: Physical and chemical properties

Ingredient name	°C	°F	Method
<mark>J-</mark> Methoxy 2-propanol	270	518	
2,2,4-trimethylpentane-1,3-diol isobutyrate	393	739.4	

Decomposition temperature : Not available.

pН : 9 to 11 [Conc. (% w/w): 100%]

Viscosity : Not available.

Solubility(ies)

Not available.

Solubility in water : Not available. Partition coefficient: n-octanol/ : Not applicable.

water

Vapour pressure

	Vapour Pressure at 20°C			Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
water	17.5	2.3				
1-Methoxy 2-propanol	8.5	1.1				

Relative density : Not available. **Density** : 1.2 g/cm³ : Not available. Vapour density

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

: Not available. **Explosive properties** : Not available. **Oxidising properties**

9.2.2 Other safety characteristics

Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

Date of issue/Date of revision : 17/11/2025 Date of previous issue : 30/05/2025 Version: 4 9/18 Label No : 1/36136

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name Result

1-Methoxy 2-propanol Rabbit - Dermal - LD50

13 g/kg

Rat - Oral - LD50 6600 mg/kg

Toxic effects: Brain and Coverings - Other degenerative changes Behavioral - General anesthetic Lung, Thorax, or

Respiration - Dyspnea

m-Xylene-α,α'-diamine Rat - Oral - LD50

930 mg/kg

Rabbit - Dermal - LD50

2 g/kg

Rat - Inhalation - LC50 Gas.

700 ppm [1 hours]

Toxic effects: Eye - Lacrimation Lung, Thorax, or Respiration -

Respiratory depression

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
FEKNOPOX AQUA COMBI 0360-04	96126.0	N/A	N/A	N/A	N/A
1-Methoxy 2-propanol	6600	13000	N/A	N/A	N/A
3-aminomethyl-3,5,5-trimethylcyclohexylamine	1030	N/A	N/A	N/A	N/A
m-Xylene-α,α'-diamine	930	N/A	4500	N/A	N/A
C16-18-(even numbered, saturated and unsaturated)-alkylamines	500	N/A	N/A	N/A	N/A

Skin corrosion/irritation

Product/ingredient name Result

1-Methoxy 2-propanol Rabbit - Skin - Mild irritant

Amount/concentration applied: 500 mg

m-Xylene-α,α'-diamine Rabbit - Skin - Severe irritant

<u>Duration of treatment/exposure</u>: 24 hours Amount/concentration applied: 750 ug

Rabbit - Skin - Mild irritant 2,4,7,9-tetramethyl-5-decyne-4,7-diol

Amount/concentration applied: 0.5 gm

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Product/ingredient name Result

Date of issue/Date of revision : 17/11/2025 Date of previous issue : 30/05/2025 Version: 4 10/18 Label No : 1/36136

SECTION 11: Toxicological information

1-Methoxy 2-propanol Rabbit - Eyes - Mild irritant

> Duration of treatment/exposure: 24 hours Amount/concentration applied: 500 mg

Rabbit - Eyes - Severe irritant m-Xylene-α,α'-diamine

> Duration of treatment/exposure: 24 hours Amount/concentration applied: 50 ug

2,4,7,9-tetramethyl-5-decyne-4,7-diol Rabbit - Eyes - Severe irritant

Amount/concentration applied: 0.1 MI

Conclusion/Summary [Product]: Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product]: Not available.

Respiratory

Conclusion/Summary [Product]: Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name Result

1-Methoxy 2-propanol STOT SE 3, H336 (Narcotic effects)

C16-18-(even numbered, saturated and STOT SE 3, H335 (Respiratory tract irritation)

unsaturated)-alkylamines

Specific target organ toxicity (repeated exposure)

Product/ingredient name

C16-18-(even numbered, saturated and STOT RE 2, H373 (oral)

unsaturated)-alkylamines

Aspiration hazard

Product/ingredient name Result

: 17/11/2025 Date of issue/Date of revision Date of previous issue . 30/05/2025 Version: 4 11/18 Label No : 1/36136

SECTION 11: Toxicological information

C16-18-(even numbered, saturated and

unsaturated)-alkylamines

Information on likely routes of exposure

Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact: Causes skin irritation. May cause an allergic skin reaction.

ASPIRATION HAZARD - Category 1

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate

effects

: Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

: Not available.

Potential chronic health effects

Potential delayed effects

Not available.

Conclusion/Summary [Product] : Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product]: The product does not meet the criteria to be considered as having endocrine

disrupting properties according to the criteria set out in either Regulation (EC)

Label No : 1/36136

No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name Result

Date of issue/Date of revision: 17/11/2025Date of previous issue: 30/05/2025Version: 412/18

SECTION 12: Ecological information

2,4,7,9-tetramethyl-5-decyne-4,7-diol

LC50

Fish - Cyprinus carpio 42 mg/l [96 hours]

EC50

Daphnia - *Daphnia magna* 91 mg/l [48 hours]

C16-18-(even numbered, saturated and unsaturated)-alkylamines

Acute - LC50

Fish

4.21 mg/l [96 hours]

Acute - EC50

Daphnia

0.98 mg/l [48 hours]

Acute - EC50

Algae

0.46 mg/l [72 hours]

Conclusion/Summary [Product]: Not available.

12.2 Persistence and degradability

Not available.

Conclusion/Summary [Product]: Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
	<1	-	Low
3-aminomethyl-	0.99	-	Low
3,5,5-trimethylcyclohexylamine			
m-Xylene-α,α'-diamine	0.18	2.69	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logKoc	Koc
Methoxy 2-propanol	1	10.447
3-aminomethyl-	2	98.3852
3,5,5-trimethylcyclohexylamine		
m-Xylene-α,α'-diamine	1.7	46.5812
2,4,7,9-tetramethyl-5-decyne-4,7-diol	1.9	83.8929

Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
Miphatic polyamine	No	No	No	No	No	No	No
1-Methoxy 2-propanol	No	No	No	No	No	No	No
3-aminomethyl- 3,5,5-trimethylcyclohexylamine	No	No	No	No	No	No	No
m-Xylene-α,α'-diamine	No	No	No	No	No	No	No
2,4,7,9-tetramethyl- 5-decyne-4,7-diol	No	No	No	No	No	No	No
C16-18-(even numbered, saturated and unsaturated)-alkylamines	No	No	No	No	No	No	No

Mobility : Not available.

Conclusion/Summary: The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Date of issue/Date of revision: 17/11/2025Date of previous issue: 30/05/2025Version: 413/18TEKNOPOX AQUA COMBI 0360-04 - All variantsLabel No : ₹36136

SECTION 12: Ecological information

Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	В	T	vPvB	νP	vB	
Miphatic polyamine	No	N/A	N/A	No	N/A	N/A	N/A	
1-Methoxy 2-propanol	No	N/A	N/A	No	N/A	N/A	N/A	
3-aminomethyl-	No	N/A	N/A	No	N/A	N/A	N/A	
3,5,5-trimethylcyclohexylamine								
m-Xylene-α,α'-diamine	No	N/A	No	No	No	N/A	No	
2,4,7,9-tetramethyl-	No	N/A	N/A	No	N/A	N/A	N/A	
5-decyne-4,7-diol								
C16-18-(even numbered,	N/A	N/A	N/A	Yes	N/A	N/A	N/A	
saturated and unsaturated)-								
alkylamines								

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	В	Т	vPvB	vP	vB	
Miphatic polyamine	No	No	No	No	No	No	No	
1-Methoxy 2-propanol	No	No	No	No	No	No	No	
3-aminomethyl- 3,5,5-trimethylcyclohexylamine	No	No	No	No	No	No	No	
m-Xylene-α,α'-diamine	No	No	No	No	No	No	No	
2,4,7,9-tetramethyl- 5-decyne-4,7-diol	No	No	No	No	No	No	No	ļ
C16-18-(even numbered, saturated and unsaturated)-alkylamines	No	No	No	No	No	No	No	

Conclusion/Summary **Regulation (EC) No. 1272/2008** [CLP]

: The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product]

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

: The classification of the product may meet the criteria for a hazardous waste.

Hazardous waste

: 080111*, 200127*

European waste catalogue (EWC)

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Version : 4 Date of issue/Date of revision : 17/11/2025 Date of previous issue . 30/05/2025 14/18 Label No : 1/36136

SECTION 13: Disposal considerations

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
TEKNOPOX AQUA COMBI 0360-04	≥90	3

Labelling

Other EU regulations

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Industrial emissions (integrated pollution

: Not listed

prevention and control) -

Water

Explosive precursors : Not applicable.

Date of issue/Date of revision : 17/11/2025 . 30/05/2025 Version: 4 15/18 Date of previous issue TEKNOPOX AQUA COMBI 0360-04 - All variants Label No : 1/36136

SECTION 15: Regulatory information

Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety

assessment

: This product contains substances for which Chemical Safety Assessments are still

required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and

acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

Date of issue/Date of revision : 17/11/2025 . 30/05/2025 Version: 4 16/18 Date of previous issue Label No : 1/36136

SECTION 16: Other information

⊮ 226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

Cute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
I .	

Date of issue/ Date of : 17/11/2025

revision

Date of previous issue : 30/05/2025

Version : 4

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Version :4 Date of issue/Date of revision : 17/11/2025 Date of previous issue : 30/05/2025 17/18 Label No : 1/36136

: 30/05/2025 Date of issue/Date of revision : 17/11/2025 Date of previous issue Version: 4 18/18 **Label No** : 1/36136