SAFETY DATA SHEET



TEKNOSAFE FLAME GUARD 2477-00 - CLEAR

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

: TEKNOSAFE FLAME GUARD 2477-00 - CLEAR **Product name**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS

: Prod-safe@teknos.com

National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

National advisory body/Poison Centre

: Emergency medical information: (seven days) contact National Poisons Information Telephone number

Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland.

Members of the public Number (8 am-10 pm): +353 (0)1 809 2166 Healthcare professional telephone Number (24hrs): +353 (0)1 809 2566

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word : Warning

Hazard statements : H317 - May cause an allergic skin reaction.

Precautionary statements

Prevention : P280 - Wear protective gloves.

P261 - Avoid breathing vapour.

: P302 + P352 - IF ON SKIN: Wash with plenty of water. Response

> P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P362 + P364 - Take off contaminated clothing and wash it before reuse.

Storage : Not applicable.

: P501 - Dispose of contents and container in accordance with all local, regional, **Disposal**

national and international regulations.

Version : 2 Date of issue/Date of revision : 22/04/2025 · 29/09/2022 1/19 Date of previous issue Label No : 91014

SECTION 2: Hazards identification

Hazardous ingredients

: Contains: Formaldehyde; 2-methyl-2H-isothiazol-3-one and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one [EC no. 220-239-6] (3:1)

Supplemental label

elements

Contains biocidal products for in-can preservation: C(M)IT/MIT (3:1).

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
midazo[4,5-d]imidazole-2,5 (1H,3H)-dione, tetrahydro-, polymer with formaldehyde, butylated	CAS: 68036-98-6	≤5	Aquatic Chronic 4, H413	-	[1]
2-(2-butoxyethoxy)ethanol	REACH #: 01-2119475104-44 EC: 203-961-6 CAS: 112-34-5 Index: 603-096-00-8	≤3	Eye Irrit. 2, H319	-	[1] [2]
Formaldehyde	REACH #: 01-2119488953-20 EC: 200-001-8 CAS: 50-00-0 Index: 605-001-00-5	<0.1	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Carc. 1B, H350 STOT SE 3, H335	ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (gases)] = 700 ppm Skin Corr. 1B, H314: $C \ge 25\%$ Skin Irrit. 2, H315: $5\% \le C < 25\%$ Eye Dam. 1, H318: $C \ge 25\%$ Eye Irrit. 2, H319: $5\% \le C < 25\%$ Skin Sens. 1, H317: $C \ge 0.2\%$ STOT SE 3, H335: $C \ge 5\%$	[1] [2]
2-methyl-2H-isothiazol- 3-one	EC: 220-239-6 CAS: 2682-20-4 Index: 613-326-00-9	<0.01	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400	ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (dusts and mists)] = 0.11 mg/l	[1]

Date of issue/Date of revision : 22/04/2025 Date of previous issue : 29/09/2022 Version : 2 2/19 **Label No: 91014**

SECTION 3: Composition/information on ingredients Aquatic Chronic 1, Skin Sens. 1, H317: H410 C ≥ 0.0015% **EUH071** M [Acute] = 10 M [Chronic] = 1< 0.0025 ATE [Oral] = 53 mg/ [1] reaction mass of: 5-chloro-EC: 911-418-6 Acute Tox. 3, H301 2-methyl-4-isothiazolin-CAS: 55965-84-9 Acute Tox. 2, H310 Acute Tox. 2, H330 3-one [EC no. 247-500-7] Index: 613-167-00-5 ATE [Dermal] = 50 and 2-methyl-2H-isothiazol-Skin Corr. 1C, H314 mg/kg 3-one [EC no. 220-239-6] Eye Dam. 1, H318 ATE [Inhalation] (3:1)Skin Sens. 1A, H317 (vapours)] = 0.5 Aguatic Acute 1, H400 mq/l Aquatic Chronic 1, Skin Corr. 1C, H410 H314: C ≥ 0.6% **EUH071** Eye Dam. 1, H318: C ≥ 0.6% Eye Irrit. 2, H319: $0.06\% \le C < 0.6\%$ Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100 See Section 16 for the full text of the H

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower evelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

statements declared

above.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Date of issue/Date of revision : 22/04/2025 Date of previous issue · 29/09/2022 Version : 2 3/19 Label No : 91014

SECTION 4: First aid measures

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact : No specific data. Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

> irritation redness

Ingestion : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

nitrogen oxides

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion products

: Decomposition products may include the following materials: carbon dioxide carbon monoxide

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Date of issue/Date of revision · 29/09/2022 Version : 2 4/19 : 22/04/2025 Date of previous issue Label No : 91014

SECTION 6: Accidental release measures

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

For leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

6.4 Reference to other sections

: See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Date of issue/Date of revision: 22/04/2025Date of previous issue: 29/09/2022Version: 25/19

Label No : 91014

SECTION 8: Exposure controls/personal protection

Product/ingredient name	Exposure limit values
	NAOSH (Ireland, 4/2024) Notes: EU derived Occupational Exposure Limit Values OELV 8 hours: 10 ppm. OELV 15 minutes: 101.2 mg/m³. OELV 8 hours: 67.5 mg/m³. OELV 15 minutes: 15 ppm.
Formaldehyde	NAOSH (Ireland, 4/2024) Carc 1B. Sensitiser. Notes: EU derived Occupational Exposure Limit Values OELV 8 hours: 0.3 ppm. OELV 15 minutes: 0.6 ppm. OELV 15 minutes: 0.738 mg/m³. OELV 8 hours: 0.37 mg/m³.

Biological exposure indices

Product/ingredient name	Exposure indices
No exposure indices known.	

Recommended monitoring procedures

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Formaldehyde

Product/ingredient name 2-(2-butoxyethoxy)ethanol

Result

DNEL - General population - Long term - Oral 6.25 mg/kg bw/day Effects: Systemic

DNEL - Workers - Long term - Inhalation 67.5 mg/m³ Effects: Local

DNEL - Workers - Short term - Inhalation 101.2 mg/m³

Effects: Local

DNEL - General population - Long term - Dermal

12 µg/cm² Effects: Local

DNEL - Workers - Long term - Dermal

37 µg/cm² Effects: Local

DNEL - General population - Long term - Inhalation

0.1 mg/m³ Effects: Local

DNEL - Workers - Long term - Inhalation

0.375 mg/m³ Effects: Local

DNEL - Workers - Short term - Inhalation

0.75 mg/m³ Effects: Local

DNEL - General population - Long term - Inhalation

Date of issue/Date of revision : 22/04/2025 · 29/09/2022 Version : 2 6/19 Date of previous issue Label No : 91014

SECTION 8: Exposure controls/personal protection

2-methyl-2H-isothiazol-3-one

reaction mass of: 5-chloro-2-methyl-

2-methyl-2H-isothiazol-3-one [EC no.

220-239-6] (3:1)

4-isothiazolin-3-one [EC no. 247-500-7] and

3.2 mg/m³

Effects: Systemic

DNEL - General population - Long term - Oral

4.1 mg/kg bw/day Effects: Systemic

DNEL - Workers - Long term - Inhalation

9 mg/m³

Effects: Systemic

DNEL - General population - Long term - Dermal

102 mg/kg bw/day Effects: Systemic

DNEL - Workers - Long term - Dermal

240 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Inhalation

0.021 mg/m³ Effects: Local

DNEL - Workers - Long term - Inhalation

0.021 mg/m³ Effects: Local

DNEL - General population - Long term - Oral

0.027 mg/kg bw/day Effects: Systemic

DNEL - General population - Short term - Inhalation

0.043 mg/m³ Effects: Local

DNEL - Workers - Short term - Inhalation

0.043 mg/m³ Effects: Local

DNEL - General population - Short term - Oral

0.053 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Inhalation

0.02 mg/m³ Effects: Local

DNEL - Workers - Long term - Inhalation

0.02 mg/m³ Effects: Local

DNEL - General population - Short term - Inhalation

0.04 mg/m³ Effects: Local

DNEL - Workers - Short term - Inhalation

0.04 mg/m³ Effects: Local

DNEL - General population - Long term - Oral

0.09 mg/kg bw/day Effects: Systemic

DNEL - General population - Short term - Oral

Label No : 91014

0.11 mg/kg bw/day

Date of issue/Date of revision : 22/04/2025 Date of previous issue : 29/09/2022 Version : 2 7/19

SECTION 8: Exposure controls/personal protection

Effects: Systemic

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls

 Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations: Wear suitable gloves tested to EN374.

> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm Not recommended polyvinyl alcohol (PVA) gloves

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type (spray application): A P

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Label No : 91014

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state: Liquid.Colour: Clear.Odour: Slight

Date of issue/Date of revision : 22/04/2025 Date of previous issue : 29/09/2022 Version : 2 8/19

SECTION 9: Physical and chemical properties

Odour threshold : Not available.

Melting point/freezing point : Not available.

Initial boiling point and boiling range

limit

:

Ingredient name	°C	°F	Method
water	100	212	
2-(2-butoxyethoxy)ethanol	225 to 227.6	437 to 441.7	

Flammability : Not available.

Lower and upper explosion

: Lower: 0.8% (2-(2-butoxyethoxy)ethanol) Upper: 9.4% (2-(2-butoxyethoxy)ethanol)

Flash point : Closed cup: >100°C (>212°F)

Auto-ignition temperature

Ingredient name	°C	°F	Method
2-2-butoxyethoxy)ethanol	210	410	DIN 51794
Dipentaerythritol	>400	>752	EU A.16

Decomposition temperature: Not available.

PH : **6** to 9 [Conc. (% w/w): 100%]

Viscosity : Not available.

Solubility(ies) :

Not available.

Solubility in water : Not available.

Partition coefficient: n-octanol/ : Not applicable.

water

Vapour pressure :

	Vapour Pressure at 20°C			Vapour pressure at 50°C			
Ingredient name	mm Hg kPa I		Method	mm Hg	kPa	Method	
water	17.5	2.3					
2-(2-butoxyethoxy)ethanol	0.022	0.0029					

Relative density : Not available.

Density : 1.2 g/cm³

Vapour density : Not available.

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties : Not available.

Oxidising properties : Not available.

9.2.2 Other safety characteristics

Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of : Under normal conditions of storage and use, hazardous reactions will not occur.
 hazardous reactions

Date of issue/Date of revision : 22/04/2025 Date of previous issue : 29/09/2022 Version : 2 9/19

TEKNOSAFE FLAME GUARD 2477-00 - CLEAR Label No : 971014

SECTION 10: Stability and reactivity

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name Result

2-(2-butoxyethoxy)ethanol Rabbit - Dermal - LD50

2700 mg/kg

Rat - Oral - LD50 4500 mg/kg

Toxic effects: Behavioral - Tetany Lung, Thorax, or Respiration

- Dyspnea Liver - Other changes

Formaldehyde Rat - Oral - LD50

100 mg/kg

Rabbit - Dermal - LD50

270 mg/kg

Rat - Inhalation - LC50 Gas.

250 ppm [4 hours]

2-methyl-2H-isothiazol-3-one Rat - Inhalation - LC50 Dusts and mists

0.11 mg/l [4 hours]

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no.

220-239-6] (3:1)

Rat - Oral - LD50

53 mg/kg

<u>Toxic effects</u>: Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration -

Label No : 91014

Respiratory depression

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
2 -(2-butoxyethoxy)ethanol	4500	2700	N/A	N/A	N/A
Formaldehyde	100	300	700	N/A	N/A
2-methyl-2H-isothiazol-3-one	100	300	N/A	N/A	0.11
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-	53	50	N/A	0.5	N/A
3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)					

Skin corrosion/irritation

Product/ingredient name Result

Date of issue/Date of revision : 22/04/2025 Date of previous issue : 29/09/2022 Version : 2 10/19

SECTION 11: Toxicological information

Formaldehyde

Human - Skin - Mild irritant

<u>Duration of treatment/exposure</u>: 72 hours <u>Amount/concentration applied</u>: 150 ug I

Human - Skin - Severe irritant

Amount/concentration applied: 0.01 %

Rabbit - Skin - Mild irritant

Amount/concentration applied: 540 mg

Rabbit - Skin - Moderate irritant

<u>Duration of treatment/exposure</u>: 24 hours Amount/concentration applied: 50 mg

Rabbit - Skin - Severe irritant

<u>Duration of treatment/exposure</u>: 24 hours Amount/concentration applied: 2 mg

Rabbit - Skin - Severe irritant

Amount/concentration applied: 0.8 %

Mouse - Skin - Moderate irritant Amount/concentration applied: 7 %

Rat - Skin - Moderate irritant
Amount/concentration applied: 7 %

Human - Skin - Severe irritant

Amount/concentration applied: 0.01 %

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Conclusion/Summary [Product]: Not available.

Serious eye damage/eye irritation

Product/ingredient name

2-(2-butoxyethoxy)ethanol

Result

Rabbit - Eyes - Moderate irritant

<u>Duration of treatment/exposure</u>: 24 hours <u>Amount/concentration applied</u>: 20 mg

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 20 mg

Formaldehyde Human - Eyes - Mild irritant

<u>Duration of treatment/exposure</u>: 6 minutes <u>Amount/concentration applied</u>: 1 ppm

Rabbit - Eyes - Severe irritant

<u>Duration of treatment/exposure</u>: 24 hours <u>Amount/concentration applied</u>: 750 ug

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 750 ug

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 37 %

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 10 mg

Mouse - Eyes - Moderate irritant

Amount/concentration applied: 3 %

Conclusion/Summary [Product]: Not available.

Date of issue/Date of revision: 22/04/2025Date of previous issue: 29/09/2022Version: 211/19TEKNOSAFE FLAME GUARD 2477-00 - CLEARLabel No : 91014

SECTION 11: Toxicological information

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product]: Not available.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product]: Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product]: Not available.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name Result

Formaldehyde STOT SE 3, H335 (Respiratory tract irritation)

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure

Not available.

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

Skin contact: May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness

Date of issue/Date of revision : 22/04/2025 Date of previous issue : 29/09/2022 Version : 2 12/19

TEKNOSAFE FLAME GUARD 2477-00 - CLEAR Label No : 971014

SECTION 11: Toxicological information

Ingestion: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects: Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

General: Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine

disrupting properties according to the criteria set out in either Regulation (EC)

No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name

2-(2-butoxyethoxy)ethanol

Result

Acute - LC50 - Fresh water

Fish - Bluegill - Lepomis macrochirus

<u>Size</u>: 33 to 75 mm 1300000 µg/l [96 hours]

Effect: Mortality

Formaldehyde Acute - EC50 - Fresh water

Daphnia - Water flea - Daphnia pulex - Neonate

Age: <24 hours 5800 µg/l [48 hours] Effect: Intoxication

Acute - EC50 - Marine water

Algae - Green algae - Ulva pertusa

0.788 mg/l [96 hours] Effect: Reproduction

Acute - LC50 - Fresh water

US EPA

Fish - Rainbow trout, donaldson trout - Oncorhynchus mykiss

1.41 ppm [96 hours] Effect: Mortality

Chronic - NOEC - Fresh water

Fish - Chinook salmon - Oncorhynchus tshawytscha - Egg

Label No : 91014

953.9 ppm [43 days] Effect: Mortality

Date of issue/Date of revision : 22/04/2025 Date of previous issue : 29/09/2022 Version : 2 13/19

SECTION 12: Ecological information

Chronic - NOEC - Marine water

Algae - Haptophyte - Isochrysis galbana - Exponential growth

phase

Age: 4 to 5 days 0.005 mg/l [96 hours] Effect: Population

2-methyl-2H-isothiazol-3-one

Acute - EC50 - Fresh water

US EPA

Daphnia - Water flea - Daphnia magna

Age: <24 hours 0.18 ppm [48 hours] Effect: Intoxication

Acute - LC50 - Fresh water

US EPA

Fish - Rainbow trout, donaldson trout - Oncorhynchus mykiss

Weight: 0.73 g 0.07 ppm [96 hours] Effect: Mortality

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Not available.

Conclusion/Summary [Product]: Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-(2-butoxyethoxy)ethanol	1	-	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logKoc	Koc
2-(2-butoxyethoxy)ethanol	1.56	36.5981
2-methyl-2H-isothiazol-3-one	1.74	54.9187

Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
midazo[4,5-d]imidazole-2,5 (1H,3H)-dione, tetrahydro-, polymer with formaldehyde, butylated	No	No	No	No	No	No	No
2-(2-butoxyethoxy)ethanol	No	No	No	No	No	No	No
Formaldehyde	No	No	No	No	No	No	No
2-methyl-2H-isothiazol-3-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No

Mobility : Not available.

Conclusion/Summary: The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment Regulation (EC) No. 1907/2006 [REACH]

Date of issue/Date of revision: 22/04/2025Date of previous issue: 29/09/2022Version: 214/19TEKNOSAFE FLAME GUARD 2477-00 - CLEARLabel No : 91014

SECTION 12: Ecological information

Product/ingredient name	PBT	P	В	T	vPvB	vP	vB
midazo[4,5-d]imidazole-2,5 (1H,3H)-dione, tetrahydro-, polymer with formaldehyde, butylated	No	No	No	No	No	No	No
2-(2-butoxyethoxy)ethanol	No	No	No	No	No	No	No
Formaldehyde	No	No	No	No	No	No	No
2-methyl-2H-isothiazol-3-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	Р	В	Т	vPvB	vP	vB
midazo[4,5-d]imidazole-2,5 (1H,3H)-dione, tetrahydro-, polymer with formaldehyde, butylated	No	No	No	No	No	No	No
2-(2-butoxyethoxy)ethanol	No	No	No	No	No	No	No
Formaldehyde	No	No	No	No	No	No	No
2-methyl-2H-isothiazol-3-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP]

: The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product]

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

European waste catalogue (EWC)

Packaging

: 080112

Date of issue/Date of revision : 22/04/2025 Date of previous issue · 29/09/2022 Version : 2 15/19 Label No : 91014

SECTION 13: Disposal considerations

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
FEKNOSAFE FLAME GUARD 2477-00 2-(2-butoxyethoxy)ethanol Formaldehyde	≥90 ≤3 <0.1	3 55 [Consumer paint] 72

Labelling

Other EU regulations

Industrial emissions (integrated pollution prevention and control) - : Not listed

Air

Date of issue/Date of revision · 29/09/2022 Version : 2 16/19 : 22/04/2025 Date of previous issue Label No : 91014

SECTION 15: Regulatory information

: Not listed **Industrial emissions**

(integrated pollution prevention and control) -

Water

Explosive precursors : Not applicable. Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety

assessment

: This product contains substances for which Chemical Safety Assessments are still

required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/20081

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent. Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification	
Skin Sens. 1, H317	Calculation method	

Full text of abbreviated H statements

Date of issue/Date of revision · 29/09/2022 Version : 2 17/19 : 22/04/2025 Date of previous issue Label No : 91014

SECTION 16: Other information

⊮ 301	Toxic if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 4	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4
Carc. 1B	CARCINOGENICITY - Category 1B
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Muta. 2	GERM CELL MUTAGENICITY - Category 2
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of issue/ Date of : 22/04/2025

revision

Date of previous issue : 29/09/2022

Version 2

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision : 22/04/2025 Date of previous issue : 29/09/2022 Version : 2 18/19 **Label No** : 91014

Date of issue/Date of revision: 22/04/2025Date of previous issue: 29/09/2022Version: 219/19

Label No : 91014