Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Ireland

SAFETY DATA SHEET



TEKNOSEAL 4002-00 - COLOURLESS

 $\overline{}$

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

-	
1.1 Product identifier	
Product name	: FEKNOSEAL 4002-00 - COLOURLESS
1.2 Relevant identified	uses of the substance or mixture and uses advised against
Product use	: Paint.
1.3 Details of the suppl	ier of the safety data sheet
Peknos Group Oy, Takł	atie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.
e-mail address of pers	son : Prod-safe@teknos.com
responsible for this S	DS
National contact	
🔽 eknos Group Oy, Takl	catie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.
1.4 Emergency telepho	ne number
National advisory bod	<u>y/Poison Centre</u>
Telephone number	: Mational Poisons Information Centre: 01 809 2566
SECTION 2: Haza	ards identification
2.1 Classification of the	substance or mixture
Product definition	: Mixture
	ng to Regulation (EC) No. 1272/2008 [CLP/GHS]
Aquatic Chronic 3, H41	2
The product is classified	as hazardous according to Regulation (EC) 1272/2008 as amended.
See Section 16 for the f	ull text of the H statements declared above.
See Section 11 for more	e detailed information on health effects and symptoms.
2.2 Label elements	
Signal word	: No signal word.

Signal word	1	No signal word.
Hazard statements	1	₩412 - Harmful to aquatic life with long lasting effects.
Precautionary statements		
Prevention	1	₱273 - Avoid release to the environment.
Response	1	Not applicable.
Storage	1	Not applicable.
Disposal	1	₱501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	Contains adipohydrazide, 3-iodo-2-propynyl-butyl carbamate, 1,2-benzisothiazol-3 (2H)-one, 2-methyl-2H-isothiazol-3-one and 2-Methyl-1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Contains biocidal products for dry film and in-can preservation: IPBC and BIT and DTBMA and MBIT. Risk of skin sensitisation.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	

: 19/10/2022 Date of previous issue

SECTION 2: Hazards identification

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII Other hazards which do not result in classification

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures Product/ingredient name	: Mixture	%	Classification	Specific Conc. Limits, M-factors	Туре
ℬ-Butoxypropan-2-ol	REACH #: 01-2119475527-28 EC: 225-878-4 CAS: 5131-66-8 Index: 603-052-00-8	≤3	Skin Irrit. 2, H315 Eye Irrit. 2, H319	and ATEs -	[1]
adipohydrazide	EC: 213-999-5 CAS: 1071-93-8	<1	Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
3-iodo-2-propynyl-butyl carbamate	EC: 259-627-5 CAS: 55406-53-6 Index: 616-212-00-7	≤0.3	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 400 mg/kg ATE [Inhalation (dusts and mists)] = 0.67 mg/l M [Acute] = 10 M [Chronic] = 1	[1]
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400	ATE [Oral] = 1020 mg/kg Skin Sens. 1, H317: C ≥ 0.05% M [Acute] = 1	[1]
2-methyl-2H-isothiazol- 3-one	EC: 220-239-6 CAS: 2682-20-4	<0.0015	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (dusts and mists)] = 0.11 mg/l Skin Sens. 1, H317: C \geq 0.0015% M [Acute] = 10 M [Chronic] = 1	[1]
2-Methyl-1,2-benzisothiazol- 3(2H)-one	CAS: 2527-66-4 Index: 613-336-00-3	<0.0015	Acute Tox. 3, H301 Acute Tox. 4, H312 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411 EUH071	ATE [Oral] = 175 mg/kg ATE [Dermal] = 1100 mg/kg Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 1	[1]
Date of issue/Date of revision	: 19/10/2022 Date	e of previous i	ssue : 03/03/2020	Version : 1.02	2 2/15

SECTION 3: Composition/information on ingredients See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

7 Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

I.1 Description of first aid measures				
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.			
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing.			
Skin contact	: Fush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.			
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel.			
Protection of first-aiders	: \mathbf{N} o action shall be taken involving any personal risk or without suitable training.			

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: 📈 specific data.
Skin contact	: 📈 specific data.
Ingestion	: 🛛 No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: F reat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	: $ ot\!$
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising f	rom the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide

5.3 Advice for firefighters

SECTION 5: Firefighting measures

-	-
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures				
Image: Mo action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.				
If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".				
: Kvoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.				
containment and cleaning up				
: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.				
: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.				
: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.				

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Fut on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Fating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Date of issue/Date of revision	: 19/10/2022	Date of previous issue	: 03/03/2020	Version : 1.02 4/15
FEKNOSEAL 4002-00 - COLOUR	LESS			Label No :38866

SECTION 7: Handling and storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

Recommendations

: Not available.

Industrial sector specific solutions

: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
No exposure limit value known.	
· · · · ·	ontains ingredients with exposure limits, personal, workplace

atmosphere or biological monitoring may be required to determine the effectiveness procedures of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
3-Butoxypropan-2-ol	DNEL	Long term Oral	8.75 mg/	General	Systemic
	DNEL	Long term Dermal	kg bw/day 16 mg/kg bw/day	population General population	Systemic
	DNEL	Long term Inhalation	33.8 mg/m ³		Systemic
	DNEL	Long term Dermal	44 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	50 %	General population	Local
	DNEL	Long term Dermal	50 %	General population	Local
	DNEL	Short term Dermal	50 %	Workers	Local
	DNEL	Long term Dermal	50 %	Workers	Local
	DNEL	Long term Inhalation	147 mg/m³	Workers	Systemic
adipohydrazide	DNEL	Long term Inhalation	8.6 mg/m³	Workers	Systemic
3-iodo-2-propynyl-butyl carbamate	DNEL	Long term Inhalation	0.023 mg/ m³	Workers	Systemic
	DNEL	Short term Inhalation	0.07 mg/m³	Workers	Systemic
	DNEL	Short term Inhalation	1.16 mg/m³	Workers	Local
	DNEL	Long term Inhalation	1.16 mg/m ³	Workers	Local
e of issue/Date of revision : 19/1	0/2022	Date of previous issue	: 03/03/20	020 Ve	rsion : 1.02 5/15

FEKNOSEAL 4002-00 - COLOURLESS

	DNEL	Long term Dermal	2 mg/kg bw/day	Workers	Systemic
1,2-benzisothiazol-3(2H)-one	DNEL	Long term Dermal	0.345 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.966 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.2 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	6.81 mg/m³		Systemic
2-methyl-2H-isothiazol-3-one	DNEL	Long term Inhalation	0.021 mg/ m³	General population	Local
	DNEL	Long term Inhalation	0.021 mg/ m³	Workers	Local
	DNEL	Long term Oral	0.027 mg/ kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	0.043 mg/ m ³	General population	Local
	DNEL	Short term Inhalation	0.043 mg/ m³	Workers	Local
	DNEL	Short term Oral	0.053 mg/ kg bw/day	General population	Systemic

PNECs

No PNECs available

8.2 Exposure controls	
Appropriate engineering controls	: Sood general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection meas	<u>ures</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
	Recommendations : Wear suitable gloves tested to EN374.
	> 8 hours (breakthrough time): Mitrile gloves. thickness > 0.3 mm
	Not recommended polyvinyl alcohol (PVA) gloves
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Repropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

SECTION 8: Exposure controls/personal protection

	· ·
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
	Filter type (spray application): 🛛 📈 P
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state	: 🗾 Iquid.
Colour	: 🖉 olourless.
Odour	: <mark>S</mark> light
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and	:
boiling range	

Ingredient name	°C	°F	Method
water	100	212	
3-Butoxypropan-2-ol	171	339.8	OECD 103

Flammability	: Not available.
--------------	------------------

Lower and upper explosion : Kower: Not applicable.

Upper: Not applicable.

ŝ,

Flash point

limit

: Ølosed cup: >100°C (>212°F)

Auto-ignition temperature

Ingredient name	°C	°F	Method
<mark>β-</mark> Butoxypropan-2-ol	260	500	EU A.15
2,2,4-trimethylpentane-1,3-diol isobutyrate	393	739.4	

Decomposition temperature	4	Not available.
рН	:	Not available.
Viscosity	:	Not available.
Solubility(ies)	:	
Not available.		
Solubility in water	:	Not available.
Partition coefficient: n-octanol/	÷	Not applicable.

Vapour pressure

water

	Vapour Pressure at 20°C			Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
water	23.8	3.2				
3-Butoxypropan-2-ol	1.05	0.14	OECD 104			
Relative density	: Not	available.	<u>-</u>			
Density	: <mark>1</mark> /g/	′cm³				
/apour density	: Not	available.				
Explosive properties	: Not	available.				
te of issue/Date of revision	: 19/10/2	2022 Date o	of previous issue	: 03/03/2020		Version : 1.02 7/2

FEKNOSEAL 4002-00 - COLOURLESS

SECTION 9: Physical and chemical properties

Oxidising properties	: Not available.
Particle characteristics	
Median particle size	: Not applicable.

SECTION 10: Stability and reactivity					
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.				
10.2 Chemical stability	: The product is stable.				

10.3 Possibility of hazardous reactions	: 🗾 Moder normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.

10.5 Incompatible materials	: No specific data.
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
♂-Butoxypropan-2-ol	LD50 Dermal	Rabbit	3100 mg/kg	-
3-iodo-2-propynyl-butyl carbamate	LC50 Inhalation Dusts and mists	Rat	0.67 g/m³	4 hours
	LC50 Inhalation Dusts and mists	Rat	0.763 mg/l	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	400 mg/kg	-
1,2-benzisothiazol-3(2H)- one	LD50 Oral	Rat	1020 mg/kg	-
2-methyl-2H-isothiazol- 3-one	LC50 Inhalation Dusts and mists	Rat	0.11 mg/l	4 hours

Acute toxicity estimates

Route	ATE value
halation (dusts and mists)	223.96 mg/l

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Butoxypropan-2-ol 3-iodo-2-propynyl-butyl carbamate	Skin - Moderate irritant Eyes - Severe irritant	Rabbit Rabbit	-	-	-
1,2-benzisothiazol-3(2H)-one	Skin - Mild irritant	Human	-	48 hours 5 %	-

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
了iodo-2-propynyl-butyl carbamate	skin	Guinea pig	Not sensitizing
Conclusion/Summary	: Based on available data, the classification criteria are not met.		

Mutagenicity

Date of issue/Date of revision	: 19/10/2022	Date of previous issue	: 03/03/2020	Version	:1.02	8/15
KNOSEAL 4002-00 - COLOUR	LESS			Label No :	38866	3

SECTION 11: Toxicological information Product/ingredient name Test Experiment Result Image: Side 2-propynyl-butyl carbamate Experiment: In vitro Subject: Bacteria Negative Conclusion/Summary : Fased on available data, the classification criteria are not met. Carcinogenicity

: Based on available data, the classification criteria are not met.

Conclusion/Summary

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
riodo-2-propynyl-butyl carbamate	Negative	-	Negative	Rabbit - Female	Oral: 20 mg/kg	13 days; 7 days per week
	Positive	-	Negative	Rabbit - Female	Oral: 50 mg/kg	13 days; 7 days per week

Conclusion/Summary : **B** ased on available data, the classification criteria are not met.

Teratogenicity

Product/ingredient name	Result	Species	Dose	Exposure
了iodo-2-propynyl-butyl carbamate	Negative - Oral	Rabbit - Female	50 mg/kg	-

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Ĩodo-2-propynyl-butyl carbamate	Category 1	-	larynx

Aspiration hazard

Not available.

Information on likely routes of exposure	: Not available.	
Potential acute health effects	<u>s</u>	
Eye contact	: No known significant effects or critical hazards.	
Inhalation	: No known significant effects or critical hazards.	
Skin contact	: No known significant effects or critical hazards.	
Ingestion	: No known significant effects or critical hazards.	
Symptoms related to the phy	vsical, chemical and toxicological characteristics	
Eye contact	: No specific data.	
Inhalation	: No specific data.	
Skin contact	: No specific data.	
Ingestion	: 📈 specific data.	
Delayed and immediate effect	cts as well as chronic effects from short and long-term expo	<u>osure</u>
Short term exposure		
Potential immediate effects	: Not available.	
Potential delayed effects	: Not available.	
Long term exposure		
Date of issue/Date of revision	: 19/10/2022 Date of previous issue : 03/03/2020	Version : 1.02 9/15
FEKNOSEAL 4002-00 - COLO	DURLESS	Label No :38866

SECTION 11: Toxicological information

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	ects
Not available.	
Conclusion/Summary	: Not available.
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting propertiesNot available.11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
3-iodo-2-propynyl-butyl	Acute EC50 0.022 mg/l Fresh water	Algae - Scenedemus	72 hours
carbamate	-	subspicatus	
	Acute EC50 0.16 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 0.067 mg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute NOEC 0.049 mg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 0.05 mg/l Fresh water	Daphnia - Daphnia Magna	21 days
1,2-benzisothiazol-3(2H)-one	Acute EC50 0.36 mg/l Marine water	Algae - Skeletonema Costatum	72 hours
	Acute EC50 3.7 mg/l	Daphnia - Daphnia Magna	48 hours
	Acute LC50 1.9 mg/l Fresh water	Fish - Onorhynchus Mykiss	96 hours
	Acute NOEC 0.15 mg/I Marine water	Algae - Skeletonema Costatum	72 hours
2-methyl-2H-isothiazol-3-one	Acute EC50 0.18 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 0.07 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
2-Methyl-1,2-benzisothiazol- 3(2H)-one	Acute EC50 0.22 ppm Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 0.92 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 0.24 ppm Fresh water	Fish - Oncorhynchus mykiss -	96 hours
		Juvenile (Fledgling, Hatchling, Weanling)	
	Chronic NOEC 0.16 ppm	Fish - Pimephales promelas	32 days

Conclusion/Summary : Farmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Product/ingredient name	Test	Result		Dose	Inoculum
7,2-benzisothiazol-3(2H)-one	EU	24 % - 28 days		-	-
Conclusion/Summary : This product has not been tested for biodegradation.					
Product/ingredient name	Aquatic half-life		Photolysis	\$	Biodegradability
Giodo-2-propynyl-butyl carbamate 1,2-benzisothiazol-3(2H)-one	-		-		Not readily Inherent

12.3 Bioaccumulative potential

SECTION 12: Ecological information						
Product/ingredient name LogPow BCF Potential						
 Butoxypropan-2-ol 3-iodo-2-propynyl-butyl carbamate 	1.2 >1	-	low low			
	Carbanate1,2-benzisothiazol-3(2H)-one-3.2Iow					

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment meth	nods
Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
European waste catalogue (EWC)	: Ø80111*
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil waterways drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name				F
14.3 Transport hazard class(es)				
Date of issue/Date of re	vision : 19/10/2	022 Date of previous issu	e : 03/03/2020	Version : 1.02 11/
KNOSEAL 4002-	Label No :38866			

SECTION 14: 14.4 Packing				
group	Þ			P
14.5 Environmental hazards	N o.	N o.	No.	No.
14.6 Special preca user	up		e that persons transport	port in closed containers that are ing the product know what to do i
14.7 Maritime trans bulk according to l instruments	MO		e to nature of the produ	ct.
SECTION 15:				
15.1 Safety, health EU Regulation (E			tion specific for the su	ubstance or mixture
	-	ubject to authorisatio	n	
Annex XIV	nponents are liste		-	
	very high conce			
on the manufact placing on the m and use of certa dangerous subs mixtures and art	narket in tances,			
Other EU regulati Industrial emiss (integrated pollu prevention and o	ions : Mo ition	ot listed		
Air Industrial emiss (integrated pollu prevention and o Water	ition	t listed		
Ozone depleting	<u>substances (10</u>	<u>05/2009/EU)</u>		
Prior Informed C	Concont (PIC) (64	19/2012/EUI)		
Not listed.	<u>, (04</u>			
Persistent Organ Not listed.	nic Pollutants			
International regu	ot controlled unde <u>Ilations</u>	r the Seveso Directive.		
Chemical Weapon Not listed.	n Convention Lis	<u>st Schedules I, II & III C</u>	<u>Chemicals</u>	
Montreal Protoco Not listed.	<u>1</u>			
	ution on Develot	ent Organic Pollutant	.	

Stockholm Convention on Persistent Organic Pollutants

SECTION 15: Regulatory information

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety	÷	This product contains substances for which Chemical Safety Assessments are still
assessment		required.

SECTION 16: Other information

Indicates information	on that has changed from previously issued version.
Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification	
Aquatic Chronic 3, H412	Calculation method	

Full text of abbreviated H statements

⊮ 301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

Acute Tox. 2	ACUTE TOXICITY - Category 2	
Acute Tox. 3	ACUTE TOXICITY - Category 3	
Acute Tox. 4	ACUTE TOXICITY - Category 4	
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1	
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1	
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2	
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3	
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1	
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2	
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B	
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C	
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2	
Skin Sens. 1	SKIN SENSITISATION - Category 1	
Date of issue/Date of rev	ision : 19/10/2022 Date of previous issue : 03/03/2020	Version : 1.02 13/15

SECTION 16: Other information	
Skin Sens. 1A STOT RE 1	SKIN SENSITISATION - Category 1A SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
Date of issue/ Date of revision	: 19/10/2022
Date of previous issue	: 03/03/2020
Version	: 1.02
	KNOSEAL 4002-00_COLOURLESS

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision: 19/10.FEKNOSEAL 4002-00 - COLOURLESS

: 19/10/2022 Date of previous issue

:03/03/2020

Version : 1.02 15/15 Label No : 38866