Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Ireland

SAFETY DATA SHEET



TEKNOSEAL 4002-10 - TS 0050 CLEAR

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product	identifier	

Product name : TEKNOSEAL 4002-10 - TS 0050 CLEAR

1.2 Relevant identified uses of the substance or mixture and uses advised against Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091. e-mail address of person : Prod-safe@teknos.com responsible for this SDS

National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number

 Emergency medical information: (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland.
 Members of the public Number (8 am-10 pm): +353 (0)1 809 2166 Healthcare professional telephone Number (24hrs): +353 (0)1 809 2566

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

: Mixture

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements	
Signal word	: No signal word.
Hazard statements	: H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements	
Prevention	: P273 - Avoid release to the environment.
Response	: Not applicable.
Storage	: Not applicable.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	 Contains adipohydrazide, 3-iodo-2-propynyl-butyl carbamate, 1,2-benzisothiazol-3 (2H)-one and 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction. Contains biocidal products for dry film and in-can preservation: IPBC and BIT and 2,2'-dithiobis[N-methylbenzamide] and MBIT. Risk of skin sensitisation.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:
2.3 Other hazards	
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
2-Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	≤3	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	ATE [Oral] = 1200 mg/kg ATE [Inhalation (vapours)] = 3 mg/l	[1] [2]
adipohydrazide	REACH #: 01-2119962900-36 EC: 213-999-5 CAS: 1071-93-8	<1	Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
3-iodo-2-propynyl-butyl carbamate	EC: 259-627-5 CAS: 55406-53-6 Index: 616-212-00-7	<1	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 400 mg/kg ATE [Inhalation (dusts and mists)] = 0.67 mg/l M [Acute] = 10 M [Chronic] = 1	[1]
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.036	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 450 mg/kg ATE [Inhalation (dusts and mists)] = 0.21 mg/l Skin Sens. 1, H317: C $\ge 0.036\%$ M [Acute] = 1 M [Chronic] = 1	[1]
2-methyl-2H-isothiazol- 3-one	EC: 220-239-6 CAS: 2682-20-4 Index: 613-326-00-9	<0.0015	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (dusts and mists)] = 0.11 mg/l Skin Sens. 1, H317: C $\geq 0.0015\%$ M [Acute] = 10 M [Chronic] = 1	[1]
Date of issue/Date of revision	: 14/04/2025 Date	e of previous is	sue : 25/10/2023	Version : 2	2/18
TEKNOSEAL 4002-10 - TS (Label No :1128	875

SECTION 3: Composition/information on ingredients See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures			
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.		
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.		
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. 		
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel.		
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.		

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms			
Eye contact	: No specific data.		
Inhalation	: No specific data.		
Skin contact	: No specific data.		
Ingestion	: No specific data.		

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising	from the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides

Date of issue/Date of revision	: 14/04/2025	Date of previous issue	: 25/10/2023	Version	:2	3/18
TEKNOSEAL 4002-10 - TS 0050 (CLEAR			Label No	: <mark>1</mark> 128	375

SECTION 5: Firefighting measures

5.3 Advice for firefighters Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

SECTION 7: Handling and storage

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

: Not available.

Recommendations Industrial sector specific solutions

: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
2-Butoxyethanol	 NAOSH (Ireland, 4/2024) Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values OELV 8 hours: 20 ppm. OELV 8 hours: 98 mg/m³. OELV 15 minutes: 50 ppm. OELV 15 minutes: 246 mg/m³.

Biological exposure indices

Product/ingredient na	ame Exposure indices
2-Butoxyethanol	NAOSH (Ireland, 1/2011) BMGV: 200 mg/g creatinine, BAA [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases.
procedures a c c f	Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 Workplace atmospheres - General requirements for the performance of procedures or the measurement of chemical agents) Reference to national guidance locuments for methods for the determination of hazardous substances will also be equired.
DNELs/DMELs	
Product/ingredient name	Result
₽-Butoxyethanol	DNEL - General population - Long term - Oral 6.3 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Short term - Oral 26.7 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Long term - Inhalation 59 mg/m ³ <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Inhalation 98 mg/m³ <u>Effects</u> : Systemic

25 Date of previous issue

: 25/10/2023

SECTION 8: Exposure controls/personal protection		
	DNEL - General population - Short term - Inhalation 147 mg/m ³ Effects: Local	
	DNEL - Workers - Short term - Inhalation 246 mg/m³ <u>Effects</u> : Local	
	DNEL - General population - Short term - Inhalation 426 mg/m ³ <u>Effects</u> : Systemic	
	DNEL - Workers - Short term - Inhalation 1091 mg/m³ <u>Effects</u> : Systemic	
adipohydrazide	DNEL - Workers - Long term - Inhalation 17.5 mg/m³ <u>Effects</u> : Systemic	
3-iodo-2-propynyl-butyl carbamate	DNEL - Workers - Long term - Inhalation 0.023 mg/m ³ Effects: Systemic	
	DNEL - Workers - Short term - Inhalation 0.07 mg/m ³ Effects: Systemic	
	DNEL - Workers - Short term - Inhalation 1.16 mg/m³ <u>Effects</u> : Local	
	DNEL - Workers - Long term - Inhalation 1.16 mg/m³ <u>Effects</u> : Local	
	DNEL - Workers - Long term - Dermal 2 mg/kg bw/day <u>Effects</u> : Systemic	
1,2-benzisothiazol-3(2H)-one	DNEL - General population - Long term - Dermal 0.345 mg/kg bw/day <u>Effects</u> : Systemic	
	DNEL - Workers - Long term - Dermal 0.966 mg/kg bw/day <u>Effects</u> : Systemic	
	DNEL - General population - Long term - Inhalation 1.2 mg/m ³ <u>Effects</u> : Systemic	
	DNEL - Workers - Long term - Inhalation 6.81 mg/m ³ Effects: Systemic	
2-methyl-2H-isothiazol-3-one	DNEL - General population - Long term - Inhalation 0.021 mg/m ³ <u>Effects</u> : Local	
	DNEL - Workers - Long term - Inhalation 0.021 mg/m ³ Effects: Local	
	DNEL - General population - Long term - Oral	

SECTION 8: Exposure controls/personal protection

0.027 mg/kg bw/day Effects: Systemic

DNEL - General population - Short term - Inhalation 0.043 mg/m³ Effects: Local

DNEL - Workers - Short term - Inhalation 0.043 mg/m³ Effects: Local

DNEL - General population - Short term - Oral 0.053 mg/kg bw/day <u>Effects</u>: Systemic

PNECs

Not available.

8.2 Exposure controls			
Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.		
Individual protection meas	ures		
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.		
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.		
Skin protection			
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.		
	Recommendations : Wear suitable gloves tested to EN374.		
	> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm		
	Not recommended polyvinyl alcohol (PVA) gloves		
Body protection	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.		
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.		
Respiratory protection	 Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Filter type (spray application): A P 		

SECTION 8: Exposure controls/personal protection

Environmental exposure
controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Colour	: Clear.
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	:

Ingredient name		°C	°F	Method	
water		100	212		
2-Butoxyethanol		171 to 171.5	339.8 to 340.7	IP 123-93	
Flammability : Not available.		ilable.	·		
Lower and upper explosion		Not applicable.			

limit	Upper: Not applicable.		
Flash point	: Closed cup: >100°C (>212°F)		

ŝ

ŝ

Auto-ignition temperature

Ingredient name	°C	°F	Method
Propanol, 1-(2-butoxy-1-methylethoxy)	194	381.2	EU A.15
2-Butoxyethanol	230	446	DIN 51794

Decomposition temperature	: Not available.
рН	: ₿ to 8.4 [Conc. (% w/w): 100%]
Viscosity	: Not available.
Solubility(ies)	:
Not available.	
Solubility in water	: Not available.
Partition coefficient: n-octanol/ water	: Not applicable.

Vapour pressure

	Va	Vapour Pressure at 20°C			Vapour pressure at 50°C			
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method		
water	17.5	2.3						
2-Butoxyethanol	0.75006	0.1						
Relative density	: Not	available.			ł			
Density	: 1 g/	cm³						
/apour density	: Not	available.						
Particle characteristics								
Median particle size	: Not	applicable.						

9.2.1 Information with regard to physical hazard classes

Explosive properties : Not available.

Date of issue/Date of revision : 14/04/2025 Date of previous issue

SECTION 9: Physical and chemical properties

Oxidising properties

ties : Not available.

9.2.2 Other safety characteristics Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	:	The product is stable.
10.3 Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	:	No specific data.
10.5 Incompatible materials	:	No specific data.
10.6 Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined	in Regulation (EC) No 1272/2008
Acute toxicity	
Product/ingredient name	Result
3-iodo-2-propynyl-butyl carbamate	Rat - Oral - LD50 400 mg/kg
	Rat - Dermal - LD50 >2000 mg/kg
	Rat - Inhalation - LC50 Dusts and mists 0.763 mg/l [4 hours]
	Rat - Inhalation - LC50 Dusts and mists 0.67 g/m ³ [4 hours]
1,2-benzisothiazol-3(2H)-one	Rat - Oral - LD50 1020 mg/kg
2-methyl-2H-isothiazol-3-one	Rat - Inhalation - LC50 Dusts and mists 0.11 mg/l [4 hours]

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
FEKNOSEAL 4002-10	100932.8	N/A	N/A	252.3	223.3
2-Butoxyethanol	1200	N/A	N/A	3	N/A
3-iodo-2-propynyl-butyl carbamate	400	N/A	N/A	N/A	0.67
1,2-benzisothiazol-3(2H)-one	450	N/A	N/A	N/A	0.21
2-methyl-2H-isothiazol-3-one	100	300	N/A	N/A	0.11

Skin corrosion/irritation

Prod	luct/i	narec	lient	name

Result

2 Putersulathered		Dobbit Ckin Mild instant
2-Butoxyethanol		Rabbit - Skin - Mild irritant Amount/concentration applied: 500 mg
1,2-benzisothiazol-3(2H)-one		Human - Skin - Mild irritant Duration of treatment/exposure: 48 hours Amount/concentration applied: 5 %
Conclusion/Summary [Product]	: Not available	e.
Serious eye damage/eye irritation		
Product/ingredient name		Result
2-Butoxyethanol		Rabbit - Eyes - Moderate irritant
		Duration of treatment/exposure: 24 hours
		Amount/concentration applied: 100 mg
		Rabbit - Eyes - Severe irritant Amount/concentration applied: 100 mg
3-iodo-2-propynyl-butyl carbamate		Rabbit - Eyes - Severe irritant
Conclusion/Summary [Product]	: Not available	9.
Respiratory corrosion/irritation		
Not available.		
Conclusion/Summary [Product]	: Not available	Э.
Respiratory or skin sensitization		
Product/ingredient name		Result
3-iodo-2-propynyl-butyl carbamate		Guinea pig - skin <u>Result</u> : Not sensitizing
Skin		
Conclusion/Summary [Product]	: Not available	Э.
Respiratory		
Conclusion/Summary [Product]	: Not available	9.
Germ cell mutagenicity		
Product/ingredient name		Result
⅔-iodo-2-propynyl-butyl carbamate		In vitro - Bacteria <u>Result</u> : Negative
Conclusion/Summary [Product]	: Not available	Э.
Carcinogenicity		
Not available.		
Conclusion/Summary [Product]	: Not available	9.
Reproductive toxicity		
Product/ingredient name		Result

-iodo-2-propynyl-butyl carb	amate	Rabbit - Female - Oral
		50 mg/kg [7 days per week] [13 days]
		<u>Maternal toxicity</u> : Positive Developmental: Negative
		Developmental. Negative
		Rabbit - Female - Oral
		20 mg/kg [7 days per week] [13 days] <u>Maternal toxicity</u> : Negative
		<u>Developmental</u> : Negative
Conclusion/Summary [P	roduct] : Not availab	le.
Specific target organ toxic	ity (single exposure)	
Not available.		
Specific target organ toxic	ity (repeated exposure	<u>)</u>
Product/ingredient name		Result
iodo-2-propynyl-butyl carb	pamate	STOT RE 1, H372 (larynx)
Achiration bazard		
<u>Aspiration hazard</u> Not available.		
Information on likely route	e of exposure	
Not available.	S OI ENDOSUIA	
Potential acute health effe	<u>cts</u>	
Eye contact		ant effects or critical hazards.
Inhalation	•	ant effects or critical hazards.
Skin contact	•	ant effects or critical hazards.
Ingestion	•	ant effects or critical hazards.
Symptoms related to the p	hysical, chemical and	toxicological characteristics
Eye contact	: No specific data.	
Inhalation	: No specific data.	
Skin contact	: No specific data.	
Ingestion	: No specific data.	
	f <mark>ects as well as chroni</mark>	c effects from short and long-term exposure
Short term exposure		
Potential immediate effects	: Not available.	
Potential delayed effects	: Not available.	
Long term exposure		
Potential immediate effects	: Not available.	
Potential delayed effects	: Not available.	
Potential chronic health ef		
Not available.		
Conclusion/Summary [P	roduct] : Not availab	e.
General	: No known signific	ant effects or critical hazards.
Carcinogenicity	: No known signific	ant effects or critical hazards.
Mutagenicity	: No known signific	ant effects or critical hazards.
Reproductive toxicity		ant effects or critical hazards.

Date of issue/Date of revision: 14/04/2025Date of previous issueTEKNOSEAL 4002-10 - TS 0050 CLEAR

Not available.

ssue : 25/10/2023

SECTION 11: Toxicological information

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity Product/ingredient name 2-Butoxyethanol

Result

Acute - LC50 - Marine water Fish - Inland silverside - *Menidia beryllina* <u>Size</u>: 40 to 100 mm 1250000 μg/l [96 hours] <u>Effect</u>: Mortality

Acute - LC50 - Marine water Crustaceans - Common shrimp, sand shrimp - Crangon

crangon 800000 µg/l [48 hours] <u>Effect</u>: Mortality

Acute - LC50 - Fresh water

Fish - Trout - *Oncorhynchus mykiss* 0.067 mg/l [96 hours]

Acute - NOEC - Fresh water

EU Fish - Trout - *Oncorhynchus mykiss* 0.049 mg/l [96 hours]

Acute - EC50 - Fresh water

EU Daphnia - Daphnia - *Daphnia magna* 0.16 mg/l [48 hours]

Chronic - NOEC - Fresh water

Daphnia - Daphnia - *Daphnia Magna* 0.05 mg/l [21 days]

Acute - EC50 - Fresh water

Algae - Algae - *Scenedemus subspicatus* 0.022 mg/l [72 hours]

Acute - LC50 - Fresh water

OECD [Fish, Acute Toxicity Test] Fish - Trout - *Onorhynchus Mykiss* 1.9 mg/l [96 hours]

Acute - EC50 OECD 202 [Daphnia sp. Acute Immobilization Test and Reproduction Test] Daphnia - Daphnia - Daphnia Magna 3.7 mg/l [48 hours]

Acute - EC50 - Marine water

OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - *Skeletonema Costatum* 0.36 mg/l [72 hours]

Acute - NOEC - Marine water

3-iodo-2-propynyl-butyl carbamate

1,2-benzisothiazol-3(2H)-one

SECTION 12: Ecological info	OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - Skeletonema Costatum
	0.15 mg/l [72 hours]
2-methyl-2H-isothiazol-3-one	Acute - EC50 - Fresh water US EPA
	Daphnia - Water flea - <i>Daphnia magna</i>
	Age: <24 hours
	0.18 ppm [48 hours]
	Effect: Intoxication
	Acute - LC50 - Fresh water
	US EPA
	Fish - Rainbow trout, donaldson trout - Oncorhynchus mykiss
	Weight: 0.73 g
	0.07 ppm [96 hours]
	<u>Effect</u> : Mortality

12.2 Persistence and degradability

Product/ingredient name

1,2-benzisothiazol-3(2H)-one

Result EU

24% [28 days]

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Fiodo-2-propynyl-butyl carbamate	-	-	Not readily
1,2-benzisothiazol-3(2H)-one	-	-	Inherent

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-Butoxyethanol	0.81	-	Low
3-iodo-2-propynyl-butyl carbamate	>1	-	Low
1,2-benzisothiazol-3(2H)-one	-	3.2	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logKoc	Кос
2-Butoxyethanol	1.83	67.3685
adipohydrazide	1.74	55.2165
3-iodo-2-propynyl-butyl carbamate	1.13	13.4558
1,2-benzisothiazol-3(2H)-one	1.86	73.142
2-methyl-2H-isothiazol-3-one	1.74	54.9187

Results of PMT and vPvM assessment

Product/ingredient name	PMT	Р	Μ	т	vPvM	vP	vM
2-Butoxyethanol	No	No	No	No	No	No	No
adipohydrazide	No	No	No	No	No	No	No
3-iodo-2-propynyl-butyl carbamate	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
2-methyl-2H-isothiazol-3-one		No	No	No	No	No	No

Mobility Conclusion/Summary : Not available.

: The product does not meet the criteria to be considered as a PMT or vPvM.

Date of issue/Date of revision

: 14/04/2025 Date of previous issue : 25/10/2023

SECTION 12: Ecological information

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	Р	В	Т	vPvB	vP	vB
2-Butoxyethanol	No	No	No	No	No	No	No
adipohydrazide	No	No	No	No	No	No	No
3-iodo-2-propynyl-butyl carbamate	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
2-methyl-2H-isothiazol-3-one	No	No	No	No	No	No	No
Regulation (EC) No. 1272/20	08 [CLP]						
Product/ingredient name	PBT	Р	В	т	vPvB	vP	vB
2-Butoxyethanol	No	No	No	No	No	No	No
adipohydrazide	No	No	No	No	No	No	No
3-iodo-2-propynyl-butyl carbamate	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP] : The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product]

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment metho	ods
Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
European waste catalogue (EWC)	: 080111*
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

: 25/10/2023

SECTION 14. Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

: Not relevant/applicable due to nature of the product.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name		%	Designatio	n [Usage]			
TEKNOSEAL 4002-10		≥90	3				
Labelling	:	•					
Other EU regulations							
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed						
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed						
Explosive precursors	: Not applicat	ole.					
Ozone depleting substanc	es (EU 2024/59	<u>0)</u>					
Not listed.							
Prior Informed Consent (P	<u>IC) (649/2012/E</u>	<u>U)</u>					
Not listed.							
Date of issue/Date of revision	: 14/04/2025	Date of pro	evious issue	: 25/10/2023	Version	:2	15/18

SECTION 15: Regulatory information

Persistent Organic Pollutants Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety	: This product contains substances for which Chemical Safety Assessments are still
assessment	required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification	
Aquatic Chronic 3, H412	Calculation method	

Full text of abbreviated H statements

H 301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

Date of issue/Date of revision	: 14/04/2025	Date of previous issue	: 25/10/2023	Version	: 2 16/18
TEKNOSEAL 4002-10 - TS 0050	CLEAR			Label No :	112875

SECTION 16: Other information

SECTION 10. OU	
Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
Date of issue/ Date of	: 14/04/2025
revision	
Date of previous issue	25/10/2023
Version	: 2

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision: 14/04/20TEKNOSEAL 4002-10 - TS 0050 CLEAR

: 14/04/2025 Date of previous issue