Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

SAFETY DATA SHEET



TEKNOSEAL 4008-00 - All variants

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name : TEKNOSEAL 4008-00 - All variants

1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use: Joint sealants

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091. e-mail address of person : Prod-safe@teknos.com

responsible for this SDS

National contact

Teknos (UK) Limited, 7 Longlands Rd, Bicester, Oxfordshire OX26 5AH, United Kingdom. Tel. +44 (0) 1869 208005.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : NHS: 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to UK CLP/GHS Skin Sens. 1, H317

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word Hazard statements	: Warning : H317 - May cause an allergic skin reaction.
Precautionary statements	
Prevention	: P280 - Wear protective gloves. P261 - Avoid breathing vapour.
Response	 P362 + P364 - Take off contaminated clothing and wash it before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.
Storage	: Not applicable.
Disposal	 P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Contains biocidal products for in-can preservation: BIT and Bronopol and MIT and OIT and DTBMA and MBIT.

SECTION 2: Hazards	ic	lentification
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

SECTION 3: Composition/information on ingredients 3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Туре
Dipropyleneglycolmethylether	REACH #: 01-2119450011-60 EC: 252-104-2	≤3	Not classified.	[2]
EO bis(benztriazolyl) phenylpropionat	CAS: 34590-94-8 REACH #: 01-0000015075-76 EC: 400-830-7 CAS: 104810-48-2 Index: 607-176-00-3	<1	Skin Sens. 1A, H317 Aquatic Chronic 2, H411	[1]
2-Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	≤0.3	Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319	[1] [2]
Ammonia	REACH #: 01-2119488876-14 EC: 215-647-6 CAS: 1336-21-6 Index: 007-001-01-2	<0.1	Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 (M=1)	[1] [2]
2-methyl-2H-isothiazol-3-one	EC: 220-239-6 CAS: 2682-20-4	<0.01	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1) EUH071	[1]
2-Octyl-2H-isothiazol-3-one	EC: 247-761-7 CAS: 26530-20-1 Index: 613-112-00-5	<0.0025	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071	[1]
Propylene glycol	REACH #: 01-2119456809-23 EC: 200-338-0	≤0.1	Not classified.	[2]

SECTION 3: Composition/information on ingredients		
	CAS: 57-55-6	See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	-	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	-	Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/sy	<u>mptoms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
4.3 Indication of any imm	ediate medical attention and special treatment needed
Notes to physician	Treat symptomatically Contact poison treatment specialist imme

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising f	rom the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures		
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.	
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).	
6.3 Methods and material for	containment and cleaning up	
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.	
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.	
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.	

: 19/10/2022 Date of previous issue

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

DipropyleneglycolmethyletherEH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. TWA: 308 mg/m³ 8 hours. TWA: 50 ppm 8 hours.2-ButoxyethanolEH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 50 ppm 15 minutes. TWA: 25 ppm 8 hours. STEL: 246 mg/m³ 15 minutes. TWA: 25 ppm 8 hours. STEL: 246 mg/m³ 15 minutes. TWA: 25 ppm 8 hours. STEL: 25 mg/m³ 15 minutes. STEL: 25 mg/m³ 15 minutes. Form: anhydrous STEL: 35 ppm 15 minutes. Form: anhydrous STEL: 35 ppm 15 minutes. Form: anhydrous STEL: 35 ppm 8 hours. Form: anhydrous TWA: 25 ppm 8 hours. Form: anhydrous STEL: 35 ppm 8 hours. Form: anhydrous TWA: 25 ppm 8 hours. Form: anhydrous TWA: 25 ppm 8 hours. Form: anhydrous TWA: 10 mg/m³ 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form:	Occupational exposure limits	
TWA: 308 mg/m³ 8 hours. TWA: 50 ppm 8 hours.2-ButoxyethanolEH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 50 ppm 15 minutes. TWA: 25 ppm 8 hours. STEL: 246 mg/m³ 15 minutes. TWA: 123 mg/m³ 8 hours.AmmoniaEH40/2005 WELs (United Kingdom (UK), 1/2020). [ammonia] STEL: 25 mg/m³ 15 minutes. Form: anhydrous STEL: 35 ppm 15 minutes. Form: anhydrous STEL: 35 ppm 15 minutes. Form: anhydrous TWA: 25 ppm 8 hours. Form: anhydrous STEL: 35 ppm 15 minutes. Form: anhydrous TWA: 25 ppm 8 hours. Form: anhydrous TWA: 25 ppm 8 hours. Form: anhydrous TWA: 18 mg/m³ 8 hours. Form: anhydrous TWA: 10 mg/m³ 8 hours. Form: total vapour and particulates TWA: 10 mg/m³ 8 hours. Form: total vapour and particulates TWA: 10 mg/m³ 8 hours. Form: total vapour and particulates TWA: 10 mg/m³ 8 hours. Form: total vapour and particulates TWA: 10 mg/m³ 8 hours. Form: total vapour and particulates TWA: 10 opm 8 hours. Form: total vapour and particulates TWA: 10 opm 8 hours. Form: total vapour and particulates TWA: 10 opm 8 hours. Form: total vapour and particulates TWA: 10 opm 8 hours. Form: total vapour and particulates TWA: 10 opm 8 hours. Form: total vapour and particulates TWA: 10 opm 8 hours. Form: total vapour and particulates TWA: 10 opm 8 hours. Form: total vapour and particulates TWA: 10 opm 8 hours. Form: total vapour and particulates TWA: 10 opm 8 hours. Form: total vapour and particulates TWA: 10 opm 8 hours. Form: total vapour and particulates TWA: 10 opm 8 hours. Form: total vapour and particulates TWA: 10 opm 8 hours. Form: total vapour and particulates TWA: 10 opm 8 hours. Form: total vapour and particulates TWA: 10 opm 8 hours. Form: total vapour and particulates TWA: 10 opm 6 hours. Form: total vapour and particulates TWA: 10 opm 6 hours. Form: total vapour and particulates TWA: 10 opm 8 hours.	Dipropyleneglycolmethylether	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed
2-ButoxyethanolTWA: 50 ppm 8 hours.2-ButoxyethanolEH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 50 ppm 15 minutes. TWA: 25 ppm 8 hours. STEL: 246 mg/m³ 15 minutes. TWA: 123 mg/m³ 8 hours.AmmoniaEH40/2005 WELs (United Kingdom (UK), 1/2020). [ammonia] STEL: 25 mg/m³ 15 minutes. Form: anhydrous STEL: 35 ppm 15 minutes. Form: anhydrous STEL: 35 ppm 8 hours. Form: anhydrous TWA: 25 ppm 8 hours. Form: anhydrous TWA: 18 mg/m³ 8 hours. Form: anhydrous TWA: 10 mg/m³ 8 hours. Form: oral yapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates twa: 150 ppm 8 hours. Form: total vapour and particulates twa: total vapour and particulates twa: total vapour and particulates	, ., .	
2-Butoxyethanol 2-Butoxyethanol EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 50 ppm 15 minutes. TWA: 25 ppm 8 hours. STEL: 246 mg/m³ 15 minutes. TWA: 123 mg/m³ 8 hours. Ammonia EH40/2005 WELs (United Kingdom (UK), 1/2020). [ammonia] STEL: 25 mg/m³ 15 minutes. Form: anhydrous STEL: 35 ppm 15 minutes. Form: anhydrous TWA: 25 ppm 8 hours. Form: anhydrous TWA: 25 ppm 8 hours. Form: anhydrous TWA: 18 mg/m³ 8 hours. Form: anhydrous TWA: 10 mg/m³ 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total va		TWA: 308 mg/m ³ 8 hours.
through skin. STEL: 50 ppm 15 minutes. TWA: 25 ppm 8 hours. STEL: 246 mg/m³ 15 minutes. TWA: 123 mg/m³ 8 hours.AmmoniaEH40/2005 WELs (United Kingdom (UK), 1/2020). [ammonia] STEL: 25 mg/m³ 15 minutes. Form: anhydrous STEL: 35 ppm 15 minutes. Form: anhydrous STEL: 35 ppm 15 minutes. Form: anhydrous TWA: 25 ppm 8 hours. Form: anhydrous TWA: 25 ppm 8 hours. Form: anhydrous TWA: 25 ppm 8 hours. Form: anhydrous TWA: 18 mg/m³ 8 hours. Form: anhydrous TWA: 10 mg/m³ 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates tWA: 150 ppm 8 hours. Form: total vapour and particulates tWA: 150 ppm 8 hours. Form: total vapour and particulates tWA: 150 ppm 8 hours. Form: total vapour and particulates tWA: 150 ppm 8 hours. Form: total vapour and particulates tWA: 150 ppm 8 hours. Form: total vapour and particulates tWA: 150 ppm 8 hours. Form: total vapour and particulates tWA: 150 ppm 8 hours. Form: total vapour and particulates tWA: 150 ppm 8 hours. Form: total vapour and particulates tWA: 150 ppm 8 hours. Form: total vapour and particulates tWA: 150 ppm 8 hours. Form: total vapour and particulates tWA: 150 ppm 8 hours. Form: total vapour and particulates twa: 150 ppm 8 hours. Form: total vapour and particulates		TWA: 50 ppm 8 hours.
STEL: 50 ppm 15 minutes. TWA: 25 ppm 8 hours. STEL: 246 mg/m³ 15 minutes. TWA: 123 mg/m³ 8 hours.AmmoniaEH40/2005 WELs (United Kingdom (UK), 1/2020). [ammonia] STEL: 25 mg/m³ 15 minutes. Form: anhydrous STEL: 35 ppm 15 minutes. Form: anhydrous TWA: 25 ppm 8 hours. Form: anhydrous TWA: 25 ppm 8 hours. Form: anhydrous TWA: 18 mg/m³ 8 hours. Form: anhydrous TWA: 10 mg/m³ 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulatesRecommended monitoring procedures: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring	2-Butoxyethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed
TWA: 25 ppm 8 hours. STEL: 246 mg/m³ 15 minutes. TWA: 123 mg/m³ 8 hours.AmmoniaEH40/2005 WELs (United Kingdom (UK), 1/2020). [ammonia] STEL: 25 mg/m³ 15 minutes. Form: anhydrous 		through skin.
STEL: 246 mg/m³ 15 minutes. TWA: 123 mg/m³ 8 hours.AmmoniaEH40/2005 WELs (United Kingdom (UK), 1/2020). [ammonia] STEL: 25 mg/m³ 15 minutes. Form: anhydrous STEL: 35 ppm 15 minutes. Form: anhydrous TWA: 25 ppm 8 hours. Form: anhydrous TWA: 25 ppm 8 hours. Form: anhydrous TWA: 18 mg/m³ 8 hours. Form: anhydrous TWA: 18 mg/m³ 8 hours. Form: anhydrous TWA: 10 mg/m³ 8 hours. Form: control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring		STEL: 50 ppm 15 minutes.
AmmoniaTWA: 123 mg/m³ 8 hours.AmmoniaEH40/2005 WELs (United Kingdom (UK), 1/2020). [ammonia] STEL: 25 mg/m³ 15 minutes. Form: anhydrous STEL: 35 ppm 15 minutes. Form: anhydrous TWA: 25 ppm 8 hours. Form: anhydrous TWA: 18 mg/m³ 8 hours. Form: anhydrous EH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 18 mg/m³ 8 hours. Form: Particulate TWA: 10 mg/m³ 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates tWA: 150 ppm 8 hours. Form: total vapour and particulates tWA: 150 ppm 8 hours. Form: total vapour and particulates tWA: 150 ppm 8 hours. Form: total vapour and particulates		TWA: 25 ppm 8 hours.
AmmoniaEH40/2005 WELs (United Kingdom (UK), 1/2020). [ammonia] STEL: 25 mg/m³ 15 minutes. Form: anhydrous STEL: 35 ppm 15 minutes. Form: anhydrous TWA: 25 ppm 8 hours. Form: anhydrous TWA: 18 mg/m³ 8 hours. Form: anhydrous EH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 18 mg/m³ 8 hours. Form: anhydrous EH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 10 mg/m³ 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulatesRecommended monitoring procedures:If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring		STEL: 246 mg/m ³ 15 minutes.
STEL: 25 mg/m³ 15 minutes. Form: anhydrous STEL: 35 ppm 15 minutes. Form: anhydrous TWA: 25 ppm 8 hours. Form: anhydrous TWA: 18 mg/m³ 8 hours. Form: anhydrousPropylene glycolEH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 10 mg/m³ 8 hours. Form: Particulate TWA: 474 mg/m³ 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulatesRecommended monitoring procedures:If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring		TWA: 123 mg/m ³ 8 hours.
STEL: 35 ppm 15 minutes. Form: anhydrous TWA: 25 ppm 8 hours. Form: anhydrous TWA: 18 mg/m³ 8 hours. Form: anhydrousPropylene glycolEH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 10 mg/m³ 8 hours. Form: Particulate TWA: 474 mg/m³ 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulatesRecommended monitoring proceduresIf this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring	Ammonia	EH40/2005 WELs (United Kingdom (UK), 1/2020). [ammonia]
TWA: 25 ppm 8 hours. Form: anhydrous TWA: 18 mg/m³ 8 hours. Form: anhydrousPropylene glycolEH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 10 mg/m³ 8 hours. Form: Particulate TWA: 474 mg/m³ 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulatesRecommended monitoring proceduresIf this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring		STEL: 25 mg/m ³ 15 minutes. Form: anhydrous
Propylene glycolTWA: 18 mg/m³ 8 hours. Form: anhydrousEH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 10 mg/m³ 8 hours. Form: Particulate TWA: 474 mg/m³ 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulatesRecommended monitoring proceduresIf this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring		STEL: 35 ppm 15 minutes. Form: anhydrous
Propylene glycol EH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 10 mg/m³ 8 hours. Form: Particulate TWA: 474 mg/m³ 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates recommended monitoring procedures If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring		TWA: 25 ppm 8 hours. Form: anhydrous
TWA: 10 mg/m³ 8 hours. Form: Particulate TWA: 474 mg/m³ 8 hours. Form: total vapour and particulates TWA: 474 mg/m³ 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulatesRecommended monitoring proceduresIf this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring		TWA: 18 mg/m ³ 8 hours. Form: anhydrous
Recommended monitoring proceduresIf this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring	Propylene glycol	EH40/2005 WELs (United Kingdom (UK), 1/2020).
Recommended monitoring proceduresTWA: 150 ppm 8 hours. Form: total vapour and particulatesIf this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring		TWA: 10 mg/m ³ 8 hours. Form: Particulate
Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring		
procedures atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring		TWA: 150 ppm 8 hours. Form: total vapour and particulates
standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.		atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the
DNELs/DMELs		

Product/ingredient name	Туре	Exposure	Value	Population	Effects
Dipropyleneglycolmethylether	DNEL	Long term Oral	0.33 mg/	General	Systemic
			kg bw/day	population	,
	DNEL	Long term	37.2 mg/m ³	General	Systemic
		Inhalation	_	population	-
	DNEL	Long term Dermal	121 mg/kg	General	Systemic
			bw/day	population	
	DNEL	Long term Dermal	283 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	308 mg/m ³	Workers	Systemic
2-Butoxyethanol	DNEL	Long term Oral	6.3 mg/kg	General	Systemic
			bw/day	population	- ,
	DNEL	Short term Oral	26.7 mg/	General	Systemic
			kg bw/day	population	- ,
	DNEL	Long term	59 mg/m ³	General	Systemic
		Inhalation		population	-
	DNEL	Long term Dermal	75 mg/kg	General	Systemic
		_	bw/day	population	-
	DNEL	Short term Dermal	89 mg/kg	General	Systemic
			bw/day	population	
	DNEL	Short term Dermal	89 mg/kg	Workers	Systemic
			bw/day		
	DNEL	Long term	98 mg/m³	Workers	Systemic
	DUE	Inhalation	105 //		
	DNEL	Long term Dermal	125 mg/kg	Workers	Systemic
	DNEL	Short term	bw/day 147 mg/m³	General	Local
	DINEL	Inhalation	147 mg/m	population	LUCAI
	DNEL	Short term	246 mg/m ³	Workers	Local
	DITE	Inhalation	210 mg/m	W ON KOTO	Loodi
	DNEL	Short term	426 mg/m ³	General	Systemic
		Inhalation	J	population	,
	DNEL	Short term	1091 mg/	Workers	Systemic
		Inhalation	m ³		
2-methyl-2H-isothiazol-3-one	DNEL	Long term	0.021 mg/		Local
		Inhalation	m³	population	
	DNEL	Long term	0.021 mg/	Workers	Local
		Inhalation	m ³	O a m a mal	Question
	DNEL	Long term Oral	0.027 mg/	General	Systemic
	DNEL	Short term	kg bw/day 0.043 mg/	population General	Local
	DINEL	Inhalation	0.043 mg/	population	LUCAI
	DNEL	Short term	0.043 mg/	Workers	Local
	DIVLL	Inhalation	m ³	WORKEIS	Local
	DNEL	Short term Oral	0.053 mg/	General	Systemic
			kg bw/day	population	
Propylene glycol	DNEL	Long term	10 mg/m ³	General	Local
· · · · · ·		Inhalation		population	
	DNEL	Long term	10 mg/m³	Workers	Local
		Inhalation			
	DNEL	Long term	50 mg/m³	General	Systemic
		Inhalation		population	
	DNEL	Long term	168 mg/m³	Workers	Systemic
		Inhalation			

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Date of issue/Date of revision TEKNOSEAL 4008-00 - All variants

: 19/10/2022 Date of previous issue

: No previous validation

SECTION 8: Exposure controls/personal protection

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
	Recommendations : Wear suitable gloves tested to EN374.
	> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm
	Not recommended polyvinyl alcohol (PVA) gloves
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
	Filter type (spray application): A P
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Colour	: Clear.
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and	:
boiling range	
Ingredient name	°C

Ingredient name	°C	°F	Method
water	100	212	
Dipropyleneglycolmethylether	189.6	373.3	EU A.2

Flammability (solid, gas) : Not a	available.
	er: Not applicable. er: Not applicable.

Upper: Not applicable.

: 19/10/2022 Date of previous issue

Date of issue/Date of revision	
TEKNOSEAL 4008-00 - All variants	s

: No previous validation

Version :1 7/15 Label No :35299

SECTION 9: Physical and chemical properties

Flash point		: Closed cup: >100°C (>212°F)					
Auto-ignition temperature	:						
Ingredient name		°C	°F	Method			
Dipropyleneglycolmethylether		207	404.6	EU A.15			
Decomposition temperature	: No	t available.	ł	ł			
рН	: 7.5	5 to 8.5 [Conc. (%	% w/w): 100%]				
Viscosity	: No	ot available.					
Solubility(ies) Not available.	:						
Solubility in water	: No	t available.					
Partition coefficient: n-octanol	' : No	t applicable.					
Vapour pressure	:						

	Vapour Pressure at 20°C			Vapour pressure at 50°C			
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
water	23.8	3.2					
Relative density	: Not	available.	<u> </u>				
Density	: 1 g/	cm³					
/apour density	: Not	available.					
Explosive properties	: Not	available.					
Dxidising properties	: Not	available.					
Particle characteristics							
Median particle size	: Not	applicable.					

SECTION 10: Stability and reactivity				
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.			
10.2 Chemical stability	: The product is stable.			
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.			
10.4 Conditions to avoid	: No specific data.			
10.5 Incompatible materials	: No specific data.			
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.			

SECTION 11: Toxicological information

11.1 Information on toxicological effects Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Ammonia	LD50 Oral	Rat	350 mg/kg	-
2-methyl-2H-isothiazol-	LC50 Inhalation Dusts and	Rat	0.11 mg/l	4 hours
3-one	mists			
2-Octyl-2H-isothiazol-3-one	LD50 Dermal	Rabbit	690 mg/kg	-
-	LD50 Oral	Rat	550 mg/kg	-
Propylene glycol	LD50 Dermal	Rabbit	20800 mg/kg	-
	LD50 Oral	Rat	20 g/kg	-

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Acute toxicity estimates

Route	ATE value
Not available.	

Irritation/Corrosion

		Species	Score	Exposure	Observation
) ipropyleneglycolmethylether	Eyes - Mild irritant	Human	-	8 mg	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
	Skin - Mild irritant	Rabbit	-	500 mg	-
-Butoxyethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100	-
				mg	
	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
mmonia	Eyes - Severe irritant	Rabbit	-	0.5 minutes	-
				1 mg	
_	Eyes - Severe irritant	Rabbit	-	250 ug	-
-Octyl-2H-isothiazol-3-one	Eyes - Severe irritant	Rabbit	-	100 mg	-
ropylene glycol	Eyes - Mild irritant	Rabbit	-	100 mg	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
	Skin - Mild irritant	Human	-	168 hours	-
		14/		500 mg	
	Skin - Mild irritant	Woman	-	96 hours 30	-
	Chin Madanata innitant	Child		%	
	Skin - Moderate irritant	Child	-	96 hours 30 % C	-
	Skin - Moderate irritant	Human		% C 72 hours 104	
	Skin - Moderale Initant	Tuillan	-	_	-
				mg l	

<u>densitisation</u>	
Conclusion/Summary	: May cause an allergic skin reaction.
Mutagenicity	

Conclusion/Summary : Based on available data, the classification criteria are not met.

Conclusion/Summary : Based on available data, the classification criteria are not met.

Conclusion/Summary : Based on available data, the classification criteria are not met.

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Ammonia	Category 3	-	Respiratory tract irritation

<u>Specific target organ toxicity (repeated exposure)</u> Not available.

Carcinogenicity

Teratogenicity

Reproductive toxicity

: 19/10/2022 Date of previous issue

SECTION 11: Toxicological information

Aspiration hazard

Not available.

Information on likely routes of exposure	1	Not available.
Potential acute health effects		
Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	May cause an allergic skin reaction.
Ingestion	;	No known significant effects or critical hazards.

Symptoms related to	the physical, chemical	and toxicological characteris	tics

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure		
Potential immediate effects	Not avail	able.
Potential delayed effects	Not avail	able.
Long term exposure		
Potential immediate effects	Not avail	able.
Potential delayed effects	Not avail	able.
Potential chronic health eff	<u>i</u>	
Not available.		
Conclusion/Summary	Not avail	able.
General	Once ser to very lo	nsitized, a severe allergic reaction may occur when subsequently exposed ow levels.
Carcinogenicity	No know	n significant effects or critical hazards.
Mutagenicity	No know	n significant effects or critical hazards.
Reproductive toxicity	No know	n significant effects or critical hazards.

Other information

: Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure		
2-Butoxyethanol	Acute EC50 >1000 mg/l Fresh water	Daphnia - Water flea - Daphnia magna	48 hours		
	Acute LC50 800000 μg/l Marine water	Crustaceans - Common shrimp, sand shrimp - Crangon crangon	48 hours		
	Acute LC50 1250000 µg/l Marine water	Fish - Inland silverside - Menidia beryllina	96 hours		
Ammonia	Acute LC50 37 ppm Fresh water	Fish - Western mosquitofish - Gambusia affinis - Adult	96 hours		
2-methyl-2H-isothiazol-3-one	Acute EC50 0.18 ppm Fresh water	Daphnia - Water flea - Daphnia 48 ho magna			
	Acute LC50 0.07 ppm Fresh water	Fish - Rainbow trout,donaldson	96 hours		
Date of issue/Date of revision	: 19/10/2022 Date of previous issue	: No previous validation Version	:1 10/15		
EKNOSEAL 4008-00 - All varia	ants	EKNOSEAL 4008-00 - All variants Label No :35299			

SECTION 12: Ecological information

		trout - Oncorhynchus mykiss	
2-Octyl-2H-isothiazol-3-one	Acute EC50 107 ppb Fresh water	Daphnia - Water flea - Daphnia magna	48 hours
	Acute LC50 47 ppb Fresh water	Fish - Rainbow trout,donaldson trout - Oncorhynchus mykiss	96 hours
	Chronic NOEC 74 ppb Fresh water	Daphnia - Water flea - Daphnia magna	21 days
	Chronic NOEC 8.5 ppb	Fish - Fathead minnow - Pimephales promelas	35 days
Propylene glycol	Acute EC50 19300 mg/l Fresh water	Algae - Algae	96 hours
	Acute EC50 43500 mg/l Fresh water	Daphnia - Daphnia - Daphnia magna	48 hours
	Acute LC50 18340000 µg/l Fresh water	Crustaceans - Water flea - Ceriodaphnia dubia	48 hours
	Acute LC50 40613 mg/l Fresh water	Fish - Trout - Oncorhynchus mykiss	96 hours

12.2 Persistence and degradability

Conclusion/Summary : This product has not been tested for biodegradation.

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Dipropyleneglycolmethylether	0.004	-	low
2-Octyl-2H-isothiazol-3-one	2.45	-	low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment meth	nods
Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
European waste catalogue (EWC)	: 080112
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 13: Disposal considerations

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

UK (GB) /REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Ozone depleting substances

Not listed.

Prior Informed Consent (PIC)

Not listed.

Persistent Organic Pollutants Not listed.

Annex XVII - Restrictions : Not applicable. on the manufacture. placing on the market and use of certain dangerous substances, mixtures and articles

Seveso Directive

This product is not controlled under the Seveso Directive.

Date of issue/Date of revision TEKNOSEAL 4008-00 - All variants

: 19/10/2022 Date of previous issue

SECTION 15: Regulatory information

EU regulations

 Industrial emissions
 : Not listed

 (integrated pollution

 prevention and control)

 Air

 Industrial emissions
 : Not listed

 (integrated pollution

 prevention and control)

 Water

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety	1	This product contains substances for which Chemical Safety Assessments are still
assessment		required.

SECTION 16: Other information

✓ Indicates information that has changed from previously issued version.

	o i j
Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and
-	Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019
	No. 720 and amendments
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = GB CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

Classification	Justification
Skin Sens. 1, H317	Calculation method

Full text of abbreviated H statements

-			
H301	H301 Toxic if swallowed.		
H302	302 Harmful if swallowed.		
H311	311 Toxic in contact with skin.		
H314	H314 Causes severe skin burns and eye damage.		
H315	H315 Causes skin irritation.		
H317	H317 May cause an allergic skin reaction.		
H318	H318 Causes serious eye damage.		
H319	1319 Causes serious eye irritation.		
H330	H330 Fatal if inhaled.		
H332	H332 Harmful if inhaled.		
H335	1335 May cause respiratory irritation.		
H400	Very toxic to aquatic life.		
Date of issue/D	te of revision : 19/10/2022 Date of previous issue : No previous validation Version : 1 13/-	15	
TEKNOSEA	TEKNOSEAL 4008-00 - All variants Label No :35299		

SECTION 16: Other information

H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Corr. 1	SKIN CORROSION/IRRITATION - Category 1
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
Date of issue/ Date of	: 19/10/2022
revision	
Date of previous issue	No previous validation
Version	: 1

TEKNOSEAL 4008-00

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision TEKNOSEAL 4008-00 - All variants

: 19/10/2022 Date of previous issue

: No previous validation