

# SAFETY DATA SHEET



TEKNOSOLV 9526

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Product name : TEKNOSOLV 9526

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Solvent.

### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS : Prod-safe@teknos.com

#### National contact

Teknos Ireland Limited, 52 Ballymoughan Road, Magherafelt, BT45 6HN, UK. Tel. +44 (0) 2879 301 472.

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

Telephone number : NHS: 111

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Product definition : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 2, H225

Eye Irrit. 2, H319

Carc. 2, H351

STOT SE 3, H336

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

Hazard pictograms :



Signal word : Danger


Hazard statements : H225 - Highly flammable liquid and vapour.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.  
H351 - Suspected of causing cancer.

#### Precautionary statements

Prevention : P201 - Obtain special instructions before use.  
P280 - Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response : P308 + P313 - IF exposed or concerned: Get medical advice or attention.

## SECTION 2: Hazards identification


<b>Storage</b>	: P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
<b>Disposal</b>	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
<b>Hazardous ingredients</b>	: Contains: 2-Methoxy-1-methylethyl acetate and Methylisobutylketone
<b>Supplemental label elements</b>	:
<b>Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles</b>	: 

### 2.3 Other hazards

<b>Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII</b>	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
<b>Other hazards which do not result in classification</b>	: None known.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
 -Methoxy-1-methylethyl acetate	REACH #: 01-2119475791-29 EC: 203-603-9 CAS: 108-65-6 Index: 607-195-00-7	≥50 - ≤75	Flam. Liq. 3, H226 STOT SE 3, H336	-	[1] [2]
Methylisobutylketone	REACH #: 01-2119473980-30 EC: 203-550-1 CAS: 108-10-1 Index: 606-004-00-4	≥25 - ≤50	Flam. Liq. 2, H225 Acute Tox. 4, H332 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H336 EUH066	ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
2-methoxypropyl acetate	EC: 274-724-2 CAS: 70657-70-4 Index: 607-251-00-0	<0.3	Flam. Liq. 3, H226 Repr. 1B, H360D STOT SE 3, H335 <b>See Section 16 for the full text of the H statements declared above.</b>	-	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness
- Skin contact** : No specific data.
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

## SECTION 5: Firefighting measures

- Hazards from the substance or mixture** : Highly flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures



### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and material for containment and cleaning up

- Small spill** :  Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** :  Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

### 6.4 Reference to other sections

- : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

## SECTION 7: Handling and storage

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### Seveso Directive - Reporting thresholds

##### Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c	5000 tonnes	50000 tonnes

### 7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
2-Methoxy-1-methylethyl acetate	<b>EH40/2005 WELs (United Kingdom (UK), 1/2020)</b> Absorbed through skin. STEL 15 minutes: 548 mg/m <sup>3</sup> . TWA 8 hours: 50 ppm. TWA 8 hours: 274 mg/m <sup>3</sup> . STEL 15 minutes: 100 ppm.
Methylisobutylketone	<b>EH40/2005 WELs (United Kingdom (UK), 1/2020)</b> Absorbed through skin. STEL 15 minutes: 416 mg/m <sup>3</sup> . STEL 15 minutes: 100 ppm. TWA 8 hours: 208 mg/m <sup>3</sup> . TWA 8 hours: 50 ppm.

#### Biological exposure indices

## SECTION 8: Exposure controls/personal protection

Product/ingredient name	Exposure indices
Methylisobutylketone	<b>EH40/2005 BMGVs (United Kingdom (UK), 1/2020)</b> BGV: 20 µmol/l, 4-methylpentan-2-one [in urine]. Sampling time: post shift.

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs/DMELs

Product/ingredient name	Result
2-Methoxy-1-methylethyl acetate	<b>DNEL - General population - Long term - Inhalation</b> 33 mg/m <sup>3</sup> <u>Effects</u> : Local  <b>DNEL - General population - Long term - Inhalation</b> 33 mg/m <sup>3</sup> <u>Effects</u> : Systemic  <b>DNEL - General population - Long term - Oral</b> 36 mg/kg bw/day <u>Effects</u> : Systemic  <b>DNEL - Workers - Long term - Inhalation</b> 275 mg/m <sup>3</sup> <u>Effects</u> : Systemic  <b>DNEL - General population - Long term - Dermal</b> 320 mg/kg bw/day <u>Effects</u> : Systemic  <b>DNEL - Workers - Short term - Inhalation</b> 550 mg/m <sup>3</sup> <u>Effects</u> : Local  <b>DNEL - Workers - Long term - Dermal</b> 796 mg/kg bw/day <u>Effects</u> : Systemic
Methylisobutylketone	<b>DNEL - General population - Long term - Dermal</b> 4.2 mg/kg bw/day <u>Effects</u> : Systemic  <b>DNEL - Workers - Long term - Dermal</b> 11.8 mg/kg bw/day <u>Effects</u> : Systemic  <b>DNEL - General population - Long term - Inhalation</b> 14.7 mg/m <sup>3</sup> <u>Effects</u> : Local  <b>DNEL - General population - Long term - Inhalation</b> 14.7 mg/m <sup>3</sup> <u>Effects</u> : Systemic  <b>DNEL - Workers - Long term - Inhalation</b> 83 mg/m <sup>3</sup> <u>Effects</u> : Local

## SECTION 8: Exposure controls/personal protection

### **DNEL - Workers - Long term - Inhalation**

83 mg/m<sup>3</sup>

Effects: Systemic

### **DNEL - General population - Short term - Inhalation**

155.2 mg/m<sup>3</sup>

Effects: Local

### **DNEL - General population - Short term - Inhalation**

155.2 mg/m<sup>3</sup>

Effects: Systemic

### **DNEL - Workers - Short term - Inhalation**

208 mg/m<sup>3</sup>

Effects: Local

### **DNEL - Workers - Short term - Inhalation**

208 mg/m<sup>3</sup>

Effects: Systemic

### **DNEL - General population - Long term - Oral**

4.2 mg/kg bw/day

Effects: Systemic

### **PNECs**

Not available.

## **8.2 Exposure controls**

### **Appropriate engineering controls**

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### **Individual protection measures**

#### **Hygiene measures**

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Eye/face protection**

- : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### **Skin protection**

#### **Hand protection**

- : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations : Wear suitable gloves tested to EN374.

< 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm

1 - 4 hours (breakthrough time): polyvinyl alcohol (PVA) thickness > 0.3 mm or 4H / Silver Shield® gloves.

> 8 hours (breakthrough time): Viton® thickness > 0.3 mm gloves

Wash hands before breaks and immediately after handling the product.



## SECTION 8: Exposure controls/personal protection

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.  
Filter type: A  
Filter type (spray application): A P
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : Colourless.
- Odour** : Slight
- Odour threshold** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** :

Ingredient name	°C	°F	Method
Methylisobutylketone	116.5	241.7	OECD 103
2-Methoxy-1-methylethyl acetate	145.8	294.4	

- Flammability** : Not available.
- Lower and upper explosion limit** : Lower: 1.4% (4-methylpentan-2-one)  
Upper: 7.5% (4-methylpentan-2-one)
- Flash point** : Closed cup: 14°C (57.2°F)
- Auto-ignition temperature** :

Ingredient name	°C	°F	Method
2-Methoxy-1-methylethyl acetate	333	631.4	DIN 51794
Methylisobutylketone	448	838.4	

- Decomposition temperature** : Not available.
- pH** : Not available.
- Viscosity** : Not available.
- Solubility(ies)** :  
Not available.
- Solubility in water** : Not available.
- Partition coefficient: n-octanol/ water** : Not applicable.
- Vapour pressure** :



## SECTION 9: Physical and chemical properties

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Methylisobutylketone	15.75128	2.1	OECD 104			
2-Methoxy-1-methylethyl acetate	2.7	0.36				

**Relative density** : Not available.

**Density** : 0.9 g/cm<sup>3</sup>

**Vapour density** : Not available.

### Particle characteristics

**Median particle size** : Not applicable.

## 9.2 Other information

### 9.2.1 Information with regard to physical hazard classes

**Explosive properties** : Not available.

**Oxidising properties** : Not available.

### 9.2.2 Other safety characteristics

Not applicable.

## SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

**10.5 Incompatible materials** : Reactive or incompatible with the following materials:  
oxidising materials

**10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Product/ingredient name

2-Methoxy-1-methylethyl acetate

##### Result

**Rat - Oral - LD50**  
8532 mg/kg

**Rabbit - Dermal - LD50**  
>5 g/kg

Methylisobutylketone

**Rat - Oral - LD50**  
2080 mg/kg

**Conclusion/Summary [Product]** : Not available.

#### Acute toxicity estimates

## SECTION 11: Toxicological information

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
TEKNOSOLV 9526	N/A	N/A	N/A	44.0	N/A
2-Methoxy-1-methylethyl acetate	8532	N/A	N/A	N/A	N/A
Methylisobutylketone	2080	N/A	N/A	11	N/A

### Skin corrosion/irritation

#### Product/ingredient name

Methylisobutylketone

#### Result

**Rabbit - Skin - Mild irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

**Conclusion/Summary [Product]** : Not available.

### Serious eye damage/eye irritation

#### Product/ingredient name

Methylisobutylketone

#### Result

**Rabbit - Eyes - Moderate irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 uL

**Rabbit - Eyes - Severe irritant**

Amount/concentration applied: 40 mg

**Conclusion/Summary [Product]** : Not available.

### Respiratory corrosion/irritation

Not available.

**Conclusion/Summary [Product]** : Not available.

### Respiratory or skin sensitization

Not available.

### Skin

**Conclusion/Summary [Product]** : Not available.

### Respiratory

**Conclusion/Summary [Product]** : Not available.

### Germ cell mutagenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Carcinogenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Reproductive toxicity

Not available.

## SECTION 11: Toxicological information

**Conclusion/Summary [Product]** : Not available.

### Specific target organ toxicity (single exposure)

#### **Product/ingredient name**

2-Methoxy-1-methylethyl acetate  
Methylisobutylketone  
2-methoxypropyl acetate

#### **Result**

STOT SE 3, H336 (Narcotic effects)  
STOT SE 3, H336 (Narcotic effects)  
STOT SE 3, H335 (Respiratory tract irritation)

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Not available.

### Information on likely routes of exposure

Not available.

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.  
**Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.  
**Skin contact** : No known significant effects or critical hazards.  
**Ingestion** : Can cause central nervous system (CNS) depression.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness  
**Inhalation** : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness  
**Skin contact** : No specific data.  
**Ingestion** : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

**Conclusion/Summary [Product]** : Not available.

**General** : No known significant effects or critical hazards.  
**Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.  
**Mutagenicity** : No known significant effects or critical hazards.  
**Reproductive toxicity** : No known significant effects or critical hazards.

## 11.2 Information on other hazards

### 11.2.1 Endocrine disrupting properties

## SECTION 11: Toxicological information

Not available.

**Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product/ingredient name

Methylisobutylketone

#### Result

##### Acute - LC50 - Fresh water

Fish - Fathead minnow - *Pimephales promelas*

Age: 29 days; Size: 21 mm; Weight: 0.141 g

505000 µg/l [96 hours]

Effect: Mortality

##### Chronic - NOEC - Fresh water

Daphnia - Water flea - *Daphnia magna*

78 mg/l [21 days]

Effect: Behavior

##### Chronic - NOEC - Fresh water

Fish - Fathead minnow - *Pimephales promelas* - Embryo

Age: <24 hours

168 mg/l [33 days]

Effect: Mortality

**Conclusion/Summary [Product]** : Not available.

### 12.2 Persistence and degradability

Not available.

**Conclusion/Summary [Product]** : Not available.

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
2-Methoxy-1-methylethyl acetate	1.2	-	Low
Methylisobutylketone	1.9	-	Low

### 12.4 Mobility in soil

#### Soil/water partition coefficient

Product/ingredient name	logK <sub>oc</sub>	K <sub>oc</sub>
2-Methoxy-1-methylethyl acetate	0.36	2.31363
Methylisobutylketone	1.61	40.9047
2-methoxypropyl acetate	0.79	6.11202

#### Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
2-Methoxy-1-methylethyl acetate	No	No	No	No	No	No	No
Methylisobutylketone	No	No	No	No	No	No	No
2-methoxypropyl acetate	No	No	No	No	No	No	No

**Mobility** : Not available.

**Conclusion/Summary** : The product does not meet the criteria to be considered as a PMT or vPvM.

### 12.5 Results of PBT and vPvB assessment

## SECTION 12: Ecological information

### Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
2-Methoxy-1-methylethyl acetate	No	No	No	No	No	No	No
Methylisobutylketone	No	No	No	No	No	No	No
2-methoxypropyl acetate	No	No	No	No	No	No	No

### Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
2-Methoxy-1-methylethyl acetate	No	No	No	No	No	No	No
Methylisobutylketone	No	No	No	No	No	No	No
2-methoxypropyl acetate	No	No	No	No	No	No	No

**Conclusion/Summary** : The product does not meet the criteria to be considered as a PBT or vPvB.  
**Regulation (EC) No. 1272/2008 [CLP]**

### 12.6 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.





**European waste catalogue (EWC)** : 080111\*, 200127\*

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL
14.3 Transport hazard class(es)	3 	3 	3 	3 
14.4 Packing group	II	II	II	II
14.5 Environmental hazards	No.	No.	No.	No.

### Additional information

ADR/RID : **Special provisions** 640 (C)  
**Tunnel code** (D/E)

ADN : **Special provisions** 640 (C)

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not relevant/applicable due to nature of the product.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

###### Annex XIV


None of the components are listed.

###### Substances of very high concern

None of the components are listed.

##### Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
TEKNOSOLV 9526	≥90	3

Labelling : 

#### Other EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Explosive precursors :  Not applicable.

## SECTION 15: Regulatory information

### [Ozone depleting substances \(EU 2024/590\)](#)

Not listed.

### [Prior Informed Consent \(PIC\) \(649/2012/EU\)](#)

Not listed.

### [Persistent Organic Pollutants](#)

Not listed.

### [Seveso Directive](#)

This product is controlled under the Seveso Directive.

### [Danger criteria](#)

Category

P5c

### [International regulations](#)

#### [Chemical Weapon Convention List Schedules I, II & III Chemicals](#)

Not listed.

#### [Montreal Protocol](#)

Not listed.

#### [Stockholm Convention on Persistent Organic Pollutants](#)

Not listed.

#### [Rotterdam Convention on Prior Informed Consent \(PIC\)](#)

Not listed.

#### [UNECE Aarhus Protocol on POPs and Heavy Metals](#)

Not listed.

### 15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

Indicates information that has changed from previously issued version.

### Abbreviations and acronyms

: ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
N/A = Not available  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
SGG = Segregation Group  
vPvB = Very Persistent and Very Bioaccumulative


### [Procedure used to derive the classification according to Regulation \(EC\) No. 1272/2008 \[CLP/GHS\]](#)

Classification	Justification
Flam. Liq. 2, H225 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H336	On basis of test data Calculation method Calculation method Calculation method


### [Full text of abbreviated H statements](#)



## SECTION 16: Other information

 H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H360D	May damage the unborn child.
EUH066	Repeated exposure may cause skin dryness or cracking.

### [Full text of classifications \[CLP/GHS\]](#)

 Acute Tox. 4	ACUTE TOXICITY - Category 4
Carc. 2	CARCINOGENICITY - Category 2
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 1B	REPRODUCTIVE TOXICITY - Category 1B
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

**Date of issue/ Date of revision** : 08/05/2025

**Date of previous issue** : 10/08/2022

**Version** : 2

TEKNOSOLV 9526

All variants

### [Notice to reader](#)

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

