Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

SAFETY DATA SHEET



TEKNOSTAIN AQUA 1996-00 - NORRLAND-STONEGREY

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name : TEKNOSTAIN AQUA 1996-00 - NORRLAND-STONEGREY

1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use: Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person : Prod-safe@teknos.com

responsible for this SDS

National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number: In an emergency, call 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word	Warning	
Hazard statements	H317 - May cause an allergic skin reaction.	
Precautionary statements		
Prevention	P280 - Wear protective gloves. P261 - Avoid breathing vapour.	
Response	P362 + P364 - Take off contaminated clothing and wash it before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attentior	۱.
Storage	Not applicable.	
Disposal	P501 - Dispose of contents and container in accordance with all local, regionant national and international regulations.	al,
Hazardous ingredients	Contains: 1,2-benzisothiazol-3(2H)-one; 2-methyl-2H-isothiazol-3-one and reamers of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-me 2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	

Date of issue/Date of revision	: 28/11/2023	Date of previous issue	: 25/08/2022	Version	:1.02	1/19
TEKNOSTAIN AQUA 1996-00 -	NORRLAND-S	TONEGREY		Label No	5 0773	;

SECTION 2: Hazards identification Supplemental label : Contains biocidal products for in-can preservation: BIT and MIT and C(M)IT/MIT (3: elements 1) and Bronopol and OIT. **Annex XVII - Restrictions** ÷ on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles 2.3 Other hazards **Product meets the criteria** : This mixture does not contain any substances that are assessed to be a PBT or a for PBT or vPvB according vPvB.

1907/2006, Annex XIIIOther hazards which do: None known.not result in classification

to Regulation (EC) No.

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
<mark>i</mark> itanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≤1	Carc. 2, H351 (inhalation)	-	[1] [*]
2-Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	≤0.3	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	ATE [Oral] = 1200 mg/kg ATE [Inhalation (vapours)] = 3 mg/l	[1] [2]
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400	ATE [Oral] = 1020 mg/kg Skin Sens. 1, H317: C ≥ 0.05% M [Acute] = 1	[1]
2-methyl-2H-isothiazol- 3-one	EC: 220-239-6 CAS: 2682-20-4	<0.01	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (dusts and mists)] = 0.11 mg/l Skin Sens. 1, H317: C $\geq 0.0015\%$ M [Acute] = 10 M [Chronic] = 1	[1]
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:1)	CAS: 55965-84-9 Index: 613-167-00-5	<0.0015	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 53 mg/ kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: $C \ge 0.6\%$ Eye Dam. 1, H318: $C \ge 0.6\%$	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

V Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter \leq 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	-	Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects	s, both acute and delayed
---	---------------------------

Over-exposure sign	<u>is/symptoms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

Date of issue/Date of revision	: 28/11/2023	Date of previous issue	
TEKNOSTAIN AQUA 1996-00 - I	NORRLAND-S	TONEGREY	

: 25/08/2022

SECTION 4: First aid measures

4.3 Indication of any immediate medical attention and special treatment needed

- **Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- **Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	:	None known.
5.2 Special hazards arising	fron	the substance or mixture
Hazards from the substance or mixture	:	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	-	No specific data.
5.3 Advice for firefighters		
Special protective actions for fire-fighters		Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters		Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for	containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

SECTION 6: Accidental release measures

6.4 Reference to other	
sections	

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

: Not available.
: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
2-Butoxyethanol	Regulation on Limit Values - MAC (Austria, 4/2021). Absorbed through skin. TWA: 20 ppm 8 hours. TWA: 98 mg/m ³ 8 hours. PEAK: 40 ppm, 4 times per shift, 30 minutes. PEAK: 200 mg/m ³ , 4 times per shift, 30 minutes.
2-methyl-2H-isothiazol-3-one	Regulation on Limit Values - MAC (Austria, 4/2021). [5-chloro- 2-methyl-2,3-dihydroisothiazol-3-one and 2-methyl-2,3-di- hydroisothiazol-3-one (mixture in the ratio 3:1)] Skin sensitiser. TWA: 0.05 mg/m ³ 8 hours.
reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Regulation on Limit Values - MAC (Austria, 4/2021). [5-chloro- 2-methyl-2,3-dihydroisothiazol-3-one and 2-methyl-2,3-di- hydroisothiazol-3-one (mixture in the ratio 3:1)] Skin sensitiser. TWA: 0.05 mg/m ³ 8 hours.
Date of issue/Date of revision : 28/11/2023	Date of previous issue : 25/08/2022 Version : 1.02 5/19
EKNOSTAIN AQUA 1996-00 - NORRLAND-ST	ONEGREY Label No :50773

2-Butoxyethanol	Limit values (Belgium, 5/2021). Absorbed through skin. TWA: 20 ppm 8 hours. TWA: 98 mg/m ³ 8 hours. STEL: 50 ppm 15 minutes. STEL: 246 mg/m ³ 15 minutes.
2-Butoxyethanol	Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 6/2021). Absorbed through skin. Limit value 8 hours: 98 mg/m ³ 8 hours. Limit value 15 min: 246 mg/m ³ 15 minutes. Limit value 15 min: 50 ppm 15 minutes. Limit value 8 hours: 20 ppm 8 hours.
2-Butoxyethanol	Ministry of Economy, Labour and Entrepreneurship ELV/ STELV (Croatia, 1/2021). Absorbed through skin. STELV: 246 mg/m ³ 15 minutes. STELV: 50 ppm 15 minutes. ELV: 98 mg/m ³ 8 hours. ELV: 20 ppm 8 hours.
No exposure limit value known.	
2-Butoxyethanol	Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 10/2022). Absorbed through skin. TWA: 100 mg/m ³ 8 hours. TWA: 20.4 ppm 8 hours. STEL: 200 mg/m ³ 15 minutes. STEL: 40.8 ppm 15 minutes.
2-Butoxyethanol	Working Environment Authority (Denmark, 6/2022). Absorbed through skin. TWA: 20 ppm 8 hours. TWA: 98 mg/m ³ 8 hours. STEL: 246 mg/m ³ 15 minutes. STEL: 50 ppm 15 minutes.
2-Butoxyethanol	Occupational exposure limits, Regulation No. 293 (Estonia, 12/2022). Absorbed through skin. Skin sensitiser. TWA: 98 mg/m ³ 8 hours. TWA: 20 ppm 8 hours. STEL: 246 mg/m ³ 15 minutes. STEL: 50 ppm 15 minutes.
2-Butoxyethanol	EU OEL (Europe, 1/2022). Absorbed through skin. Notes: list of indicative occupational exposure limit values TWA: 20 ppm 8 hours. TWA: 98 mg/m ³ 8 hours. STEL: 50 ppm 15 minutes. STEL: 246 mg/m ³ 15 minutes.
2-Butoxyethanol	Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021). Absorbed through skin. TWA: 20 ppm 8 hours. TWA: 98 mg/m ³ 8 hours. STEL: 50 ppm 15 minutes. STEL: 250 mg/m ³ 15 minutes.
2-Butoxyethanol	Ministry of Labor (France, 10/2022). Absorbed through skin. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) TWA: 10 ppm 8 hours. TWA: 49 mg/m ³ 8 hours. STEL: 246 mg/m ³ 15 minutes. STEL: 50 ppm 15 minutes.
1,2-benzisothiazol-3(2H)-one 2-methyl-2H-isothiazol-3-one	DFG MAC-values list (Germany, 10/2021). Skin sensitiser. DFG MAC-values list (Germany, 10/2021). Skin sensitiser.

2-Butoxyethanol	Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021). Absorbed through skin. TWA: 25 ppm 8 hours. TWA: 120 mg/m ³ 8 hours.
No exposure limit value known.	
eaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	SUVA (Switzerland, 1/2021). Skin sensitiser.
	STEL: 0.4 mg/m ³ 15 minutes. Form: Inhalable fraction TWA: 0.2 mg/m ³ 8 hours. Form: Inhalable fraction
2-Butoxyethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 50 ppm 15 minutes. TWA: 25 ppm 8 hours. STEL: 246 mg/m ³ 15 minutes. TWA: 123 mg/m ³ 8 hours.
Dipropyleneglycolmethylether	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. TWA: 308 mg/m ³ 8 hours. TWA: 50 ppm 8 hours.
Ammonia	EH40/2005 WELs (United Kingdom (UK), 1/2020). [ammonia] STEL: 25 mg/m ³ 15 minutes. Form: anhydrous STEL: 35 ppm 15 minutes. Form: anhydrous TWA: 25 ppm 8 hours. Form: anhydrous TWA: 18 mg/m ³ 8 hours. Form: anhydrous

Biological exposure indices

Product/ingredient nam	e	Exposure indices	5
No exposure indices known.			
No exposure indices known.			
No exposure indices known.			
No exposure indices known.			
No exposure indices known.			
Date of issue/Date of revision : 28	3/11/2023 Date of previous issue	: 25/08/2022	Version : 1.02 7/19
TEKNOSTAIN AQUA 1996-00 - NORF	RLAND-STONEGREY		Label No :50773

2-Butoxyethanol	Government regulation of Czech Republic Limit Values of Biological Exposure Tests (Czech Republic, 9/2015) Biological limit values: 0.17 mmol/mmol creatinine, butoxyacetic
	acid (after hydrolysis) [in urine]. Sampling time: the end of the shift at the end of the week. Biological limit values: 200 mg/g creatinine, butoxyacetic acid (ofter bydrolygic) in urine). Sampling time: the end of the shift of
	(after hydrolysis) [in urine]. Sampling time: the end of the shift at the end of the week.
No exposure indices known.	
Recommended monitoring procedures	 Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
2-Butoxyethanol	DNEL	Long term Oral	6.3 mg/kg	General	Systemic
			bw/day	population	
	DNEL	Short term Oral	26.7 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Long term	59 mg/m³	General	Systemic
		Inhalation		population	
	DNEL	Long term	98 mg/m ³	Workers	Systemic
	DNEL	Inhalation Short term	$147 mg/m^3$	General	Local
	DINEL	Inhalation	147 mg/m³	population	LUCAI
	DNEL	Short term	246 mg/m ³	Workers	Local
	DINLL	Inhalation	240 mg/m	VVUIKEIS	LUCAI
	DNEL	Short term	426 mg/m ³	General	Systemic
	DINCL	Inhalation	420 mg/m	population	Oysterine
	DNEL	Short term	1091 mg/	Workers	Systemic
	DITLE	Inhalation	m ³	W of Role	Cyclonno
1,2-benzisothiazol-3(2H)-one	DNEL	Long term Dermal	0.345 mg/	General	Systemic
.,			kg bw/day	population	-)
	DNEL	Long term Dermal	0.966 mg/	Workers	Systemic
		5	kg bw/day		,
	DNEL	Long term	1.2 mg/m ³	General	Systemic
		Inhalation	Ū	population	
	DNEL	Long term	6.81 mg/m ³	Workers	Systemic
		Inhalation	_		-
2-methyl-2H-isothiazol-3-one	DNEL	Long term	0.021 mg/	General	Local
		Inhalation	m³	population	
	DNEL	Long term	0.021 mg/	Workers	Local
		Inhalation	m³		
	DNEL	Long term Oral	0.027 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Short term	0.043 mg/	General	Local
		Inhalation	m^3	population	
	DNEL	Short term	0.043 mg/	Workers	Local
	DNEL	Inhalation Short term Oral	m³ 0.053 mg/	General	Systemic
	DNEL	Short term Oral	kg bw/day	population	Systemic
reaction mass of: 5-chloro-2-methyl-	DNEL	Long term	0.02 mg/m^3	General	Local
4-isothiazolin-3-one [EC no.	DINCL	Inhalation	0.02 mg/m	population	Local
247-500-7] and 2-methyl-2H-				population	
isothiazol-3-one [EC no. 220-239-6]					
(3:1)					
· ·	DNEL	Long term	0.02 mg/m ³	Workers	Local
		Inhalation	_		
	DNEL	Short term	0.04 mg/m ³		Local
		Inhalation	_	population	
	DNEL	Short term	0.04 mg/m ³	Workers	Local
		Inhalation			
	DNEL	Long term Oral	0.09 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Short term Oral	0.11 mg/	General	Systemic
			kg bw/day	population	

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Date of issue/Date of revision	: 28/11/2023	Date of previous issue
TEKNOSTAIN AQUA 1996-00 -	NORRLAND-S	TONEGREY

: 25/08/2022

SECTION 8: Exposure controls/personal protection

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
	Recommendations : Wear suitable gloves tested to EN374.
	> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm
	Not recommended polyvinyl alcohol (PVA) gloves
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
	Filter type (spray application): A P
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance	
Physical state	: Liquid.
Colour	: Grey.
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and	1
boiling range	

Ingredient name		°C	°F	Method
water		100	212	
Flammability	: Not ava	ilable.		
Lower and upper explosion	: Lower:	Not applicable.		

Lower and upper explosion	 Lower:
limit	Upper:

Upper: Not applicable.

SECTION 9: Physical and chemical properties

2

Flash point	÷	Not available.
Auto-ignition temperature	:	Not available.
Decomposition temperature	1	Not available.
рН	1	Not applicable.
Viscosity	4	Not available.
Solubility(ies)	1	
Not available.		
Solubility in water	;	Not available.
Partition coefficient: n-octanol/ water	:	Not applicable.

Vapour pressure

	Vd	Vapour Pressure at 20°C		Vapour pressure at 50°C			
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
water	17.5	2.3					
Relative density	: Not	available.	<u> </u>	Į			
Density	: 1 g/	cm³					
Vapour density	: Not	available.					
Explosive properties	: Not	available.					
Oxidising properties	: Not	available.					
Particle characteristics							
Median particle size	: Not	applicable.					

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredient	s.
10.2 Chemical stability	: The product is stable.	
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.	
10.4 Conditions to avoid	: No specific data.	
10.5 Incompatible materials	: No specific data.	
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.	

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-benzisothiazol-3(2H)-	LD50 Oral	Rat	1020 mg/kg	-
one				
2-methyl-2H-isothiazol-	LC50 Inhalation Dusts and	Rat	0.11 mg/l	4 hours
3-one	mists			
reaction mass of: 5-chloro-	LD50 Oral	Rat	53 mg/kg	-
2-methyl-4-isothiazolin-				
3-one [EC no. 247-500-7]				
and 2-methyl-2H-isothiazol-				
3-one [EC no. 220-239-6] (3:				
te of issue/Date of revision	: 28/11/2023 Date of previous i	ssue : 25/08,	/2022	Version : 1.02 11/
KNOSTAIN AQUA 1996-00 -	NORRLAND-STONEGREY			Label No :50773

S	SECTION 11: Toxicological information						
	1)						
Conclusion/Summary : Based on available data, the classification criteria are not met.							

Acute toxicity estimates

Route	ATE value
halation (vapours)	2402.4 mg/l

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
titanium dioxide	Skin - Mild irritant	Human	-	72 hours 300 ug l	-
2-Butoxyethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100	-
	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
1,2-benzisothiazol-3(2H)-one		Human	-	48 hours 5 %	-
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	Skin - Severe irritant	Human	-	0.01 %	-
Conclusion/Summary	: Based on available data, the	e classification c	riteria are	e not met.	
<u>Sensitisation</u>					
Conclusion/Summary	: May cause an allergic skin	reaction.			
Mutagenicity	,				
Conclusion/Summary	: Based on available data, the	e classification c	riteria are	not met.	
Carcinogenicity					
Conclusion/Summary	: Based on available data, the	e classification o	riteria are	not met.	
Reproductive toxicity	,				
Conclusion/Summary	: Based on available data, the classification criteria are not met.				
<u>Teratogenicity</u>				not mot	
Conclusion/Summary	: Based on available data, th	e classification c	riteria are	not met	
Specific target organ toxicit				not mot.	
Not available.	<u>y (Single exposure)</u>				
Specific target organ toxicit	<u>y (repeated exposure)</u>				
Not available.					
Aspiration hazard Not available.					
nformation on likely routes f exposure	: Not available.				
otential acute health effects					
Eye contact	: No known significant effects	s or critical haza	rds.		
Inhalation	: No known significant effects	s or critical haza	rds.		
Skin contact	: May cause an allergic skin	reaction.			
Ingestion	: No known significant effects		rds.		
symptoms related to the phy	sical, chemical and toxicolog	ical characteris	<u>stics</u>		
	NI				
Eye contact	: No specific data.				

Skin contact	: Adverse symptoms may include the following: irritation
	redness
Ingestion	: No specific data.
ingestion	. No specific data.
Delayed and immediate effect	ts as well as chronic effects from short and long-term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	<u>ects</u>
Not available.	
Conclusion/Summary	: Not available.
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties
Not available.
11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Acute LC50 3 mg/l Fresh water Acute LC50 6.5 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate Daphnia - Daphnia pulex -	48 hours
Acute LC50 6.5 mg/l Fresh water	Daphnia - <i>Daphnia pulex</i> -	
	Neonate	48 hours
Acute LC50 >1000000 μg/l Marine <i>w</i> ater	Fish - Fundulus heteroclitus	96 hours
Acute EC50 >1000 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
Acute LC50 800000 µg/l Marine water	Crustaceans - Crangon crangon	48 hours
Acute LC50 1250000 μg/l Marine water	Fish - <i>Menidia beryllina</i>	96 hours
Acute EC50 0.36 mg/l Marine water	Algae - Skeletonema Costatum	72 hours
Acute EC50 3.7 mg/l	Daphnia - <i>Daphnia Magna</i>	48 hours
Acute LC50 1.9 mg/l Fresh water	Fish - Onorhynchus Mykiss	96 hours
Acute NOEC 0.15 mg/l Marine water	Algae - Skeletonema Costatum	72 hours
Acute EC50 0.18 ppm Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
Acute LC50 0.07 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
~ ~ ~ ~ ~	rater cute EC50 >1000 mg/l Fresh water cute LC50 800000 µg/l Marine water cute LC50 1250000 µg/l Marine water cute EC50 0.36 mg/l Marine water cute EC50 3.7 mg/l cute LC50 1.9 mg/l Fresh water cute NOEC 0.15 mg/l Marine water cute EC50 0.18 ppm Fresh water cute LC50 0.07 ppm Fresh water	rater cute EC50 >1000 mg/l Fresh water cute LC50 800000 µg/l Marine water cute LC50 1250000 µg/l Marine water cute EC50 0.36 mg/l Marine water cute EC50 3.7 mg/l cute LC50 1.9 mg/l Fresh water cute NOEC 0.15 mg/l Marine water cute EC50 0.18 ppm Fresh water

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
2-benzisothiazol-3(2H)-one	EU	24 % - 28 days	-	-
Conclusion/Summary : This product has not been tested for biodegradation.				

S	SECTION 12: Ecologi	cal information	
	Product/ingredient name	Aquatic half-life	Photolysis
	7,2-benzisothiazol-3(2H)-one	-	-

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-Butoxyethanol	0.81	-	Low
1,2-benzisothiazol-3(2H)-one	-	3.2	Low

Biodegradability

Inherent

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

D	 1.12	4
	iuc	λ.

Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
European waste catalogue (EWC)	: 080112, 200128
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
Date of issue/Date of revi	sion : 28/11/2023	Date of previous issue	: 25/08/2022	Version : 1.02 14/19
TEKNOSTAIN AQUA 1996-00 - NORRLAND-STONEGREY				Label No :50773

SECTION 14: Transport information				
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in : Not relevant/applicable due to nature of the product. bulk according to IMO instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous

substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]	
FEKNOSTAIN AQUA 1996-00	≥90	3	
Labelling :			
<u> Dther EU regulations</u>			
Industrial emissions : Not liste (integrated pollution prevention and control) - Air	d		
Industrial emissions : Not liste (integrated pollution prevention and control) - Water	d		
Explosive precursors : Not app	licable.		
Ozone depleting substances (1005/20	<u>09/EU)</u>		
Not listed.			
Prior Informed Consent (PIC) (649/201	2/EU)		
Not listed.			
Persistent Organic Pollutants Not listed.			
Seveso Directive			
This product is not controlled under the S	Seveso Directi	ve.	
National regulations			
Austria			
ate of issue/Date of revision : 28/11/2	023 Date of pro	evious issue : 25/08/2022	Version : 1.02 15/19
EKNOSTAIN AQUA 1996-00 - NORRLAN	D-STONEGR	EY	Label No :50773

Limitation of the use of organic solvents	: Permitted.				
Czech Republic					
Denmark					
Executive Order No. 1795/2	2015				
Ingredient name		Annex I Section A	Annex I Section B		
titanium dioxide		Listed	-		
MAL-code	: 00-1				
Protection based on MAL	: According to the regulation	ns on work involving coded p se of personal protective equi			
	coveralls/protective clothing clothes do not adequately pr shield must be worn in work	orn for all work that may result in must be worn when soiling is so rotect skin against contact with th involving spattering if a full mash se of eye protection is not requir	great that regular wor ne product. A face k is not required. In this		
		which there is return spray, the form protectors/apron/coveralls/pro			
	MAL-code: 00-1 Application: When spraying spray zone.	g in existing* spray booths, if the	operator is outside th		
	- Arm protectors must be wo	rn.			
		omisation occurs in cabins or spi zone and during spraying outside			
	- Full mask with combined fil	lter, coveralls and hood must be	worn.		
	rack trolleys, etc, must be ec	ring ovens that are temporarily pl quipped with a mechanical exhau passing through workers' inhalati	ust system to prevent		
		treated surfaces, a mask with du e protection must be worn. Work			
	Caution The regulations co	ntain other stipulations in additio	n to the above.		
	*See Regulations.				
Restrictions on use		nal users below 18 years of age. rities Executive Order regarding			
List of undesirable substances	: Not listed				
Carcinogenic waste		abeled: Contains a substance or ent legislation on cancer risks.	substances regulated		
Finland	-	-			
France		50.0			
Social Security Code, Articles L 461-1 to L 461-7	: 2-Butoxyethanol	RG 8	4		
Reinforced medical surveillance	: Act of July 11, 1977 determinedical surveillance: not appreciate the surveillance of	ning the list of activities which re	quire reinforced		

TEKNOSTAIN AQUA 1996-00 - NORRLAND-STONEGREY

SECTION 15: Regulatory information

<u>Germany</u>	
Storage class (TRGS 510)	: 12
Hazardous incident ordinal	nce
This product is not controlled	under the Germany Hazardous Incident Ordinance.
Hazard class for water	: 1
Technical instruction on air quality control	: TA-Luft Number 5.2.5: 6.1%
ΑΟΧ	: The product contains organically bound halogens and can contribute to the AOX value in waste water.
<u>Italy</u>	
D.Lgs. 152/06	: Not determined.
Netherlands	
Water Discharge Policy (ABM)	: A(3) Hazardous for aquatic organisms, may have long-term hazardous effects in aquatic environment. Decontamination effort: A
<u>Norway</u>	
<u>Sweden</u>	
Switzerland	
VOC content	: Exempt.
International regulations	
Chemical Weapon Convention	on List Schedules I, II & III Chemicals
Not listed.	
Montreal Protocol	
Not listed.	
Stockholm Convention on P Not listed.	ersistent Organic Pollutants
Rotterdam Convention on P	rior Informed Consent (PIC)
Not listed.	
UNECE Aarhus Protocol on	POPs and Heavy Metals
Not listed.	
15.2 Chemical safety assessment	: This product contains substances for which Chemical Safety Assessments are stil required.

✓ Indicates information that has changed from previously issued version.

Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group PDUE = Very Description of Very Disconveryed time
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Sens. 1, H317	Calculation method

Full text of abbreviated H statements

Date of issue/Date of revision	: 28/11/2023	Date of previous issue	: 25/08/2022	Version : 1.02 17/19
TEKNOSTAIN AQUA 1996-00 -	NORRLAND-S	TONEGREY		Label No :50773

SECTION 16: Other information	
⊮ 301 T	oxic if swallowed.
H302 H	larmful if swallowed.
H310 F	atal in contact with skin.
H311 T	oxic in contact with skin.
H314 C	Causes severe skin burns and eye damage.
H315 C	Causes skin irritation.
H317 N	lay cause an allergic skin reaction.
H318 C	causes serious eye damage.
H319 C	Causes serious eye irritation.
H330 F	atal if inhaled.
H331 T	oxic if inhaled.
	Suspected of causing cancer.
	/ery toxic to aquatic life.
H410 V	ery toxic to aquatic life with long lasting effects.
EUH071 C	Corrosive to the respiratory tract.
Full text of classifications [CLP/GHS]	
Cute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
Date of issue/ Date	e of : 28/11/2023
revision	
Date of previous is	sue : 25/08/2022
Version	: 1.02
	TEKNOSTAIN AQUA 1996-00_NORRLAND- NORRLAND-STONEGREY STONEGREY

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision: 28/11/2023Date of previous issueTEKNOSTAIN AQUA 1996-00 - NORRLAND-STONEGREY

: 25/08/2022

Version : 1.02 19/19 Label No : 50773