Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

SAFETY DATA SHEET



TEKNOTOP 2980-11 - All variants

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier Product name

TEKNOTOP 2980-11 - All variants

1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use: Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person : Prod-safe@teknos.com

responsible for this SDS

National contact

Teknos (UK) Limited, 7 Longlands Rd, Bicester, Oxfordshire OX26 5AH, United Kingdom. Tel. +44 (0) 1869 208005.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : NHS: 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to UK CLP/GHS

Aquatic Chronic 3, H412

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements		
Signal word	:	No signal word.
Hazard statements	:	H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	P273 - Avoid release to the environment.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	Contains 3-iodo-2-propynyl-butyl carbamate, adipohydrazide, 1,2-benzisothiazol-3 (2H)-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) and 2-Methyl-1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Contains biocidal products for dry film and in-can preservation: IPBC and BIT and DTBMA and MBIT. Risk of skin sensitisation.

SECTION 2: Hazards	identification
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
2.3 Other hazards	
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients 3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Туре
Dipropyleneglycolmethylether	REACH #: 01-2119450011-60 EC: 252-104-2 CAS: 34590-94-8	≤3	Not classified.	[2]
3-iodo-2-propynyl-butyl carbamate	EC: 259-627-5 CAS: 55406-53-6 Index: 616-212-00-7	≤0.3	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)	[1]
adipohydrazide	REACH #: 01-2119962900-36 EC: 213-999-5 CAS: 1071-93-8	≤0.3	Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
2-Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	≤0.1	Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319	[1] [2]
Ammonia	REACH #: 01-2119488876-14 EC: 215-647-6 CAS: 1336-21-6 Index: 007-001-01-2	<0.1	Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 (M=1)	[1] [2]
Propylene glycol	REACH #: 01-2119456809-23 EC: 200-338-0 CAS: 57-55-6	≤0.1	Not classified.	[2]
pyrithione zinc	REACH #: 01-2119511196-46 EC: 236-671-3 CAS: 13463-41-7 Index: 613-333-00-7	≤0.0015	Acute Tox. 3, H301 Acute Tox. 2, H330 Eye Dam. 1, H318 Repr. 1B, H360D STOT RE 1, H372 Aquatic Acute 1, H400 (M=1000) Aquatic Chronic 1, H410 (M=10)	[1]
Formaldehyde	REACH #: 01-2119488953-20 EC: 200-001-8	<0.1	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330	[1] [2]

SECTION 3: Comp	oosition/information on ingred	ients
	CAS: 50-00-0 Index: 605-001-00-5	Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Carc. 1B, H350 STOT SE 3, H335
		See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	:	None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the	: In a fire or if heated, a pressure increase will occur and the container may burst.
substance or mixture	This material is harmful to aquatic life with long lasting effects. Fire water
	contaminated with this material must be contained and prevented from being
	discharged to any waterway, sewer or drain.

Date of issue/Date of revision	: 26/10/2023	Date of previous issue	: 05/10/2022	Version	: 1.01	3/17
TEKNOTOP 2980-11 - All variants				Label No :	38863	3

SECTION 5: Firefighting measures Hazardous combustion : Decomposition products may include the following materials: carbon dioxide products carbon monoxide **5.3 Advice for firefighters Special protective actions** : Promptly isolate the scene by removing all persons from the vicinity of the incident if for fire-fighters there is a fire. No action shall be taken involving any personal risk or without suitable training. **Special protective** Fire-fighters should wear appropriate protective equipment and self-contained ŝ, equipment for fire-fighters breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	te	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

 Protective measures Put on appropriate personal protective equipment (see Section 8). Do Avoid contact with eyes, skin and clothing. Avoid breathing vapour or release to the environment. Keep in the original container or an approal alternative made from a compatible material, kept tightly closed when Empty containers retain product residue and can be hazardous. Do n container.
--

SECTION 7: Handling and storage

Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional
	information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific	: Not available.
solutions	

SECTION 8: Exposure controls/personal protection

8.1 Control parameters	
Occupational exposure limits	
Dipropyleneglycolmethylether	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.
2-Butoxyethanol	TWA: 308 mg/m ³ 8 hours. TWA: 50 ppm 8 hours. EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed
	through skin.
	STEL: 50 ppm 15 minutes.
	TWA: 25 ppm 8 hours.
	STEL: 246 mg/m ³ 15 minutes.
	TWA: 123 mg/m³ 8 hours.
Ammonia	EH40/2005 WELs (United Kingdom (UK), 1/2020). [ammonia
	anhydrous]
	STEL: 25 mg/m ³ 15 minutes. Form: anhydrous
	STEL: 35 ppm 15 minutes. Form: anhydrous
	TWA: 25 ppm 8 hours. Form: anhydrous
	TWA: 18 mg/m ³ 8 hours. Form: anhydrous
Propylene glycol	EH40/2005 WELs (United Kingdom (UK), 1/2020).
	TWA: 10 mg/m ³ 8 hours. Form: Particulate
	TWA: 474 mg/m ³ 8 hours. Form: total vapour and particulates
	TWA: 150 ppm 8 hours. Form: total vapour and particulates
Formaldehyde	EH40/2005 WELs (United Kingdom (UK), 1/2020).
	STEL: 2.5 mg/m ³ 15 minutes.
	STEL: 2 ppm 15 minutes.
	TWA: 2 ppm 8 hours.
	TWA: 2.5 mg/m³ 8 hours.

Biological exposure indices

Product/ingredient name	Exposure indices
2-Butoxyethanol	EH40/2005 BMGVs (United Kingdom (UK), 8/2018) BGV: 240 mmol/mol creatinine, butoxyacetic acid [in urine]. Sampling time: post shift.
procedures natior	ence should be made to appropriate monitoring standards. Reference to nal guidance documents for methods for the determination of hazardous ances will also be required.

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
<i>fipropyleneglycolmethylether</i>	DNEL	Long term Oral	36 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	37.2 mg/m ³	General	Systemic
	DNEL	Long term Dermal	121 mg/kg	population General	Systemic
	DNEL	Long term Dermal	bw/day 283 mg/kg	population Workers	Systemic
	DNEL	Long term Inhalation	bw/day 308 mg/m³	Workers	Systemic
3-iodo-2-propynyl-butyl carbamate	DNEL	Long term	0.023 mg/	Workers	Systemic
	DNEL	Inhalation Short term	m ³ 0.07 mg/m ³	Workers	Systemic
	DNEL	Inhalation Short term	1.16 mg/m ³	Workers	Local
	DNEL	Inhalation Long term	1.16 mg/m ³	Workers	Local
	DNEL	Inhalation Long term Dermal	2 mg/kg	Workers	Systemic
adipohydrazide	DNEL	Long term	bw/day 17.5 mg/m³	Workers	Systemic
2-Butoxyethanol	DNEL	Inhalation Long term Oral	6.3 mg/kg	General	Systemic
	DNEL	Short term Oral	bw/day 26.7 mg/	population General	Systemic
	DNEL	Long term	kg bw/day 59 mg/m³	population General	Systemic
	DNEL	Inhalation Long term	98 mg/m³	population Workers	Systemic
	DNEL	Inhalation Short term	147 mg/m³	General	Local
	DNEL	Inhalation Short term	246 mg/m ³	population Workers	Local
	DNEL	Inhalation Short term	426 mg/m ³	General	Systemic
	DNEL	Inhalation Short term	1091 mg/	population Workers	Systemic
Propylene glycol	DNEL	Inhalation Long term	m³ 10 mg/m³	General	Local
	DNEL	Inhalation Long term	10 mg/m ³	population Workers	Local
	DNEL	Inhalation Long term	50 mg/m ³	General	Systemic
	DNEL	Inhalation Long term	168 mg/m ³	population Workers	Systemic
pyrithione zinc	DNEL	Inhalation Long term Dermal	0.01 mg/	Workers	Systemic
Formaldehyde	DNEL	Long term	kg bw/day 0.375 mg/	Workers	Local
	DNEL	Inhalation Short term	m ³ 0.75 mg/m ³		Local
	DNEL	Inhalation Long term Dermal	12 µg/cm ²	General	Local
	DNEL	Long term Dermal	37 µg/cm²	population Workers	Local
	DNEL	Long term Inhalation	0.1 mg/m ³	General	Local
	DNEL	Long term	3.2 mg/m³	population General	Systemic
	DNEL	Inhalation Long term Oral	4.1 mg/kg	population General	Systemic
	DNEL	Long term Inhalation	bw/day 9 mg/m³	population Workers	Systemic

Γ

SECTION 8: Exposure controls/personal protection							
	DI	NEL	Long term Dermal	102 mg/kg bw/day	General population	Systemic	
	D	NEL	Long term Dermal	240 mg/kg bw/day	Workers	Systemic	

PNECs

No PNECs available

8.2 Exposure controls Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.						
Individual protection meas	<u>ures</u>						
Hygiene measures	 Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. 						
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.						
Skin protection							
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.						
	Recommendations : Wear suitable gloves tested to EN374.						
	> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm						
	Not recommended polyvinyl alcohol (PVA) gloves						
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.						
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. 						
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.						
	Filter type (spray application): A P						
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.						

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance	
Physical state	: Liquid.
Colour	: Various
Odour	: Slight

Date of issue/Date of revision TEKNOTOP 2980-11 - All variants

: 26/10/2023 Date of previous issue

:05/10/2022

Odour threshold	: Not a	available.						
Melting point/freezing point	: Not	: Not available.						
Initial boiling point and boiling range	:							
Ingredient name		°C	°F	Method				
water		100	212					
Dipropyleneglycolmethylether		189.6	373.3	EU A.2				
Flammability (solid, gas)	: Not	available.						
Upper/lower flammability or explosive limits		er: Not applicab er: Not applicab						
Flash point	: Clos	ed cup: >100°C	C(>212°F)					
Auto-ignition temperature								
Ingredient name		°C	°F	Method				
Propanol, 1-(2-butoxy-1-methyleth	ioxy)	194	381.2	EU A.15				
Dipropyleneglycolmethylether		207	404.6	EU A.15				
Decomposition temperature	: Not a	available.						
рН	: <mark>8</mark> .3 t	o 8.8						
Viscosity	: Not	available.						
Solubility(ies) Not available.	:							
Solubility in water	: Not	available.						
Partition coefficient: n-octan water	ol/ : Not a	applicable.						
Vapour pressure	:							
	Va	pour Pressure	at 20°C	Vapour pressure at 50°C				

	Va	Vapour Pressure at 20°C			Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
water	17.5	2.3					
2-Propanol, 1-(2-butoxy- 1-methylethoxy)	0.045	0.006					
Relative density	: Not	available.					
Density	: 1 g/d	: 1 g/cm ³					
Vapour density	: Not	available.					
Explosive properties	: Not	available.					
Oxidising properties	: Not	available.					
Particle characteristics							
Median particle size	: Not	applicable.					

SECTION 10: Stability and reactivity							
10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredier							
10.2 Chemical stability	: The product is stable.						
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.						
10.4 Conditions to avoid	: No specific data.						
10.5 Incompatible materials	: No specific data.						

Date of issue/Date of revision	: 26/10/2023	Date of previous issue	:05/10/2022	Version : 1.01 8/17
TEKNOTOP 2980-11 - All variants				Label No :38863

SECTION 10: Stability and reactivity

10.6 Hazardous

decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
͡Ĵ∕-iodo-2-propynyl-butyl carbamate	LC50 Inhalation Dusts and mists	Rat	0.67 g/m³	4 hours
	LC50 Inhalation Dusts and mists	Rat	0.763 mg/l	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	400 mg/kg	-
Ammonia	LD50 Oral	Rat	350 mg/kg	-
Propylene glycol	LD50 Dermal	Rabbit	20800 mg/kg	-
	LD50 Oral	Rat	20 g/kg	-
pyrithione zinc	LC50 Inhalation Dusts and mists	Rat	140 mg/m ³	4 hours
	LD50 Dermal	Rabbit	100 mg/kg	-
	LD50 Oral	Rat	177 mg/kg	-
Formaldehyde	LC50 Inhalation Gas.	Rat	250 ppm	4 hours
	LD50 Dermal	Rabbit	270 mg/kg	-
	LD50 Oral	Rat	100 mg/kg	-

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Acute toxicity estimates

Route	ATE value
Inhalation (dusts and mists)	227.19 mg/l

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observatio
Dipropyleneglycolmethylether	Eyes - Mild irritant	Human	-	8 mg	-
, ., .,	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
	Skin - Mild irritant	Rabbit	-	500 mg	-
3-iodo-2-propynyl-butyl	Eyes - Severe irritant	Rabbit	-	-	-
carbamate					
2-Butoxyethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100	-
,	5			mg	
	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
Ammonia	Eyes - Severe irritant	Rabbit	-	0.5 minutes	-
	5			1 mg	
	Eyes - Severe irritant	Rabbit	-	250 ug	-
Propylene glycol	Eyes - Mild irritant	Rabbit	-	100 mg	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
	Skin - Mild irritant	Human	_	168 hours	-
				500 mg	
	Skin - Mild irritant	Woman	_	96 hours 30	-
				%	
	Skin - Moderate irritant	Child	_	96 hours 30	-
		•••••		% C	
	Skin - Moderate irritant	Human	_	72 hours 104	-
				mg l	
Formaldehyde	Eyes - Mild irritant	Human	-	6 minutes 1	-
,				ppm	
	Eyes - Severe irritant	Rabbit	-	24 hours 750	-
				ug	
	Eyes - Severe irritant	Rabbit	-	750 ug	-
	Skin - Mild irritant	Human	-	72 hours 150	-
				ug l	
			1		

SECTION 11: Toxicological information					
	Skin - Mild irritant	Rabbit	-	540 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 50	-
				mg	
	Skin - Severe irritant	Human	-	0.01 %	-
	Skin - Severe irritant	Rabbit	-	0.8 %	-
	Skin - Severe irritant	Rabbit	-	24 hours 2	-
				mg	

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
3-iodo-2-propynyl-butyl carbamate	skin	Guinea pig	Not sensitizing
Conclusion/Summary : Based on available data, the classification criteria are not met.			

Mutagenicity

Product/ingredient name	Test	Experiment	Result
3-iodo-2-propynyl-butyl carbamate	-	Experiment: In vitro Subject: Bacteria	Negative

Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
3-iodo-2-propynyl-butyl carbamate	Negative	-	Negative	Rabbit - Female	Oral: 20 mg/kg	13 days; 7 days per week
	Positive	-	Negative	Rabbit - Female		13 days; 7 days per week

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Teratogenicity

Product/ingredient name	Result	Species	Dose	Exposure
3-iodo-2-propynyl-butyl carbamate	Negative - Oral	Rabbit - Female	50 mg/kg	-

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Ammonia	Category 3		Respiratory tract irritation
Formaldehyde	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
	Category 1 Category 1	-	larynx -

Aspiration hazard

Not available.

SECTION 11: Toxicological information

		-
Information on likely routes of exposure	1	Not available.
Potential acute health effects	<u>i</u>	
Eye contact	1	No known significant effects or critical hazards.
Inhalation	1	No known significant effects or critical hazards.
Skin contact	1	No known significant effects or critical hazards.
Ingestion	1	No known significant effects or critical hazards.
Symptoms related to the phy	<u>sic</u>	cal, chemical and toxicological characteristics
Eye contact	1	No specific data.
Inhalation	1	No specific data.
Skin contact	1	No specific data.
Ingestion	1	No specific data.
Delayed and immediate effec	<u>ts</u>	as well as chronic effects from short and long-term exposure
<u>Short term exposure</u>		
Potential immediate effects	1	Not available.
Potential delayed effects	1	Not available.
Long term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health effe	<u>ect</u>	<u>s</u>
Not available.		
Conclusion/Summary	1	Not available.
General	1	No known significant effects or critical hazards.
Carcinogenicity	1	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Reproductive toxicity	:	No known significant effects or critical hazards.

Other information

: Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
iodo-2-propynyl-butyl carbamate	Acute EC50 0.022 mg/l Fresh water	Algae - Algae - Scenedemus subspicatus	72 hours
	Acute EC50 0.16 mg/l Fresh water	Daphnia - Daphnia - <i>Daphnia</i> magna	48 hours
	Acute LC50 0.067 mg/l Fresh water	Fish - Trout - Oncorhynchus mykiss	96 hours
	Acute NOEC 0.049 mg/l Fresh water	Fish - Trout - Oncorhynchus mykiss	96 hours
	Chronic NOEC 0.05 mg/l Fresh water	Daphnia - Daphnia - <i>Daphnia</i> <i>Magna</i>	21 days
2-Butoxyethanol	Acute EC50 >1000 mg/l Fresh water	Daphnia - Water flea - <i>Daphnia magna</i>	48 hours
	Acute LC50 800000 μg/l Marine water	Crustaceans - Common shrimp, sand shrimp - <i>Crangon crangon</i>	48 hours
	Acute LC50 1250000 µg/l Marine water	Fish - Inland silverside - Menidia beryllina	96 hours
Ammonia	Acute LC50 37 ppm Fresh water	Fish - Western mosquitofish - <i>Gambusia affinis</i> - Adult	96 hours
ate of issue/Date of revision	: 26/10/2023 Date of previous issue	: 05/10/2022 Version	:1.01 11/17
EKNOTOP 2980-11 - All vari	ants	Label No	38863

Propylene glycol	Acute EC50 19300 mg/l Fresh water	Algae - Algae	96 hours
	Acute EC50 43500 mg/l Fresh water	Daphnia - Daphnia - Daphnia magna	48 hours
	Acute LC50 18340000 µg/l Fresh water	Crustaceans - Water flea - Ceriodaphnia dubia	48 hours
	Acute LC50 40613 mg/l Fresh water	Fish - Trout - Oncorhynchus mykiss	96 hours
yrithione zinc	Acute EC50 0.51 µg/l Marine water	Algae - Diatom - Thalassiosira pseudonana	96 hours
	Acute EC50 38 µg/l Fresh water	Crustaceans - Ostracod - Ilyocypris dentifera	48 hours
	Acute EC50 8.25 ppb Fresh water	Daphnia - Water flea - Daphnia magna	48 hours
	Acute LC50 2.68 ppb Fresh water	Fish - Fathead minnow - Pimephales promelas	96 hours
	Chronic EC10 0.36 µg/l Marine water	Algae - Diatom - <i>Thalassiosira</i> pseudonana	96 hours
	Chronic NOEC 2.7 ppb Fresh water	Daphnia - Water flea - Daphnia magna	21 days
ormaldehyde	Acute EC50 3.48 mg/l Fresh water	Algae - Green algae - Desmodesmus subspicatus	72 hours
	Acute EC50 0.788 mg/l Marine water	Algae - Green algae - Ulva pertusa	96 hours
	Acute EC50 12.98 mg/l Fresh water	Crustaceans - Water flea - <i>Ceriodaphnia dubia</i> - Neonate	48 hours
	Acute EC50 5800 µg/l Fresh water	Daphnia - Water flea - Daphnia pulex - Neonate	48 hours
	Acute LC50 1.41 ppm Fresh water	Fish - Rainbow trout, donaldson trout - Oncorhynchus mykiss	96 hours
	Chronic NOEC 0.005 mg/l Marine water	Algae - Haptophyte - <i>Isochrysis</i> <i>galbana</i> - Exponential growth phase	96 hours
	Chronic NOEC 953.9 ppm Fresh water	Fish - Chinook salmon - Oncorhynchus tshawytscha - Egg	43 days

Conclusion/Summary : Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Conclusion/Summary	: This product has not been	tested for biodegradation.	
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
riodo-2-propynyl-butyl carbamate Propylene glycol	-	-	Not readily Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
D ipropyleneglycolmethylether	0.004	-	Low
3-iodo-2-propynyl-butyl	>1	-	Low
carbamate			
2-Butoxyethanol	0.81	-	Low
Propylene glycol	-1.07	-	Low
pyrithione zinc	0.9	11	Low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

Date of issue/Date of revision : 26/10/202

: 26/10/2023 Date of previous issue

:05/10/2022

SECTION 12: Ecological information

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment meth	ods
Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
European waste catalogue (EWC)	: 080111*
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture **UK (GB)/REACH**

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Ozone depleting substances

Not listed.

Prior Informed Consent (PIC)

Not listed.

Persistent Organic Pollutants

Not listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

No listed substance

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Product/ingredient name	List name	Name on list	Classification	Notes
₽ ormaldehyde	UK Occupational Exposure Limits EH40 - WEL	formaldehyde; methanal	Carc.	-
	ļ	<u> </u>	<u>_</u>	

Е <u>regulations</u>

Date of issue/Date of revision	: 26/10/2023	Date of previous issue	: 05/10/2022	Version	: 1.01	14/17
15.2 Chemical safety assessment	: This product required.	t contains substances	for which Chemical Sa	fety Assessme	ents are	e still
UNECE Aarhus Protocol or Not listed.	<u>IPOPs and Hea</u>	<u>vy Metals</u>				
Rotterdam Convention on I Not listed.						
Stockholm Convention on Not listed.	<u>Persistent Orga</u>	<u>nic Pollutants</u>				
Montreal Protocol Not listed.						
Chemical Weapon Convent Not listed.	<u>ion List Schedu</u>	iles I, II & III Chemica	<u>ils</u>			
International regulations						
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed					
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed					

Version : 1.01 14/17 Label No :38863

SECTION 16: Other information

Indicates information that has changed	from previously issued version.
Abbreviations and acronyms: ATE = A GB CLP Packagin No. 720 DMEL = DNEL = EUH stat N/A = NC PBT = P PNEC = RRN = R SGG = S	cute Toxicity Estimate = UK CLP (EC No 1272/2008) on the Classification, Labelling and ng of Substances and Mixtures as amended by (EU Exit) Regulations 2019 and amendments Derived Minimal Effect Level Derived No Effect Level tement = GB CLP-specific Hazard statement ot available ersistent, Bioaccumulative and Toxic Predicted No Effect Concentration REACH Registration Number segregation Group /ery Persistent and Very Bioaccumulative
Procedure used to derive the classificati	0.P

Procedure used to derive the classification

Classification	Justification
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H360D	May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications

Neute Teur O		
	ACUTE TOXICITY - Category 2	
Acute Tox. 3	ACUTE TOXICITY - Category 3	
Acute Tox. 4	ACUTE TOXICITY - Category 4	
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1	
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1	
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2	
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3	
Carc. 1B	CARCINOGENICITY - Category 1B	
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1	
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2	
Muta. 2	GERM CELL MUTAGENICITY - Category 2	
Repr. 1B	REPRODUCTIVE TOXICITY - Category 1B	
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B	
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2	
Skin Sens. 1	SKIN SENSITISATION - Category 1	
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1	
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3	
Date of issue/ Date of	f : 26/10/2023	
revision		
Date of previous issue	e : 05/10/2022	
Date of issue/Date of revision	ion : 26/10/2023 Date of previous issue : 05/10/2022 Version : 1.03	1 15/17

Label No :38863

TEKNOTOP 2980-11 - All variants

SECTION 16: Other information

Version

: 1.01

EKNOTOP 2980-11

All variants

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision TEKNOTOP 2980-11 - All variants