Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Malta

SAFETY DATA SHEET



TEKNOTOP 2980-11 - All variants

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier Product name

: TEKNOTOP 2980-11 - All variants

1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use: Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person : Prod-safe@teknos.com

responsible for this SDS

National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

National advisory body/Poison Centre

 Telephone number
 : Malta Competition and Consumer Affairs Authority (MCCAA): +356 2395 2000

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements Signal word : No signal word. **Hazard statements** : H412 - Harmful to aquatic life with long lasting effects. **Precautionary statements** : P273 - Avoid release to the environment. Prevention Response : Not applicable. Storage : Not applicable. : P501 - Dispose of contents and container in accordance with all local, regional, Disposal national and international regulations. Supplemental label : Contains 3-iodo-2-propynyl-butyl carbamate, adipohydrazide, 1,2-benzisothiazol-3 (2H)-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. elements 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) and 2-Methyl-1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Contains biocidal products for dry film and in-can preservation: IPBC and BIT and DTBMA and MBIT. Risk of skin sensitisation.

SECTION 2: Hazards identification

Annex XVII - Restrictions : on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

2.3 Other hazards

Product meets the criteria : TI for PBT or vPvB according vF to Regulation (EC) No. 1907/2006, Annex XIII Other hazards which do : No not result in classification

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

: None known.

SECTION 3: Composition/information on ingredients

3-iodo-2-propynyl-butyl carbamateCi 252-104-2 CAS: 354500-94-8S0.3Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 STOT RE 1, H372 (larynx) Aquatic Chronic 1, H410ATE [Oral] = 400 mg/kg ATE [Inhalation (dusts and mists)] = 0.67 mg/l M [Acute] = 10 M [Acute] = 10 M [Acute] = 10 M [Chronic] = 1adipohydrazideREACH #: 01-2119962900-36 EC: 213-999-5 CAS: 1071-93-8 ≤ 0.3 Acute Tox. 4, H302 Aquatic Chronic 2, H411ATE [Oral] = 400 mg/kg ATE [Inhalation M [Acute] = 10 M [Chronic] = 11,2-benzisothiazol-3(2H)- oneEC: 220-120-9 CAS: 1071-93-8 ≤ 0.05 Acute Tox. 4, H302 Aquatic Chronic 2, H411ATE [Oral] = 1020 mg/kg Skin Sens. 1, H317 Aquatic Acute 1, H4001,2-benzisothiazol-3(2H)- oneEC: 220-120-9 CAS: 55965-84-9 Index: 613-088-00-6 < 0.05 Acute Tox. 4, H302 Acute Tox. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 C $\geq 0.05\%$ M [Acute] = 1reaction mass of: 5-chloro- 2-methyl-4H-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- (3:1)CAS: 55965-84-9 Index: 613-167-00-5 < 0.001 Acute Tox. 2, H310 Acute Tox. 2, H317 M [Acute] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/kg <b< th=""><th>3.2 Mixtures Product/ingredient name</th><th>: Mixture</th><th>%</th><th>Classification</th><th>Specific Conc. Limits, M-factors and ATEs</th><th>Туре</th></b<>	3.2 Mixtures Product/ingredient name	: Mixture	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
carbamateCAS: 55406-53-6 Index: 616-212-00-7Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 Aquatic Chronic 1, H410 mg/kg ATE [Inhalation 	Dipropyleneglycolmethylether	01-2119450011-60 EC: 252-104-2	≤3	Not classified.	-	[2]
$\begin{array}{llllllllllllllllllllllllllllllllllll$		CAS: 55406-53-6	≤0.3	Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 Aquatic Chronic 1,	mg/kg ATE [Inhalation (dusts and mists)] = 0.67 mg/l M [Acute] = 10	[1]
one CAS: 2634-33-5 Index: 613-088-00-6 CAS: 25965-84-9 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- (3:1) CAS: 55965-84-9 Index: 613-167-00-5 CAS: 55965-84-9 Index: 613-167-0	adipohydrazide	01-2119962900-36 EC: 213-999-5	≤0.3	Aquatic Chronic 2,	-	[1]
2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:1) Index: 613-167-00-5 Acute Tox. 2, H310 Acute Tox. 2, H310 Acute Tox. 2, H310 Acute Tox. 2, H310 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071 Kg ATE [Dermal] = 50 mg/l Skin Corr. 1C, H314: C \geq 0.6% Eye Dam. 1, H318: C \geq 0.6% Eye Irrit. 2, H319: 0.06% \leq C < 0.6%	. ,	CAS: 2634-33-5	<0.05	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317	mg/kg Skin Sens. 1, H317: C ≥ 0.05%	[1]
C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100	2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6]		<0.001	Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: C \geq 0.6% Eye Dam. 1, H318: C \geq 0.6% Eye Irrit. 2, H319: 0.06% \leq C $<$ 0.6% Skin Sens. 1, H317: C \geq 0.0015% M [Acute] = 100	[1]

pyrithione zinc	REACH #: 01-2119511196-46 EC: 236-671-3 CAS: 13463-41-7 Index: 613-333-00-7	≤0.0015	Acute Tox. 3, H301 Acute Tox. 2, H330 Eye Dam. 1, H318 Repr. 1B, H360D STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 221 mg/kg ATE [Inhalation (dusts and mists)] = 0.14 mg/l M [Acute] = 1000 M [Chronic] = 10	[1]
2-Methyl-1,2-benzisothiazol- 3(2H)-one	CAS: 2527-66-4 Index: 613-336-00-3	<0.0015	Acute Tox. 3, H301 Acute Tox. 4, H312 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411 EUH071 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 175 mg/kg ATE [Dermal] = 1100 mg/kg Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 1	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Our existing the extension to	N N

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

CECTION 0. Throngh	
5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising	rom the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	te	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

: 26/10/2023 Date of previous issue

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

Recommendations : Not available. Industrial sector specific : Not available. solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
	EU OEL (Europe, 1/2022). [(2-Methoxymethylethoxy)-propanol] Absorbed through skin. Notes: list of indicative occupational exposure limit values TWA: 50 ppm 8 hours. TWA: 308 mg/m ³ 8 hours.

Biological exposure indices

Product/ingredient name No exposure indices known.		Exposure indices	
Recommended monitoring procedures : Reference shoul European Stand assessment of e values and meas atmospheres - G of exposure to cl (Workplace atmos		Ild be made to monitoring standards, such as the following: dard EN 689 (Workplace atmospheres - Guidance for the exposure by inhalation to chemical agents for comparison with limit asurement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment chemical and biological agents) European Standard EN 482 nospheres - General requirements for the performance of procedures ement of chemical agents) Reference to national guidance methods for the determination of hazardous substances will also be	
DNELs/DMELs			

Product/ingredient name	Туре	Exposure	Value	Population	Effects
Dipropyleneglycolmethylether	DNEL	Long term Oral	36 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	37.2 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	121 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	283 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	308 mg/m ³	Workers	Systemic
3-iodo-2-propynyl-butyl carbamate	DNEL	Long term Inhalation	0.023 mg/ m³	Workers	Systemic
	DNEL	Short term Inhalation	0.07 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	1.16 mg/m³	Workers	Local
	DNEL	Long term Inhalation	1.16 mg/m³	Workers	Local
	DNEL	Long term Dermal	2 mg/kg bw/day	Workers	Systemic
adipohydrazide	DNEL	Long term Inhalation	17.5 mg/m ³	Workers	Systemic
1,2-benzisothiazol-3(2H)-one	DNEL	Long term Dermal	0.345 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.966 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.2 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	6.81 mg/m³	Workers	Systemic
reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6]	DNEL	Long term Inhalation	0.02 mg/m³	General population	Local
(3:1)	DNEL	Long term Inhalation	0.02 mg/m³	Workers	Local
	DNEL	Short term Inhalation	0.04 mg/m ³	General population	Local
	DNEL	Short term Inhalation	0.04 mg/m ³	Workers	Local
	DNEL	Long term Oral	0.09 mg/ kg bw/day	General population	Systemic
	DNEL	Short term Oral	0.11 mg/ kg bw/day	General population	Systemic
pyrithione zinc	DNEL	Long term Dermal	0.01 mg/ kg bw/day	Workers	Systemic

PNECs

No PNECs available

8.2 Exposure controls
 Appropriate engineering controls
 Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
 Individual protection measures
 Hygiene measures
 Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

: 26/10/2023 Date of previous issue

SECTION 8: Exposure controls/personal protection

Eye/face protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses wit side-shields.		
Skin protection			
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard shoul be worn at all times when handling chemical products if a risk assessment indicate this is necessary. Considering the parameters specified by the glove manufacture check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.		
	Recommendations : Wear suitable gloves tested to EN374.		
	> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm		
	Not recommended polyvinyl alcohol (PVA) gloves		
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.		
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.		
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.		
	Filter type (spray application): A P		
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.		

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance	
Physical state	: Liquid.
Colour	: Various
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	:
Ingredient name	°C

Ingredient name		°C	°F	Method	
water		100	212		
Dipropyleneglycolmethylether		189.6	373.3	EU A.2	
Flammability	: Not ava	ilable.	•		
Lower and upper explosion limit		Not applical Not applical			
Flash point	: Closed	cup: >100°0	C (>212°F)		
Auto-ignition temperature	:				

: 26/10/2023 Date of previous issue

Ingredient name		°C	°F	Method	
Propanol, 1-(2-butoxy-1-methylethoxy)		194	381.2	EU A.15	
Dipropyleneglycolmethylether		207	404.6	EU A.15	
Decomposition temperature	: Not ava	ailable.			
рН	: <mark>8</mark> .3 to 8	3.8			
Viscosity	: Not ava	ailable.			
Solubility(ies)	:				
Not available.					
Solubility in water	: Not ava	ailable.			
Partition coefficient: n-octanol/ water	: Not ap	olicable.			

Vapour pressure

	Vapour Pressure at 20°C			V	apour pres	ssure at 50°C
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
water	17.5	2.3				
2-Propanol, 1-(2-butoxy- 1-methylethoxy)	0.045	0.006				
Relative density	: Not	available.				
Density	: 1 g/	′cm³				
/apour density	: Not	available.				
Explosive properties	: Not	available.				
Oxidising properties	: Not	available.				
Particle characteristics						
Median particle size	: Not	applicable.				
article characteristics						

SECTION 10: Stability and reactivity

2

	-
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: No specific data.
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure	
⅔-iodo-2-propynyl-butyl carbamate	LC50 Inhalation Dusts and mists	Rat	0.67 g/m³	4 hours	
	LC50 Inhalation Dusts and mists	Rat	0.763 mg/l	4 hours	
	LD50 Dermal	Rat	>2000 mg/kg	-	
	LD50 Oral	Rat	400 mg/kg	-	
1,2-benzisothiazol-3(2H)- one	LD50 Oral	Rat	1020 mg/kg	-	
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	LD50 Oral	Rat	53 mg/kg	-	
pyrithione zinc	LC50 Inhalation Dusts and mists	Rat	140 mg/m ³	4 hours	
	LD50 Dermal	Rabbit	100 mg/kg	-	
	LD50 Oral	Rat	177 mg/kg	-	

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Acute toxicity estimates

Route	ATE value
Inhalation (dusts and mists)	227.19 mg/l

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Dipropyleneglycolmethylether	Eyes - Mild irritant	Human	-	8 mg	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
	Skin - Mild irritant	Rabbit	-	500 mg	-
3-iodo-2-propynyl-butyl carbamate	Eyes - Severe irritant	Rabbit	-	-	-
1,2-benzisothiazol-3(2H)-one	Skin - Mild irritant	Human	-	48 hours 5 %	-
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	Skin - Severe irritant	Human	-	0.01 %	-

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
3-iodo-2-propynyl-butyl carbamate	skin	Guinea pig	Not sensitizing

Conclusion/Summary : Based on available data, the classification criteria are not met.

Mutagenicity

Product/ingredient name	Test	Experiment	Result
3-iodo-2-propynyl-butyl carbamate	-	Experiment: In vitro Subject: Bacteria	Negative
Conclusion/Summary <u>Carcinogenicity</u>	: Based on available da	ta, the classification criteria are not	met.
Conclusion/Summary <u>Reproductive toxicity</u>	: Based on available da	ta, the classification criteria are not	met.

: 26/10/2023 Date of previous issue

SECTION 11: Toxicological information								
Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure		
3-iodo-2-propynyl-butyl carbamate	Negative	-	Negative	Rabbit - Female	Oral: 20 mg/kg	13 days; 7 days per week		
	Positive	-	Negative	Rabbit - Female	Oral: 50 mg/kg	13 days; 7 days per week		

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Teratogenicity

Product/ingredient name	Result	Species	Dose	Exposure
3-iodo-2-propynyl-butyl carbamate	Negative - Oral	Rabbit - Female	50 mg/kg	-

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
	Category 1 Category 1	-	larynx -

Aspiration hazard

Not available.

Information on likely routes : Not available. of exposure

Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

<u>Short term exposure</u>		
Potential immediate effects	: Not available.	
Potential delayed effects	: Not available.	
<u>Long term exposure</u>		
Potential immediate effects	: Not available.	
Potential delayed effects	: Not available.	
Potential chronic health eff	<u>ects</u>	
Not available.		
Conclusion/Summary	: Not available.	

SECTION 11: Toxicological information

General

- : No known significant effects or critical hazards.
- Carcinogenicity **Mutagenicity**
- : No known significant effects or critical hazards. : No known significant effects or critical hazards.
- **Reproductive toxicity**
- : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
3-iodo-2-propynyl-butyl	Acute EC50 0.022 mg/l Fresh water	Algae - Scenedemus	72 hours
carbamate		subspicatus	
	Acute EC50 0.16 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 0.067 mg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute NOEC 0.049 mg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 0.05 mg/l Fresh water	Daphnia - <i>Daphnia Magna</i>	21 days
1,2-benzisothiazol-3(2H)-one	Acute EC50 0.36 mg/l Marine water	Algae - Skeletonema Costatum	72 hours
	Acute EC50 3.7 mg/l	Daphnia - <i>Daphnia Magna</i>	48 hours
	Acute LC50 1.9 mg/l Fresh water	Fish - Onorhynchus Mykiss	96 hours
	Acute NOEC 0.15 mg/l Marine water	Algae - Skeletonema Costatum	72 hours
pyrithione zinc	Acute EC50 0.51 µg/l Marine water	Algae - Thalassiosira	96 hours
		pseudonana	
	Acute EC50 38 µg/l Fresh water	Crustaceans - Ilyocypris	48 hours
		dentifera	
	Acute EC50 8.25 ppb Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 2.68 ppb Fresh water	Fish - Pimephales promelas	96 hours
	Chronic EC10 0.36 µg/l Marine water	Algae - Thalassiosira	96 hours
		pseudonana	
	Chronic NOEC 2.7 ppb Fresh water	Daphnia - <i>Daphnia magna</i>	21 days
2-Methyl-1,2-benzisothiazol-	Acute EC50 0.22 ppm Fresh water	Algae - Pseudokirchneriella	96 hours
3(2H)-one		subcapitata	
	Acute EC50 0.92 ppm Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 0.24 ppm Fresh water	Fish - Oncorhynchus mykiss -	96 hours
		Juvenile (Fledgling, Hatchling,	
		Weanling)	
	Chronic NOEC 0.16 ppm	Fish - Pimephales promelas	32 days
Conclusion/Summary	: Harmful to aquatic life with long lastir	g effects.	

12.2 Persistence and degradability

Product/ingredient name	Test	Result		Dose	Inoculum
2-benzisothiazol-3(2H)-one	EU	24 % - 28 days		-	-
Conclusion/Summary	: This product ha	as not been tested fo	r biodegrada	ation.	
Product/ingredient name	Aquatic half-life		Photolysis	5	Biodegradability
Fiodo-2-propynyl-butyl carbamate 1,2-benzisothiazol-3(2H)-one	-		-		Not readily

12.3 Bioaccumulative potential

: 26/10/2023 Date of previous issue

SECTION 12: Ecologi	cal informati	on	
Product/ingredient name	LogPow	BCF	Potential
Dipropyleneglycolmethylether 3-iodo-2-propynyl-butyl carbamate	0.004 >1	-	Low Low
1,2-benzisothiazol-3(2H)-one pyrithione zinc	- 0.9	3.2 11	Low Low

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment meth	lods
Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
European waste catalogue (EWC)	: 080111*
Packaging	
Methods of disposal	 The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
Date of issue/Date of rev	ision : 26/10/2023	Date of previous issue	: 05/10/2022	Version : 1.01 12/16
TEKNOTOP 2980-11 - All variants			. 00/10/2022	Label No :38863

SECTION 14:	Transport inform	ation		
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

14.6 Special precautions for	:	Transport within user's premises: always transport in closed containers that are
user		upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in
bulk according to IMO
instruments

: Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name		%	Designation [Usage]			
FEKNOTOP 2980-11		≥90	3			
Labelling	:	4				
ther EU regulations						
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed					
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed					
Explosive precursors	: Not applicab	ole.				
Ozone depleting substand	<u>es (1005/2009/E</u>	<u>EU)</u>				
Not listed.						
Prior Informed Consent (P Not listed.	<u>PIC) (649/2012/E</u>	<u>U)</u>				
Persistent Organic Polluta Not listed.	<u>ints</u>					
Seveso Directive						
This product is not controlle	d under the Seve	eso Directiv	re.			
ternational regulations						
hemical Weapon Convent	ion List Schedu	<u>iles I, II & I</u>	<u>II Chemicals</u>			
lot listed.						
ontreal Protocol						
te of issue/Date of revision	: 26/10/2023	Date of pre	vious issue : 05/10/2022	Version	: 1.01	13/1

TEKNOTOP 2980-11 - All variants

SECTION 15: Regulatory information

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety :	This product contains substances for which Chemical Safety Assessments are still
assessment	required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification			
Aquatic Chronic 3, H412	Calculation method			

Full text of abbreviated H statements

H 301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H360D	May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

		-					
Acute Tox. 2	ACUTE	TOXICITY - C	ategory 2				
Acute Tox. 3	ACUTE	ACUTE TOXICITY - Category 3					
Acute Tox. 4	ACUTE	ACUTE TOXICITY - Category 4					
Aquatic Acute 1	SHORT-	TERM (ACUT	E) AQUATIC HAZAR	RD - Category 1			
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1						
Aquatic Chronic 2	LONG-T	ERM (CHRON	NIC) AQUATIC HAZA	RD - Category 2			
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3						
Eye Dam. 1	SERIOU	S EYÈ DAMA	GE/EYE IRRITATION	I - Category 1			
Repr. 1B	REPRO	DUCTIVE TOX	KICITY - Category 1B	0,			
			0.7				
Date of issue/Date of revis	sion	: 26/10/2023	Date of previous issue	: 05/10/2022	Version	: 1.01	14/16

SECTION 16: Ot	ier information
Skin Corr. 1C Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1A	SKIN CORROSION/IRRITATION - Category 1C SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SKIN SENSITISATION - Category 1A
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
Date of issue/ Date of revision	: 26/10/2023
Date of previous issue	: 05/10/2022
Version	1.01 TEKNOTOP 2980-11 All variants

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision TEKNOTOP 2980-11 - All variants