

# SAFETY DATA SHEET



UVILUX 1493-13 - SPRAY TS 21488 CLEAR

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Product name : UVILUX 1493-13 - SPRAY TS 21488 CLEAR

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS : Prod-safe@teknos.com

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

Telephone number : In an emergency, call 112

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Product definition : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315

Eye Dam. 1, H318

Skin Sens. 1, H317

Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements :  
H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H318 - Causes serious eye damage.  
H411 - Toxic to aquatic life with long lasting effects.

#### Precautionary statements

Prevention : P280 - Wear protective gloves. Wear eye or face protection.  
P273 - Avoid release to the environment.

Response : P391 - Collect spillage.  
P305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Immediately call a POISON CENTER or doctor.

Storage : Not applicable.

## SECTION 2: Hazards identification

<b>Disposal</b>	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
<b>Hazardous ingredients</b>	: Contains: Poly[oxy(methyl-1,2-ethanediyl)], $\alpha,\alpha'$ -(2,2-dimethyl-1,3-propanediyl)bis[ $\omega$ -(1-oxo-2-propen-1-yl)oxy]-; Propylidynetrimethanol, ethoxylated, esters with acrylic acid; 2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide and 2,2-bis(acryloyloxymethyl)butyl acrylate
<b>Supplemental label elements</b>	:
<b>Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles</b>	:

### 2.3 Other hazards

<b>Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII</b>	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
<b>Other hazards which do not result in classification</b>	: None known.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Ethoxylated acrylated ester	-	$\geq 25$ - $\leq 50$	Skin Irrit. 2, H315 Eye Irrit. 2, H319	-	[1]
Poly[oxy(methyl-1,2-ethanediyl)], $\alpha,\alpha'$ -(2,2-dimethyl-1,3-propanediyl)bis[ $\omega$ -(1-oxo-2-propen-1-yl)oxy]-	REACH #: 01-2119970213-43 CAS: 84170-74-1	$\geq 10$ - $\leq 25$	Skin Sens. 1B, H317 Aquatic Chronic 2, H411	-	[1]
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	REACH #: 01-2119489900-30 EC: 500-066-5 CAS: 28961-43-5	$\geq 10$ - $\leq 25$	Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412	-	[1]
Dimetoxidifenyletanon	EC: 246-386-6 CAS: 24650-42-8	$\leq 5$	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
2-hydroxy-2-methylpropiophenone	REACH #: 01-2119472306-39 EC: 231-272-0 CAS: 7473-98-5	$\leq 5$	Acute Tox. 4, H302 Aquatic Chronic 3, H412	ATE [Oral] = 1694 mg/kg	[1]
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide	REACH #: 01-2120140608-57 EC: 810-703-1 CAS: 1187441-10-6	$\leq 5$	Eye Dam. 1, H318 Skin Sens. 1B, H317	-	[1]
Acrylic acid	REACH #: 01-2119452449-31 EC: 201-177-9 CAS: 79-10-7	$\leq 0.3$	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Corr. 1A, H314 Eye Dam. 1, H318	ATE [Oral] = 500 mg/kg ATE [Dermal] = 1100 mg/kg ATE [Inhalation (vapours)] = 11 mg/	[1] [2]

**Date of issue/Date of revision** : 17/12/2025 **Date of previous issue** : 16/12/2025 **Version** : 4 **2/25**

 VILUX 1493-13 - SPRAY TS 21488 CLEAR

**Label No** : 138182

## SECTION 3: Composition/information on ingredients

2,2-bis(acryloyloxymethyl) butyl acrylate	REACH #: 01-2119489896-11 EC: 239-701-3 CAS: 15625-89-5 Index: 607-111-00-9	≤0.3	STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 2, H411  Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410  <b>See Section 16 for the full text of the H statements declared above.</b>	I STOT SE 3, H335: C ≥ 1% M [Acute] = 1  M [Acute] = 1 M [Chronic] = 1	[1]
---	---	------	--	--	-----

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### Eye contact

- : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

#### Inhalation

- : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Skin contact

- : Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

#### Ingestion

- : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Protection of first-aiders

- : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

Date of issue/Date of revision

: 17/12/2025

Date of previous issue

: 16/12/2025

Version : 4

3/25

VILUX 1493-13 - SPRAY TS 21488 CLEAR

Label No : 138182

## SECTION 4: First aid measures

### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur
- Ingestion** : Adverse symptoms may include the following:  
stomach pains

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
metal oxide/oxides

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

## SECTION 6: Accidental release measures

**6.2 Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

**6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### Seveso Directive - Reporting thresholds

##### Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
E2	200 tonnes	500 tonnes

### 7.3 Specific end use(s)

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
Acrylic acid	<b>Regulation on Limit Values - MAC (Austria, 12/2024)</b> CEIL: 59 mg/m <sup>3</sup> . CEIL: 20 ppm. TWA 8 hours: 29 mg/m <sup>3</sup> . TWA 8 hours: 10 ppm.
Acrylic acid	<b>Limit values (Belgium, 12/2023)</b> Absorbed through skin. TWA 8 hours: 2 ppm. TWA 8 hours: 6 mg/m <sup>3</sup> . STEL 1 minutes: 59 mg/m <sup>3</sup> . STEL 1 minutes: 20 ppm.
Acrylic acid	<b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024)</b> Limit value 8 hours: 29 mg/m <sup>3</sup> . Limit value 1 minutes: 20 ppm. Limit value 1 minutes: 59 mg/m <sup>3</sup> . Limit value 8 hours: 10 ppm.
Acrylic acid	<b>Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023)</b> ELV 8 hours: 29 mg/m <sup>3</sup> . ELV 8 hours: 10 ppm. STELV 1 minutes: 59 mg/m <sup>3</sup> . STELV 1 minutes: 20 ppm.
Acrylic acid	<b>Department of labour inspection (Cyprus, 7/2021)</b> STEL 1 minutes: 20 ppm. STEL 1 minutes: 59 mg/m <sup>3</sup> . TWA 8 hours: 10 ppm. TWA 8 hours: 29 mg/m <sup>3</sup> .
Acrylic acid	<b>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 12/2023)</b> TWA 8 hours: 29 mg/m <sup>3</sup> . STEL 1 minutes: 59 mg/m <sup>3</sup> . TWA 8 hours: 9.7 ppm. STEL 1 minutes: 19.7 ppm.
Acrylic acid	<b>Working Environment Authority (Denmark, 12/2024)</b> Absorbed through skin. STEL 1 minutes: 59 mg/m <sup>3</sup> . STEL 1 minutes: 20 ppm. TWA 8 hours: 2 ppm. TWA 8 hours: 5.9 mg/m <sup>3</sup> .
Acrylic acid	<b>Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024)</b> TWA 8 hours: 29 mg/m <sup>3</sup> . TWA 8 hours: 10 ppm. STEL 1 minutes: 20 ppm. STEL 1 minutes: 59 mg/m <sup>3</sup> .
Acrylic acid	<b>EU OEL (Europe, 1/2022)</b> STEL 15 minutes: 20 ppm. STEL 15 minutes: 59 mg/m <sup>3</sup> . TWA 8 hours: 10 ppm. TWA 8 hours: 29 mg/m <sup>3</sup> .

## SECTION 8: Exposure controls/personal protection

Acrylic acid	<p><b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021)</b>  TWA 8 hours: 2 ppm.  TWA 8 hours: 6 mg/m<sup>3</sup>.  CEIL: 15 ppm.  CEIL: 45 mg/m<sup>3</sup>.</p>
Acrylic acid	<p><b>Ministry of Labor (France, 6/2024)</b>  TWA 8 hours: 10 ppm. Notes: Indicative regulatory limit values (decree of 30-06-2004 modified)  TWA 8 hours: 29 mg/m<sup>3</sup>. Notes: Indicative regulatory limit values (decree of 30-06-2004 modified)  STEL 1 minutes: 20 ppm. Notes: Indicative regulatory limit values (decree of 30-06-2004 modified)  STEL 1 minutes: 59 mg/m<sup>3</sup>. Notes: Indicative regulatory limit values (decree of 30-06-2004 modified)</p>
Acrylic acid	<p><b>TRGS 900 OEL (Germany, 6/2024)</b> Absorbed through skin.  TWA 8 hours: 30 mg/m<sup>3</sup>.  PEAK 15 minutes: 30 mg/m<sup>3</sup>.  TWA 8 hours: 10 ppm.  PEAK 15 minutes: 10 ppm.  CEIL: 60 mg/m<sup>3</sup>.  CEIL: 20 ppm.</p> <p><b>DFG MAC-values list (Germany, 7/2024)</b> Develop C.  TWA 8 hours: 30 mg/m<sup>3</sup>.  TWA 8 hours: 10 ppm.  PEAK 15 minutes: 10 ppm 4 times per shift [Interval: 1 hour].  PEAK 15 minutes: 30 mg/m<sup>3</sup> 4 times per shift [Interval: 1 hour].</p>
2,2-bis(acryloyloxymethyl)butyl acrylate	<p><b>DFG MAC-values list (Germany, 7/2024)</b> Skin sensitiser.</p>
Acrylic acid	<p><b>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 8/2024)</b>  TWA 8 hours: 10 ppm.  TWA 8 hours: 29 mg/m<sup>3</sup>.  STEL 1 minutes: 20 ppm.  STEL 1 minutes: 59 mg/m<sup>3</sup>.</p>
Acrylic acid	<p><b>5/2020. (II. 6.) ITM Decree (Hungary, 1/2025)</b>  TWA 8 hours: 29 mg/m<sup>3</sup>.  PEAK 1 minutes: 59 mg/m<sup>3</sup>.  PEAK 1 minutes: 20 ppm.  TWA 8 hours: 10 ppm.</p>
Acrylic acid	<p><b>Ministry of Welfare, List of Exposure Limits (Iceland, 11/2024)</b>  TWA 8 hours: 5.9 mg/m<sup>3</sup>.  TWA 8 hours: 2 ppm.</p>
Acrylic acid	<p><b>NAOSH (Ireland, 4/2024)</b> Notes: EU derived Occupational Exposure Limit Values  OELV 8 hours: 10 ppm.  OELV 8 hours: 29 mg/m<sup>3</sup>.  OELV 1 minutes: 59 mg/m<sup>3</sup>.  OELV 1 minutes: 20 ppm.</p>
Acrylic acid	<p><b>Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 9/2024)</b>  Absorbed through skin.  Short Term 1 minutes: 20 ppm.  Short Term 1 minutes: 59 mg/m<sup>3</sup>.  Limit value 8 hours: 10 ppm.  Limit value 8 hours: 29 mg/m<sup>3</sup>.</p>
Acrylic acid	<p><b>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024)</b>  TWA 8 hours: 5 mg/m<sup>3</sup>.  STEL 1 minutes: 20 ppm.  STEL 1 minutes: 59 mg/m<sup>3</sup>.  TWA 8 hours: 1.7 ppm.</p>

## SECTION 8: Exposure controls/personal protection

Acrylic acid	<b>Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024)</b> TWA 8 hours: 29 mg/m <sup>3</sup> . TWA 8 hours: 10 ppm. CEIL: 59 mg/m <sup>3</sup> . CEIL: 20 ppm.
Acrylic acid	<b>Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021)</b> STEL 1 minutes: 20 ppm. STEL 1 minutes: 59 mg/m <sup>3</sup> . TWA 8 hours: 10 ppm. TWA 8 hours: 29 mg/m <sup>3</sup> .
Acrylic acid	<b>EU OEL (Europe, 1/2022)</b> STEL 15 minutes: 20 ppm. STEL 15 minutes: 59 mg/m <sup>3</sup> . TWA 8 hours: 10 ppm. TWA 8 hours: 29 mg/m <sup>3</sup> .
Acrylic acid	<b>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 5/2024)</b> STEL 1 minutes: 59 mg/m <sup>3</sup> . TWA 8 hours: 29 mg/m <sup>3</sup> . TWA 8 hours: 10 ppm. STEL 1 minutes: 20 ppm.
Acrylic acid	<b>FOR-2011-12-06-1358 (Norway, 5/2024)</b> Sensitiser. TWA 8 hours: 10 ppm. TWA 8 hours: 29 mg/m <sup>3</sup> . STEL 15 minutes: 59 mg/m <sup>3</sup> . STEL 15 minutes: 20 ppm.
Acrylic acid	<b>Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024)</b> Absorbed through skin. TWA 8 hours: 10 mg/m <sup>3</sup> . STEL 15 minutes: 29.5 mg/m <sup>3</sup> . STEL 15 minutes: 10.2 ppm. TWA 8 hours: 3.4 ppm.
Acrylic acid	<b>Portuguese Institute of Quality (Portugal, 11/2014)</b> A4. Absorbed through skin. TWA 8 hours: 2 ppm. <b>Decree-Law 24/2012 - Occupational exposure limits for chemical agents (Portugal, 6/2021)</b> STEL 1 minutes: 20 ppm. STEL 1 minutes: 59 mg/m <sup>3</sup> . TWA 8 hours: 10 ppm. TWA 8 hours: 29 mg/m <sup>3</sup> .
Acrylic acid	<b>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024)</b> VLA 8 hours: 29 mg/m <sup>3</sup> . VLA 8 hours: 10 ppm. Short term 1 minutes: 59 mg/m <sup>3</sup> . Short term 1 minutes: 20 ppm.
Acrylic acid	<b>Government regulation SR c. 355/2006 (Slovakia, 6/2024)</b> Inhalation sensitiser. STEL 1 minutes: 59 mg/m <sup>3</sup> . STEL 1 minutes: 20 ppm. TWA 8 hours: 29 mg/m <sup>3</sup> . TWA 8 hours: 10 ppm.

## SECTION 8: Exposure controls/personal protection

Acrylic acid	<p><b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024)</b>  Absorbed through skin.  KTV 1 minutes: 20 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].  TWA 8 hours: 10 ppm.  KTV 1 minutes: 59 mg/m<sup>3</sup> 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].  TWA 8 hours: 29 mg/m<sup>3</sup>.</p>
Acrylic acid	<p><b>National institute of occupational safety and health (Spain, 1/2024)</b> Absorbed through skin.  TWA 8 hours: 10 ppm.  TWA 8 hours: 29 mg/m<sup>3</sup>.  STEL 15 minutes: 59 mg/m<sup>3</sup>.  STEL 15 minutes: 20 ppm.</p>
Acrylic acid	<p><b>Work environment authority Regulation 2018:1 (Sweden, 11/2022)</b>  TWA 8 hours: 10 ppm.  TWA 8 hours: 29 mg/m<sup>3</sup>.  STEL 15 minutes: 20 ppm.  STEL 15 minutes: 59 mg/m<sup>3</sup>.</p>
Acrylic acid	<p><b>SUVA (Switzerland, 1/2025)</b> Sensitiser.  TWA 8 hours: 10 ppm.  TWA 8 hours: 29 mg/m<sup>3</sup>.  STEL 15 minutes: 20 ppm.  STEL 15 minutes: 59 mg/m<sup>3</sup>.</p>
Acrylic acid	<p><b>EH40/2005 WELs (United Kingdom (UK), 1/2020)</b>  STEL 1 minutes: 59 mg/m<sup>3</sup>.  STEL 1 minutes: 20 ppm.  TWA 8 hours: 29 mg/m<sup>3</sup>.  TWA 8 hours: 10 ppm.</p>

### Biological exposure indices

Product/ingredient name	Exposure indices
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	

## SECTION 8: Exposure controls/personal protection

No exposure indices known.  
No exposure indices known.  
No exposure indices known.  
No exposure indices known.  
No exposure indices known.  
No exposure indices known.  
No exposure indices known.  
No exposure indices known.  
No exposure indices known.  
No exposure indices known.  
No exposure indices known.  
No exposure indices known.

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following:  
European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs/DMELs

#### **Product/ingredient name**

Propylidynetrimethanol, ethoxylated, esters with acrylic acid

#### **Result**

##### **DNEL - Workers - Long term - Dermal**

10.5 mg/kg bw/day

Effects: Systemic

##### **DNEL - Workers - Long term - Inhalation**

37 mg/m<sup>3</sup>

Effects: Systemic

Dimetoxidifenyletanon

##### **DNEL - General population - Long term - Oral**

0.214 mg/kg bw/day

Effects: Systemic

##### **DNEL - General population - Long term - Dermal**

0.214 mg/kg bw/day

Effects: Systemic

##### **DNEL - General population - Long term - Inhalation**

0.372 mg/m<sup>3</sup>

Effects: Systemic

##### **DNEL - Workers - Long term - Dermal**

0.599 mg/kg bw/day

Effects: Systemic

##### **DNEL - Workers - Long term - Inhalation**

2.11 mg/m<sup>3</sup>

Effects: Systemic

2-hydroxy-2-methylpropiophenone

##### **DNEL - General population - Long term - Oral**

0.4 mg/kg bw/day

Effects: Systemic

##### **DNEL - General population - Long term - Dermal**

## SECTION 8: Exposure controls/personal protection

0.5 mg/kg bw/day

Effects: Systemic

**DNEL - General population - Long term - Inhalation**

0.9 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Long term - Dermal**

1 mg/kg bw/day

Effects: Systemic

**DNEL - Workers - Long term - Inhalation**

3.5 mg/m<sup>3</sup>

Effects: Systemic

Acrylic acid

**DNEL - General population - Short term - Inhalation**

3.6 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - General population - Long term - Oral**

0.4 mg/kg bw/day

Effects: Systemic

**DNEL - General population - Short term - Oral**

1.2 mg/kg bw/day

Effects: Systemic

**DNEL - General population - Short term - Inhalation**

3.6 mg/m<sup>3</sup>

Effects: Local

**DNEL - General population - Long term - Inhalation**

3.6 mg/m<sup>3</sup>

Effects: Local

**DNEL - General population - Long term - Inhalation**

3.6 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Short term - Inhalation**

30 mg/m<sup>3</sup>

Effects: Local

**DNEL - Workers - Long term - Inhalation**

30 mg/m<sup>3</sup>

Effects: Local

**DNEL - Workers - Short term - Inhalation**

30 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Long term - Inhalation**

30 mg/m<sup>3</sup>

Effects: Systemic

2,2-bis(acryloyloxymethyl)butyl acrylate

**DNEL - Workers - Long term - Inhalation**

17.1 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Long term - Dermal**

404 mg/kg bw/day

Effects: Systemic

### PNECs

**Date of issue**/**Date of revision**

: 17/12/2025

**Date of previous issue**

: 16/12/2025

**Version** : 4

11/25

 VILUX 1493-13 - SPRAY TS 21488 CLEAR

**Label No** : 138182

## SECTION 8: Exposure controls/personal protection

Not available.

### 8.2 Exposure controls

**Appropriate engineering controls** : If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

#### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

#### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations : Wear suitable gloves tested to EN374.

< 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm

> 8 hours (breakthrough time): 4H / Silver Shield® gloves.

Wash hands before breaks and immediately after handling the product.

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type: A

Filter type (spray application): A P

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

**Physical state** : Liquid.

**Colour** : Clear.

**Odour** : Slight

## SECTION 9: Physical and chemical properties

**Odour threshold** : Not available.

**Melting point/freezing point** : Not available.

**Initial boiling point and boiling range** :

Ingredient name	°C	°F	Method
2-hydroxy-2-methylpropiophenone	252.1	485.8	OECD 104
Dimetoxidifenyletanon	352.25	666	

**Flammability** : Not available.

**Lower and upper explosion limit** : Lower: Not applicable.  
Upper: Not applicable.

**Flash point** : Closed cup: >100°C (>212°F)

**Auto-ignition temperature** :

Ingredient name	°C	°F	Method
Poly[oxy(methyl-1,2-ethanediyl)], α,α'-(2,2-dimethyl-1,3-propanediyl)bis[ω-[(1-oxo-2-propen-1-yl)oxy]-	>240	>464	
Dimetoxidifenyletanon	>400	>752	

**Decomposition temperature** : Not available.

**pH** : Not applicable.

**Viscosity** : Not available.

**Solubility(ies)** :

Not available.

**Solubility in water** : Not available.

**Partition coefficient: n-octanol/ water** : Not applicable.

**Vapour pressure** :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
2-hydroxy-2-methylpropiophenone	0.00428	0.00057	OECD 104	0.09751	0.013	OECD 104
Poly[oxy(methyl-1,2-ethanediyl)], α,α'-(2,2-dimethyl-1,3-propanediyl)bis[ω-[(1-oxo-2-propen-1-yl)oxy]-	0.00044	0.000059				

**Relative density** : Not available.

**Density** : 1.2 g/cm<sup>3</sup>

**Vapour density** : Not available.

### Particle characteristics

**Median particle size** : Not applicable.

## 9.2 Other information

### 9.2.1 Information with regard to physical hazard classes

**Explosive properties** : Not available.

**Oxidising properties** : Not available.

### 9.2.2 Other safety characteristics

Not applicable.

## SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : No specific data.
- 10.5 Incompatible materials** : No specific data.
- 10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Product/ingredient name

Propylidynetrimethanol, ethoxylated, esters with acrylic acid

2-hydroxy-2-methylpropiophenone

2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide

Acrylic acid

2,2-bis(acryloyloxymethyl)butyl acrylate

##### Result

**Rabbit - Dermal - LD50**

>13 g/kg

**Rat - Oral - LD50**

1694 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity) Behavioral - Tremor Liver - Other changes

**Rat - Dermal - LD50**

6929 mg/kg

**Rat - Oral - LD50**

>2000 mg/kg

**Rabbit - Dermal - LD50**

>2000 mg/kg

**Rabbit - Dermal - LD50**

640 mg/kg

Toxic effects: Cardiac - Cardiomegaly Lung, Thorax, or Respiration - Acute pulmonary edema Skin After topical exposure - Corrosive

**Rat - Oral - LD50**

33500 µg/kg

**Rabbit - Dermal - LD50**

5170 mg/kg

**Conclusion/Summary [Product]** : Not available.

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
UVILUX 1493-13	35893.4	N/A	N/A	N/A	N/A
2-hydroxy-2-methylpropiophenone	1694	6929	N/A	N/A	N/A
Acrylic acid	500	1100	N/A	11	N/A
2,2-bis(acryloyloxymethyl)butyl acrylate	N/A	5170	N/A	N/A	N/A

## SECTION 11: Toxicological information

### Skin corrosion/irritation

#### **Product/ingredient name**

Propylidynetrimethanol, ethoxylated, esters with acrylic acid

Acrylic acid

2,2-bis(acryloyloxymethyl)butyl acrylate

#### **Result**

##### **Rabbit - Skin - Moderate irritant**

Amount/concentration applied: 500 mg

##### **Rabbit - Skin - Severe irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 5 mg

##### **Rabbit - Skin - Severe irritant**

Amount/concentration applied: 500 mg

##### **Rabbit - Skin - Moderate irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

**Conclusion/Summary [Product]** : Not available.

### Serious eye damage/eye irritation

#### **Product/ingredient name**

Propylidynetrimethanol, ethoxylated, esters with acrylic acid

Acrylic acid

2,2-bis(acryloyloxymethyl)butyl acrylate

#### **Result**

##### **Rabbit - Eyes - Moderate irritant**

Amount/concentration applied: 100 mg

##### **Rabbit - Eyes - Severe irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 250 ug

##### **Rabbit - Eyes - Severe irritant**

Amount/concentration applied: 1 mg

##### **Rabbit - Eyes - Moderate irritant**

Amount/concentration applied: 100 mg

**Conclusion/Summary [Product]** : Not available.

### Respiratory corrosion/irritation

Not available.

**Conclusion/Summary [Product]** : Not available.

### Respiratory or skin sensitization

Not available.

### **Skin**

**Conclusion/Summary [Product]** : Not available.

### **Respiratory**

**Conclusion/Summary [Product]** : Not available.

### Germ cell mutagenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Carcinogenicity

Not available.

## SECTION 11: Toxicological information

**Conclusion/Summary [Product]** : Not available.

### Reproductive toxicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Specific target organ toxicity (single exposure)

#### **Product/ingredient name**

Acrylic acid

#### **Result**

STOT SE 3, H335 (Respiratory tract irritation)

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Not available.

### Information on likely routes of exposure

Not available.

### Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
  - pain
  - watering
  - redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
  - pain or irritation
  - redness
  - blistering may occur
- Ingestion** : Adverse symptoms may include the following:
  - stomach pains

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

**Conclusion/Summary [Product]** : Not available.

- General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

## SECTION 11: Toxicological information

### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

#### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product/ingredient name

2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide

Acrylic acid

#### Result

##### LC50 - Fresh water

OECD [Fish, Acute Toxicity Test]

Fish - *Cyprinus carpio*

>100 mg/l [96 hours]

##### EC50

Daphnia - Daphnia - *Daphnia magna*

>100 mg/l [48 hours]

##### Chronic - NOEC - Fresh water

Daphnia - Water flea - *Daphnia magna* - Neonate

Age: <24 hours

3.8 mg/l [21 days]

Effect: Reproduction

**Conclusion/Summary [Product]** : Not available.

### 12.2 Persistence and degradability

Not available.

**Conclusion/Summary [Product]** : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	-	-	Readily
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide	-	71%; 28 day(s)	Readily

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	2.89	-	Low
2-hydroxy-2-methylpropiophenone	1.62	-	Low
Acrylic acid	0.38	3.162	Low
2,2-bis(acryloyloxymethyl) butyl acrylate	0.67	-	Low

### 12.4 Mobility in soil

#### Soil/water partition coefficient

## SECTION 12: Ecological information

Product/ingredient name	logKoc	Koc
Dimetoxidifenyletanon	2.6	374.295
2-hydroxy-2-methylpropiofenone	1.9	80.7076
Acrylic acid	0.9	7.90304
2,2-bis(acryloyloxymethyl)butyl acrylate	2.2	157.193

### Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
Ethoxylated acrylated ester	No	No	No	No	No	No	No
Poly[oxy(methyl-1,2-ethanediyl)], α,α'-(2,2-dimethyl-1,3-propanediyl)bis[ω-[(1-oxo-2-propen-1-yl)oxy]-Propylidynetrimethanol, ethoxylated, esters with acrylic acid	No	No	No	No	No	No	No
Dimetoxidifenyletanon	No	No	No	No	No	No	No
2-hydroxy-2-methylpropiofenone	No	No	No	No	No	No	No
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide	No	No	No	No	No	No	No
Acrylic acid	No	No	No	No	No	No	No
2,2-bis(acryloyloxymethyl)butyl acrylate	No	No	No	No	No	No	No

**Mobility** : Not available.

**Conclusion/Summary** : The product does not meet the criteria to be considered as a PMT or vPvM.

### 12.5 Results of PBT and vPvB assessment

#### Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Ethoxylated acrylated ester	No	N/A	N/A	No	N/A	N/A	N/A
Poly[oxy(methyl-1,2-ethanediyl)], α,α'-(2,2-dimethyl-1,3-propanediyl)bis[ω-[(1-oxo-2-propen-1-yl)oxy]-Propylidynetrimethanol, ethoxylated, esters with acrylic acid	No	N/A	N/A	No	N/A	N/A	N/A
Dimetoxidifenyletanon	No	N/A	N/A	No	N/A	N/A	N/A
2-hydroxy-2-methylpropiofenone	No	N/A	N/A	No	N/A	N/A	N/A
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide	No	N/A	N/A	No	N/A	N/A	N/A
Acrylic acid	No	N/A	No	No	No	N/A	No
2,2-bis(acryloyloxymethyl)butyl acrylate	No	N/A	N/A	No	N/A	N/A	N/A

#### Regulation (EC) No. 1272/2008 [CLP]

## SECTION 12: Ecological information

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Ethoxylated acrylated ester	No	No	No	No	No	No	No
Poly[oxy(methyl-1,2-ethanediyl)], α,α'-(2,2-dimethyl-1,3-propanediyl)bis[ω-[(1-oxo-2-propen-1-yl)oxy]-Propylidynetrimethanol, ethoxylated, esters with acrylic acid	No	No	No	No	No	No	No
Dimetoxidifenyletanon	No	No	No	No	No	No	No
2-hydroxy-2-methylpropiophenone	No	No	No	No	No	No	No
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide	No	No	No	No	No	No	No
Acrylic acid	No	No	No	No	No	No	No
2,2-bis(acryloyloxymethyl) butyl acrylate	No	No	No	No	No	No	No

**Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP]** : The product does not meet the criteria to be considered as a PBT or vPvB.

### 12.6 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.





**European waste catalogue (EWC)** : 080111\*

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN3082	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)
14.3 Transport hazard class(es)	9 	9 	9 	9 
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes.

### Additional information

#### ADR/RID

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

#### Tunnel code (-)

#### ADN

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

#### IMDG

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

#### IATA

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in bulk according to IMO instruments** : Not relevant/applicable due to nature of the product.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

#### Annex XIV - List of substances subject to authorisation

##### Annex XIV

None of the components are listed.

#### Substances of very high concern

None of the components are listed.

#### Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
UVILUX 1493-13	≥90	3

## SECTION 15: Regulatory information

Labelling :

### Other EU regulations

Industrial emissions  
(integrated pollution  
prevention and control) -  
Air : Not listed

Industrial emissions  
(integrated pollution  
prevention and control) -  
Water : Not listed

Explosive precursors : Not applicable.

### Ozone depleting substances (EU 2024/590)

Not listed.

### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

### Persistent Organic Pollutants

Not listed.

### Seveso Directive

This product is controlled under the Seveso Directive.

### Danger criteria

Category
E2

### National regulations

#### Austria

Limitation of the use of  
organic solvents : Permitted.

#### Belgium

#### Czech Republic

Storage code : IV

#### Denmark

Fire class : IV-1

MAL-code : 1-5

Protection based on MAL : According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:

**General:** Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

MAL-code: 1-5

**Application:** When using scraper or knife, brush, roller etc. for pre- and post-treatments in a spray booth where the operator is outside the spray zone and when working in similar new\* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. When spraying in new\* booths and cabins with non-atomizing guns. When using scraper or knife, brush, roller, etc. for pre- and post-treatments in cabins or booths of the existing\* facility type, if the operator is inside the spray zone. When using scraper or knife, brush,

## SECTION 15: Regulatory information

roller, etc. for pre- and post-treatments outside a closed facility, spray booth or spray cabin.

- Protective clothing must be worn.

During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents.

- Gas filter mask and protective clothing must be worn.

When spraying in existing\* spray booths, if the operator is outside the spray zone.

- Air-supplied full mask and protective clothing must be worn.

During non-atomising spraying in existing\* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone.

- Air-supplied half mask, protective clothing and eye protection must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Air-supplied full mask, protective clothing and hood must be worn.

**Drying:** Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

**Polishing:** When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

**Caution** The regulations contain other stipulations in addition to the above.

\*See Regulations.

**Restrictions on use** : Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.

**List of undesirable substances** : Not listed

**Finland**

**France**

**Reinforced medical surveillance** : Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable

**Germany**

**Storage class (TRGS 510)** : 10

**Hazardous incident ordinance**

This product is controlled under the Germany Hazardous Incident Ordinance.

**Danger criteria**

Category	Reference number
E2	1.3.2

**Hazard class for water** : 2

**Technical instruction on air quality control (TA Luft)**

## SECTION 15: Regulatory information

Number [Class]	Description	%
5.2.1	Total dust	18.6
5.2.5	Organic substances	76.7
5.2.5 [I]	Organic substances	0.98
5.2.7.2	Poorly degradable, easily accumulating and highly toxic organic substances	4.7

### Italy

**D.Lgs. 152/06** : Not determined.

### Netherlands

**Water Discharge Policy (ABM)** : A(2) Toxic for aquatic organisms, may have long-term hazardous effects in aquatic environment. Decontamination effort: A

### Norway

### Sweden

### Switzerland

**VOC content** : Exempt.

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

**15.2 Chemical safety assessment** : This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

Indicates information that has changed from previously issued version.

### **Abbreviations and acronyms**

: ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
N/A = Not available  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
SGG = Segregation Group  
vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Calculation method Calculation method Calculation method Calculation method

#### Full text of abbreviated H statements

**Date of issue/Date of revision** : 17/12/2025 **Date of previous issue** : 16/12/2025 **Version** : 4 **23/25**

 VILUX 1493-13 - SPRAY TS 21488 CLEAR

**Label No** : 138182

## SECTION 16: Other information

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

### Full text of classifications [CLP/GHS]

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Skin Corr. 1A	SKIN CORROSION/IRRITATION - Category 1A
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

**Date of issue/ Date of revision** : 17/12/2025

**Date of previous issue** : 16/12/2025

**Version** : 4

 VILUX 1493-13\_SPRAY TS 21488 CLEAR

 SPRAY TS 21488 CLEAR

### Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

