

SAFETY DATA SHEET



UVILUX 6790-02 - TS 21367 NCS S 5010-B50G

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : UVILUX 6790-02 - TS 21367 NCS S 5010-B50G

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS : Prod-safe@teknos.com

National contact

Teknos (UK) Limited, 7 Longlands Rd, Bicester, Oxfordshire OX26 5AH, United Kingdom. Tel. +44 (0) 1869 208005.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : NHS: 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to UK CLP/GHS

Skin Irrit. 2, H315
Eye Irrit. 2, H319
Skin Sens. 1, H317
Aquatic Acute 1, H400
Aquatic Chronic 2, H411

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention : P280 - Wear protective gloves. Wear eye or face protection.
P273 - Avoid release to the environment.
P261 - Avoid breathing vapour.
P264 - Wash thoroughly after handling.

Response : P391 - Collect spillage.

Date of issue/Date of revision : 24/10/2023 **Date of previous issue** : 26/05/2023

Version : 1.01 1/20

UVILUX 6790-02 - TS 21367 NCS S 5010-B50G

Label No : 52002

SECTION 2: Hazards identification

Storage	: Not applicable.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Type
Hexamethylene diacrylate	REACH #: 01-2119484737-22 EC: 235-921-9 CAS: 13048-33-4 Index: 607-109-00-8	≥25 - ≤50	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411	[1]
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≤10	Carc. 2, H351 (inhalation)	[1] [*]
Oligotriacrylate	REACH #: 01-2119487948-12 EC: 500-114-5 CAS: 52408-84-1	≤10	Eye Irrit. 2, H319 Skin Sens. 1, H317	[1]
Acrylate resin (1-methyl-1,2-ethanediyl)bis[oxy (methyl-2,1-ethanediyl)] diacrylate	- REACH #: 01-2119484613-34 EC: 256-032-2 CAS: 42978-66-5 Index: 607-249-00-X	≤10 ≤3	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 2, H411	[1] [1]
Benzene, (1-methylethenyl)-, homopolymer, ar-(2-hydroxy-2-methyl-1-oxopropyl) derivs. Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	CAS: 163702-01-0 REACH #: 01-2119489401-38 EC: 423-340-5 CAS: 162881-26-7 Index: 015-189-00-5	<3 ≤3	Repr. 2, H361f Skin Sens. 1A, H317 Aquatic Chronic 4, H413	[1] [1]
Methylbenzoylformiat	REACH #: 01-2120101338-67 EC: 239-263-3 CAS: 15206-55-0	≤3	Skin Sens. 1, H317	[1]
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	REACH #: 01-2119489900-30 EC: 500-066-5 CAS: 28961-43-5	≤3	Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412	[1]

SECTION 3: Composition/information on ingredients

Fatty acids, C18-unsatd., dimers, polymers with acrylic acid, bisphenol A, epichlorohydrin and nonanoic acid	CAS: 216689-76-8	<1	Skin Sens. 1B, H317	[1]
2-Methoxy-1-methylethyl acetate	REACH #: 01-2119475791-29 EC: 203-603-9 CAS: 108-65-6 Index: 607-195-00-7	<1	Flam. Liq. 3, H226 STOT SE 3, H336	[1] [2]
2-Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	≤0.3	Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319	[1] [2]
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	REACH #: 01-2119489900-30 EC: 500-066-5 CAS: 28961-43-5	≤0.3	Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 3, H412	[1]
2-ethylhexan-1-ol	REACH #: 01-2119487289-20 EC: 203-234-3 CAS: 104-76-7	≤0.1	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335	[1] [2]
copper bis (dimethyldithiocarbamate)	REACH #: 01-2120770993-40 EC: 205-287-8 CAS: 137-29-1	<0.01	Acute Tox. 2, H330 Aquatic Acute 1, H400 (M=10)	[1] [2]
1,4-Dihydroxybenzene	EC: 204-617-8 CAS: 123-31-9 Index: 604-005-00-4	<0.01	Acute Tox. 4, H302 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Carc. 2, H351 Aquatic Acute 1, H400 (M=10)	[1] [2]
Toluene	REACH #: 01-2119471310-51 EC: 203-625-9 CAS: 108-88-3 Index: 601-021-00-3	≤0.1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 See Section 16 for the full text of the H statements declared above.	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter ≤ 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

SECTION 4: First aid measures

- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is very toxic to aquatic life. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

SECTION 5: Firefighting measures

Hazardous combustion products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
phosphorus oxides
metal oxide/oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

6.4 Reference to other sections

: See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

SECTION 7: Handling and storage

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Seveso Directive - Reporting thresholds

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
E1	100 tonne	200 tonne

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

2-Methoxy-1-methylethyl acetate	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 548 mg/m ³ 15 minutes. TWA: 50 ppm 8 hours. TWA: 274 mg/m ³ 8 hours. STEL: 100 ppm 15 minutes.
2-Butoxyethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 50 ppm 15 minutes. TWA: 25 ppm 8 hours. STEL: 246 mg/m ³ 15 minutes. TWA: 123 mg/m ³ 8 hours.
2-ethylhexan-1-ol	EH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 5.4 mg/m ³ 8 hours. TWA: 1 ppm 8 hours.
copper bis(dimethyldithiocarbamate)	EH40/2005 WELs (United Kingdom (UK), 1/2020). [Copper and compounds dust and mists, as Cu] STEL: 2 mg/m ³ , (as Cu) 15 minutes. Form: Dusts and Mists TWA: 1 mg/m ³ , (as Cu) 8 hours. Form: Dusts and Mists
1,4-Dihydroxybenzene	EH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 0.5 mg/m ³ 8 hours.
Toluene	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 384 mg/m ³ 15 minutes. TWA: 191 mg/m ³ 8 hours. TWA: 50 ppm 8 hours. STEL: 100 ppm 15 minutes.

Biological exposure indices

Product/ingredient name	Exposure indices
2-Butoxyethanol	EH40/2005 BMGVs (United Kingdom (UK), 8/2018) BGV: 240 mmol/mol creatinine, butoxyacetic acid [in urine]. Sampling time: post shift.

SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
Hexamethylene diacrylate	DNEL	Long term Inhalation	7.2 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	1.66 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	2.1 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	2.77 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	24.5 mg/m ³	Workers	Systemic
Oligotriacrylate	DNEL	Long term Inhalation	7.4 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	2.1 mg/kg bw/day	Workers	Systemic
(1-methyl-1,2-ethanediyl)bis[oxy (methyl-2,1-ethanediyl)] diacrylate	DNEL	Long term Dermal	1.7 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	2.35 mg/m ³	Workers	Systemic
Benzene, (1-methylethenyl)-, homopolymer, ar-(2-hydroxy-2-methyl-1-oxopropyl) derivs.	DNEL	Long term Oral	5.28 µg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	5.28 µg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	9.18 µg/m ³	General population	Systemic
	DNEL	Long term Dermal	14.8 µg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	52.1 µg/m ³	Workers	Systemic
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	DNEL	Long term Inhalation	21 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	21 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	3.3 mg/kg	Workers	Systemic
	DNEL	Short term Dermal	3.3 mg/kg	Workers	Systemic
	DNEL	Long term Inhalation	5.2 mg/m ³	General population [Consumers]	Systemic
	DNEL	Long term Dermal	1.5 mg/kg	General population [Consumers]	Systemic
	DNEL	Long term Oral	1.5 mg/kg	General population [Consumers]	Systemic
	DNEL	Short term Oral	1.67 ng/kg bw/day	General population	Systemic
	DNEL	Long term Oral	1.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	1.5 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	1.67 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	1.93 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	1.93 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	3 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	3.33 mg/	Workers	Systemic

SECTION 8: Exposure controls/personal protection

Methylbenzoylformiat	DNEL	Short term Inhalation	kg bw/day 7.84 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	7.84 mg/m ³	Workers	Systemic
	DNEL	Long term Oral	1.67 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	1.67 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	3.33 mg/ kg bw/day	Workers	Systemic
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	DNEL	Long term Dermal	10.5 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	37 mg/m ³	Workers	Systemic
Fatty acids, C18-unsatd., dimers, polymers with acrylic acid, bisphenol A, epichlorohydrin and nonanoic acid	DNEL	Long term Dermal	0.33 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.18 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	33 mg/m ³	General population	Local
2-Methoxy-1-methylethyl acetate	DNEL	Long term Inhalation	33 mg/m ³	General population	Systemic
	DNEL	Long term Oral	36 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	275 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	320 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	550 mg/m ³	Workers	Local
2-Butoxyethanol	DNEL	Long term Dermal	796 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Oral	6.3 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	26.7 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	59 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	98 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	147 mg/m ³	General population	Local
	DNEL	Short term Inhalation	246 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	426 mg/m ³	General population	Systemic
	DNEL	Short term Inhalation	1091 mg/ m ³	Workers	Systemic
	DNEL	Long term Dermal	10.5 mg/ kg bw/day	Workers	Systemic
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	DNEL	Long term Inhalation	37 mg/m ³	Workers	Systemic
	DNEL	Long term Oral	1.1 mg/kg bw/day	General population	Systemic
2-ethylhexan-1-ol	DNEL	Long term Inhalation	2.3 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	11.4 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	12.8 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	23 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	26.6 mg/m ³	General population	Local

SECTION 8: Exposure controls/personal protection

1,4-Dihydroxybenzene	DNEL	Long term Inhalation	26.6 mg/m ³	General population	Local
	DNEL	Short term Inhalation	53.2 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	53.2 mg/m ³	Workers	Local
	DNEL	Long term Oral	0.6 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	1.05 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	1.66 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	2.1 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	3.33 mg/kg bw/day	Workers	Systemic
Toluene	DNEL	Long term Oral	8.13 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	56.5 mg/m ³	General population	Local
	DNEL	Long term Inhalation	56.5 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	192 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	192 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	226 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	226 mg/m ³	General population	Local
	DNEL	Short term Inhalation	226 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	384 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	384 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	384 mg/m ³	Workers	Systemic

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

SECTION 8: Exposure controls/personal protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Recommendations : Wear suitable gloves tested to EN374.
< 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm
1 - 4 hours (breakthrough time): 4H / Silver Shield® gloves.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Filter type: A
Filter type (spray application): A P
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.


SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.


9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Dark grey.
- Odour** : Slight
- Odour threshold** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** :

Ingredient name	°C	°F	Method
 1-methyl-1,2-ethanediylbis[oxy(methyl-2,1-ethanediyl)] diacrylate	>120	>248	OECD 103
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	>391	>735.8	

- Flammability (solid, gas)** : Not available.
- Upper/lower flammability or explosive limits** : Lower: Not applicable.
Upper: Not applicable.
- Flash point** : Closed cup: >100°C (>212°F)
- Auto-ignition temperature** :

Ingredient name	°C	°F	Method
 Hexamethylene diacrylate	235	455	DIN 51794

- Decomposition temperature** : Not available.
- pH** : Not applicable.
- Viscosity** : Not available.

SECTION 9: Physical and chemical properties

Solubility(ies)

Not available.

Solubility in water

: Not available.

Partition coefficient: n-octanol/ water

: Not applicable.

Vapour pressure

:

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Hexamethylene diacrylate	0.00045	0.00006	EU A.4			
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate	0.00003	0.000004	EU A.4			

Relative density

: Not available.

Density

: 1.2 g/cm³

Vapour density

: Not available.

Explosive properties

: Not available.

Oxidising properties

: Not available.

Particle characteristics

Median particle size

: Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

: The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid

: No specific data.

10.5 Incompatible materials

: No specific data.

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Hexamethylene diacrylate (1-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)] diacrylate	LD50 Oral	Rat	5 g/kg	-
	LD50 Oral	Rat	6200 mg/kg	-
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	LD50 Oral	Rat	>2000 mg/kg	-
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	LD50 Dermal	Rabbit	>13 g/kg	-
2-Methoxy-1-methylethyl acetate	LD50 Dermal	Rabbit	>5 g/kg	-
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	LD50 Oral	Rat	8532 mg/kg	-
	LD50 Dermal	Rabbit	>13 g/kg	-

Date of issue/Date of revision

: 24/10/2023

Date of previous issue

: 26/05/2023

Version : 1.01 11/20

UVILUX 6790-02 - TS 21367 NCS S 5010-B50G

Label No : 52002

SECTION 11: Toxicological information

2-ethylhexan-1-ol	LD50 Dermal	Rabbit	1970 mg/kg	-
	LD50 Oral	Rat	3730 mg/kg	-
copper bis (dimethyldithiocarbamate)	LC50 Inhalation Dusts and mists	Rat	0.12 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
1,4-Dihydroxybenzene	LD50 Oral	Rat	302 mg/kg	-
Toluene	LC50 Inhalation Vapour	Rat	49 g/m ³	4 hours
	LD50 Oral	Rat	636 mg/kg	-

Conclusion/Summary : Based on available data, the classification criteria are not met.

Acute toxicity estimates

Route	ATE value
Not available.	

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Hexamethylene diacrylate	Skin - Severe irritant	Rabbit	-	24 hours 500 mg	-
titanium dioxide	Skin - Mild irritant	Human	-	72 hours 300 ug l	-
(1-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)] diacrylate	Eyes - Severe irritant	Rabbit	-	24 hours 100 uL	-
	Skin - Moderate irritant	Rabbit	-	500 mg	-
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	Eyes - Moderate irritant	Rabbit	-	100 mg	-
	Skin - Moderate irritant	Rabbit	-	500 mg	-
2-Butoxyethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 mg	-
	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	Eyes - Moderate irritant	Rabbit	-	100 mg	-
	Skin - Moderate irritant	Rabbit	-	500 mg	-
2-ethylhexan-1-ol	Eyes - Moderate irritant	Rabbit	-	24 hours 20 mg	-
	Eyes - Moderate irritant	Rabbit	-	20 ug	-
	Eyes - Severe irritant	Rabbit	-	20 mg	-
	Skin - Mild irritant	Rabbit	-	415 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Severe irritant	Rabbit	-	0.5 MI	-
1,4-Dihydroxybenzene	Skin - Mild irritant	Human	-	2 %	-
	Skin - Severe irritant	Human	-	5 %	-
Toluene	Eyes - Mild irritant	Rabbit	-	0.5 minutes 100 mg	-
	Eyes - Mild irritant	Rabbit	-	870 ug	-
	Eyes - Severe irritant	Rabbit	-	24 hours 2 mg	-
	Skin - Mild irritant	Pig	-	24 hours 250 uL	-
	Skin - Mild irritant	Rabbit	-	435 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 mg	-
	Skin - Moderate irritant	Rabbit	-	500 mg	-

Conclusion/Summary : Causes skin irritation.

Sensitisation

SECTION 11: Toxicological information

Product/ingredient name	Route of exposure	Species	Result
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	skin	Guinea pig	Sensitising

Conclusion/Summary : May cause an allergic skin reaction.

Mutagenicity

Product/ingredient name	Test	Experiment	Result
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	-	Subject: Bacteria	Negative

Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

Conclusion/Summary : Based on available data, the classification criteria are not met.

Reproductive toxicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Teratogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate	Category 3	-	Respiratory tract irritation
2-Methoxy-1-methylethyl acetate	Category 3	-	Narcotic effects
2-ethylhexan-1-ol	Category 3	-	Respiratory tract irritation
Toluene	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Toluene	Category 2	-	-

Aspiration hazard

Product/ingredient name	Result
Toluene	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure : Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.
Inhalation : No known significant effects or critical hazards.
Skin contact : Causes skin irritation. May cause an allergic skin reaction.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness
Inhalation : No specific data.

SECTION 11: Toxicological information

Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Long term exposure

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Potential chronic health effects

Not available.

Conclusion/Summary	: Not available.
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

Other information	: Not available.
--------------------------	------------------

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Hexamethylene diacrylate	EC50 1.09 mg/l	Algae - Algae - <i>Selenastrum capricornutum</i>	72 hours
	EC50 2.7 mg/l	Daphnia - Daphnia - <i>Daphnia magna</i>	48 hours
	LC50 0.38 mg/l	Fish - <i>Oryzias latipes</i>	96 hours
	NOEC 0.5 mg/l	Algae - Algae - <i>Desmodesmus subspicatus</i>	72 hours
	NOEC 0.14 mg/l	Daphnia - Daphnia - <i>Daphnia magna</i>	21 days
titanium dioxide	NOEC 0.072 mg/l	Fish - <i>Oryzias latipes</i>	96 hours
	Acute LC50 3 mg/l Fresh water	Crustaceans - Water flea - <i>Ceriodaphnia dubia</i> - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - Water flea - <i>Daphnia pulex</i> - Neonate	48 hours
	Acute LC50 >1000000 µg/l Marine water	Fish - Mummichog - <i>Fundulus heteroclitus</i>	96 hours
	EC50 ≥0.26 mg/l	Aquatic plants - <i>Desmodesmus subspicatus</i>	72 hours
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	NOEC ≥0.008 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	21 days
	Acute EC50 >1.175 mg/l	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 >0.09 mg/l	Fish - <i>Brachydanio rerio</i>	96 hours
	Acute EC50 >1000 mg/l Fresh water	Daphnia - Water flea - <i>Daphnia magna</i>	48 hours
	Acute LC50 800000 µg/l Marine water	Crustaceans - Common shrimp, sand shrimp - <i>Crangon crangon</i>	48 hours
2-Butoxyethanol	Acute LC50 1250000 µg/l Marine water	Fish - Inland silverside - <i>Menidia beryllina</i>	96 hours
	Acute LC50 28200 µg/l Fresh water	Fish - Fathead minnow - <i>Pimephales promelas</i>	96 hours

SECTION 12: Ecological information

copper bis (dimethyldithiocarbamate) 1,4-Dihydroxybenzene Toluene	Acute LC50 71 µg/l Fresh water	Fish - Fathead minnow - <i>Pimephales promelas</i>	96 hours
	Acute EC50 130 µg/l Fresh water	Daphnia - Water flea - <i>Daphnia magna</i> - Larvae	48 hours
	Acute LC50 44 µg/l Fresh water	Fish - Rainbow trout, donaldson trout - <i>Oncorhynchus mykiss</i>	96 hours
	Acute EC50 12500 µg/l Fresh water	Algae - Green algae - <i>Pseudokirchneriella subcapitata</i>	72 hours
	Acute EC50 11600 µg/l Fresh water	Crustaceans - Scud - <i>Gammarus pseudolimnaeus</i> - Adult	48 hours
	Acute EC50 5.56 mg/l Fresh water	Daphnia - Water flea - <i>Daphnia magna</i> - Neonate	48 hours
	Acute LC50 5500 µg/l Fresh water	Fish - Coho salmon, silver salmon - <i>Oncorhynchus kisutch</i> - Fry	96 hours
	Chronic NOEC 1000 µg/l Fresh water	Daphnia - Water flea - <i>Daphnia magna</i>	21 days

Conclusion/Summary : Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Conclusion/Summary : This product has not been tested for biodegradation.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-Propylidynetrimethanol, ethoxylated, esters with acrylic acid	-	-	Not readily
	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Hexamethylene diacrylate	2.81	-	Low
Oligotriacrylate	2.52	-	Low
(1-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)] diacrylate	2	-	Low
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-Propylidynetrimethanol, ethoxylated, esters with acrylic acid	5.77	<5	Low
	2.89	-	Low
2-Methoxy-1-methylethyl acetate	1.2	-	Low
2-Butoxyethanol	0.81	-	Low
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	2.89	-	Low
2-ethylhexan-1-ol	2.9	25.33	Low
1,4-Dihydroxybenzene	0.59	3.162	Low
Toluene	2.73	90	Low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 12: Ecological information

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.





European waste catalogue (EWC) : 080111*

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN3082	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)
14.3 Transport hazard class(es)	9 	9 	9 	9 
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes.

Additional information

ADR/RID : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

Tunnel code (-)

ADN : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IMDG : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

SECTION 14: Transport information

IATA : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture UK (GB)/REACH

[Annex XIV - List of substances subject to authorisation](#)

[Annex XIV](#)

None of the components are listed.

[Substances of very high concern](#)

None of the components are listed.

[Ozone depleting substances](#)

Not listed.

[Prior Informed Consent \(PIC\)](#)

Not listed.

[Persistent Organic Pollutants](#)

Not listed.

[Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles](#)

No listed substance

[Seveso Directive](#)

This product is controlled under the Seveso Directive.

[Danger criteria](#)

Category

E1

[EU regulations](#)

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

[International regulations](#)

[Chemical Weapon Convention List Schedules I, II & III Chemicals](#)

Not listed.

[Montreal Protocol](#)

Not listed.

[Stockholm Convention on Persistent Organic Pollutants](#)

SECTION 15: Regulatory information

Not listed.

[Rotterdam Convention on Prior Informed Consent \(PIC\)](#)

Not listed.

[UNECE Aarhus Protocol on POPs and Heavy Metals](#)

Not listed.

15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate
GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = GB CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

[Procedure used to derive the classification](#)

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Acute 1, H400	Calculation method
Aquatic Chronic 2, H411	Calculation method

[Full text of abbreviated H statements](#)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

[Full text of classifications](#)

SECTION 16: Other information

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Aquatic Chronic 4	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Muta. 2	GERM CELL MUTAGENICITY - Category 2
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of issue/ Date of revision : 24/10/2023

Date of previous issue : 26/05/2023

Version : 1.01

UVILUX 6790-02_TS 21367 NCS S 5010-B50G TS 21367 NCS S 5010-B50G

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

