Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Ireland

SAFETY DATA SHEET



UVILUX 6790-03 - TS 6868 WHITE

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier
Product name

: UVILUX 6790-03 - TS 6868 WHITE

1.2 Relevant identified uses of the substance or mixture and uses advised against Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091. e-mail address of person : Prod-safe@teknos.com responsible for this SDS

National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

National advisory body/Poison Centre

- Telephone number
- Emergency medical information: (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland.
 Members of the public Number (8 am-10 pm): +353 (0)1 809 2166 Healthcare professional telephone Number (24hrs): +353 (0)1 809 2566

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 1B, H360F Aquatic Acute 1, H400 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word	: Danger
Hazard statements	: ┣ᠯ315 - Causes skin irritation.
	H317 - May cause an allergic skin reaction.
	H318 - Causes serious eye damage.
	H360F - May damage fertility.
	H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements

Date of issue/Date of revision	: 24/07/2025	Date of previous issue	: 24/10/2022	Version : 2	1/21
UVILUX 6790-03 - TS 6868 WHIT	E			Label No :1/24784	4

SECTION 2: Hazards identification

Prevention	:	 P201 - Obtain special instructions before use. P280 - Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection. P273 - Avoid release to the environment.
Response	:	₱391 - Collect spillage. P308 + P313 - IF exposed or concerned: Get medical advice or attention.
Storage	1	Not applicable.
Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	:	Contains: Hexamethylene diacrylate; Dipropylenglycol diacrylate; Propylidynetrimethanol, ethoxylated, esters with acrylic acid and 4,4'- Isopropylidenediphenol
Supplemental label elements	:	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Restricted to professional users.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

to Regulation (EC) No. 1907/2006, Annex XIII Other hazards which do : None known. not result in classification

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Hexamethylene diacrylate	REACH #: 01-2119484737-22 EC: 235-921-9 CAS: 13048-33-4 Index: 607-109-00-8	≥25 - ≤50	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411	M [Acute] = 1	[1]
Dipropylenglycol diacrylate	REACH #: 01-2119484629-21 EC: 260-754-3 CAS: 57472-68-1	≥10 - ≤25	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317	-	[1]
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	REACH #: 01-2119489900-30 EC: 500-066-5 CAS: 28961-43-5	≤5	Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412	-	[1]
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≤5	Carc. 2, H351 (inhalation)	-	[1] [*]
4,4'-Isopropylidenediphenol	REACH #: 01-2119490020-53 EC: 500-130-2 CAS: 55818-57-0	≤5	Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]

SECTION 3: Compo	sition/informat	ion on in	gredients		
2-Propenoic acid, 1,1'-[(1-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)]] ester, reaction products with diethylamine		≤5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 2, H411	-	[1]
2-hydroxy- 2-methylpropiophenone	REACH #: 01-2119472306-39 EC: 231-272-0 CAS: 7473-98-5	≤5	Acute Tox. 4, H302 Aquatic Chronic 3, H412	ATE [Oral] = 1694 mg/kg	[1]
(1-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)] diacrylate	REACH #: 01-2119484613-34 EC: 256-032-2 CAS: 42978-66-5 Index: 607-249-00-X	≤3	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 2, H411	STOT SE 3, H335: C ≥ 10%	[1]
hydroxycyclohexyl phenyl ketone	REACH #: 01-2119457404-40 EC: 213-426-9 CAS: 947-19-3	≤3	Aquatic Chronic 3, H412	-	[1]
Diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide	REACH #: 01-2119972295-29 EC: 278-355-8 CAS: 75980-60-8 Index: 015-203-00-X	<3	Skin Sens. 1B, H317 Repr. 1B, H360Fd	-	[1] [2]
Fatty acids, C18-unsatd., dimers, polymers with acrylic acid, bisphenol A, epichlorohydrin and nonanoic acid	CAS: 216689-76-8	<1	Skin Sens. 1B, H317	-	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

Substance classified with a health or environmental hazard

[2] Substance with carcinogenic, mutagenic or reproductive toxicity properties

[*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter \leq 10 µm not bound within a matrix.

Containing 176 of more of intainant dioxide particles with actouyhamic diameter = 10 p

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first a	id measures
Eye contact	: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
Inhalation	: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire,

Date of issue/Date of revision	: 24/07/2025	Date of previous issue	: 24/10/2022	Version	:2	3/21
UVILUX 6790-03 - TS 6868 WHIT	E			Label No	1 247	784

SECTION 4: First aid measures

	symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/sy	mptoms
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	 Koverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations
Skin contact	 Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations
Ingestion	 Adverse symptoms may include the following: stomach pains reduced foetal weight increase in foetal deaths skeletal malformations
4.3 Indication of any imm	ediate medical attention and special treatment needed
Notes to physician	: In case of inhalation of decomposition products in a fire, sy

Notes to physician: In case of inhalation of decomposition products in a fire, symptoms may be delayed.
The exposed person may need to be kept under medical surveillance for 48 hours.Specific treatments: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	:	None known.

: 24/07/2025 Date of previous issue

SECTION 5: Firefighting measures

5.2 Special hazards arising f	rom the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is very toxic to aquatic life. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides phosphorus oxides halogenated compounds metal oxide/oxides
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

: 24/07/2025 Date of previous issue

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria		
	Notification and MAPP threshold	Safety report threshold
E1	100 tonnes	200 tonnes

7.3 Specific end use(s)

Recommendations

: Not available.

Industrial sector specific solutions

: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
No exposure limit value known.	

Biological exposure indices

Product/ingredient name	Exposure indices
No exposure indices known.	

SECTION 8: Exposure controls/personal protection

Recommended monitoring : procedures	European St assessment values and n atmospheres of exposure (Workplace for the meas	should be made to monitoring standards, such as the following: Standard EN 689 (Workplace atmospheres - Guidance for the it of exposure by inhalation to chemical agents for comparison with lim measurement strategy) European Standard EN 14042 (Workplace es - Guide for the application and use of procedures for the assessme to chemical and biological agents) European Standard EN 482 atmospheres - General requirements for the performance of procedur surement of chemical agents) Reference to national guidance for methods for the determination of hazardous substances will also b	nt ires
DNELs/DMELs			
Product/ingredient name		Result	
⊮ examethylene diacrylate		DNEL - General population - Long term - Dermal 1.66 mg/kg bw/day <u>Effects</u> : Systemic	
		DNEL - General population - Long term - Oral 2.1 mg/kg bw/day <u>Effects</u> : Systemic	
		DNEL - Workers - Long term - Dermal 2.77 mg/kg bw/day <u>Effects</u> : Systemic	
		DNEL - General population - Long term - Inhalation 7.2 mg/m ³ <u>Effects</u> : Systemic	
		DNEL - Workers - Long term - Inhalation 24.5 mg/m³ <u>Effects</u> : Systemic	
Dipropylenglycol diacrylate		DNEL - Workers - Long term - Dermal 1.7 mg/kg bw/day <u>Effects</u> : Systemic	
		DNEL - Workers - Long term - Inhalation 2.35 mg/m ³ <u>Effects</u> : Systemic	
Propylidynetrimethanol, ethoxyl with acrylic acid	ated, esters	DNEL - Workers - Long term - Dermal 10.5 mg/kg bw/day <u>Effects</u> : Systemic	
		DNEL - Workers - Long term - Inhalation 37 mg/m ³ Effects: Systemic	
titanium dioxide		DNEL - General population - Long term - Inhalation 28 µg/m³ <u>Effects</u> : Local	
		DNEL - Workers - Long term - Inhalation 170 μg/m³ <u>Effects</u> : Local	
4,4'-Isopropylidenediphenol		DNEL - Workers - Long term - Inhalation 1.17 mg/m ³ <u>Effects</u> : Systemic	
		DNEL - Workers - Long term - Dermal 33 mg/kg bw/day <u>Effects</u> : Systemic	
2-hydroxy-2-methylpropiopheno	one	DNEL - General population - Long term - Oral	
Date of issue/Date of revision	: 24/07/2025	Date of previous issue : 24/10/2022 Version : 2 7/2	?1

SECTION 8: Exposure controls/personal protection

	0.4 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Long term - Dermal 0.5 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Long term - Inhalation 0.9 mg/m ³ <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Dermal 1 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Inhalation 3.5 mg/m³ <u>Effects</u> : Systemic
(1-methyl-1,2-ethanediyl)bis[oxy(methyl- 2,1-ethanediyl)] diacrylate	DNEL - Workers - Long term - Dermal 1.7 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Inhalation 2.35 mg/m ³ <u>Effects</u> : Systemic
hydroxycyclohexyl phenyl ketone	DNEL - General population - Long term - Oral 0.694 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Long term - Dermal 0.694 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Long term - Inhalation 1.21 mg/m ³ <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Dermal 1.94 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Inhalation 6.8 mg/m ³ <u>Effects</u> : Systemic
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	DNEL - General population - Long term - Oral 83.3 μg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Long term - Dermal 83.3 μg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Long term - Inhalation 0.145 mg/m ³ <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Dermal 0.233 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Inhalation 0.822 mg/m ³ <u>Effects</u> : Systemic
Date of issue/Date of revision : 24/07/2025	Date of previous issue : 24/10/2022 Version : 2

SECTION 8: Exposure controls/personal protection

Fatty acids, C18-unsatd., dimers, polymers with acrylic acid, bisphenol A, epichlorohydrin and nonanoic acid **DNEL - Workers - Long term - Dermal** 0.33 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - Workers - Long term - Inhalation 1.18 mg/m³ <u>Effects</u>: Systemic

PNECs

Not available.

8.2 Exposure controls	
Appropriate engineering controls	 If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Individual protection meas	sures
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
	Recommendations : Wear suitable gloves tested to EN374.
	< 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm
	1 - 4 hours (breakthrough time): $4H$ / Silver Shield® gloves.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	 Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Filter type: A
Environmental exposure controls	 Filter type (spray application): A P Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Colour	: White.
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and	:
boiling range	

Ingredient name	°C	°F	Method	
#-methyl-1,2-ethanediyl)bis[oxy(methyl- 2,1-ethanediyl)] diacrylate	>120	>248		
2-hydroxy-2-methylpropiophenone	252.1	485.8	OECD 104	
- Flammability : No	t available.	1		

i lainna sinty	
Lower and upper explosion	
limit	

Flash point

: Not available.

: Lower: Not applicable. Upper: Not applicable.

: Closed cup: >100°C (>212°F)

ż

ŝ

Auto-ignition temperature

Ingredient name		°C	°F	Method	
Hexamethylene diacrylate		235	455	DIN 51794	
Dipropylenglycol diacrylate		240	464	DIN 51794	
Decomposition temperature : Not avai		vailable.			
рН	: Not a	pplicable.			
Viscosity	: Not a	vailable.			
Solubility(ies)	:				
Not available.					
Solubility in water	: Not a	vailable.			
Partition coefficient: n-octanol/ water	: Not a	pplicable.			

Vapour pressure

	Vapour Pressure at 20°C		Vapour pressure at 50°C			
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
Anydroxy-2-methylpropiophenone	0.00428	0.00057	OECD 104	0.09751	0.013	OECD 104
Dipropylenglycol diacrylate	0.00064	0.000085	OECD 104			

Relative density	: Not available.
Density	: 1.2 g/cm ³
Vapour density	: Not available.
Particle characteristics	
Median particle size	: Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

- **Explosive properties** : Not available.
- **Oxidising properties** : Not available.
- 9.2.2 Other safety characteristics
- Not applicable.

SECTION 10: Stability and reactivity			
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.		
10.2 Chemical stability	: The product is stable.		
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.		
10.4 Conditions to avoid	: No specific data.		
10.5 Incompatible materials	: No specific data.		
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.		

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in	n Regulation (EC) No 1272/2008
Acute toxicity	
Product/ingredient name	Result
✓examethylene diacrylate	Rat - Oral - LD50
	5 g/kg
Dipropylenglycol diacrylate	Rat - Oral - LD50
	4600 mg/kg
	Toxic effects: Behavioral - Somnolence (general depressed
	activity) Behavioral - Ataxia Gastrointestinal - Hypermotility, diarrhea
	diarmea
Propylidynetrimethanol, ethoxylated, esters	Rabbit - Dermal - LD50
with acrylic acid	>13 g/kg
2-hydroxy-2-methylpropiophenone	Rat - Oral - LD50
	1694 mg/kg
	Toxic effects: Behavioral - Somnolence (general depressed
	activity) Behavioral - Tremor Liver - Other changes
	Rat - Dermal - LD50
	6929 mg/kg
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-	Rat - Oral - LD50
2,1-ethanediyl)] diacrylate	6200 mg/kg
	Toxic effects: Eye - Ptosis Lung, Thorax, or Respiration -
	Respiratory depression Other - Hair

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
VILUX 6790-03	53943.6	N/A	N/A	N/A	N/A
Hexamethylene diacrylate	5000	N/A	N/A	N/A	N/A
Dipropylenglycol diacrylate	4600	N/A	N/A	N/A	N/A
2-hydroxy-2-methylpropiophenone	1694	6929	N/A	N/A	N/A
(1-methyl-1,2-ethanediyl)bis[oxy(methyl- 2,1-ethanediyl)] diacrylate	6200	N/A	N/A	N/A	N/A

Skin corrosion/irritation

Date of issue/Date of revision : UVILUX 6790-03 - TS 6868 WHITE

: 24/07/2025 Date of previous issue

Ç

SECTION 11: Toxicological information			
Product/ingredient name Mexamethylene diacrylate	Result Rabbit - Skin - Severe irritant Duration of treatment/exposure: 24 hours Amount/concentration applied: 500 mg		
Dipropylenglycol diacrylate	Rabbit - Skin - Severe irritant Amount/concentration applied: 500 mg		
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	Rabbit - Skin - Moderate irritant Amount/concentration applied: 500 mg		
titanium dioxide	Human - Skin - Mild irritant Duration of treatment/exposure: 72 hours Amount/concentration applied: 300 ug l		
(1-methyl-1,2-ethanediyl)bis[oxy(methyl- 2,1-ethanediyl)] diacrylate	Rabbit - Skin - Moderate irritant Amount/concentration applied: 500 mg		
Conclusion/Summary [Product] : Not available	ð.		
Serious eye damage/eye irritation			
Product/ingredient name	Result		
Dipropylenglycol diacrylate	Rabbit - Eyes - Severe irritant Amount/concentration applied: 100 mg		
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	Rabbit - Eyes - Moderate irritant Amount/concentration applied: 100 mg		
(1-methyl-1,2-ethanediyl)bis[oxy(methyl- 2,1-ethanediyl)] diacrylate	Rabbit - Eyes - Severe irritant <u>Duration of treatment/exposure</u> : 24 hours <u>Amount/concentration applied</u> : 100 uL		
Conclusion/Summary [Product] : Not available).		
Respiratory corrosion/irritation Not available.			
Conclusion/Summary [Product] : Not available			
Respiratory or skin sensitization Not available.			
Skin Conclusion/Summary [Product] : Not available	s.		
Respiratory Conclusion/Summary [Product] : Not available	s.		
Germ cell mutagenicity Not available.			

Conclusion/Summary [Product] : Not available.

Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. Not available.

Date of issue/Date of revision : 24/10/2022 : 24/07/2025 Date of previous issue UVILUX 6790-03 - TS 6868 WHITE

SECTION 11: Toxicological information

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name

-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate Result STOT SE 3, H335 (Respiratory tract irritation)

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard	
Not available.	
Information on likely routes	s of exposure
Not available.	
Potential acute health effec	<u>ts</u>
Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the ph	nysical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced foetal weight increase in foetal deaths skeletal malformations
Delayed and immediate effe	ects as well as chronic effects from short and long-term exposure
Short term exposure	

Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

: 24/07/2025 Date of previous issue

: 24/10/2022

Date of issue/Date of revision

SECTION 11: Toxicological information

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.	
Carcinogenicity	: No known significant effects or critical hazards.	
Mutagenicity	: No known significant effects or critical hazards.	

: May damage fertility. **Reproductive toxicity**

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name Hexamethylene diacrylate

Result

NOEC

OECD [Alga, Growth Inhibition Test] Algae - Algae - Desmodesmus subspicatus 0.5 mg/l [72 hours]

EC50

OECD [Alga, Growth Inhibition Test] Algae - Algae - Selenastrum capricornutum 1.09 mg/l [72 hours]

LC50

OECD [Fish, Acute Toxicity Test] Fish - Oryzias latipes 0.38 mg/l [96 hours]

NOEC

OECD [Fish, Early-Life Stage Toxicity Test] Fish - Oryzias latipes 0.072 mg/l [96 hours]

EC50

OECD [Daphnia sp. Acute Immobilization Test and Reproduction Test] Daphnia - Daphnia - Daphnia magna 2.7 mg/l [48 hours]

NOEC

OECD [Daphnia sp. Acute Immobilization Test and Reproduction Test] Daphnia - Daphnia - Daphnia magna 0.14 mg/l [21 days]

Acute - LC50 - Marine water

Fish - Mummichog - Fundulus heteroclitus >1000000 µg/l [96 hours] Effect: Mortality

Acute - LC50 - Fresh water

Crustaceans - Water flea - Ceriodaphnia dubia - Neonate Age: <24 hours

SECTION 12: Ecological information

3 mg/l [48 hours] <u>Effect</u>: Mortality

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Not available.

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Hexamethylene diacrylate	2.81	-	Low
Dipropylenglycol diacrylate	0.01 to 0.39	-	Low
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	2.89	-	Low
4,4'-Isopropylidenediphenol	1.6 to 3	-	Low
2-hydroxy-	1.62	-	Low
2-methylpropiophenone			
(1-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)] diacrylate	2	-	Low
hydroxycyclohexyl phenyl ketone	2.81	4 to 12 [Bioaccumulation test of chemical substance in fish and shellfish]	Low
Diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide	-	53 to 72	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logKoc	Кос	
Hexamethylene diacrylate	2.5	332.947	
2-hydroxy-2-methylpropiophenone	1.9	80.7076	
(1-methyl-1,2-ethanediyl)bis[oxy(methyl- 2,1-ethanediyl)] diacrylate	2.9	803.136	
hydroxycyclohexyl phenyl ketone	2.1	131.578	
Diphenyl(2,4,6-trimethylbenzoyl) phosphine oxide	2.8	630.017	

Results of PMT and vPvM assessment

Product/ingredient name	PMT	Р	Μ	т	vPvM	vP	vM
Hexamethylene diacrylate	No	No	No	No	No	No	No
Dipropylenglycol diacrylate	No	No	No	No	No	No	No
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	No	No	No	No	No	No	No
titanium dioxide	No	No	No	No	No	No	No
4,4'-Isopropylidenediphenol	No	No	No	No	No	No	No
2-Propenoic acid, 1,1'-[(1-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)]] ester, reaction products with diethylamine	No	No	No	No	No	No	No
2-hydroxy-	No	No	No	No	No	No	No
ate of issue/Date of revision	: 24/07	/2025 Date c	of previous issu	ie : 24	/10/2022	Versio	on: 2 15/2
VILUX 6790-03 - TS 6868 WI	HITE					Label N	o: <mark>1⁄</mark> 24784

2-methylpropiophenone (1-methyl-1,2-ethanediyl)bis	No						
oxy(methyl-2,1-ethanediyl)] diacrylate							
hydroxycyclohexyl phenyl ketone	No						
Diphenyl (2,4,6-trimethylbenzoyl) ohosphine oxide	No						
Fatty acids, C18-unsatd., dimers, polymers with acrylic acid, bisphenol A, epichlorohydrin and nonanoic acid	No						

Mobility

: Not available.

: The product does not meet the criteria to be considered as a PMT or vPvM.

Product/ingredient name	PBT	Р	В	Т	vPvB	vP	vB
examethylene diacrylate	No	N/A	N/A	No	N/A	N/A	N/A
Dipropylenglycol diacrylate	No	N/A	N/A	No	N/A	N/A	N/A
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	No	N/A	N/A	No	N/A	N/A	N/A
itanium dioxide	No	No	No	No	No	No	No
1,4'-Isopropylidenediphenol	No	N/A	N/A	No	N/A	N/A	N/A
2-Propenoic acid, 1,1'-[1-methyl-1,2-ethanediyl)bis oxy(methyl-2,1-ethanediyl)]] ester, reaction products with diethylamine	No	N/A	N/A	No	N/A	N/A	N/A
2-hydroxy- 2-methylpropiophenone	No	N/A	N/A	No	N/A	N/A	N/A
(1-methyl-1,2-ethanediyl)bis oxy(methyl-2,1-ethanediyl)] diacrylate	No	N/A	N/A	No	N/A	N/A	N/A
nydroxycyclohexyl phenyl ketone	No	N/A	No	No	No	N/A	No
Diphenyl 2,4,6-trimethylbenzoyl) bhosphine oxide	No	N/A	No	Yes	No	N/A	No
Fatty acids, C18-unsatd., limers, polymers with acrylic acid, bisphenol A, epichlorohydrin and nonanoic acid	No	N/A	N/A	No	N/A	N/A	N/A
egulation (EC) No. 1272/20	08 [CLP]						
Product/ingredient name	PBT	Р	В	т	vPvB	vP	vB
examethylene diacrylate	No	No	No	No	No	No	No
Dipropylenglycol diacrylate	No	No	No	No	No	No	No
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	No	No	No	No	No	No	No
itanium dioxide	No	No	No	No	No	No	No
1,4'-Isopropylidenediphenol	No	No	No	No	No	No	No
2-Propenoic acid, 1,1'-[1-methyl-1,2-ethanediyl)bis oxy(methyl-2,1-ethanediyl)]] ester, reaction products with	No	No	No	No	No	No	No
diethylamine							
diethylamine te of issue/Date of revision	: 24/07/	/2025 Date o	f previous iss	ue : 24	4/10/2022	Versie	on:2 16/2

12.5 Results of PBT and vPvB assessment Regulation (EC) No. 1907/2006 [REACH]

Conclusion/Summary

SECTION 12: Ecological information

		•••••••					
2-hydroxy-	No	No	No	No	No	No	No
2-methylpropiophenone							
(1-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)] diacrylate	No	No	No	No	No	No	No
hydroxycyclohexyl phenyl ketone	No	No	No	No	No	No	No
Diphenyl	No	No	No	No	No	No	No
(2,4,6-trimethylbenzoyl) phosphine oxide							
Fatty acids, C18-unsatd., dimers, polymers with acrylic acid, bisphenol A, epichlorohydrin and nonanoic acid	No	No	No	No	No	No	No

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP] : The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product]

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	Yes.
European waste catalogue (EWC)	080111*
Packaging	
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

: 24/07/2025 Date of previous issue

	ADR/RID	ADN	IMDG	IATA		
14.1 UN number or ID number	UN3082	UN3082	UN3082	UN3082		
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)		
14.3 Transport hazard class(es)	9	9	9	9		
14.4 Packing group	111			111		
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes.		
Additional informa	tion	-	•	ł		
ADR/RID	or ≤5 kg, j	uct is not regulated as a d provided the packagings r 4 to 4.1.1.8. Dde (-)				
ADN	or ≤5 kg, j	 This product is not regulated as a dangerous good when transported in sizes of or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1. and 4.1.1.4 to 4.1.1.8. 				
IMDG	or ≤5 kg, j	uct is not regulated as a d provided the packagings r 4 to 4.1.1.8.				
ΙΑΤΑ	or ≤5 kg, j	 This product is not regulated as a dangerous good when transported in sizes of ≤ or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8. 				
14.6 Special precau user	upright an	t within user's premises d secure. Ensure that per of an accident or spillage.	sons transporting the pro			
	4.7 Maritime transport in : Not relevant/applicable due to nature of the product. ulk according to IMO					

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

Intrinsic property	Ingredient name			Date of revision
F oxic to reproduction	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Candidate	-	6/15/2023

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Date of issue/Date of revision	: 24/07/2025	Date of previous issue	: 24/10/2022	Version	:2	18/21
UVILUX 6790-03 - TS 6868 WHITI	Ξ			Label No	1⁄2 47	84

Product/ingredient name	%	Designation [Usage]
VILUX 6790-03	≥90	3
Diphenyl(2,4,6-trimethylbenzoyl)phosphine	e <3	30 30
	to professiona	
Other EU regulations		
Industrial emissions : Not listed (integrated pollution prevention and control) - Air		
Industrial emissions : Not listed (integrated pollution prevention and control) - Water		
Explosive precursors : Not applica		
Ozone depleting substances (EU 2024/5 Not listed.	<u>90)</u>	
Prior Informed Consent (PIC) (649/2012/	<u>EU)</u>	
Not listed.		
Persistent Organic Pollutants Not listed.		
Seveso Directive		
This product is controlled under the Seves	Directive.	
Danger criteria		
Category		
E1		
Lengulations		
Chemical Weapon Convention List Sched	dules I, II & III	Chemicals
Not listed.		
Iontreal Protocol		
Not listed.		
Stockholm Convention on Persistent Org	anic Pollutar	<u>its</u>
	0	2)
Rotterdam Convention on Prior Informed Not listed.	Consent (Pl	
JNECE Aarhus Protocol on POPs and He	avy Metals	
Not listed.		
.2 Chemical safety : This produ sessment required.	ct contains su	bstances for which Chemical Safety Assessments are still

: 24/07/2025 Date of previous issue

SECTION 16: Other information

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
	1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative
Procedure used to derive	the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method
Repr. 1B, H360F	Calculation method
Aquatic Acute 1, H400	Calculation method
Aquatic Chronic 2, H411	Calculation method

Full text of abbreviated H statements

H 302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H360F	May damage fertility.
H360Fd	May damage fertility. Suspected of damaging the unborn child.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Repr. 1B	REPRODUCTIVE TOXICITY - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
Date of issue/ Date of revision	: 24/07/2025

Date of previous issue	: 24/10/2022	
Version	: 2	
	UVILUX 6790-03_TS 6868 WHITE	

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

: 24/07/2025 Date of previous issue

Date of issue/Date of revision : UVILUX 6790-03 - TS 6868 WHITE

: 24/07/2025 Date of previous issue