### SAFETY DATA SHEET



UVILUX PRIMER 1754-11 - DUSTIE BLUE TS 21105

### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

: UVILUX PRIMER 1754-11 - DUSTIE BLUE TS 21105 **Product name** 

1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS

: Prod-safe@teknos.com

### 1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : Emergency medical information: (seven days) contact National Poisons Information

Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland.

Members of the public Number (8 am-10 pm): +353 (0)1 809 2166 Healthcare professional telephone Number (24hrs): +353 (0)1 809 2566

### SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** 







Signal word : Danger

**Hazard statements** : H315 - Causes skin irritation.

> H317 - May cause an allergic skin reaction. H318 - Causes serious eye damage.

H411 - Toxic to aquatic life with long lasting effects.

**Precautionary statements** 

**Prevention** : P280 - Wear protective gloves. Wear eye or face protection.

P273 - Avoid release to the environment.

Response P391 - Collect spillage.

> P305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor.

Date of issue/Date of revision : 03/12/2025 Date of previous issue · 15/11/2023 Version : 2 1/22 Label No : 1/37184

### **SECTION 2: Hazards identification**

**Storage** 

: Not applicable.

Disposal

: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazardous ingredients** 

: Contains: exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate; 2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide; (1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate and Propylidynetrimethanol,

ethoxylated, esters with acrylic acid

Supplemental label

elements

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

:

#### 2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

: None known.

### **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
exo-1,7,7-trimethylbicyclo [2.2.1]hept-2-yl methacrylate	REACH #: 01-2119886505-27 EC: 231-403-1 CAS: 7534-94-3	≥10 - ≤25	Aquatic Chronic 3, H412	-	[1]
exo-1,7,7-trimethylbicyclo [2.2.1]hept-2-yl acrylate	REACH #: 01-2119957862-25 EC: 227-561-6 CAS: 5888-33-5	≤11	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide	REACH #: 01-2120140608-57 EC: 810-703-1 CAS: 1187441-10-6	≤5	Eye Dam. 1, H318 Skin Sens. 1B, H317	-	[1]
(1-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)] diacrylate	REACH #: 01-2119484613-34 EC: 256-032-2 CAS: 42978-66-5 Index: 607-249-00-X	≤4.2	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 2, H411	STOT SE 3, H335: C ≥ 10%	[1]
2-hydroxy- 2-methylpropiophenone	REACH #: 01-2119472306-39 EC: 231-272-0 CAS: 7473-98-5	≤3	Acute Tox. 4, H302 Aquatic Chronic 3, H412	ATE [Oral] = 1694 mg/kg	[1]
Propylidynetrimethanol, ethoxylated, esters with	REACH #: 01-2119489900-30	≤3	Eye Irrit. 2, H319 Skin Sens. 1, H317	-	[1]

 Date of issue/Date of revision
 : 03/12/2025
 Date of previous issue
 : 15/11/2023
 Version
 : 2
 2/22

 UVILUX PRIMER 1754-11 - DUSTIE BLUE TS 21105
 Label No : 737184

### **SECTION 3: Composition/information on ingredients**

•			<u> </u>		
acrylic acid	EC: 500-066-5 CAS: 28961-43-5		Aquatic Chronic 3, H412		
Dipropylenglycol diacrylate	REACH #: 01-2119484629-21 EC: 260-754-3 CAS: 57472-68-1	≤3	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317	-	[1]
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	REACH #: 01-2119489401-38 EC: 423-340-5 CAS: 162881-26-7 Index: 015-189-00-5	≤3	Skin Sens. 1A, H317 Aquatic Chronic 4, H413	-	[1]
Acrylated resin	-	≤3	Eye Irrit. 2, H319	-	[1]
4-methylbenzophenone	EC: 205-159-1 CAS: 134-84-9	≤3	STOT RE 2, H373 (oral) Aquatic Chronic 3, H412	-	[1]
copper bis (dimethyldithiocarbamate)	REACH #: 01-2120770993-40 EC: 205-287-8 CAS: 137-29-1	≤0.028	Acute Tox. 2, H330 Aquatic Acute 1, H400	ATE [Inhalation (dusts and mists)] = 0.12 mg/l M [Acute] = 10	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

### Type

Substance classified with a health or environmental hazard Occupational exposure limits, if available, are listed in Section 8.

### SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### **Eye contact**

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

### Inhalation

Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Skin contact

Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Date of issue/Date of revision : 03/12/2025 Date of previous issue · 15/11/2023 Version : 2 3/22 Label No : 1/37184

### **SECTION 4: First aid measures**

### Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### **Protection of first-aiders**

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

### Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:

> pain watering redness

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

> pain or irritation redness

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

### SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous combustion** products

Decomposition products may include the following materials: carbon dioxide

carbon monoxide phosphorus oxides metal oxide/oxides

### 5.3 Advice for firefighters

**Special protective actions** for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Date of issue/Date of revision · 15/11/2023 Version : 2 4/22 : 03/12/2025 Date of previous issue Label No : 1/37184

### SECTION 5: Firefighting measures

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

### SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

#### Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

### 6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

### SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

### Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Date of issue/Date of revision : 03/12/2025 Date of previous issue · 15/11/2023 Version : 2 5/22 Label No : 1/37184

### SECTION 7: Handling and storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### **Seveso Directive - Reporting thresholds**

### **Danger criteria**

	Notification and MAPP threshold	Safety report threshold
<b>2</b>	200 tonnes	500 tonnes

### 7.3 Specific end use(s)

Recommendations : Not available. **Industrial sector specific** : Not available.

# solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

### **Occupational exposure limits**

Product/ingredient name	Exposure limit values
No exposure limit value known.	

### **Biological exposure indices**

Product/ingredient name	Exposure indices
No exposure indices known.	

# procedures

Recommended monitoring : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### **DNELs/DMELs**

### **Product/ingredient name**

exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate

DNEL - General population - Long term - Oral

0.21 mg/kg bw/day Effects: Systemic

**DNEL - General population - Long term - Dermal** 

0.21 mg/kg bw/day Effects: Systemic

**DNEL - Workers - Long term - Dermal** 

0.35 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Inhalation

0.36 mg/m<sup>3</sup> Effects: Systemic

**DNEL - Workers - Long term - Inhalation** 

Date of issue/Date of revision : 03/12/2025 Date of previous issue : 15/11/2023 Version : 2 6/22 UVILUX PRIMER 1754-11 - DUSTIE BLUE TS 21105 Label No : 1/37184

1.22 mg/m³

Effects: Systemic

exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate

DNEL - General population - Long term - Oral

0.83 mg/kg bw/day Effects: Systemic

**DNEL - General population - Long term - Dermal** 

0.83 mg/kg bw/day Effects: Systemic

**DNEL - Workers - Long term - Dermal** 

1.39 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Inhalation

1.45 mg/m³ Effects: Systemic

**DNEL - Workers - Long term - Inhalation** 

4.9 mg/m³ Effects: Systemic

(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate

**DNEL - Workers - Long term - Dermal** 

1.7 mg/kg bw/day Effects: Systemic

**DNEL - Workers - Long term - Inhalation** 

2.35 mg/m³ Effects: Systemic

2-hydroxy-2-methylpropiophenone

DNEL - General population - Long term - Oral

0.4 mg/kg bw/day Effects: Systemic

**DNEL - General population - Long term - Dermal** 

0.5 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Long term - Inhalation

0.9 mg/m³ Effects: Systemic

**DNEL - Workers - Long term - Dermal** 

1 mg/kg bw/day Effects: Systemic

**DNEL - Workers - Long term - Inhalation** 

3.5 mg/m³

Effects: Systemic

Propylidynetrimethanol, ethoxylated, esters with acrylic acid

DNEL - Workers - Long term - Dermal

10.5 mg/kg bw/day Effects: Systemic

**DNEL - Workers - Long term - Inhalation** 

37 mg/m<sup>3</sup>

Effects: Systemic

Dipropylenglycol diacrylate DNEL - Workers - Long term - Dermal

1.7 mg/kg bw/day <u>Effects</u>: Systemic

**DNEL - Workers - Long term - Inhalation** 

Label No : 1/37184

2.35 mg/m³ Effects: Systemic

Date of issue/Date of revision : 03/12/2025 Date of previous issue : 15/11/2023 Version : 2 7/22

Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-

**DNEL - Workers - Long term - Inhalation** 

21 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Short term - Inhalation** 

21 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Long term - Dermal** 

3.3 mg/kg

Effects: Systemic

**DNEL - Workers - Short term - Dermal** 

3.3 mg/kg

Effects: Systemic

DNEL - General population - Consumers - Long term -

Inhalation

5.2 mg/m<sup>3</sup>

Effects: Systemic

DNEL - General population - Consumers - Long term -

**Dermal** 

1.5 mg/kg

Effects: Systemic

DNEL - General population - Consumers - Long term - Oral

1.5 mg/kg

Effects: Systemic

DNEL - General population - Short term - Oral

1.67 ng/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Oral

1.5 mg/kg bw/day

Effects: Systemic

**DNEL - General population - Long term - Dermal** 

1.5 mg/kg bw/day

Effects: Systemic

**DNEL - General population - Short term - Dermal** 

1.67 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Inhalation

1.93 mg/m<sup>3</sup>

Effects: Systemic

DNEL - General population - Long term - Inhalation

1.93 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Long term - Dermal** 

3 mg/kg bw/day

Effects: Systemic

**DNEL - Workers - Short term - Dermal** 

3.33 mg/kg bw/day

Effects: Systemic

**DNEL - Workers - Short term - Inhalation** 

Label No : 1/37184

7.84 mg/m<sup>3</sup>

Effects: Systemic

Date of issue/Date of revision : 03/12/2025 Date of previous issue : 15/11/2023 Version : 2 8/22

**DNEL - Workers - Long term - Inhalation** 

7.84 mg/m<sup>3</sup> Effects: Systemic

4-methylbenzophenone

DNEL - General population - Long term - Oral

0.05 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Dermal

0.05 mg/kg bw/day Effects: Systemic

**DNEL - Workers - Long term - Dermal** 

0.1 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Inhalation

0.17 mg/m<sup>3</sup> Effects: Systemic

**DNEL - Workers - Long term - Inhalation** 

0.7 ma/m<sup>3</sup>

Effects: Systemic

#### **PNECs**

Not available.

#### 8.2 Exposure controls

**Appropriate engineering** controls

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

### Individual protection measures

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### **Eye/face protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

### **Skin protection**

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations: Wear suitable gloves tested to EN374.

< 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm

1 - 4 hours (breakthrough time): 4H / Silver Shield® gloves.

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Version : 2 Date of issue/Date of revision · 15/11/2023 9/22 : 03/12/2025 Date of previous issue Label No : 1/37184

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type:

A P Filter type (spray application):

**Environmental exposure** controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

### **Appearance**

**Physical state** : Liquid. Colour Blue. Odour Slight

**Odour threshold** : Not available. : Not available. Melting point/freezing point

Initial boiling point and

boiling range

Ingredient name	°C	°F	Method
methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate	>120	>248	
Phosphine oxide, phenylbis(2,4,6-trimethylbenzoyl)-	>168	>334.4	EU A.2

**Flammability** : Not available.

Lower and upper explosion

limit

: Lower: Not applicable. Upper: Not applicable.

: Closed cup: >100°C (>212°F) Flash point

**Auto-ignition temperature** 

Ingredient name	°C	°F	Method
Phosphine oxide, phenylbis(2,4,6-trimethylbenzoyl)-	>131.4	>268.5	EU A.16
Dipropylenglycol diacrylate	240	464	DIN 51794

**Decomposition temperature** : Not available. pН : Not applicable. **Viscosity** Not available.

Solubility(ies)

Not available.

Solubility in water : Not available. Partition coefficient: n-octanol/ : Not applicable.

water

Vapour pressure

Date of issue/Date of revision : 15/11/2023 Version : 2 10/22 : 03/12/2025 Date of previous issue Label No : 1/37184

### SECTION 9: Physical and chemical properties

	Vapour Pressure at 20°C			Vapour Pressure at 20°C Vapour pressure at 50		re at 50°C
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
o-1,7,7-trimethylbicyclo[2.2.1] hept-2-yl methacrylate	0.009	0.0012	EU A.4			
2-hydroxy-2-methylpropiophenone	0.00428	0.00057	OECD 104	0.09751	0.013	OECD 104

Relative density : Not available. : 1.3 g/cm<sup>3</sup> **Density** : Not available. Vapour density

**Particle characteristics** 

Median particle size : Not applicable.

### 9.2 Other information

9.2.1 Information with regard to physical hazard classes

**Explosive properties** : Not available. **Oxidising properties** : Not available.

9.2.2 Other safety characteristics

Not applicable.

### SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

: 03/12/2025

#### **Acute toxicity**

Product/ingredient name

exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl

acrylate

Rat - Oral - LD50

4890 mg/kg

Toxic effects: Behavioral - Tremor Lung, Thorax, or

Respiration - Dyspnea Other - Hair

Rabbit - Dermal - LD50

>5 g/kg

Result

2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide

Rat - Oral - LD50 >2000 mg/kg

Rabbit - Dermal - LD50

>2000 mg/kg

(1-methyl-1,2-ethanediyl)bis[oxy(methyl-

2,1-ethanediyl)] diacrylate

Rat - Oral - LD50

6200 mg/kg

Toxic effects: Eye - Ptosis Lung, Thorax, or Respiration -

Version : 2

11/22

: 15/11/2023

Respiratory depression Other - Hair

Date of issue/Date of revision Date of previous issue UVILUX PRIMER 1754-11 - DUSTIE BLUE TS 21105 Label No : 1/37184

2-hydroxy-2-methylpropiophenone Rat - Oral - LD50

1694 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed

activity) Behavioral - Tremor Liver - Other changes

Rat - Dermal - LD50

6929 mg/kg

Propylidynetrimethanol, ethoxylated, esters

with acrylic acid

Rabbit - Dermal - LD50

>13 g/kg

Rat - Oral - LD50 Dipropylenglycol diacrylate

4600 mg/kg

<u>Toxic effects</u>: Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Gastrointestinal - Hypermotility,

diarrhea

Rat - Oral - LD50 Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-

>2000 mg/kg

**OECD** [Acute Oral Toxicity]

copper bis(dimethyldithiocarbamate) Rat - Oral - LD50

>5000 mg/kg

Rabbit - Dermal - LD50

>2000 mg/kg

Rat - Inhalation - LC50 Dusts and mists

0.12 mg/l [4 hours]

**Conclusion/Summary [Product]**: Mot available.

### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
VILUX PRIMER 1754-11	62669.3	N/A	N/A	N/A	N/A
exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate	4890	N/A	N/A	N/A	N/A
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-	6200	N/A	N/A	N/A	N/A
2,1-ethanediyl)] diacrylate					
2-hydroxy-2-methylpropiophenone	1694	6929	N/A	N/A	N/A
Dipropylenglycol diacrylate	4600	N/A	N/A	N/A	N/A
copper bis(dimethyldithiocarbamate)	N/A	N/A	N/A	N/A	0.12

### **Skin corrosion/irritation**

Product/ingredient name

exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate

(1-methyl-1,2-ethanediyl)bis[oxy(methyl-

2,1-ethanediyl)] diacrylate

Propylidynetrimethanol, ethoxylated, esters

with acrylic acid

Dipropylenglycol diacrylate

Result

Rabbit - Skin - Moderate irritant Amount/concentration applied: 500 uL

Rabbit - Skin - Moderate irritant Amount/concentration applied: 500 mg

Rabbit - Skin - Moderate irritant Amount/concentration applied: 500 mg

Rabbit - Skin - Severe irritant

Amount/concentration applied: 500 mg

**Conclusion/Summary [Product]**: Not available.

Date of issue/Date of revision · 15/11/2023 Version : 2 12/22 : 03/12/2025 Date of previous issue Label No : 1/37184

Serious eye damage/eye irritation

Product/ingredient name

xo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl

acrylate

(1-methyl-1,2-ethanediyl)bis[oxy(methyl-

2,1-ethanediyl)] diacrylate

Propylidynetrimethanol, ethoxylated, esters

with acrylic acid

Dipropylenglycol diacrylate

Result

Rabbit - Eyes - Mild irritant

Amount/concentration applied: 100 uL

Rabbit - Eyes - Severe irritant

Duration of treatment/exposure: 24 hours Amount/concentration applied: 100 uL

Rabbit - Eyes - Moderate irritant

Amount/concentration applied: 100 mg

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 100 mg

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Not available.

**Conclusion/Summary [Product]**: Not available.

Respiratory or skin sensitization

Product/ingredient name

Phosphine oxide, phenylbis

(2,4,6-trimethylbenzoyl)-

Result

Guinea pig - skin

OECD [Skin Sensitization]

Result: Sensitising

Skin

**Conclusion/Summary [Product]**: Not available.

Respiratory

**Conclusion/Summary [Product]**: Not available.

Germ cell mutagenicity

Product/ingredient name Phosphine oxide, phenylbis

(2,4,6-trimethylbenzoyl)-

Result

**Bacteria** 

Result: Negative

Conclusion/Summary [Product] : Not available.

**Carcinogenicity** 

Not available.

**Conclusion/Summary [Product]**: Not available.

Ingredient name

Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-

**Conclusion/Summary** 

No results available.

Label No : 1/37184

Reproductive toxicity

Not available.

**Conclusion/Summary [Product]**: Not available.

Specific target organ toxicity (single exposure)

Date of issue/Date of revision : 03/12/2025 Date of previous issue · 15/11/2023 Version : 2 13/22

Product/ingredient name

exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl STOT SE 3, H335 (Respiratory tract irritation)

acrylate

(1-methyl-1,2-ethanediyl)bis[oxy(methyl-STOT SE 3, H335 (Respiratory tract irritation)

2,1-ethanediyl)] diacrylate

### Specific target organ toxicity (repeated exposure)

Product/ingredient name Result

4-methylbenzophenone STOT RE 2, H373 (oral)

### **Aspiration hazard**

Not available.

### Information on likely routes of exposure

Not available.

### Potential acute health effects

**Eye contact** : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

**Skin contact** : Causes skin irritation. May cause an allergic skin reaction.

: No known significant effects or critical hazards. Ingestion Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

> pain watering redness

Inhalation : No specific data.

: Adverse symptoms may include the following: **Skin contact** 

pain or irritation

redness

blistering may occur

Ingestion Adverse symptoms may include the following:

stomach pains

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

**Potential immediate** : Not available.

effects

: Not available. Potential delayed effects

Potential chronic health effects

Not available.

**Conclusion/Summary [Product]** : Not available.

**General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards. : No known significant effects or critical hazards. Mutagenicity : No known significant effects or critical hazards. Reproductive toxicity

### 11.2 Information on other hazards

### 11.2.1 Endocrine disrupting properties

Not available.

Date of issue/Date of revision · 15/11/2023 Version : 2 14/22 : 03/12/2025 Date of previous issue Label No : 1/37184

Conclusion/Summary [Product]

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

### 11.2.2 Other information

Not available.

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

### Product/ingredient name

Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide

# Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-

#### Result

#### LC50 - Fresh water

OECD [Fish, Acute Toxicity Test] Fish - Cyprinus carpio >100 mg/l [96 hours]

#### **EC50**

Daphnia - Daphnia - Daphnia magna >100 mg/l [48 hours]

#### Acute - LC50

OECD [Fish, Acute Toxicity Test] Fish - *Brachydanio rerio* >0.09 mg/l [96 hours]

#### Acute - EC50

Daphnia sp. Acute Immobilization Test and Reproduction Test Daphnia - *Daphnia magna* >1.175 mg/l [48 hours]

#### **EC50**

Alga, Growth Inhibition Test Aquatic plants - *Desmodesmus subspicatus* ≥0.26 mg/l [72 hours]

#### NOEC - Fresh water

OECD [Daphnia Magna Reproduction Test] Daphnia - *Daphnia magna* ≥0.008 mg/l [21 days]

#### copper bis(dimethyldithiocarbamate)

### Acute - LC50 - Fresh water

Fish - Fathead minnow - Pimephales promelas

Size: 38 to 64 mm; Weight: 1 to 2 g

71 µg/l [96 hours] Effect: Mortality

### **Conclusion/Summary [Product]**: Not available.

### 12.2 Persistence and degradability

Not available.

### **Conclusion/Summary [Product]**: Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
<b>2</b> -Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide	-	71%; 28 day(s)	Readily
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	-	-	Readily
Phosphine oxide, phenylbis	-	-	Not readily

 Date of issue/Date of revision
 : 03/12/2025
 Date of previous issue
 : 15/11/2023
 Version
 : 2
 15/22

 UVILUX PRIMER 1754-11 - DUSTIE BLUE TS 21105
 Label No : ₹37184

(2,4,6-trimethylbenzoyl)-

### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
xo-1,7,7-trimethylbicyclo	5.09	-	High
[2.2.1]hept-2-yl methacrylate (1-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)] diacrylate	2	-	Low
2-hydroxy- 2-methylpropiophenone	1.62	-	Low
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	2.89	-	Low
Dipropylenglycol diacrylate Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	0.01 to 0.39 5.77	- <5	Low Low

### 12.4 Mobility in soil

### Soil/water partition coefficient

Product/ingredient name	logKoc	Koc
xo-1,7,7-trimethylbicyclo[2.2.1]hept-	3.2	1501.87
2-yl methacrylate		
exo-1,7,7-trimethylbicyclo[2.2.1]hept-	3.2	1609.94
2-yl acrylate		
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-	2.9	803.136
2,1-ethanediyl)] diacrylate		
2-hydroxy-2-methylpropiophenone	1.9	80.7076
Phosphine oxide, phenylbis	5	108908
(2,4,6-trimethylbenzoyl)-		
4-methylbenzophenone	2.8	649.71
copper bis(dimethyldithiocarbamate)	1.8	59.2181

### Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	νP	νM
xo-1,7,7-trimethylbicyclo [2.2.1]hept-2-yl methacrylate	No	No	No	No	No	No	No
exo-1,7,7-trimethylbicyclo [2.2.1]hept-2-yl acrylate	No	No	No	No	No	No	No
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide	No	No	No	No	No	No	No
(1-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)] diacrylate	No	No	No	No	No	No	No
2-hydroxy- 2-methylpropiophenone	No	No	No	No	No	No	No
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	No	No	No	No	No	No	No
Dipropylenglycol diacrylate	No	No	No	No	No	No	No
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	No	No	No	No	No	No	No
Acrylated resin	No	No	No	No	No	No	No
4-methylbenzophenone	No	No	No	No	No	No	No
copper bis (dimethyldithiocarbamate)	No	No	No	No	No	No	No

Mobility

: Not available.

**Conclusion/Summary** 

: The product does not meet the criteria to be considered as a PMT or vPvM.

 Date of issue/Date of revision
 : 03/12/2025
 Date of previous issue
 : 15/11/2023
 Version
 : 2
 16/22

 UVILUX PRIMER 1754-11 - DUSTIE BLUE TS 21105
 Label No : \$\frac{1}{3}\$7184

# 12.5 Results of PBT and vPvB assessment Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	В	T	vPvB	vP	vB
xo-1,7,7-trimethylbicyclo [2.2.1]hept-2-yl methacrylate	No	N/A	N/A	No	N/A	N/A	N/A
exo-1,7,7-trimethylbicyclo	No	N/A	N/A	No	N/A	N/A	N/A
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide	No	N/A	N/A	No	N/A	N/A	N/A
(1-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)] diacrylate	No	N/A	N/A	No	N/A	N/A	N/A
2-hydroxy- 2-methylpropiophenone	No	N/A	N/A	No	N/A	N/A	N/A
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	No	N/A	N/A	No	N/A	N/A	N/A
Dipropylenglycol diacrylate	No	N/A	N/A	No	N/A	N/A	N/A
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	No	N/A	No	Yes	No	N/A	No
Acrylated resin	No	N/A	N/A	No	N/A	N/A	N/A
4-methylbenzophenone	N/A	N/A	N/A	Yes	N/A	N/A	N/A
copper bis (dimethyldithiocarbamate)	No	N/A	N/A	No	N/A	N/A	N/A

### **Regulation (EC) No. 1272/2008 [CLP]**

Product/ingredient name	PBT	P	В	Т	vPvB	vP	vB
xo-1,7,7-trimethylbicyclo [2.2.1]hept-2-yl methacrylate	No	No	No	No	No	No	No
exo-1,7,7-trimethylbicyclo [2.2.1]hept-2-yl acrylate	No	No	No	No	No	No	No
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide	No	No	No	No	No	No	No
(1-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)] diacrylate	No	No	No	No	No	No	No
2-hydroxy- 2-methylpropiophenone	No	No	No	No	No	No	No
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	No	No	No	No	No	No	No
Dipropylenglycol diacrylate	No	No	No	No	No	No	No
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	No	No	No	No	No	No	No
Acrylated resin	No	No	No	No	No	No	No
4-methylbenzophenone	No	No	No	No	No	No	No
copper bis (dimethyldithiocarbamate)	No	No	No	No	No	No	No

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP] : The product does not meet the criteria to be considered as a PBT or vPvB.

### 12.6 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** 

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

 Date of issue/Date of revision
 : 03/12/2025
 Date of previous issue
 : 15/11/2023
 Version
 : 2
 17/22

 UVILUX PRIMER 1754-11 - DUSTIE BLUE TS 21105
 Label No : ₹37184

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

### **Product**

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** 

**European waste** catalogue (EWC)

Yes. : 080111\*

**Packaging** 

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** 

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

### **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN3082	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)			
14.3 Transport hazard class(es)	9	9	9	9
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes.

#### **Additional information**

ADR/RID

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

Tunnel code (-)

**ADN** 

This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

**IMDG** 

This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

Version : 2 Date of issue/Date of revision : 03/12/2025 Date of previous issue · 15/11/2023 18/22 Label No : 1/37184

### SECTION 14: Transport information

**IATA** 

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not relevant/applicable due to nature of the product.

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed.

### Substances of very high concern

None of the components are listed.

### Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
UVILUX PRIMER 1754-11	≥90	3

Labelling

Other EU regulations

**Industrial emissions** : Not listed

(integrated pollution prevention and control) -

Air

**Industrial emissions** : Not listed

(integrated pollution prevention and control) -

Water

: Not applicable. **Explosive precursors** Ozone depleting substances (EU 2024/590)

Prior Informed Consent (PIC) (649/2012/EU)

Not listed

**Persistent Organic Pollutants** 

Not listed.

### **Seveso Directive**

This product is controlled under the Seveso Directive.

### **Danger criteria**

Category

**E**2

### International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

### **Montreal Protocol**

Date of issue/Date of revision · 15/11/2023 Version · 2 19/22 : 03/12/2025 Date of previous issue UVILUX PRIMER 1754-11 - DUSTIE BLUE TS 21105 Label No : 1/37184

### **SECTION 15: Regulatory information**

Not listed.

### **Stockholm Convention on Persistent Organic Pollutants**

Not listed.

### **Rotterdam Convention on Prior Informed Consent (PIC)**

Not listed.

### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

15.2 Chemical safety

assessment

acronyms

: This product contains substances for which Chemical Safety Assessments are still

required.

### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

**Abbreviations and** 

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification	
Skin Irrit. 2, H315	Calculation method	
Eye Dam. 1, H318	Calculation method	
Skin Sens. 1, H317	Calculation method	
Aquatic Chronic 2, H411	Calculation method	

### Full text of abbreviated H statements

<b>⊮</b> 302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

#### Full text of classifications [CLP/GHS]

ACUTE TOXICITY - Category 2
ACUTE TOXICITY - Category 4
SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4
SERIOUS EYÈ DAMAGE/EYE IRRITATION - Category 1
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
SKIN CORROSION/IRRITATION - Category 2
SKIN SENSITISATION - Category 1

Date of issue/Date of revision : 15/11/2023 Version : 2 20/22 : 03/12/2025 Date of previous issue Label No : 1/37184

### SECTION 16: Other information

SKIN SENSITISATION - Category 1A Skin Sens. 1A SKIN SENSITISATION - Category 1B Skin Sens. 1B

STOT RE 2 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 STOT SE 3 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of issue/ Date of

Date of previous issue

revision

: 03/12/2025 : 15/11/2023

**Version** : 2

#### **Notice to reader**

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision : 03/12/2025 Date of previous issue : 15/11/2023 Version :2 21/22 Label No : 1/37184

Date of issue/Date of revision : 03/12/2025 Date of previous issue : 15/11/2023 Version : 2 22/22 **Label No** : 1/37184