Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

SAFETY DATA SHEET



UVILUX PRIMER 1754-11 - TS 21417 NCS S0502-Y

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier Product name

: UVILUX PRIMER 1754-11 - TS 21417 NCS S0502-Y

1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use: Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091. e-mail address of person : Prod-safe@teknos.com responsible for this SDS

National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number: In an emergency, call 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word	: Danger
Hazard statements	 H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H318 - Causes serious eye damage. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements	
Prevention	 P280 - Wear protective gloves. Wear eye or face protection. P273 - Avoid release to the environment. P261 - Avoid breathing vapour.
Response	: P305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Date of issue/Date of revision	: 20/02/2024	Date of previous issue	: No previous validation	Version	:1	1/19
UVILUX PRIMER 1754-11 - TS 21	417 NCS S0	502-Y		Label No	:77580	C

SECTION 2: Hazards identification

SECTION 2. Hazarus	IC	ientification
Storage	1	Not applicable.
Disposal	1	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	:	Contains: Dipropylenglycol diacrylate; 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid; Hexanedioic acid, polymer with (chloromethyl)oxirane, 2-ethyl-2-(hydroxymethyl) -1,3-propanediol, 4,4'-(1-methylethylidene)bis[phenol] and oxirane, 2-propenoate and Phosphine oxide, phenylbis(2,4,6-trimethylbenzoyl)-
Supplemental label elements	1	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	
2.3 Other hazards Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do : None known. not result in classification

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥25 - ≤50	Carc. 2, H351 (inhalation)	-	[1] [*]
Dipropylenglycol diacrylate	REACH #: 01-2119484629-21 EC: 260-754-3 CAS: 57472-68-1	≥10 - ≤25	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317	-	[1]
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane, esters with acrylic acid	REACH #: 01-2119490020-53 EC: 500-130-2 CAS: 55818-57-0	≥10 - <25	Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
Hexanedioic acid, polymer with (chloromethyl)oxirane, 2-ethyl-2-(hydroxymethyl) -1,3-propanediol, 4,4'- (1-methylethylidene)bis [phenol] and oxirane, 2-propenoate	CAS: 184181-05-3	≤10	Skin Sens. 1, H317	-	[1]
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	REACH #: 01-2119489401-38 EC: 423-340-5 CAS: 162881-26-7 Index: 015-189-00-5	<1	Skin Sens. 1A, H317 Aquatic Chronic 4, H413	-	[1]
Propylidynetrimethanol,	REACH #:	<1	Eye Irrit. 2, H319	-	[1]

SECTION 3: Comp	osition/informat	tion on	ingredients		
ethoxylated, esters with acrylic acid	01-2119489900-30 EC: 500-066-5 CAS: 28961-43-5		Skin Sens. 1, H317 Aquatic Chronic 3, H412		
propylidynetrimethanol	REACH #: 01-2119486799-10 EC: 201-074-9 CAS: 77-99-6	≤0.3	Repr. 2, H361fd	-	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter \leq 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures : Get medical attention immediately. Call a poison center or physician. Immediately Eye contact flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Inhalation : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Skin contact : Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse. : Get medical attention immediately. Call a poison center or physician. Wash out Ingestion mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. **Protection of first-aiders** No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed <u>Over-exposure signs/symptoms</u>

SECTION 4: First aid measures Eye contact : Adverse symptoms may include the following: pain watering redness Inhalation : No specific data. **Skin contact** : Adverse symptoms may include the following: pain or irritation redness blistering may occur Ingestion : Adverse symptoms may include the following: stomach pains 4.3 Indication of any immediate medical attention and special treatment needed Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. **Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	Use an extinguishing agent suitable for the surrounding fire.	
Unsuitable extinguishing media	None known.	
5.2 Special hazards arising	n the substance or mixture	
Hazards from the substance or mixture	In a fire or if heated, a pressure increase will occur and the container may burs. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.	st.
Hazardous combustion products	Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides	
5.3 Advice for firefighters		
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incid there is a fire. No action shall be taken involving any personal risk or without suitable training.	dent if
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves conforming to European standard EN 469 will provide a basic level of protection chemical incidents.	re s)

SECTION 6: Accidental release measures

6.1 Personal precautions, prote	ctive equipment and emergency procedures
For non-emergency : personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders :	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

SECTION 6: Accidental release measures

6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and materia	I for containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)		
Recommendations	:	Not available.
Industrial sector specific	:	Not available.
solutions		

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
No exposure limit value known.	
No exposure limit value known.	
propylidynetrimethanol	Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 6/2021). Limit value 8 hours: 50 mg/m ³ 8 hours.
No exposure limit value known.	
propylidynetrimethanol	Lithuanian Hygiene Standard HN 23 (Lithuania, 7/2022). CEIL: 5 ppm
No exposure limit value known.	
propylidynetrimethanol	Work environment authority Regulation 2018:1 (Sweden, 9/2021). TWA: 5 mg/m ³ 8 hours.
No exposure limit value known.	
No exposure limit value known.	

Biological exposure indices

Product/ingredient name	Exposure indices
No exposure indices known.	
procedures Europ asses value atmo of ex	rence should be made to monitoring standards, such as the following: bean Standard EN 689 (Workplace atmospheres - Guidance for the ssment of exposure by inhalation to chemical agents for comparison with limi s and measurement strategy) European Standard EN 14042 (Workplace spheres - Guide for the application and use of procedures for the assessmer posure to chemical and biological agents) European Standard EN 482 kplace atmospheres - General requirements for the performance of procedur

DNELs/DMELs

required.

for the measurement of chemical agents) Reference to national guidance

documents for methods for the determination of hazardous substances will also be

Product/ingredient name	Туре	Exposure	Value	Population	Effects
Dipropylenglycol diacrylate	DNEL	Long term Dermal	1.66 mg/	General	Systemic
		5	kg bw/day	population	,
	DNEL	Long term Oral	2.08 mg/	General	Systemic
			kg bw/day	population	-
	DNEL	Long term Dermal	2.77 mg/	Workers	Systemic
		_	kg bw/day		-
	DNEL	Long term	7.24 mg/m ³	General	Systemic
		Inhalation		population	
	DNEL	Long term	24.48 mg/	Workers	Systemic
		Inhalation	m³		
1,4'-Isopropylidenediphenol,	DNEL	Long term	1.17 mg/m ³	Workers	Systemic
oligomeric reaction products with		Inhalation			
I-chloro-2,3-epoxypropane, esters					
vith acrylic acid					
	DNEL	Long term Dermal	33 mg/kg	Workers	Systemic
			bw/day		
Phosphine oxide, phenylbis	DNEL	Long term	21 mg/m³	Workers	Systemic
2,4,6-trimethylbenzoyl)-		Inhalation	04	\ \ /	O un tra maile
	DNEL	Short term	21 mg/m³	Workers	Systemic
		Inhalation	2.2 mg/kg	W/orkoro	Sustamia
	DNEL	Long term Dermal	3.3 mg/kg	Workers	Systemic
	DNEL	Short term Dermal	3.3 mg/kg	Workers	Systemic
	DNEL	Long term	5.2 mg/m ³	General	Systemic
		Inhalation		population	
	DNEL	Long torm Dormal	1.5 mg/kg	[Consumers]	Svotomio
	DNEL	Long term Dermal	1.5 mg/kg	General	Systemic
				population	
	DNEL	Long torm Oral	1.5 mg/kg	[Consumers] General	Svotomio
	DNEL	Long term Oral	1.5 mg/kg	population	Systemic
				[Consumers]	
	DNEL	Short term Oral	1.67 ng/kg	General	Systemic
	DNEL	Short term Oral	bw/day	population	Systemic
	DNEL	Long term Oral	1.5 mg/kg	General	Systemic
	DINCL	Long term Oral	bw/day	population	Oysternic
	DNEL	Long term Dermal	1.5 mg/kg	General	Systemic
	DIVLL	Long term Derma	bw/day	population	Oysternie
	DNEL	Short term Dermal	1.67 mg/	General	Systemic
			kg bw/day	population	-)
	DNEL	Short term	1.93 mg/m ³	General	Systemic
		Inhalation	J	population	,
	DNEL	Long term	1.93 mg/m ³	General	Systemic
		Inhalation	Ū.	population	
	DNEL	Long term Dermal	3 mg/kg	Workers	Systemic
		_	bw/day		-
	DNEL	Short term Dermal	3.33 mg/	Workers	Systemic
			kg bw/day		
	DNEL	Short term	7.84 mg/m ³	Workers	Systemic
		Inhalation			
	DNEL	Long term	7.84 mg/m ³	Workers	Systemic
		Inhalation			
Propylidynetrimethanol, ethoxylated,	DNEL	Long term Dermal	10.5 mg/	Workers	Systemic
esters with acrylic acid			kg bw/day		
	DNEL	Long term	37 mg/m³	Workers	Systemic
		Inhalation	0.04		
propylidynetrimethanol	DNEL	Long term Oral	0.34 mg/	General	Systemic
		Long torm Damas	kg bw/day	population	Sustamia
	DNEL	Long term Dermal	0.34 mg/	General	Systemic
		Long torm	kg bw/day	population	Sustamia
	DNEL	Long term	0.58 mg/m ³	General	Systemic
		Inhalation	0.04 mal	population Workers	Suctomia
	DNEL	Long term Dermal	0.94 mg/	Workers	Systemic
		Long torm	kg bw/day	Workers	Systemic
	DNEL	Long term	3.3 mg/m³	VVUIKEIS	Systemic

UVILUX PRIMER 1754-11 - TS 21417 NCS S0502-Y

Label No :77580

		Inhalation			
PNECs	Į				
No PNECs available					
2 Exposure controls					
Appropriate engineering	: If user op	erations generate du	st, fumes, gas, v	apour or mist, use	process
controls	enclosure	s, local exhaust vent to airborne contamir	ilation or other e	ngineering controls	to keep worker
Individual protection meas	<u>es</u>				
Hygiene measures	before ea Appropria Contamin contamina	nds, forearms and fa- ting, smoking and us te techniques should ated work clothing sl ated clothing before r are close to the work	ing the lavatory a l be used to rem nould not be allo eusing. Ensure	and at the end of th ove potentially cont wed out of the work	e working period aminated clothing place. Wash
Eye/face protection	assessme gases or o unless the	ewear complying with ent indicates this is n dusts. If contact is p e assessment indicat nd/or face shield. If nstead.	ecessary to avoi ossible, the follo es a higher degr	d exposure to liquid wing protection sho ree of protection: c	l splashes, mists ould be worn, hemical splash
Skin protection					
Hand protection	be worn a this is neo check dur should be different f	resistant, impervious t all times when han essary. Considering ing use that the glov noted that the time to or different glove ma ubstances, the protect.	dling chemical p the parameters es are still retain to breakthrough nufacturers. In t	roducts if a risk ass specified by the gl ing their protective for any glove mater he case of mixture	essment indicate ove manufacture properties. It ial may be s, consisting of
	Recomme	endations :Wear su	itable gloves tes	sted to EN374.	
	< 1 hour (breakthrough time):	Nitrile gloves	. thickness > 0.3 r	nm
	1 - 4 hour	s (breakthrough time	e): 4H / Silver S	Shield® gloves.	
Body protection	being per	protective equipment formed and the risks ndling this product.			
Other skin protection	selected b	te footwear and any based on the task be by a specialist before	ing performed a	nd the risks involve	
Respiratory protection	: Based on appropria	the hazard and pote te standard or certific y protection program	ntial for exposur cation. Respirate	e, select a respirato ors must be used a	ccording to a
	Filter type	: A			
	Filter type	(spray application):	AP		
Environmental exposure controls	ensure the In some c	s from ventilation or v ey comply with the re ases, fume scrubber t will be necessary to	equirements of e	nvironmental protect neering modification	ction legislation. ns to the process

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9/19

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Colour	: Off-white.

Date of issue/Date of revision	: 20/02/2024	Date of previous issue	: No previous validation	Version	:1
UVILUX PRIMER 1754-11 - TS	21417 NCS S0	502-Y		Label No	:77580

SECTION 9: Physical and chemical properties

Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	: Not available.
Flammability	: Not available.
Lower and upper explosion limit	: Lower: Not applicable. Upper: Not applicable.
Flash point	: Closed cup: >100°C (>212°F)

2

2

Auto-ignition temperature

Ingredient name	°C	°F	Method
Dipropylenglycol diacrylate	240	464	DIN 51794
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid	465	869	EU A.15

Decomposition temperature	4	Not available.
рН	:	Not available.
Viscosity	:	Not available.
Solubility(ies)	:	
Not available.		
Solubility in water	:	Not available.
Partition coefficient: n-octanol/ water	:	Not applicable.

Vapour pressure

	Var	Vapour Pressure at 20°C			Vapour pressure a		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
Dipropylenglycol diacrylate	0.00064	0.000085	OECD 104				
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid	0.00000075	0.0000001	OECD 104	0.00000075	0.0000001	OECD 104	
Relative density	: Not a	vailable.	•				
Density	: 1.9 g	/cm³					
apour density	: Not a	vailable.					
xplosive properties	: Not a	vailable.					
Dxidising properties	: Not a	vailable.					
article characteristics							
Median particle size	: Not a	applicable.					

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: No specific data.
Date of issue/Date of revision UVILUX PRIMER 1754-11 - TS	: 20/02/2024 Date of previous issue : No previous validation Version : 1 10/19 S 21417 NCS S0502-Y Label No :77580

SECTION 10: Stability and reactivity

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Dipropylenglycol diacrylate	LD50 Oral	Rat	4600 mg/kg	-
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	LD50 Oral	Rat	>2000 mg/kg	-
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	LD50 Dermal	Rabbit	>13 g/kg	-
propylidynetrimethanol	LD50 Oral	Rat	14000 mg/kg	-
Conclusion/Summary	: Based on available data, th	e classification crit	teria are not met.	•
Acute toxicity estimates				
	Deute			lue

Route	ATE value
Not available.	

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
titanium dioxide	Skin - Mild irritant	Human	-	72 hours 300	-
Dipropylenglycol diacrylate	Eyes - Severe irritant Skin - Severe irritant	Rabbit Rabbit	-	ug I 100 mg 500 mg	-
Propylidynetrimethanol, ethoxylated, esters with	Eyes - Moderate irritant	Rabbit	-	100 mg	-
acrylic acid	Chin Madavata initant	Dabbit		500 m r	
	Skin - Moderate irritant	Rabbit	-	500 mg	-

Conclusion/Summary

: Causes skin irritation.

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	skin	Guinea pig	Sensitising

Conclusion/Summary : May cause an allergic skin reaction.

Mutagenicity

Product/ingredient name	Test	Experiment	Result
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	-	Subject: Bacteria	Negative

Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

Conclusion/Summary	: Based on available data, the classification criteria are not met.	
Reproductive toxicity		
Conclusion/Summary	: Based on available data, the classification criteria are not met.	
Teratogenicity		
Conclusion/Summary	: Based on available data, the classification criteria are not met.	
Specific target organ toxicity	<u>r (single exposure)</u>	
Not available.		
Specific target organ toxicity (repeated exposure)		

Date of issue/Date of revision	: 20/02/2024	Date of previous issue
UVILUX PRIMER 1754-11 - TS 21	417 NCS S0	502-Y

SECTION 11: Toxicological information

Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure	:	Not available.
Potential acute health effects	<u>s</u>	
Eye contact	1	Causes serious eye damage.
Inhalation	1	No known significant effects or critical hazards.
Skin contact	1	Causes skin irritation. May cause an allergic skin reaction.
Ingestion	:	No known significant effects or critical hazards.
Symptoms related to the phy		cal, chemical and toxicological characteristics
Eye contact	1	Adverse symptoms may include the following:
		pain watering
		redness
Inhalation	:	No specific data.
Skin contact	1	Adverse symptoms may include the following:
		pain or irritation
		redness blistering may occur
Ingestion		Adverse symptoms may include the following:
		stomach pains
Delayed and immediate effect	<u>cts</u>	as well as chronic effects from short and long-term exposure
<u>Short term exposure</u>		
Potential immediate	1	Not available.
effects		
Potential delayed effects	÷	Not available.
Long term exposure		
Potential immediate effects	1	Not available.
Potential delayed effects	۰.	Not available.
Potential chronic health eff		
Not available.	201	
Conclusion/Summary	1	Not available.
General	1	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

- Mutagenicity : No known significant effects or critical hazards.
- **Reproductive toxicity** : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - <i>Daphnia pulex -</i> Neonate	48 hours
	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	EC50 ≥0.26 mg/l	Aquatic plants - <i>Desmodesmus subspicatus</i>	72 hours
	NOEC ≥0.008 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	21 days
	Acute EC50 >1.175 mg/l	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 >0.09 mg/l	Fish - Brachydanio rerio	96 hours
propylidynetrimethanol	Acute EC50 13000000 µg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 14400000 µg/l Marine water	Fish - Cyprinodon variegatus	96 hours

Conclusion/Summary

: Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)- Propylidynetrimethanol, ethoxylated, esters with acrylic acid	-	-	Not readily Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Dipropylenglycol diacrylate	0.01 to 0.39	-	Low
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-	1.6 to 3	-	Low
2,3-epoxypropane, esters with acrylic acid			
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	5.77	<5	Low
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	2.89	-	Low
propylidynetrimethanol	-0.47	<1	Low

12.4 Mobility in soil	
Soil/water partition coefficient (K _{oc})	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

Date of issu	<i>le/Date of revision</i>	: 20/02/2024	Date of previous issue
UVILUX F	PRIMER 1754-11 - TS 2	1417 NCS S0	502-Y

SECTION 13: Disposal considerations

13.1 Waste treatment method	ls
Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
European waste catalogue (EWC)	: 080111*
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

14.6 Special precautions for	:	Transport within user's premises: always transport in closed containers that are
user		upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in : Not relevant/applicable due to nature of the product. **bulk according to IMO instruments**

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorisation

<u>Annex XIV</u>

None of the components are listed.

Substances of very high concern

None of the components are listed.

<u>Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous</u> <u>substances, mixtures and articles</u>

Date of issue/Date of revision	: 20/02/2024	Date of previous issue
UVILUX PRIMER 1754-11 - TS 21	417 NCS S0	502-Y

: No previous validation

Version :1 14/19 Label No :77580

Product/ingredient name		%	Designation [Usage]	
UVILUX PRIMER 1754-11		≥90	3	
Labelling	:			
<u>ther EU regulations</u>				
Industrial emissions (integrated pollution prevention and control) - Air	: Not liste	ed		
Industrial emissions (integrated pollution prevention and control) - Water	: Not liste	ed		
Explosive precursors	: Not app	licable.		
Ozone depleting substanc	es (1005/20	<u>)09/EU)</u>		
Not listed.				
Prior Informed Consent (P Not listed.	<u>PIC) (649/20</u>	<u>12/EU)</u>		
Persistent Organic Polluta Not listed.	<u>ints</u>			
<u>Seveso Directive</u> This product is not controlled ational regulations Austria	d under the	Seveso Directi	ive.	
VbF class	: Not reg	ulated.		
Limitation of the use of organic solvents	: Permitt	ed.		
Czech Republic				
Storage code	: IV			
<u>Denmark</u>				
Danish fire class	: IV-1			
Executive Order No. 1795/	<u>2015</u>			
Ingredient name			Annex I Section A	Annex I Section B
titanium dioxide			Listed	-
MAL-code	: 00-5			
Protection based on MAL			ulations on work involving coded p the use of personal protective equ	
	coveral clothes shield r	ls/protective clo do not adequa nust be worn ir	st be worn for all work that may result othing must be worn when soiling is so ately protect skin against contact with t n work involving spattering if a full mas nded use of eye protection is not requi	o great that regular wor the product. A face sk is not required. In thi
	respirat		ons in which there is return spray, the and arm protectors/apron/coveralls/pr	

appropriate or as instructed.

SECTION 15: Regulatory information

Lonon io. Regula		'y mornation
		MAL-code: 00-5 Application: When using scraper or knife, brush, roller etc. for pre- and post- treatments in a spray booth where the operator is outside the spray zone and when working in similar new* facilities of the combined-cabin, spray-cabin and spray-boot type where the operator is working inside the spray zone. When spraying in new* booths and cabins with non-atomizing guns. During downtimes, cleaning and repa in closed facilities, spray booths or cabins, if there is a risk of contact with wet pain or organic solvents. During non-atomising spraying in existing* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. When using scraper or knife, brush, roller, etc, for pre- and post-treatments in cabins or booths of the existing* facility type, if the operator is inside the spray zone. When using scraper or knife, brush, roller, etc. for pre- and post-treatments outside a closed facility, spray booth or spray cabin.
		- Protective clothing must be worn.
		When spraying in existing* spray booths, if the operator is outside the spray zone.
		- Air-supplied full mask and protective clothing must be worn.
		During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabi or booth.
		- Air-supplied full mask, protective clothing and hood must be worn.
		Drying: Items for drying/drying ovens that are temporarily placed on such things a rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.
		Polishing: When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always k worn.
		Caution The regulations contain other stipulations in addition to the above.
		*See Regulations.
Restrictions on use	:	Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Wo
List of undesirable substances	-	Not listed
Carcinogenic waste	:	Waste containers must be labeled: Contains a substance or substances regulated by Danish working environment legislation on cancer risks.
<u>Finland</u>		
France Reinforced medical		Act of July 11, 1077 determining the list of activities which require minforced
Reinforced medical surveillance	÷	Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable
<u>Germany</u>		
Storage class (TRGS 510)	:	10
Hazardous incident ordina	anc	<u>e</u>
This product is not controlle	d u	nder the Germany Hazardous Incident Ordinance.
Hazard class for water	:	2
Technical instruction on air quality control	:	TA-Luft Number 5.2.5: 41.7%
AOX	:	The product contains organically bound halogens and can contribute to the AOX value in waste water.
Itoly		Value III Waste Water.
<u>Italy</u>		

41

SECTION 15: Regul	atory information
Netherlands	
Water Discharge Policy (ABM)	: A(2) Toxic for aquatic organisms, may have long-term hazardous effects in aquatic environment. Decontamination effort: A
<u>Norway</u>	
<u>Sweden</u>	
Switzerland	
VOC content	: Exempt.
International regulations	
Chemical Weapon Conver	ntion List Schedules I, II & III Chemicals
Not listed.	
Montreal Protocol	
Not listed.	
Stockholm Convention or	n Persistent Organic Pollutants
Not listed.	
Rotterdam Convention on	Prior Informed Consent (PIC)
Not listed.	
	on POPs and Heavy Metals
Not listed.	
15.2 Chemical safety assessment	: This product contains substances for which Chemical Safety Assessments are still required.
SECTION 16: Other	information

Indicates information that has changed from previously issued version.

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
-	1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H351	Suspected of causing cancer.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Full text of classifications [CLP/GHS]

Date of issue/Date of revision	: 20/02/2024	Date of previous issue	: No previous validation	
UVILUX PRIMER 1754-11 - TS 21	417 NCS S0	502-Y		La

Version :1 17/19 .abel No :77580

SECTION 16: Other information

Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2	
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3	
Aquatic Chronic 4	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4	
Carc. 2	CARCINOGENICITY - Category 2	
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1	
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2	
Repr. 2	REPRODUCTIVE TOXICITY - Category 2	
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2	
Skin Sens. 1	SKIN SENSITISATION - Category 1	
Skin Sens. 1A	SKIN SENSITISATION - Category 1A	
Date of issue/ Date of revision	: 20/02/2024	
Date of previous issue	e : No previous validation	
Version	: 1	
	UVILUX PRIMER 1754-11_TS 21417 NCS TS 21417 NCS S0502-Y S0502-Y	

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision: 20/02/2024Date of previous issueUVILUX PRIMER 1754-11 - TS 21417 NCS S0502-Y

: No previous validation