

SAFETY DATA SHEET



UVILUX SEALER 1453-02 - HY 0020 CLEAR

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : UVILUX SEALER 1453-02 - HY 0020 CLEAR

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS : Prod-safe@teknos.com

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : NHS: 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

☑ Skin Irrit. 2, H315
Eye Dam. 1, H318
Skin Sens. 1, H317
Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : ☑ H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H318 - Causes serious eye damage.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention : P280 - Wear protective gloves. Wear eye or face protection.
P273 - Avoid release to the environment.

Response : ☑ P391 - Collect spillage.
P305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER or doctor.

Storage : ☑ Not applicable.

SECTION 2: Hazards identification

Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	: Contains: 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid; Dipropylenglycol diacrylate; 2-Propenoic acid, 1,1'-[(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)]] ester, reaction products with diethylamine and Propylidynetrimethanol, ethoxylated, esters with acrylic acid
Supplemental label elements	:
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid	REACH #: 01-2119490020-53 EC: 500-130-2 CAS: 55818-57-0	≥25 - ≤50	Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
Dipropylenglycol diacrylate	REACH #: 01-2119484629-21 EC: 260-754-3 CAS: 57472-68-1	≥10 - ≤25	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317	-	[1]
Ethoxylated acrylated ester	-	≤10	Skin Irrit. 2, H315 Eye Irrit. 2, H319	-	[1]
2-Propenoic acid, 1,1'-[(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)]] ester, reaction products with diethylamine	REACH #: 01-2119961351-42 CAS: 111497-86-0	≤5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 2, H411	-	[1]
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	REACH #: 01-2119489900-30 EC: 500-066-5 CAS: 28961-43-5	≤5	Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412	-	[1]
2-hydroxy-2-methylpropiophenone	REACH #: 01-2119472306-39 EC: 231-272-0 CAS: 7473-98-5	≤3	Acute Tox. 4, H302 Aquatic Chronic 3, H412	ATE [Oral] = 1694 mg/kg	[1]
Fatty acids, C14-18 and C16-18-unsatd., maleated	REACH #: 01-2119976378-19 EC: 288-306-2 CAS: 85711-46-2	≤0.3	Skin Irrit. 2, H315 Skin Sens. 1, H317	-	[1]

Date of issue/Date of revision : 03/07/2026 Date of previous issue : 27/11/2025 Version : 3.01 2/20

UVILUX SEALER 1453-02 - HY 0020 CLEAR

Label No : 47098

SECTION 3: Composition/information on ingredients

2-Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	≤0.3	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	ATE [Oral] = 1200 mg/kg ATE [Inhalation (vapours)] = 3 mg/l	[1] [2]
Maleic anhydride	REACH #: 01-2119472428-31 EC: 203-571-6 CAS: 108-31-6 Index: 607-096-00-9	≤0.01	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1A, H317 STOT RE 1, H372 (respiratory system) (inhalation) EUH071	ATE [Oral] = 400 mg/kg Skin Sens. 1, H317: C ≥ 0.001%	[1] [2]

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

SECTION 4: First aid measures

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
halogenated compounds
metal oxide/oxides

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria

SECTION 7: Handling and storage

Category	Notification and MAPP threshold	Safety report threshold
E2	200 tonnes	500 tonnes

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
2-Butoxyethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin. STEL 15 minutes: 50 ppm. TWA 8 hours: 25 ppm. STEL 15 minutes: 246 mg/m ³ . TWA 8 hours: 123 mg/m ³ .
Maleic anhydride	EH40/2005 WELs (United Kingdom (UK), 1/2020) Inhalation sensitiser. STEL 15 minutes: 3 mg/m ³ . TWA 8 hours: 1 mg/m ³ .

Biological exposure indices

Product/ingredient name	Exposure indices
2-Butoxyethanol	EH40/2005 BMGVs (United Kingdom (UK), 1/2020) BGV: 240 mmol/mol creatinine, butoxyacetic acid [in urine]. Sampling time: post shift.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid

Dipropylglycol diacrylate

Result

DNEL - Workers - Long term - Inhalation

1.17 mg/m³
Effects: Systemic

DNEL - Workers - Long term - Dermal

33 mg/kg bw/day
Effects: Systemic

DNEL - Workers - Long term - Dermal

1.7 mg/kg bw/day
Effects: Systemic

DNEL - Workers - Long term - Inhalation

2.35 mg/m³

Date of issue/Date of revision : 03/07/2026 Date of previous issue : 27/11/2025

Version : 3.01 6/20

UVILUX SEALER 1453-02 - HY 0020 CLEAR

Label No : 47098

SECTION 8: Exposure controls/personal protection

Propylidynetrimethanol, ethoxylated, esters with acrylic acid	<u>Effects</u> : Systemic
	DNEL - Workers - Long term - Dermal 10.5 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Inhalation 37 mg/m ³ <u>Effects</u> : Systemic
2-hydroxy-2-methylpropiophenone	DNEL - General population - Long term - Oral 0.4 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Long term - Dermal 0.5 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Long term - Inhalation 0.9 mg/m ³ <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Dermal 1 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Inhalation 3.5 mg/m ³ <u>Effects</u> : Systemic
	DNEL - General population - Long term - Oral 1.5 mg/kg bw/day <u>Effects</u> : Systemic
Fatty acids, C14-18 and C16-18-unsatd., maleated	DNEL - General population - Long term - Dermal 1.5 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Dermal 3 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Long term - Oral 6.3 mg/kg bw/day <u>Effects</u> : Systemic
2-Butoxyethanol	DNEL - General population - Short term - Oral 26.7 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Long term - Inhalation 59 mg/m ³ <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Inhalation 98 mg/m ³ <u>Effects</u> : Systemic
	DNEL - General population - Short term - Inhalation 147 mg/m ³ <u>Effects</u> : Local
	DNEL - Workers - Short term - Inhalation 246 mg/m ³ <u>Effects</u> : Local

SECTION 8: Exposure controls/personal protection

Maleic anhydride

DNEL - General population - Short term - Inhalation

426 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Inhalation

1091 mg/m³

Effects: Systemic

DNEL - General population - Long term - Inhalation

0.05 mg/m³

Effects: Systemic

DNEL - General population - Long term - Oral

0.06 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

0.08 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

0.081 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

0.081 mg/m³

Effects: Systemic

DNEL - General population - Short term - Oral

0.1 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Dermal

0.1 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

0.1 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Short term - Dermal

0.2 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

0.2 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Short term - Inhalation

0.2 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

0.2 mg/m³

Effects: Systemic

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Date of issue/*Date of revision*

: 03/07/2026

Date of previous issue

: 27/11/2025

Version : 3.01 8/20

UVILUX SEALER 1453-02 - HY 0020 CLEAR

Label No : 47098

SECTION 8: Exposure controls/personal protection

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Recommendations : Wear suitable gloves tested to EN374.
< 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm
1 - 4 hours (breakthrough time): 4H / Silver Shield® gloves.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
- Filter type: A
Filter type (spray application): A P
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Clear.
- Odour** : Slight
- Odour threshold** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** :

SECTION 9: Physical and chemical properties

Ingredient name	°C	°F	Method
2-hydroxy-2-methylpropiophenone	252.1	485.8	OECD 104
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	>391	>735.8	OECD 103

- Flammability** : Not available.
Lower and upper explosion limit : Lower: Not applicable.
Upper: Not applicable.
Flash point : Closed cup: >100°C (>212°F)
Auto-ignition temperature :

Ingredient name	°C	°F	Method
Dipropylenglycol diacrylate	240	464	DIN 51794
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid	465	869	EU A.15

- Decomposition temperature** : Not available.
pH : Not applicable.
Viscosity : Not available.
Solubility(ies) :
Not available.
Solubility in water : Not available.
Partition coefficient: n-octanol/ water : Not applicable.
Vapour pressure :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
2-hydroxy-2-methylpropiophenone	0.00428	0.00057	OECD 104	0.09751	0.013	OECD 104
Dipropylenglycol diacrylate	0.00064	0.000085	OECD 104			

- Relative density** : Not available.
Density : 1.3 g/cm³
Vapour density : Not available.
Particle characteristics
Median particle size : Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

- Explosive properties** : Not available.
Oxidising properties : Not available.

9.2.2 Other safety characteristics

Not applicable.

SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability : The product is stable.
10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid : No specific data.

SECTION 10: Stability and reactivity

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name

Dipropylenglycol diacrylate

Result

Rat - Oral - LD50

4600 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Gastrointestinal - Hypermotility, diarrhea

Propylidynetrimethanol, ethoxylated, esters with acrylic acid

Rabbit - Dermal - LD50

>13 g/kg

2-hydroxy-2-methylpropiophenone

Rat - Oral - LD50

1694 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity) Behavioral - Tremor Liver - Other changes

Maleic anhydride

Rat - Oral - LD50

400 mg/kg

Rabbit - Dermal - LD50

2620 mg/kg

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
<input checked="" type="checkbox"/> UVILUX SEALER 1453-02	86419.9	N/A	N/A	1249.9	N/A
Dipropylenglycol diacrylate	4600	N/A	N/A	N/A	N/A
2-hydroxy-2-methylpropiophenone	1694	6929	N/A	N/A	N/A
2-Butoxyethanol	1200	N/A	N/A	3	N/A
Maleic anhydride	400	2620	N/A	N/A	N/A

Skin corrosion/irritation

Product/ingredient name

Dipropylenglycol diacrylate

Result

Rabbit - Skin - Severe irritant

Amount/concentration applied: 500 mg

Propylidynetrimethanol, ethoxylated, esters with acrylic acid

Rabbit - Skin - Moderate irritant

Amount/concentration applied: 500 mg

2-Butoxyethanol

Rabbit - Skin - Mild irritant

Amount/concentration applied: 500 mg

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Date of issue/Date of revision

: 03/07/2026

Date of previous issue

: 27/11/2025

Version : 3.01 11/20

UVILUX SEALER 1453-02 - HY 0020 CLEAR

Label No : 47098

SECTION 11: Toxicological information

Product/ingredient name

Dipropylenglycol diacrylate

Propylidynetrimethanol, ethoxylated, esters with acrylic acid

2-Butoxyethanol

Maleic anhydride

Result

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 100 mg

Rabbit - Eyes - Moderate irritant

Amount/concentration applied: 100 mg

Rabbit - Eyes - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 mg

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 100 mg

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 1 %

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name

Maleic anhydride

Result

STOT RE 1, H372 (respiratory system) (inhalation)

SECTION 11: Toxicological information

Aspiration hazard

Not available.

Information on likely routes of exposure

Not available.

Potential acute health effects

- Eye contact** : Causes serious eye damage.
Inhalation : No known significant effects or critical hazards.
Skin contact : Causes skin irritation. May cause an allergic skin reaction.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : Not available.
Potential delayed effects : Not available.

Long term exposure

- Potential immediate effects** : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

- General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
Mutagenicity : No known significant effects or critical hazards.
Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name

2-Butoxyethanol

Result

Acute - LC50 - Marine water

Fish - Inland silverside - *Menidia beryllina*

Size: 40 to 100 mm

1250000 µg/l [96 hours]

Effect: Mortality

Acute - LC50 - Marine water

Crustaceans - Common shrimp, sand shrimp - *Crangon crangon*

800000 µg/l [48 hours]

Effect: Mortality

Maleic anhydride

Acute - LC50 - Fresh water

Fish - Western mosquitofish - *Gambusia affinis* - Adult

230000 µg/l [96 hours]

Effect: Mortality

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Not available.

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid	1.6 to 3	-	Low
Dipropylenglycol diacrylate	0.01 to 0.39	-	Low
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	2.89	-	Low
2-hydroxy-2-methylpropiophenone	1.62	-	Low
2-Butoxyethanol	0.81	-	Low
Maleic anhydride	-2.78	-	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	Value
2-hydroxy-2-methylpropiophenone	logKoc: 1.9 Koc: 80.7076
2-Butoxyethanol	logKoc: 1.8 Koc: 67.3685
Maleic anhydride	logKoc: 1.1 Koc: 11.4841

Results of PMT and vPvM assessment

SECTION 12: Ecological information

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid	No	No	No	No	No	No	No
Dipropylenglycol diacrylate	No	No	No	No	No	No	No
Ethoxylated acrylated ester	No	No	No	No	No	No	No
2-Propenoic acid, 1,1'-[(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)]] ester, reaction products with diethylamine	No	No	No	No	No	No	No
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	No	No	No	No	No	No	No
2-hydroxy-2-methylpropiophenone	No	No	No	No	No	No	No
Fatty acids, C14-18 and C16-18-unsatd., maleated	No	No	No	No	No	No	No
2-Butoxyethanol	No	No	No	No	No	No	No
Maleic anhydride	No	No	No	No	No	No	No

Mobility : Not available.

Conclusion/Summary : The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid	No	N/A	N/A	No	N/A	N/A	N/A
Dipropylenglycol diacrylate	No	N/A	N/A	No	N/A	N/A	N/A
Ethoxylated acrylated ester	No	N/A	N/A	No	N/A	N/A	N/A
2-Propenoic acid, 1,1'-[(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)]] ester, reaction products with diethylamine	No	N/A	N/A	No	N/A	N/A	N/A
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	No	N/A	N/A	No	N/A	N/A	N/A
2-hydroxy-2-methylpropiophenone	No	N/A	N/A	No	N/A	N/A	N/A
Fatty acids, C14-18 and C16-18-unsatd., maleated	No	N/A	N/A	No	N/A	N/A	N/A
2-Butoxyethanol	No	N/A	N/A	No	N/A	N/A	N/A
Maleic anhydride	N/A	N/A	N/A	Yes	N/A	N/A	N/A

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid	No	No	No	No	No	No	No
Dipropylenglycol diacrylate	No	No	No	No	No	No	No
Ethoxylated acrylated ester	No	No	No	No	No	No	No
2-Propenoic acid, 1,1'-[(1-methyl-1,2-ethanediyl)bis	No	No	No	No	No	No	No

Date of issue/Date of revision : 03/07/2026 Date of previous issue : 27/11/2025 Version : 3.01 15/20

UVILUX SEALER 1453-02 - HY 0020 CLEAR

Label No : 47098

SECTION 12: Ecological information

[oxy(methyl-2,1-ethanediyl)] ester, reaction products with diethylamine	No	No	No	No	No	No	No
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	No	No	No	No	No	No	No
2-hydroxy-2-methylpropiophenone	No	No	No	No	No	No	No
Fatty acids, C14-18 and C16-18-unsatd., maleated	No	No	No	No	No	No	No
2-Butoxyethanol	No	No	No	No	No	No	No
Maleic anhydride	No	No	No	No	No	No	No

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP] : The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations. Avoid release to the environment. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue (EWC) : 080111*

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information





	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN3082	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)

Date of issue/Date of revision : 03/07/2026 **Date of previous issue** : 27/11/2025 **Version** : 3.01 16/20

UVILUX SEALER 1453-02 - HY 0020 CLEAR

Label No : 47098

SECTION 14: Transport information

14.3 Transport hazard class(es)	9 	9 	9 	9 
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes.

Additional information

ADR/RID	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. Tunnel code (-)
ADN	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IMDG	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IATA	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
<input checked="" type="checkbox"/> UVILUX SEALER 1453-02	≥90	3

Labelling :

Synthetic polymer microparticles - Designation 78

Generic identity of polymer(s) : 3902 - Polymers of propylene or of other olefins.

Total percentage of synthetic polymer microparticles : 0.29%

The synthetic polymer microparticles supplied is subject to conditions laid down by entry 78 of Annex XVII to Regulation (EC) No 1907/2006 of the European Parliament and of the Council.

SECTION 15: Regulatory information

Other EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Explosive precursors : Not applicable.

(EC) No 273/2004 on drug precursors

Not listed.

(EC) No 111/2005 Trade between the Union and third countries in drug precursors

Not listed.

Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category
E2

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic

Date of issue/Date of revision : 03/07/2026 **Date of previous issue** : 27/11/2025

Version : 3.01 18/20

UVILUX SEALER 1453-02 - HY 0020 CLEAR

Label No : 47098

SECTION 16: Other information

PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Calculation method Calculation method Calculation method Calculation method

Full text of abbreviated H statements

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Resp. Sens. 1	RESPIRATORY SENSITISATION - Category 1
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1

Date of issue/ Date of revision : 03/07/2026

Date of previous issue : 27/11/2025

Version : 3.01

UVILUX SEALER 1453-02_HY 0020 CLEAR HY 0020 CLEAR

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision : 03/07/2026 **Date of previous issue** : 27/11/2025 **Version** : 3.01 19/20

UVILUX SEALER 1453-02 - HY 0020 CLEAR

Label No : 47098

