Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Ireland

# **SAFETY DATA SHEET**



UVILUX SEALER 1453-02 - TS 20408 LIGHT BLUE

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

Product name : UVILUX SEALER 1453-02 - TS 20408 LIGHT BLUE

**1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use**: Paint.

#### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091. e-mail address of person : Prod-safe@teknos.com responsible for this SDS

#### **National contact**

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

#### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

Telephone number : National Poisons Information Centre: 01 809 2566

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

**Hazard pictograms** 



Signal word	langer	
Hazard statements	<sup>7</sup> 315 - Causes skin irritation. I317 - May cause an allergic skin reaction. I318 - Causes serious eye damage. I412 - Harmful to aquatic life with long lasting effects.	
Precautionary statements		
Prevention	280 - Wear protective gloves. Wear eye or face protection. 273 - Avoid release to the environment. 261 - Avoid breathing vapour.	
Response	305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water f ninutes. Remove contact lenses, if present and easy to do. Continue rin nmediately call a POISON CENTER or doctor.	

Date of issue/Date of revision	: 19/06/2023	Date of previous issue	: 13/12/2022	Version	:1.05	1/17
UVILUX SEALER 1453-02 - TS 2	0408 LIGHT E	BLUE		Label No	: <mark>#</mark> 6819	)

# **SECTION 2: Hazards identification**

Storage	1	Not applicable.
Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	-	Dipropylenglycol diacrylate 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane, esters with acrylic acid Propylidynetrimethanol, ethoxylated, esters with acrylic acid (1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate
Supplemental label elements	:	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do : None known. not result in classification

# **SECTION 3: Composition/information on ingredients**

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Dipropylenglycol diacrylate	REACH #: 01-2119484629-21 EC: 260-754-3 CAS: 57472-68-1	≥10 - ≤25	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317	-	[1]
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane, esters with acrylic acid	REACH #: 01-2119490020-53 EC: 500-130-2 CAS: 55818-57-0	≥10 - ≤20	Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥10 - ≤25	Carc. 2, H351 (inhalation)	-	[1] [*]
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	REACH #: 01-2119489900-30 EC: 500-066-5 CAS: 28961-43-5	≤10	Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412	-	[1]
Ethoxylated acrylated ester	-	≤10	Skin Irrit. 2, H315 Eye Irrit. 2, H319	-	[1]
(1-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)] diacrylate	REACH #: 01-2119484613-34 EC: 256-032-2 CAS: 42978-66-5 Index: 607-249-00-X	≤4	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 2, H411	STOT SE 3, H335: C ≥ 10%	[1]
2-Propenoic acid, 1,1'-[	REACH #:	≤5	Skin Irrit. 2, H315	-	[1]
Date of issue/Date of revision		e of previous is	sue : 13/12/2022		5 <b>2/17</b>
UVILUX SEALER 1453-02 - 1	IS 20408 LIGHT BLUE	<u> </u>		Label No :#68	19

(1-methyl-1,2-ethanediyl)bis			Eye Irrit. 2, H319		
[oxy(methyl-2,1-ethanediyl)]] ester, reaction products with diethylamine	CAS: 111497-86-0		Skin Sens. 1B, H317		
Fatty acids, C18-unsatd., dimers, polymers with acrylic acid, bisphenol A, epichlorohydrin and nonanoic acid	CAS: 216689-76-8	≤3	Skin Sens. 1B, H317	-	[1]
4,4'-Isopropylidenediphenol	REACH #: 01-2119490020-53 EC: 500-130-2 CAS: 55818-57-0	≤0.3	Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
Oligotriacrylate	REACH #: 01-2119487948-12 EC: 500-114-5 CAS: 52408-84-1	≤0.3	Eye Irrit. 2, H319 Skin Sens. 1, H317	-	[1]
Fatty acids, C14-18 and C16-18-unsatd., maleated	REACH #: 01-2119976378-19 EC: 288-306-2 CAS: 85711-46-2	≤0.3	Skin Irrit. 2, H315 Skin Sens. 1, H317	-	[1]
Diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide	REACH #: 01-2119972295-29 EC: 278-355-8 CAS: 75980-60-8 Index: 015-203-00-X	≤0.3	Skin Sens. 1B, H317 Repr. 2, H361f (causing atrophy of the testes) Aquatic Chronic 2, H411	-	[1]
Maleic anhydride	REACH #: 01-2119472428-31 EC: 203-571-6 CAS: 108-31-6 Index: 607-096-00-9	≤0.1	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1A, H317 STOT RE 1, H372 (respiratory system) (inhalation) EUH071	ATE [Oral] = 400 mg/kg Skin Sens. 1, H317: C ≥ 0.001%	[1] [2]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[\*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter  $\leq$  10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

# **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

- Eye contact
- : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

# **SECTION 4: First aid measures**

SECTION 4: FIrst ald		leasures
Inhalation	:	Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/sy	mptoms
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains
4.3 Indication of any imm	ediate medical attention and special treatment needed
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

### **Specific treatments** : No specific treatment.

SECTION 5:	Firefighting	measures
------------	--------------	----------

5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.

:13/12/2022

# **SECTION 5: Firefighting measures**

5.2 Special hazards arising f	om the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides halogenated compounds metal oxide/oxides
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

# **SECTION 6: Accidental release measures**

6.1 Personal precautions, pro	te	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Kvoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

#### 6.3 Methods and material for containment and cleaning up

	• •
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

# **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

Protective measures	: Fut on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

#### 7.3 Specific end use(s)

Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

### **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

#### **Occupational exposure limits**

Product/ingredient name	Exposure limit values
Maleic anhydride	NAOSH (Ireland, 5/2021). Sensitization potential. Notes: Advisory Occupational Exposure Limit Values (OELVs) OELV-8hr: 0.01 ppm 8 hours. Form: The Inhalable Fraction and Vapour note is used when a material exerts sufficient vapour pressure such that it may be present in both particle and vapour phases.

#### **Biological exposure indices**

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
Dipropylenglycol diacrylate	DNEL	Long term Dermal	1.66 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Long term Oral	2.08 mg/	General	Systemic
	DNEL	Long term Dermal	kg bw/day 2.77 mg/	population Workers	Systemic
	DINCL	Long term Derma	kg bw/day	WOIKEI3	Oysternic
	DNEL	Long term	7.24 mg/m <sup>3</sup>	General	Systemic
		Inhalation	Ũ	population	-
	DNEL	Long term	24.48 mg/	Workers	Systemic
		Inhalation	$m^3$		Cuatamia
4,4'-Isopropylidenediphenol, oligomeric reaction products with	DNEL	Long term Inhalation	1.17 mg/m <sup>3</sup>	VUIKEIS	Systemic
1-chloro-2,3-epoxypropane, esters					
with acrylic acid					0
	DNEL	Long term Dermal	33 mg/kg bw/day	Workers	Systemic
Propylidynetrimethanol, ethoxylated,	DNEL	Long term Dermal	10.5 mg/	Workers	Systemic
esters with acrylic acid			kg bw/day		
-	DNEL	Long term	37 mg/m <sup>3</sup>	Workers	Systemic
		Inhalation			
(1-methyl-1,2-ethanediyl)bis[oxy (methyl-2,1-ethanediyl)] diacrylate	DNEL	Long term Dermal	1.7 mg/kg bw/day	Workers	Systemic
(metry-z, r-ethanediyi)] diaci yiate	DNEL	Long term	2.35 mg/m <sup>3</sup>	Workers	Systemic
		Inhalation	5		,
Fatty acids, C18-unsatd., dimers,	DNEL	Long term Dermal	0.33 mg/	Workers	Systemic
polymers with acrylic acid, bisphenol			kg bw/day		
A, epichlorohydrin and nonanoic acid	DNEL	Long term	1.18 mg/m <sup>3</sup>	Workers	Systemic
	DILL	Inhalation	1.10 mg/m	Wonters	Cysternie
4,4'-Isopropylidenediphenol	DNEL	Long term	1.17 mg/m <sup>3</sup>	Workers	Systemic
		Inhalation			
	DNEL	Long term Dermal	33 mg/kg	Workers	Systemic
Oligotriacrylate	DNEL	Long term	bw/day 7.4 mg/m³	Workers	Systemic
ongotitadi yiate	DILL	Inhalation	7.4 mg/m	Wonters	Cysternie
	DNEL	Long term Dermal	2.1 mg/kg	Workers	Systemic
			bw/day	<b>a</b> 1	
Fatty acids, C14-18 and C16-18-unsatd., maleated	DNEL	Long term Oral	1.5 mg/kg bw/day	General population	Systemic
J16-18-unsatd., maleated	DNEL	Long term Dermal	1.5 mg/kg	General	Systemic
	DITLE	Long toni Donna	bw/day	population	Cyclonic
	DNEL	Long term Dermal	3 mg/kg	Workers	Systemic
			bw/day		
Diphenyl(2,4,6-trimethylbenzoyl)	DNEL	Long term Oral	83.3 µg/kg	General	Systemic
phosphine oxide	DNEL	Long term Dermal	bw/day 83.3 µg/kg	population General	Systemic
	DINCL	Long term Derma	bw/day	population	Oysternic
	DNEL	Long term	0.145 mg/	General	Systemic
		Inhalation	m³	population	
	DNEL	Long term Dermal	0.233 mg/	Workers	Systemic
	DNEL	Long term	kg bw/day 0.822 mg/	Workers	Systemic
	DNEL	Inhalation	0.022 mg/ m <sup>3</sup>	VUINEIS	Systemic
Maleic anhydride	DNEL	Long term	0.081 mg/	Workers	Local
-		Inhalation	m³		
	DNEL	Long term	0.081 mg/	Workers	Systemic
	DNEL	Inhalation Short term	m³ 0.2 mg/m³	Workers	Local
		Inhalation	5.2 mg/m	V VINCIO	
	DNEL	Short term	0.2 mg/m <sup>3</sup>	Workers	Systemic
		Inhalation	-	-	
	DNEL	Long term	0.05 mg/m <sup>3</sup>	General	Systemic
		Inhalation		population	

DNEL	Long term Oral	0.06 mg/	General	Systemic
	-	kg bw/day	population	-
DNEL	Long term Inhalation	0.08 mg/m <sup>3</sup>	General population	Local
DNEL	Short term Oral	0.1 mg/kg bw/day	General population	Systemic
DNEL	Short term Dermal	0.1 mg/kg bw/day	General population	Systemic
DNEL	Long term Dermal	0.1 mg/kg bw/day	General population	Systemic
DNEL	Short term Dermal	0.2 mg/kg bw/day	Workers	Systemic
DNEL	Long term Dermal	0.2 mg/kg bw/day	Workers	Systemic

#### **PNECs**

No PNECs available

8.2 Exposure controls	
Appropriate engineering controls	: Fuser operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Individual protection meas	<u>sures</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
	Recommendations : Wear suitable gloves tested to EN374.
	< 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm
	1 - 4 hours (breakthrough time): 4H / Silver Shield® gloves.
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
	Filter type: A
	Filter type (spray application): A P

```
Date of issue/Date of revision: 19/06/2023Date of previous issue: 13/12/2022UVILUX SEALER 1453-02 - TS 20408 LIGHT BLUE
```

### **SECTION 8: Exposure controls/personal protection**

<b>Environmental exposure</b>	
controls	

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Colour	: Blue.
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	:

Ingredient name	°C	°F	Method
//-methyl-1,2-ethanediyl)bis[oxy(methyl- 2,1-ethanediyl)] diacrylate	>120	>248	
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	>391	>735.8	OECD 103

Flammability	: Not available.
Lower and upper explosion	: Lower: Not applicable.
limit	Upper: Not applicable.
Flash point	: Closed cup: >100°C (>212°F)

2

#### **Auto-ignition temperature**

Ingredient name	°C	°F	Method
Propylenglycol diacrylate	240	464	DIN 51794
Ethene, homopolymer	330 to 410	626 to 770	

Decomposition temperature	1	Not available.
рН	\$	Not applicable.
Viscosity	1	Not available.
Solubility(ies)	\$	
Not available.		
Solubility in water	:	Not available.
Partition coefficient: n-octanol/ water	:	Not applicable.

### Vapour pressure

ŝ,

	Vapour Pressure at 20°C			V	Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
Propenoic acid, 1,1'-[(1-methyl- 1,2-ethanediyl)bis[oxy(methyl- 2,1-ethanediyl)]] ester, reaction products with diethylamine	0.0001	0.000013					
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	0.000024	0.0000032	OECD 104				
Relative density	: Not	available.	•	·			
Density	: 1.5	g/cm³					
/apour density	: Not	available.					
Explosive properties	: Not	available.					
ate of issue/Date of revision	: 19/06/2	2023 Date of J	previous issue	: 13/12/2022		Version : 1.05 9/1	

# **SECTION 9: Physical and chemical properties**

Oxidising properties	: Not available.
Particle characteristics	
Median particle size	: Not applicable.

SECTION 10: Stabilit	y and reactivity
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: No specific data.
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
☑ propylenglycol diacrylate	LD50 Oral	Rat	4600 mg/kg	-
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	LD50 Dermal	Rabbit	>13 g/kg	-
(1-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)] diacrylate	LD50 Oral	Rat	6200 mg/kg	-
Maleic anhydride	LD50 Dermal LD50 Oral	Rabbit Rat	2620 mg/kg 400 mg/kg	-

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

#### Acute toxicity estimates

Route	ATE value
Not available.	

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Fipropylenglycol diacrylate	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Severe irritant	Rabbit	-	500 mg	-
titanium dioxide	Skin - Mild irritant	Human	-	72 hours 300	-
				ug l	
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	Eyes - Moderate irritant	Rabbit	-	100 mg	-
-	Skin - Moderate irritant	Rabbit	-	500 mg	-
(1-methyl-1,2-ethanediyl)bis	Eyes - Severe irritant	Rabbit	-	24 hours 100	-
[oxy(methyl-2,1-ethanediyl)]				uL	
diacrylate					
	Skin - Moderate irritant	Rabbit	-	500 mg	-
Maleic anhydride	Eyes - Severe irritant	Rabbit	-	1 %	-
Conclusion/Summary	: Causes skin irritation.	·	·		•

Sensitisation

Date of issue/Date of revision

:13/12/2022

#### **SECTION 11: Toxicological information Conclusion/Summary** : May cause an allergic skin reaction. **Mutagenicity Conclusion/Summary** : Based on available data, the classification criteria are not met. **Carcinogenicity** It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. : Based on available data, the classification criteria are not met. **Conclusion/Summary Reproductive toxicity Conclusion/Summary** : Based on available data, the classification criteria are not met. **Teratogenicity Conclusion/Summary** : Based on available data, the classification criteria are not met.

#### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate	Category 3	-	Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Maleic anhydride	Category 1	inhalation	respiratory system

#### Aspiration hazard

Not available.

Information on likely routes	Not available	
of exposure		
Potential acute health effects		
Eye contact	Causes serious eye damage.	
Inhalation	No known significant effects or critical hazards.	
Skin contact	Causes skin irritation. May cause an allergic skin reaction.	
Ingestion	No known significant effects or critical hazards.	
Symptoms related to the phy	cal, chemical and toxicological characteristics	
Eye contact	Adverse symptoms may include the following: pain watering redness	
Inhalation	No specific data.	
Skin contact	Adverse symptoms may include the following: pain or irritation redness blistering may occur	
Ingestion	Adverse symptoms may include the following: stomach pains	
Delayed and immediate effect	as well as chronic effects from short and long-term exposure	
<u>Short term exposure</u>		
Potential immediate effects	Not available.	
Potential delayed effects	Not available.	
Long term exposure		
Potential immediate effects	Not available.	

# **SECTION 11: Toxicological information**

Potential delayed effects: Not available.Potential chronic health effectsNot available.

Conclusion/Summary	: Not available.
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

#### 11.2 Information on other hazards

**11.2.1 Endocrine disrupting properties** Not available.

11.2.2 Other information

Not available.

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
inanium dioxide	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours
Maleic anhydride	Acute LC50 230000 µg/l Fresh water	Fish - Gambusia affinis - Adult	96 hours
Maleic anhydride Conclusion/Summary	Acute LC50 230000 µg/l Fresh water : Farmful to aquatic life with long lasting		96 ho

#### 12.2 Persistence and degradability

Conclusion/Summary	: This product has not been tested for biodegradation.				
Product/ingredient name	Aquatic half-life Photolysis Biodegradab				
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	-	-	Readily		

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential	
Dipropylenglycol diacrylate	0.01 to 0.39	-	low	
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-	1.6 to 3	-	low	
2,3-epoxypropane, esters with acrylic acid				
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	2.89	-	low	
(1-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)] diacrylate	2	-	low	
4,4'-Isopropylidenediphenol	1.6 to 3	-	low	
Oligotriacrylate	2.52	-	low	
Diphenyl	-	53 to 72	low	
(2,4,6-trimethylbenzoyl) phosphine oxide				
Maleic anhydride	-2.78	-	low	

Date of issue/Date of revision: 19/06/2023Date of previous issueUVILUX SEALER 1453-02 - TS 20408 LIGHT BLUE

: 13/12/2022

# **SECTION 12: Ecological information**

#### 12.4 Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### 12.6 Endocrine disrupting properties

Not available.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
European waste catalogue (EWC)	: 080111*
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA	
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	
14.2 UN proper shipping name					
14.3 Transport hazard class(es)					
14.4 Packing group	<b>F</b>				
14.5 Environmental hazards	No.	No.	No.	<b>N</b> o.	

### **SECTION 14: Transport information**

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

#### 14.7 Maritime transport in bulk according to IMO

: Not relevant/applicable due to nature of the product.

instruments

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

# Annex XIV - List of substances subject to authorisation

### **Annex XIV**

None of the components are listed.

#### Substances of very high concern

I	ntrinsic property	Ingredient name	Status	Reference number	Date of revision
Ī	oxic to reproduction	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Candidate	-	6/15/2023
on pla an da mi <u>Oth</u>	nex XVII - Restriction the manufacture, acing on the market d use of certain ngerous substances xtures and articles er EU regulations	,			
(in	lustrial emissions tegrated pollution evention and control	: Not listed			
(in pre	lustrial emissions tegrated pollution evention and control ater	: Not listed			
	one depleting substa ot listed.	<u>ances (1005/2009/EU)</u>			
	or Informed Consent ot listed.	<u>t (PIC) (649/2012/EU)</u>			
	rsistent Organic Poll ot listed.	<u>utants</u>			
Inte Che	rnational regulations	olled under the Seveso Directive. E ention List Schedules I, II & III Chemicals			
	treal Protocol				
	ckholm Convention of listed.	on Persistent Organic Pollutants			
	terdam Convention of listed.	on Prior Informed Consent (PIC)			
	figure/Data of revision	10/06/2022 Pate of provious issue	• 12/12/2022	Manajara	1 05 14/17

# **SECTION 15: Regulatory information**

### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

<b>15.2 Chemical</b>	safety
assessment	

: This product contains substances for which Chemical Safety Assessments are still required.

# **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	<ul> <li>ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group</li> </ul>
	vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 3, H412	Calculation method

#### Full text of abbreviated H statements

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H361f	Suspected of damaging fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

#### Full text of classifications [CLP/GHS]

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Resp. Sens. 1	RESPIRATORY SENSITISATION - Category 1
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
Date of issue/ Date of	: 19/06/2023

### revision

Date of issue/Date of revision	: 19/06/2023	Date of previous issue	: 13/12/2022	Version	:1.05 <b>15/17</b>
UVILUX SEALER 1453-02 - TS 20408 LIGHT BLUE				Label No :#6819	

# **SECTION 16: Other information**

Date of previous issue	: 13/12/2022
Version	: 1.05

UVILUX SEALER 1453-02\_TS 20408 LIGHT BLUE TS 20408 LIGHT BLUE

#### Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.