Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - United Kingdom: Northern Ireland

SAFETY DATA SHEET



UVILUX SEALER 1456-00 - TS 21364 CLEAR

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

| 1.1 | Prod | uct id | entifier |
|-----|------|--------|----------|
| | | | |

Product name

: UVILUX SEALER 1456-00 - TS 21364 CLEAR

1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use: Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person : Prod-safe@teknos.com responsible for this SDS

National contact

Teknos Ireland Limited, 52 Ballymoughan Road, Magherafelt, BT45 6HN, UK. Tel. +44 (0) 2879 301 472.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : NHS: 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



| Signal word | Danger | |
|--------------------------|--|--|
| Hazard statements | H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H318 - Causes serious eye damage. H412 - Harmful to aquatic life with long lasting effects. | |
| Precautionary statements | | |
| Prevention | P280 - Wear protective gloves. Wear eye or face protection. P273 - Avoid release to the environment. P261 - Avoid breathing vapour. | |
| Response | P305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water for minutes. Remove contact lenses, if present and easy to do. Continue ring Immediately call a POISON CENTER or doctor. | |

| Date of issue/Date of revision | : 04/05/2023 | Date of previous issue | : No previous validation | Version | :1 | 1/14 |
|--------------------------------|---------------|------------------------|--------------------------|----------|-------|----------------|
| UVILUX SEALER 1456-00 - T | S 21364 CLEAR | | | Label No | :4569 |) 7 |

SECTION 2: Hazards identification

| Storage | 1 | Not applicable. |
|---|---|--|
| Disposal | ; | P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Hazardous ingredients | : | Hexanedioic acid, polymer with (chloromethyl)oxirane, 2-ethyl-2-(hydroxymethyl) -1,3-propanediol, 4,4'-(1-methylethylidene)bis[phenol] and oxirane, 2-propenoate Dipropylenglycol diacrylate 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane, esters with acrylic acid |
| Supplemental label elements | : | |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : | |
| 2.3 Other hazards | | |
| Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII | : | This mixture does not contain any substances that are assessed to be a PBT or a vPvB. |
| Other hazards which do | | None known. |

not result in classification

SECTION 3: Composition/information on ingredients

| Product/ingredient name | Identifiers | % | Classification | Specific Conc. Limits, M-factors and ATEs | Туре |
|--|---|-----------|---|---|---------|
| Hexanedioic acid, polymer with (chloromethyl)oxirane, 2-ethyl-2-(hydroxymethyl) -1,3-propanediol, 4,4'- (1-methylethylidene)bis [phenol] and oxirane, 2-propenoate | CAS: 184181-05-3 | ≥10 - ≤25 | Skin Sens. 1, H317 | - | [1] |
| Dipropylenglycol diacrylate | REACH #: 01-2119484629-21 EC: 260-754-3 CAS: 57472-68-1 | ≥10 - ≤25 | Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 | - | [1] |
| 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane, esters with acrylic acid | REACH #: 01-2119490020-53 EC: 500-130-2 CAS: 55818-57-0 | ≥10 - <25 | Skin Sens. 1, H317 Aquatic Chronic 2, H411 | - | [1] |
| Polymeric alkoxylate | - | ≤3 | Eye Irrit. 2, H319 | - | [1] |
| 2-hydroxy- 2-methylpropiophenone | REACH #: 01-2119472306-39 EC: 231-272-0 CAS: 7473-98-5 | ≤3 | Acute Tox. 4, H302 Aquatic Chronic 3, H412 | ATE [Oral] = 1694 mg/kg | [1] |
| 1-Methoxy 2-propanol | REACH #: 01-2119457435-35 EC: 203-539-1 CAS: 107-98-2 Index: 603-064-00-3 | ≤0.3 | Flam. Liq. 3, H226 STOT SE 3, H336 | - | [1] [2] |

SECTION 3: Composition/information on ingredients See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

| 4.1 Description of first aid r | neasures |
|--------------------------------|--|
| Eye contact | : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. |
| Inhalation | : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |
| Skin contact | : Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse. |
| Ingestion | : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. |

4.2 Most important symptoms and effects, both acute and delayed

| Over-exposure signs/sy | <u>ymptoms</u> |
|------------------------|--|
| Eye contact | : Adverse symptoms may include the following: pain watering redness |
| Inhalation | : No specific data. |
| Skin contact | : Adverse symptoms may include the following: pain or irritation redness blistering may occur |

| Date of issue/Date of revision | : 04/05/2023 | Date of previous issue | : No previous validation | Version | :1 | 3/14 |
|--------------------------------|--------------|------------------------|--------------------------|----------|-------|------|
| UVILUX SEALER 1456-00 - TS 2 | 1364 CLEAR | | | Label No | :4569 | 7 |

| SECTION 4: First aid | measures |
|---|---|
| Ingestion | : Adverse symptoms may include the following: stomach pains |
| 4.3 Indication of any immedia | ate medical attention and special treatment needed |
| Notes to physician | Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |
| Specific treatments | : No specific treatment. |
| SECTION 5: Firefight | ting measures |
| 5.1 Extinguishing media | |
| Suitable extinguishing media | : Use an extinguishing agent suitable for the surrounding fire. |
| Unsuitable extinguishing media | : None known. |
| 5.2 Special hazards arising f | rom the substance or mixture |
| Hazards from the substance or mixture | In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. |
| Hazardous combustion products | : Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides |
| 5.3 Advice for firefighters | |
| Special protective actions for fire-fighters | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents. |

SECTION 6: Accidental release measures

| 6.1 Personal precautions, pro | ote | ctive equipment and emergency procedures |
|--------------------------------|-----|--|
| For non-emergency personnel | : | No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. |
| For emergency responders | : | If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". |
| 6.2 Environmental precautions | : | Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. |
| 6.3 Methods and material for | СС | entainment and cleaning up |
| Ownell and!! | | Other lack if with evidence in the sector in the sector and the sector and the sector and the sector is the sector and the sector is the sector and the sector is the sect |

Small spill: Stop leak if without risk. Move containers from spill area. Dilute with water and mop
up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry
material and place in an appropriate waste disposal container. Dispose of via a
licensed waste disposal contractor.

| Date of issue/Date of revision | : 04/05/2023 | Date of previous issue | : No previous validation | Version | :1 | 4/14 |
|--------------------------------|----------------|------------------------|--------------------------|----------|-------|------|
| UVILUX SEALER 1456-00 | TS 21364 CLEAR | | | Label No | :4569 | 97 |

SECTION 6: Accidental release measures

| Large spill | |
|-------------|--|
| | |
| | |

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.

6.4 Reference to other
sections: See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

| Protective measures | : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. |
|--|---|
| Advice on general occupational hygiene | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

| Recommendations | : Not available. |
|--------------------------------------|------------------|
| Industrial sector specific solutions | : Not available. |
| Solutions | |

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

| Product/ingredient name | Exposure limit values |
|-------------------------|---|
| 1-Methoxy 2-propanol | EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 560 mg/m ³ 15 minutes. STEL: 150 ppm 15 minutes. TWA: 375 mg/m ³ 8 hours. TWA: 100 ppm 8 hours. |

5/14

Biological exposure indices

No exposure indices known.

SECTION 8: Exposure controls/personal protection

procedures

Recommended monitoring : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

| Product/ingredient name | Туре | Exposure | Value | Population | Effects |
|---|------|-------------------------|------------------------------------|-----------------------|----------|
| Dipropylenglycol diacrylate | DNEL | Long term Dermal | 1.66 mg/ kg bw/day | General population | Systemic |
| | DNEL | Long term Oral | 2.08 mg/ | General | Systemic |
| | DNEL | Long term Dermal | kg bw/day 2.77 mg/ kg bw/day | population Workers | Systemic |
| | DNEL | Long term Inhalation | 7.24 mg/m ³ | General population | Systemic |
| | DNEL | Long term Inhalation | 24.48 mg/ m ³ | Workers | Systemic |
| 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid | DNEL | Long term Inhalation | 1.17 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Dermal | 33 mg/kg bw/day | Workers | Systemic |
| 2-hydroxy-2-methylpropiophenone | DNEL | Long term Dermal | 1 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Oral | 0.4 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 0.5 mg/kg bw/day | General | Systemic |
| | DNEL | Long term Inhalation | 0.9 mg/m ³ | General | Systemic |
| | DNEL | Long term Inhalation | 3.5 mg/m ³ | Workers | Systemic |

PNECs

No PNECs available

8.2 Exposure controls

| Appropriate engineering controls | : | If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. |
|----------------------------------|------|--|
| Individual protection meas | ures | |
| Hygiene measures | : | Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. |
| Eye/face protection | : | Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead. |

Skin protection

SECTION 8: Exposure controls/personal protection

| Hand protection | : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. |
|---------------------------------|---|
| | Recommendations : Wear suitable gloves tested to EN374. |
| | < 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm |
| | > 8 hours (breakthrough time): 4H / Silver Shield® gloves. |
| | Wash hands before breaks and immediately after handling the product. |
| Body protection | Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Other skin protection | Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Respiratory protection | : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. |
| | Filter type: A |
| | Filter type (spray application): A P |
| Environmental exposure controls | : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. |

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

| <u>Appearance</u> | |
|--|--|
| Physical state | : Liquid. |
| Colour | : Clear. |
| Odour | : Slight |
| Odour threshold | : Not available. |
| Melting point/freezing point | : Not available. |
| Initial boiling point and boiling range | : Not available. |
| Flammability | : Not available. |
| Lower and upper explosion limit | : Lower: Not applicable. Upper: Not applicable. |
| Flash point | : Closed cup: >100°C (>212°F) |
| | |

ŝ

Auto-ignition temperature

| Ingredient name | | °C | °F | Method | |
|--|--|----------|-----|-----------|--|
| Dipropylenglycol diacrylate | | 240 | 464 | DIN 51794 | |
| 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid | | 465 | 869 | EU A.15 | |
| Decomposition temperature : Not ava | | ilable. | | | |
| oH : Not app | | licable. | | | |
| /iscosity : Not ava | | ilable. | | | |

| sity | : Not availal |
|------|---------------|
| | |

Solubility(ies) ŝ,

Date of issue/Date of revision UVILUX SEALER 1456-00 - TS 21364 CLEAR

: 04/05/2023 Date of previous issue

SECTION 9: Physical and chemical properties

2

Not available.

Solubility in water : Not available.

Partition coefficient: n-octanol/ : Not applicable. water

Vapour pressure

| | Vapour Pressure at 20°C | | | Va | Vapour pressure at 50°C | | | |
|---|-------------------------|-------------|----------|------------|-------------------------|----------|--|--|
| Ingredient name | mm Hg | kPa | Method | mm Hg | kPa | Method | | |
| 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid | 0.00000075 | 0.000001 | OECD 104 | 0.00000075 | 0.000001 | OECD 104 | | |
| Dipropylenglycol diacrylate | 0 | 0 | OECD 104 | | | | | |
| Relative density | : Not available. | | | | | | | |
| Density | : 1.5 g | /cm³ | | | | | | |
| Vapour density | : Not a | available. | | | | | | |
| Explosive properties | : Not a | available. | | | | | | |
| Oxidising properties | : Not a | available. | | | | | | |
| Particle characteristics | | | | | | | | |
| Median particle size | : Not a | applicable. | | | | | | |

| SECTION 10: Stabilit | y and reactivity |
|--|--|
| 10.1 Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
| 10.2 Chemical stability | : The product is stable. |
| 10.3 Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| 10.4 Conditions to avoid | : No specific data. |
| 10.5 Incompatible materials | : No specific data. |
| 10.6 Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure | | |
|---|--------------------------|------------|--------------------------|----------|--|--|
| Dipropylenglycol diacrylate 2-hydroxy- | LD50 Oral LD50 Dermal | Rat Rat | 4600 mg/kg 6929 mg/kg | - | | |
| 2-methylpropiophenone | LD50 Oral | Rat | 1694 mg/kg | - | | |
| Conclusion/Summary : Based on available data, the classification criteria are not met. | | | | | | |

Acute toxicity estimates

| Route | ATE value |
|-------|-------------|
| Oral | 84700 mg/kg |

Irritation/Corrosion

| SECTION 11: Toxicol | ogical information | | | | |
|--|---|-------------------|-------------|-------------------|-------------|
| Product/ingredient name | Result | Species | Score | Exposure | Observation |
| Dipropylenglycol diacrylate | Eyes - Severe irritant Skin - Severe irritant | Rabbit Rabbit | - | 100 mg 500 mg | - |
| Conclusion/Summary Sensitisation | : Causes skin irritation. | | | | |
| Conclusion/Summary | : May cause an allergic skin re | eaction. | | | |
| <u>Mutagenicity</u> Conclusion/Summary | : Based on available data, the | classification c | riteria are | not met. | |
| <u>Carcinogenicity</u> Conclusion/Summary | : Based on available data, the | classification o | riteria are | not met | |
| Reproductive toxicity | | | | | |
| Conclusion/Summary <u>Teratogenicity</u> | : Based on available data, the | classification c | riteria are | not met. | |
| Conclusion/Summary | : Based on available data, the | classification c | riteria are | not met. | |
| Specific target organ toxicit Not available. | <u>y (single exposure)</u> | | | | |
| Specific target organ toxicit Not available. | <u>y (repeated exposure)</u> | | | | |
| Aspiration hazard Not available. | | | | | |
| Information on likely routes of exposure | : Not available. | | | | |
| Potential acute health effects | | | | | |
| Eye contact | : Causes serious eye damage | | | | |
| Inhalation | : No known significant effects | | | | |
| Skin contact | : Causes skin irritation. May c | - | | iction. | |
| Ingestion | : No known significant effects | or critical nazal | ras. | | |
| Symptoms related to the phy | sical, chemical and toxicologic | cal characteris | stics | | |
| Eye contact | : Adverse symptoms may inclu pain watering | ude the followin | ıg: | | |
| | redness | | | | |
| Inhalation | : No specific data. | | | | |
| Skin contact | : Adverse symptoms may inclu pain or irritation redness blistering may occur | ude the followin | ıg: | | |
| Ingestion | : Adverse symptoms may inclusion stomach pains | ude the followin | ıg: | | |
| | ts as well as chronic effects fr | om short and | long-tern | <u>n exposure</u> | |
| <u>Short term exposure</u> | | | | | |
| Potential immediate effects | : Not available. | | | | |
| Potential delayed effects | : Not available. | | | | |
| Long term exposure Potential immediate effects | : Not available. | | | | |
| Potential delayed effects | : Not available. | | | | |
| Date of issue/Date of revision | : 04/05/2023 Date of previous i | ssue : No | previous va | lidation Vers | ion :1 9/14 |
| UVILUX SEALER 1456-00 - TS | 21364 CLEAR | | | Label | No :45697 |

SECTION 11: Toxicological information

Potential chronic health effects

Not available.

| Conclusion/Summary | : Not available. |
|---------------------------|---|
| General | Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. |
| Carcinogenicity | : No known significant effects or critical hazards. |
| Mutagenicity | : No known significant effects or critical hazards. |
| Reproductive toxicity | : No known significant effects or critical hazards. |

11.2 Information on other hazards

| 11.2.1 | Endocrine | disrupting | properties |
|--------|-----------|------------|------------|
|--------|-----------|------------|------------|

11.2.2 Other information

Not available.

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Conclusion/Summary : Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Conclusion/Summary : This product has not been tested for biodegradation.

12.3 Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|---|--------------|-----|-----------|
| Dipropylenglycol diacrylate | 0.01 to 0.39 | - | low |
| 4,4'-Isopropylidenediphenol, | 1.6 to 3 | - | low |
| oligomeric reaction products with 1-chloro- | | | |
| 2,3-epoxypropane, esters with acrylic acid | | | |
| 2-hydroxy- 2-methylpropiophenone | 1.62 | - | low |

| 12.4 Mobility in soil | |
|--|------------------|
| Soil/water partition coefficient (Koc) | : Not available. |
| Mobility | : Not available. |

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

| 13.1 Waste treatment met | ods |
|-----------------------------------|---|
| Product | |
| Methods of disposal | : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. |
| Hazardous waste | : The classification of the product may meet the criteria for a hazardous waste. |
| European waste catalogue (EWC) | : 080111* |
| Packaging | |
| Methods of disposal | : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. |
| Special precautions | : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. |

SECTION 14: Transport information

| | ADR/RID | ADN | IMDG | ΙΑΤΑ |
|------------------------------------|----------------|--|-------------------------|------------------|
| 14.1 UN number or ID number | Not regulated. | 9006 | Not regulated. | Not regulated. |
| 14.2 UN proper shipping name | - | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. | - | - |
| 14.3 Transport hazard class(es) | - | 9 | - | - |
| 14.4 Packing group | - | - | - | - |
| 14.5 Environmental hazards | No. | Yes. | No. | No. |
| Additional informa | | t is only regulated as a c | langerous good when tra | nsported in tank |

ΙΑΤΑ : The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in user the event of an accident or spillage.

14.7 Maritime transport in : Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

| 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture |
|--|
| EU Regulation (EC) No. 1907/2006 (REACH) |
| Annex XIV - List of substances subject to authorisation Annex XIV |
| None of the components are listed. |
| |
| Substances of very high concern |
| None of the components are listed. |
| Annex XVII - Restrictions : on the manufacture, |
| placing on the market |
| and use of certain |
| dangerous substances, mixtures and articles |
| Other EU regulations |
| Industrial emissions : Not listed |
| (integrated pollution |
| prevention and control) - Air |
| Industrial emissions : Not listed |
| (integrated pollution |
| prevention and control) - |
| Water <u>Ozone depleting substances (1005/2009/EU)</u> |
| Not listed. |
| |
| Prior Informed Consent (PIC) (649/2012/EU) Not listed. |
| |
| <u>Persistent Organic Pollutants</u> Not listed. |
| |
| Seveso Directive |
| This product is not controlled under the Seveso Directive. |
| International regulations Chemical Weapon Convention List Schedules I, II & III Chemicals |
| Not listed. |
| |
| Montreal Protocol Not listed. |
| |
| Stockholm Convention on Persistent Organic Pollutants |
| Not listed. |
| Rotterdam Convention on Prior Informed Consent (PIC) |
| Not listed. |
| UNECE Aarhus Protocol on POPs and Heavy Metals |
| Not listed. |
| |
| 15.2 Chemical safety : This product contains substances for which Chemical Safety Assessments are still required. |
| assessment required. |

SECTION 16: Other information

Indicates information that has changed from previously issued version.

| | nat has onanged nom previously issued version. |
|-------------------------------|--|
| Abbreviations and acronyms | ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative |
| | |

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification | Justification |
|-------------------------|--------------------|
| Skin Irrit. 2, H315 | Calculation method |
| Eye Dam. 1, H318 | Calculation method |
| Skin Sens. 1, H317 | Calculation method |
| Aquatic Chronic 3, H412 | Calculation method |

Full text of abbreviated H statements

| H226 | Flammable liquid and vapour. | |
|------|--|--|
| H302 | Harmful if swallowed. | |
| H315 | Causes skin irritation. | |
| H317 | May cause an allergic skin reaction. | |
| H318 | Causes serious eye damage. | |
| H319 | Causes serious eye irritation. | |
| H336 | May cause drowsiness or dizziness. | |
| H411 | Toxic to aquatic life with long lasting effects. | |
| H412 | Harmful to aquatic life with long lasting effects. | |

Full text of classifications [CLP/GHS]

| Acute Tox. 4 | ACUTE TOXICITY - Category 4 |
|---------------------------------|---|
| Aquatic Chronic 2 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 |
| Aquatic Chronic 3 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 |
| Eye Dam. 1 | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 |
| Eye Irrit. 2 | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 |
| Flam. Liq. 3 | FLAMMABLE LIQUIDS - Category 3 |
| Skin Irrit. 2 | SKIN CORROSION/IRRITATION - Category 2 |
| Skin Sens. 1 | SKIN SENSITISATION - Category 1 |
| STOT SE 3 | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3 |
| Date of issue/ Date of revision | : 04/05/2023 |
| Date of previous issue | e : No previous validation |
| Version | : 1 |

JVILUX SEALER 1456-00 TS 21364 CLEAR

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.