

# SAFETY DATA SHEET



WINTOL - All variants

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : WINTOL - All variants

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Paint.

### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

**e-mail address of person responsible for this SDS** : Prod-safe@teknos.com

#### National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

**Telephone number** : Malta Competition and Consumer Affairs Authority (MCCAA): +356 2395 2000

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

Skin Sens. 1, H317

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Warning

**Hazard statements** : H226 - Flammable liquid and vapour.  
H317 - May cause an allergic skin reaction.  
H412 - Harmful to aquatic life with long lasting effects.

#### Precautionary statements

**General** : P102 - Keep out of reach of children.

**Prevention** : P280 - Wear protective gloves.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P273 - Avoid release to the environment.

**Response** : P362 + P364 - Take off contaminated clothing and wash it before reuse.

**Storage** : Not applicable.

**Date of issue/Date of revision**

: 05/06/2024

**Date of previous issue**

: 10/10/2023

**Version** : 4

1/17

WINTOL - All variants

**Label No** : 83189

## SECTION 2: Hazards identification

<b>Disposal</b>	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
<b>Hazardous ingredients</b>	: Contains: 3-iodo-2-propynyl-butyl carbamate; neodecanoic acid, cobalt salt and 4,5-dichloro-2-octyl-2H-isothiazol-3-one
<b>Supplemental label elements</b>	: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains biocidal products for dry film and in-can preservation: IPBC and DCOIT. Risk of skin sensitisation.
<b>Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles</b>	:

### 2.3 Other hazards

<b>Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII</b>	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
<b>Other hazards which do not result in classification</b>	: None known.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Naphtha (petroleum), hydrotreated heavy	REACH #: 01-2119463258-33 EC: 265-150-3 CAS: 64742-48-9 Index: 649-327-00-6	≥10 - <20	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 EUH066	EUH066: C ≥ 50%	[1]
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥10 - ≤25	Carc. 2, H351 (inhalation)	-	[1] [*]
Naphtha (petroleum), hydrotreated heavy	REACH #: 01-2119457273-39 EC: 265-150-3 CAS: 64742-48-9 Index: 649-327-00-6	≤3	Asp. Tox. 1, H304 EUH066	EUH066: C ≥ 50%	[1]
3-iodo-2-propynyl-butyl carbamate	EC: 259-627-5 CAS: 55406-53-6 Index: 616-212-00-7	≤0.2	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 400 mg/kg ATE [Inhalation (dusts and mists)] = 0.67 mg/l M [Acute] = 10 M [Chronic] = 1	[1]
neodecanoic acid, cobalt salt	REACH #: 01-2119970733-31 EC: 248-373-0 CAS: 27253-31-2	≤0.3	Acute Tox. 4, H302 Skin Sens. 1, H317 STOT RE 1, H372 Aquatic Chronic 3, H412	ATE [Oral] = 500 mg/kg	[1]
4,5-dichloro-2-octyl-2H-isothiazol-3-one	EC: 264-843-8 CAS: 64359-81-5	≤0.022	Acute Tox. 4, H302 Acute Tox. 2, H330	ATE [Oral] = 567 mg/kg	[1]

## SECTION 3: Composition/information on ingredients

	Index: 613-335-00-8		Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071  <b>See Section 16 for the full text of the H statements declared above.</b>	ATE [Inhalation (dusts and mists)] = 0.16 mg/l Skin Corr. 1, H314: C ≥ 5% Skin Irrit. 2, H315: 0.025% ≤ C < 5% Eye Dam. 1, H318: C ≥ 3% Eye Irrit. 2, H319: 0.025% ≤ C < 3% Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100	
--	---------------------	--	--	--	--

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

### Type

[1] Substance classified with a health or environmental hazard

[\*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter ≤ 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

Date of issue/Date of revision

: 05/06/2024

Date of previous issue

: 10/10/2023

Version : 4

3/17

WINTOL - All variants

Label No : 83189

## SECTION 4: First aid measures

<b>Eye contact</b>	: No specific data.
<b>Inhalation</b>	: No specific data.
<b>Skin contact</b>	: Adverse symptoms may include the following: irritation redness
<b>Ingestion</b>	: No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

<b>Notes to physician</b>	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
<b>Specific treatments</b>	: No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

<b>Suitable extinguishing media</b>	: Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.
<b>Unsuitable extinguishing media</b>	: Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

<b>Hazards from the substance or mixture</b>	: Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
<b>Hazardous combustion products</b>	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides

### 5.3 Advice for firefighters

<b>Special protective actions for fire-fighters</b>	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
<b>Special protective equipment for fire-fighters</b>	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

<b>For non-emergency personnel</b>	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
<b>For emergency responders</b>	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
--

## SECTION 6: Accidental release measures

### 6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

### 6.4 Reference to other sections

- : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

#### Seveso Directive - Reporting thresholds

##### Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c	5000 tonne	50000 tonne

### 7.3 Specific end use(s)

- Recommendations** : Not available.

## SECTION 7: Handling and storage

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
No exposure limit value known.	

#### Biological exposure indices

Product/ingredient name	Exposure indices
No exposure indices known.	

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
Naphtha (petroleum), hydrotreated heavy	DNEL	Long term Inhalation	0.41 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	1.9 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	178.57 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Oral	300 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	300 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	300 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	640 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	837.5 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	1066.67 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	1152 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Short term Inhalation	1286.4 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	0.41 mg/m <sup>3</sup>	General population	Systemic
Naphtha (petroleum), hydrotreated heavy	DNEL	Long term Inhalation	1.9 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	178.57 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Oral	300 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	300 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	300 mg/kg	Workers	Systemic



## SECTION 8: Exposure controls/personal protection

3-iodo-2-propynyl-butyl carbamate	DNEL	Short term Inhalation	bw/day 640 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	837.5 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	1066.67 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	1152 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Short term Inhalation	1286.4 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	0.023 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	0.07 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	1.16 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Inhalation	1.16 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Dermal	2 mg/kg bw/day	Workers	Systemic
neodecanoic acid, cobalt salt	DNEL	Long term Oral	32 µg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	43 µg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	273.2 µg/m <sup>3</sup>	Workers	Local

### PNECs

No PNECs available

## 8.2 Exposure controls

### **Appropriate engineering controls**

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Individual protection measures

#### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Eye/face protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

### Skin protection

#### **Hand protection**

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations : Wear suitable gloves tested to EN374.

< 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm

1 - 4 hours (breakthrough time): polyvinyl alcohol (PVA) thickness > 0.3 mm or 4H / Silver Shield® gloves.

## SECTION 8: Exposure controls/personal protection

> 8 hours (breakthrough time): Viton® thickness > 0.3 mm gloves

Wash hands before breaks and immediately after handling the product.

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.  
Filter type: A  
Filter type (spray application): A P
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : Various
- Odour** : Slight
- Odour threshold** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** :

Ingredient name	°C	°F	Method
Naphtha (petroleum), hydrotreated heavy	155 to 217	311 to 422.6	
Naphtha (petroleum), hydrotreated heavy	155 to 217	311 to 422.6	

- Flammability** : Not available.
- Lower and upper explosion limit** : Lower: 1.4%  
Upper: 12.6%
- Flash point** : Closed cup: 38°C (100.4°F)
- Auto-ignition temperature** :

Ingredient name	°C	°F	Method
Naphtha (petroleum), hydrotreated heavy	280 to 470	536 to 878	
Naphtha (petroleum), hydrotreated heavy	280 to 470	536 to 878	

- Decomposition temperature** : Not available.
- pH** : Not applicable.
- Viscosity** : Kinematic (40°C): >20.5 mm<sup>2</sup>/s
- Solubility(ies)** :  
Not available.
- Solubility in water** : Not available.



## SECTION 9: Physical and chemical properties

**Partition coefficient: n-octanol/ water** : Not applicable.

**Vapour pressure** :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Naphtha (petroleum), hydrotreated heavy	0.75006 to 2.25018	0.1 to 0.3				
Naphtha (petroleum), hydrotreated heavy	0.75006 to 2.25018	0.1 to 0.3				

**Relative density** : Not available.

**Density** : 1.3 g/cm<sup>3</sup>

**Vapour density** : Not available.

**Explosive properties** : Not available.

**Oxidising properties** : Not available.

### Particle characteristics

**Median particle size** : Not applicable.

## SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

**10.5 Incompatible materials** : Reactive or incompatible with the following materials:  
oxidising materials

**10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Naphtha (petroleum), hydrotreated heavy	LC50 Inhalation Vapour	Rat	8500 mg/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	>6 g/kg	-
Naphtha (petroleum), hydrotreated heavy	LC50 Inhalation Vapour	Rat	8500 mg/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	>6 g/kg	-
3-iodo-2-propynyl-butyl carbamate	LC50 Inhalation Dusts and mists	Rat	0.67 g/m <sup>3</sup>	4 hours
	LC50 Inhalation Dusts and mists	Rat	0.763 mg/l	4 hours
4,5-dichloro-2-octyl-2H-isothiazol-3-one	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	400 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat - Male, Female	0.26 mg/l	4 hours
	LD50 Dermal	Rabbit	>652 mg/kg	-
	LD50 Oral	Rat	1585 mg/kg	-

**Date of issue/Date of revision** : 05/06/2024 **Date of previous issue** : 10/10/2023 **Version** : 4 **9/17**

WINTOL - All variants

**Label No** : 83189

## SECTION 11: Toxicological information

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Acute toxicity estimates

Route	ATE value
Inhalation (dusts and mists)	378.26 mg/l

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
titanium dioxide	Skin - Mild irritant	Human	-	72 hours 300 ug l	-
3-iodo-2-propynyl-butyl carbamate	Eyes - Severe irritant	Rabbit	-	-	-

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Sensitisation

Product/ingredient name	Route of exposure	Species	Result
3-iodo-2-propynyl-butyl carbamate	skin	Guinea pig	Not sensitizing

**Conclusion/Summary** : May cause an allergic skin reaction.

### Mutagenicity

Product/ingredient name	Test	Experiment	Result
3-iodo-2-propynyl-butyl carbamate	-	Experiment: In vitro Subject: Bacteria	Negative

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
3-iodo-2-propynyl-butyl carbamate	Negative	-	Negative	Rabbit - Female	Oral: 20 mg/kg	13 days; 7 days per week
	Positive	-	Negative	Rabbit - Female	Oral: 50 mg/kg	13 days; 7 days per week

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Teratogenicity

Product/ingredient name	Result	Species	Dose	Exposure
3-iodo-2-propynyl-butyl carbamate	Negative - Oral	Rabbit - Female	50 mg/kg	-

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Naphtha (petroleum), hydrotreated heavy	Category 3	-	Narcotic effects

### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
3-iodo-2-propynyl-butyl carbamate	Category 1	-	larynx
neodecanoic acid, cobalt salt	Category 1	-	-

## SECTION 11: Toxicological information

### Aspiration hazard

Product/ingredient name	Result
Naphtha (petroleum), hydrotreated heavy	ASPIRATION HAZARD - Category 1
Naphtha (petroleum), hydrotreated heavy	ASPIRATION HAZARD - Category 1

**Information on likely routes of exposure** : Not available.

### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards.  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : May cause an allergic skin reaction.  
**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : No specific data.  
**Inhalation** : No specific data.  
**Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
**Ingestion** : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

**Conclusion/Summary** : Not available.  
**General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.  
**Carcinogenicity** : No known significant effects or critical hazards.  
**Mutagenicity** : No known significant effects or critical hazards.  
**Reproductive toxicity** : No known significant effects or critical hazards.

## 11.2 Information on other hazards

### 11.2.1 Endocrine disrupting properties

Not available.

### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 3 mg/l Fresh water	Crustaceans - <i>Ceriodaphnia dubia</i> - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - <i>Daphnia pulex</i> - Neonate	48 hours
	Acute LC50 >1000000 µg/l Marine water	Fish - <i>Fundulus heteroclitus</i>	96 hours
3-iodo-2-propynyl-butyl carbamate	Acute EC50 0.022 mg/l Fresh water	Algae - <i>Scenedemus subspicatus</i>	72 hours
	Acute EC50 0.16 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 0.067 mg/l Fresh water	Fish - <i>Oncorhynchus mykiss</i>	96 hours
4,5-dichloro-2-octyl-2H-isothiazol-3-one	Acute NOEC 0.049 mg/l Fresh water	Fish - <i>Oncorhynchus mykiss</i>	96 hours
	Chronic NOEC 0.05 mg/l Fresh water	Daphnia - <i>Daphnia Magna</i>	21 days
	Acute EC50 0.003 mg/l Fresh water	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours
	Acute EC50 18 ppb Marine water	Algae - <i>Skeletonema costatum</i>	96 hours
	Acute EC50 0.001 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 22 µg/l Fresh water	Crustaceans - <i>Gammarus pulex</i>	48 hours
	Acute LC50 2.7 ppb Fresh water	Fish - <i>Oncorhynchus mykiss</i>	96 hours
	Chronic NOEC 19.789 µg/l Marine water	Algae - <i>Nitzschia pungens</i>	96 hours
	Chronic NOEC 0.56 ppb	Fish - <i>Oncorhynchus mykiss</i>	97 days

**Conclusion/Summary** : Harmful to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

**Conclusion/Summary** : This product has not been tested for biodegradation.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
3-iodo-2-propynyl-butyl carbamate	-	-	Not readily

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Naphtha (petroleum), hydrotreated heavy	-	10 to 2500	High
Naphtha (petroleum), hydrotreated heavy	-	10 to 2500	High
3-iodo-2-propynyl-butyl carbamate	>1	-	Low
neodecanoic acid, cobalt salt	-	15600	High

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
- Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal.





**European waste catalogue (EWC)** : 080111\*, 200127\*

#### Packaging

- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

- Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	Paint
14.3 Transport hazard class(es)	3 	3 	3 	3 
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	No.	No.	No.	No.

#### Additional information

- ADR/RID** : **Viscous liquid exception** This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.  
**Tunnel code** (D/E)
- ADN** : **Viscous liquid exception** This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.
- IMDG** : **Viscous liquid exception** This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.3.2.5.

- 14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

## SECTION 14: Transport information

**14.7 Maritime transport in bulk according to IMO instruments** : Not relevant/applicable due to nature of the product.

## SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU Regulation (EC) No. 1907/2006 (REACH)**

**Annex XIV - List of substances subject to authorisation**

**Annex XIV**

None of the components are listed.

**Substances of very high concern**

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles**

Product/ingredient name	%	Designation [Usage]
TEKNOLIN	≥90	3

**Labelling** :

**Other EU regulations**

**Industrial emissions (integrated pollution prevention and control) - Air** : Not listed

**Industrial emissions (integrated pollution prevention and control) - Water** : Not listed

**Explosive precursors** : Not applicable.

**Ozone depleting substances (1005/2009/EU)**

Not listed.

**Prior Informed Consent (PIC) (649/2012/EU)**

Not listed.

**Persistent Organic Pollutants**

Not listed.

**Seveso Directive**

This product is controlled under the Seveso Directive.

**Danger criteria**

Category
P5c

**International regulations**

**Chemical Weapon Convention List Schedules I, II & III Chemicals**

Not listed.

**Montreal Protocol**

Not listed.

**Stockholm Convention on Persistent Organic Pollutants**

Not listed.

**Rotterdam Convention on Prior Informed Consent (PIC)**

Not listed.



## SECTION 15: Regulatory information

### [UNECE Aarhus Protocol on POPs and Heavy Metals](#)

Not listed.

#### 15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

Indicates information that has changed from previously issued version.

#### Abbreviations and acronyms

: ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
N/A = Not available  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
SGG = Segregation Group  
vPvB = Very Persistent and Very Bioaccumulative

#### [Procedure used to derive the classification according to Regulation \(EC\) No. 1272/2008 \[CLP/GHS\]](#)

Classification	Justification
Flam. Liq. 3, H226 Skin Sens. 1, H317 Aquatic Chronic 3, H412	On basis of test data Calculation method Calculation method

#### [Full text of abbreviated H statements](#)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.

#### [Full text of classifications \[CLP/GHS\]](#)

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Skin Corr. 1	SKIN CORROSION/IRRITATION - Category 1
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

## SECTION 16: Other information

**Date of issue/ Date of revision** : 05/06/2024

**Date of previous issue** : 10/10/2023

**Version** : 4

WINTOL

All variants

### Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

