# SAFETY DATA SHEET



WOODEX AQUA CLASSIC - All variants

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

: WOODEX AQUA CLASSIC - All variants **Product name** 

1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person

: Prod-safe@teknos.com

responsible for this SDS

**National contact** 

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

**National advisory body/Poison Centre** 

: Malta Competition and Consumer Affairs Authority (MCCAA): +356 2395 2000 Telephone number

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

Signal word : No signal word.

: H412 - Harmful to aquatic life with long lasting effects. **Hazard statements** 

**Precautionary statements** 

: P273 - Avoid release to the environment. **Prevention** 

Response : Not applicable. **Storage** : Not applicable.

: P501 - Dispose of contents and container in accordance with all local, regional, **Disposal** 

national and international regulations.

Supplemental label

elements

: Contains 3-iodo-2-propynyl-butyl carbamate, 2,4,7,9-tetramethyl-5-decyne-4,7-diol, 1,2-benzisothiazol-3(2H)-one and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3: 1). May produce an allergic reaction. Contains biocidal products for dry film and incan preservation: IPBC and EGForm and BIT and C(M)IT/MIT (3:1). Risk of skin sensitisation. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Safety data sheet available on request.

Date of issue/Date of revision : 16/04/2025 : 10/10/2024 1/19 Date of previous issue Version: 4 Label No: 85993

## **SECTION 2: Hazards identification**

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

#### 2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a

Other hazards which do not result in classification

: None known.

# **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
<b>2</b> -Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	≤3	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	ATE [Oral] = 1200 mg/kg ATE [Inhalation (vapours)] = 3 mg/l	[1] [2]
3-iodo-2-propynyl-butyl carbamate	EC: 259-627-5 CAS: 55406-53-6 Index: 616-212-00-7	≤0.3	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 400 mg/kg ATE [Inhalation (dusts and mists)] = 0.67 mg/l M [Acute] = 10 M [Chronic] = 1	[1]
2,4,7,9-tetramethyl- 5-decyne-4,7-diol	REACH #: 01-2119954390-39 EC: 204-809-1 CAS: 126-86-3	≤0.3	Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 3, H412	-	[1]
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.036	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 450 mg/kg ATE [Inhalation (dusts and mists)] = 0.21 mg/l Skin Sens. 1, H317: C ≥ 0.036% M [Acute] = 1 M [Chronic] = 1	[1]
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:1)	EC: 911-418-6 CAS: 55965-84-9 Index: 613-167-00-5	<0.0015	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 53 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: $C \ge 0.6\%$ Eye Dam. 1, H318: $C \ge 0.6\%$ Eye Irrit. 2, H319:	[1]

Date of issue/Date of revision: 16/04/2025Date of previous issue: 10/10/2024Version: 42/19WOODEX AQUA CLASSIC - All variantsLabel No :85993

<b>SECTION 3: Composition/infor</b>	SECTION 3: Composition/information on ingredients						
	See Section 16 for the full text of the H statements declared above.	0.06% ≤ C < 0.6% Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100					

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Contains: > 1 % TiO2

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

**Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Get medical attention if irritation

occurs.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

: Flush contaminated skin with plenty of water. Remove contaminated clothing and Skin contact

shoes. Get medical attention if symptoms occur.

Ingestion : Wash out mouth with water. If material has been swallowed and the exposed

person is conscious, give small quantities of water to drink. Do not induce vomiting

unless directed to do so by medical personnel.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

#### 4.2 Most important symptoms and effects, both acute and delayed

### Over-exposure signs/symptoms

**Eye contact** : No specific data. Inhalation : No specific data. Skin contact : No specific data. Ingestion : No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

: Treat symptomatically. Contact poison treatment specialist immediately if large Notes to physician

quantities have been ingested or inhaled.

: No specific treatment. **Specific treatments** 

# **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** 

media

: None known.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Date of issue/Date of revision : 16/04/2025 : 10/10/2024 Version : 4 Date of previous issue 3/19 Label No: 85993

## SECTION 5: Firefighting measures

**Hazardous combustion** products

: Decomposition products may include the following materials: carbon dioxide carbon monoxide

#### 5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective** equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### **6.2 Environmental** precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

#### 6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

# SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Label No: 85993

Date of issue/Date of revision : 16/04/2025 : 10/10/2024 Version: 4 4/19 Date of previous issue

## SECTION 7: Handling and storage

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

onot store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### 7.3 Specific end use(s)

Recommendations : Not available. **Industrial sector specific** : Not available. solutions

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
2-Butoxyethanol	EU OEL (Europe, 1/2022) Absorbed through skin.
	TWA 8 hours: 20 ppm. TWA 8 hours: 98 mg/m³. STEL 15 minutes: 50 ppm. STEL 15 minutes: 246 mg/m³.

#### **Biological exposure indices**

Product/ingredient name	Exposure indices
No exposure indices known.	

### **Recommended monitoring** procedures

: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

Product/ingredient name

2-Butoxyethanol

#### Result

DNEL - General population - Long term - Oral

6.3 mg/kg bw/day Effects: Systemic

DNEL - General population - Short term - Oral

26.7 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Inhalation

59 mg/m<sup>3</sup>

Effects: Systemic

Date of issue/Date of revision : 16/04/2025 : 10/10/2024 Date of previous issue Version : 4 5/19 Label No: 85993

## **SECTION 8: Exposure controls/personal protection**

**DNEL - Workers - Long term - Inhalation** 

98 mg/m<sup>3</sup>

Effects: Systemic

DNEL - General population - Short term - Inhalation

147 mg/m³ Effects: Local

**DNEL - Workers - Short term - Inhalation** 

246 mg/m³ Effects: Local

DNEL - General population - Short term - Inhalation

426 mg/m³ Effects: Systemic

**DNEL - Workers - Short term - Inhalation** 

1091 mg/m³ Effects: Systemic

3-iodo-2-propynyl-butyl carbamate

**DNEL - Workers - Long term - Inhalation** 

0.023 mg/m³ Effects: Systemic

**DNEL - Workers - Short term - Inhalation** 

0.07 mg/m³ Effects: Systemic

**DNEL - Workers - Short term - Inhalation** 

1.16 mg/m³ Effects: Local

**DNEL - Workers - Long term - Inhalation** 

1.16 mg/m³ Effects: Local

**DNEL - Workers - Long term - Dermal** 

2 mg/kg bw/day <u>Effects</u>: Systemic

2,4,7,9-tetramethyl-5-decyne-4,7-diol

DNEL - General population - Long term - Oral

0.29 mg/kg bw/day Effects: Systemic

**DNEL - General population - Long term - Dermal** 

0.29 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Inhalation

0.505 mg/m³ Effects: Systemic

**DNEL - Workers - Long term - Dermal** 

0.812 mg/kg bw/day Effects: Systemic

**DNEL - Workers - Long term - Inhalation** 

2.86 mg/m³ Effects: Systemic

1,2-benzisothiazol-3(2H)-one

DNEL - General population - Long term - Dermal

Label No: 85993

0.345 mg/kg bw/day Effects: Systemic

**DNEL - Workers - Long term - Dermal** 

0.966 mg/kg bw/day

Date of issue/Date of revision : 16/04/2025 Date of previous issue : 10/10/2024 Version : 4 6/19

# **SECTION 8: Exposure controls/personal protection**

Effects: Systemic

DNEL - General population - Long term - Inhalation

1.2 mg/m³ Effects: Systemic

**DNEL - Workers - Long term - Inhalation** 

6.81 mg/m³ Effects: Systemic

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

DNEL - General population - Long term - Inhalation

0.02 mg/m³ Effects: Local

**DNEL - Workers - Long term - Inhalation** 

0.02 mg/m³ Effects: Local

DNEL - General population - Short term - Inhalation

0.04 mg/m³ <u>Effects</u>: Local

**DNEL - Workers - Short term - Inhalation** 

0.04 mg/m³ Effects: Local

DNEL - General population - Long term - Oral

0.09 mg/kg bw/day Effects: Systemic

DNEL - General population - Short term - Oral

0.11 mg/kg bw/day <u>Effects</u>: Systemic

#### **PNECs**

Not available.

### 8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** 

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

**Skin protection** 

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Label No: 85993

Date of issue/Date of revision : 16/04/2025 Date of previous issue : 10/10/2024 Version : 4 7/19

## SECTION 8: Exposure controls/personal protection

Recommendations: Wear suitable gloves tested to EN374.

> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm Not recommended

polyvinyl alcohol (PVA) gloves

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist

before handling this product.

: Appropriate footwear and any additional skin protection measures should be Other skin protection

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Based on the hazard and potential for exposure, select a respirator that meets the Respiratory protection

appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important

aspects of use.

Filter type (spray application):

**Environmental exposure** 

**Body protection** 

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

#### **Appearance**

**Physical state** : Liquid. Colour Various Odour Slight

**Odour threshold** Not available. : Not available. Melting point/freezing point

Initial boiling point and

boiling range

Ingredient name	°C	°F	Method
water	100	212	
2-Butoxyethanol	171 to 171.5	339.8 to 340.7	IP 123-93

**Flammability** : Not available.

Lower and upper explosion : Lower: Not applicable. Upper: Not applicable. limit

Closed cup: >100°C (>212°F) Flash point

**Auto-ignition temperature** 

Ingredient name	°C	°F	Method
Butoxyethanol	230	446	DIN 51794

**Decomposition temperature** : Not available. 8.4 to 9.1 Not available. **Viscosity** 

Solubility(ies)

Not available.

Solubility in water : Not available. Partition coefficient: n-octanol/ : Not applicable.

water

Vapour pressure

Date of issue/Date of revision : 16/04/2025 : 10/10/2024 Date of previous issue Version: 4 8/19 Label No: 85993

# SECTION 9: Physical and chemical properties

	Vapour Pressure at 20°C			Va	oour pressu	re at 50°C
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
water value	17.5	2.3				
2-Butoxyethanol	0.75006	0.1				

**Relative density** : Not available. : 1 g/cm<sup>3</sup> **Density** Vapour density : Not available.

**Particle characteristics** 

Median particle size : Not applicable.

#### 9.2 Other information

9.2.1 Information with regard to physical hazard classes

**Explosive properties** : Not available. **Oxidising properties** : Not available.

9.2.2 Other safety characteristics

Not applicable.

## SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute toxicity** 

Product/ingredient name Result

3-iodo-2-propynyl-butyl carbamate Rat - Oral - LD50

400 mg/kg

Rat - Dermal - LD50

>2000 mg/kg

Rat - Inhalation - LC50 Dusts and mists

0.763 mg/l [4 hours]

Rat - Inhalation - LC50 Dusts and mists

0.67 g/m<sup>3</sup> [4 hours]

1,2-benzisothiazol-3(2H)-one Rat - Oral - LD50

1020 mg/kg

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no.

220-239-6] (3:1)

Rat - Oral - LD50

53 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration -

: 10/10/2024 Date of issue/Date of revision : 16/04/2025 Date of previous issue Version: 4 9/19 Label No: 85993

# **SECTION 11: Toxicological information**

Respiratory depression

**Conclusion/Summary [Product]** : Not available.

#### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
₩OODEX AQUA CLASSIC	62204.0	N/A	N/A	155.5	338.1
2-Butoxyethanol	1200	N/A	N/A	3	N/A
3-iodo-2-propynyl-butyl carbamate	400	N/A	N/A	N/A	0.67
1,2-benzisothiazol-3(2H)-one	450	N/A	N/A	N/A	0.21
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-	53	50	N/A	0.5	N/A
3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)					

Result

Skin corrosion/irritation

Product/ingredient name

2-Butoxyethanol Rabbit - Skin - Mild irritant

Amount/concentration applied: 500 mg

2,4,7,9-tetramethyl-5-decyne-4,7-diol Rabbit - Skin - Mild irritant

Amount/concentration applied: 0.5 gm

1,2-benzisothiazol-3(2H)-one Human - Skin - Mild irritant

> Duration of treatment/exposure: 48 hours Amount/concentration applied: 5 %

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no.

220-239-6] (3:1)

Human - Skin - Severe irritant Amount/concentration applied: 0.01 %

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Product/ingredient name Result

2-Butoxyethanol Rabbit - Eyes - Moderate irritant Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 mg

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 100 mg

3-iodo-2-propynyl-butyl carbamate Rabbit - Eyes - Severe irritant

2,4,7,9-tetramethyl-5-decyne-4,7-diol Rabbit - Eyes - Severe irritant

Amount/concentration applied: 0.1 MI

Conclusion/Summary [Product] : Not available.

**Respiratory corrosion/irritation** 

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

**Product/ingredient name** Result

Date of issue/Date of revision : 16/04/2025 Date of previous issue : 10/10/2024 Version: 4 10/19 Label No: 85993

# **SECTION 11: Toxicological information**

3-iodo-2-propynyl-butyl carbamate

Guinea pig - skin Result: Not sensitizing

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

**Germ cell mutagenicity** 

Product/ingredient name Result

Result: Negative

**Conclusion/Summary [Product]**: Not available.

**Carcinogenicity** 

Not available.

**Conclusion/Summary [Product]**: Not available.

**Reproductive toxicity** 

Product/ingredient name Result

3-iodo-2-propynyl-butyl carbamate Rabbit - Female - Oral

50 mg/kg [7 days per week] [13 days]

Maternal toxicity: Positive Developmental: Negative

Rabbit - Female - Oral

20 mg/kg [7 days per week] [13 days]

<u>Maternal toxicity</u>: Negative Developmental: Negative

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name Result

3-iodo-2-propynyl-butyl carbamate STOT RE 1, H372 (larynx)

**Aspiration hazard** 

Not available.

Information on likely routes of exposure

Not available.

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.
 Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

Date of issue/Date of revision : 16/04/2025 Date of previous issue : 10/10/2024 Version : 4 11/19

WOODEX AQUA CLASSIC - All variants

Label No :85993

## SECTION 11: Toxicological information

Skin contact : No specific data.

Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

**Long term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

#### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine

disrupting properties according to the criteria set out in either Regulation (EC)

No. 1907/2006 or Regulation (EC) No 1272/2008.

#### 11.2.2 Other information

Not available.

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

### Product/ingredient name Result

Z-Butoxyethanol Acute - LC50 - Marine water

Fish - Inland silverside - Menidia beryllina

<u>Size</u>: 40 to 100 mm 1250000 μg/l [96 hours]

Effect: Mortality

Acute - LC50 - Marine water

Crustaceans - Common shrimp, sand shrimp - Crangon

Label No: 85993

crangon

800000 μg/l [48 hours] Effect: Mortality

3-iodo-2-propynyl-butyl carbamate Acute - LC50 - Fresh water

ΕU

Fish - Trout - Oncorhynchus mykiss

0.067 mg/l [96 hours]

Acute - NOEC - Fresh water

EU

Fish - Trout - Oncorhynchus mykiss

0.049 mg/l [96 hours]

Acute - EC50 - Fresh water

EU

Daphnia - Daphnia magna

0.16 mg/l [48 hours]

Date of issue/Date of revision : 16/04/2025 Date of previous issue : 10/10/2024 Version : 4 12/19

# **SECTION 12: Ecological information**

Chronic - NOEC - Fresh water

EU

Daphnia - Daphnia - Daphnia Magna

0.05 mg/l [21 days]

Acute - EC50 - Fresh water

ΕIJ

Algae - Algae - Scenedemus subspicatus

0.022 mg/l [72 hours]

2,4,7,9-tetramethyl-5-decyne-4,7-diol

LC50

Fish - *Cyprinus carpio* 42 mg/l [96 hours]

EC50

Daphnia - Daphnia magna

91 mg/l [48 hours]

1,2-benzisothiazol-3(2H)-one

Acute - LC50 - Fresh water

OECD [Fish, Acute Toxicity Test] Fish - Trout - Onorhynchus Mykiss

1.9 mg/l [96 hours]

Acute - EC50

OECD 202 [Daphnia sp. Acute Immobilization Test and

Reproduction Test]

Daphnia - Daphnia - Daphnia Magna

3.7 mg/l [48 hours]

Acute - EC50 - Marine water

OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - *Skeletonema Costatum* 

0.36 mg/l [72 hours]

Acute - NOEC - Marine water

OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - Skeletonema Costatum

0.15 mg/l [72 hours]

**Conclusion/Summary [Product]**: Not available.

12.2 Persistence and degradability

Product/ingredient name

Result

√,2-benzisothiazol-3(2H)-one

EU

24% [28 days]

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
<b>3</b> ∕iodo-2-propynyl-butyl carbamate	-	-	Not readily
1,2-benzisothiazol-3(2H)-one	-	-	Inherent

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-Butoxyethanol	0.81	-	Low
3-iodo-2-propynyl-butyl	>1	-	Low
carbamate		0.0	1
1,2-benzisothiazol-3(2H)-one	-	3.2	Low

#### 12.4 Mobility in soil

Date of issue/Date of revision: 16/04/2025Date of previous issue: 10/10/2024Version: 413/19WOODEX AQUA CLASSIC - All variantsLabel No :85993

# **SECTION 12: Ecological information**

## Soil/water partition coefficient

Product/ingredient name	logKoc	Koc
<b>2</b> -Butoxyethanol	1.83	67.3685
3-iodo-2-propynyl-butyl carbamate	1.13	13.4558
2,4,7,9-tetramethyl-5-decyne-4,7-diol	1.92	83.8929
1,2-benzisothiazol-3(2H)-one	1.86	73.142

#### Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	νM
<b>2</b> -Butoxyethanol	No	No	No	No	No	No	No
3-iodo-2-propynyl-butyl carbamate	No	No	No	No	No	No	No
2,4,7,9-tetramethyl- 5-decyne-4,7-diol	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No

Mobility

: Not available.

**Conclusion/Summary** 

: The product does not meet the criteria to be considered as a PMT or vPvM.

## 12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	В	T	vPvB	vP	vB
2-Butoxyethanol	No	No	No	No	No	No	No
3-iodo-2-propynyl-butyl carbamate	No	No	No	No	No	No	No
2,4,7,9-tetramethyl- 5-decyne-4,7-diol	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No

### Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	Р	В	Т	vPvB	vP	vB
2-Butoxyethanol	No	No	No	No	No	No	No
3-iodo-2-propynyl-butyl carbamate	No	No	No	No	No	No	No
2,4,7,9-tetramethyl- 5-decyne-4,7-diol	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP] : The product does not meet the criteria to be considered as a PBT or vPvB.

### 12.6 Endocrine disrupting properties

Date of issue/Date of revision: 16/04/2025Date of previous issue: 10/10/2024Version: 414/19WOODEX AQUA CLASSIC - All variantsLabel No :85993

# **SECTION 12: Ecological information**

Not available.

**Conclusion/Summary [Product]** 

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

# SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

#### **Product**

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**European waste** catalogue (EWC) : 080111\*, 200127\*

**Packaging** 

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** 

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not relevant/applicable due to nature of the product.

Date of issue/Date of revision : 16/04/2025 : 10/10/2024 15/19 Date of previous issue Version : 4 Label No: 85993

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed.

#### Substances of very high concern

None of the components are listed.

### Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
WOODEX AQUA CLASSIC	≥90	3

Labelling

Other EU regulations

**Industrial emissions** : Not listed

(integrated pollution prevention and control) -

**Industrial emissions** : Not listed

(integrated pollution prevention and control) -

Water

**Explosive precursors** : Not applicable. Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

**Persistent Organic Pollutants** 

Not listed.

**Seveso Directive** 

This product is not controlled under the Seveso Directive.

### **International regulations**

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

**Montreal Protocol** 

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

**Rotterdam Convention on Prior Informed Consent (PIC)** 

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

Date of issue/Date of revision : 10/10/2024 16/19 : 16/04/2025 Date of previous issue Version : 4 Label No: 85993

## **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation (EC) No.

1272/2008

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Aquatic Chronic 3, H412	Calculation method

#### Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

#### Full text of classifications [CLP/GHS]

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1

Date of issue/ Date of

revision

: 16/04/2025

Date of previous issue : 10/10/2024

Version : 4

WOODEX AQUA CLASSIC All variants

**Notice to reader** 

Date of issue/Date of revision: 16/04/2025Date of previous issue: 10/10/2024Version: 417/19

Label No: 85993

## **SECTION 16: Other information**

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision: 16/04/2025Date of previous issue: 10/10/2024Version: 418/19

**Label No**:85993

Date of issue/Date of revision: 16/04/2025Date of previous issue: 10/10/2024Version: 419/19

WOODEX AQUA CLASSIC - All variants Label No :85993