

DRYWOOD End Grain Sealer Premium

Contains no or minimal solvents
Waterborne brush quality for professional use

PRODUCT DESCRIPTION

DRYWOOD End Grain Sealer Premium is a waterborne quick drying sealer for end grains in joinery, wooden constructions and plywood, MDF and HDF. It can be used as a primer for further application of Drywood products.

See www.teknosdrywood.nl for use of this product in a total paint system.

TECHNICAL DATA

General	DRYWOOD End Grain Sealer Premium is based on a combination of waterborne binders and is suited for use as sealer for end grains. It is tested according to SKH publication 04-01 d.d 2009-03-20	
Properties	DRYWOOD End Grain Sealer Premium has excellent sealing properties of end grains and is very easy to apply in high layer thicknesses. The product has high penetration into the wood and dries very quickly. The product has good adhesion, high blocking properties and is good paintable. DRYWOOD End Grain Sealer Premium ED is a special quality to apply one layer of the product by spraying directly on a pile of wood panels.	
Colours and packaging	DRYWOOD End Grain Sealer Premium is available in transparent, grey, white and brown colour. Colours can vary and can change over time. The product is available in 1 and 2,5 liter packaging. Shelf-life is at least 12 months in unopened and closed packaging and at frost-free storage.	
Density	ca. 1,1 - 1,2 kg/l	(depending the colour)
Solids content	approx. 45 Vol%	(depending the colour)
VOC content	max. 40 g/l	EU-Limit (2004/42/EC annex. II A(d): 130 g/l)
Consumption	approx. 0,5 m2/l	at 500 g/m2

APPLICATION

General	DRYWOOD End Grain Sealer Premium can be applied by brushing, spraying or rolling on a clean surface, sanded and dry, free of dust and grease. Drying time depends on layerthickness, temperature, relative humidity and ventilation. According to SKH publicatie 04-01 d.d 2009-03-20 a minimal amount of 500 gram per square meter end grain of wood, plywood, HDF or MDF should be applied for good efficacy of the product. Drying times at 15 °C and 60 % R.H. at 500 g/m2: paintable after approx. 24 hours. Stirr well immediately prior to use.
Environment	The product has low toxicity to environment, has little smell and is not flammable.
Cleaning	Clean equipment after use with water and soap or other suited cleaners. Dilute with water.
Waste	Material and all related packaging must be disposed in a safe way in accordance with full requirements of local authorities.

SAFETY INFORMATION

see Material Safety Data Sheet
Contains Cobaltcarboxylate. May produce an allergic reaction

PIB nr. 241003EN
Revisedatum 14 February 2018

The above information is given according to our present knowledge. Teknos Drywood B.V. tries to keep the technical information up-to-date. In case further dates or informations of importance should come to our disposal this technical informationsheet will be updated (see date of issue). Teknos Drywood B.V. reserves the right to modify paint-formulations, processing-instructions, etc. without previous notice. We can not accept liability for mis use of the product or any loss or damage arising out of such for not giving Teknos Drywood B.V. the opportunity to evaluate test surfaces prior to coating the full surface.