

# COLOUR SAMPLE

Colour sample for colour testing and inspiration for your home.



Colour sample is available in 105 standard interior shades from Teknos Colour Your Story - Collection. These samples give you possibility to choose the right colour for your home with confidence.

Colour sample contains water-borne matt interior paint. With the contents of one can it is possible to paint approx. 1 m<sup>2</sup> once. We recommend, that the test surface is painted twice, so the colour accuracy is as close to the actual result as possible. It is convenient to try the paint on a separate board or e.g. cardboard, so the painted surface can also be moved around. After deciding the colour, choose the paint according to the object and surface. Please note, that colour appearance may differ due to different gloss of paint.



## TECHNICAL DATA

<b>Certificates, approvals and classification</b>	M1 classification, Finnish Key Flag
<b>Fields of application</b>	Indoor wall
<b>Recommended substrate</b>	Acrylate paint, Building board, Concrete, Filler, Gypsum board
<b>Solids</b>	Approx. 39% by volume
<b>Volatile organic compound (VOC)</b>	EU VOC limit value (kat A/a): 30 g/l. The product's VOC: max. 30 g/l.
<b>Theoretical spreading rate</b>	8 m <sup>2</sup> /l
<b>Colours</b>	105 standard colours
<b>Gloss (60°)</b>	Matt
<b>Density</b>	Approx. 1.3 g/ml
<b>Storage</b>	Must not freeze.
<b>Packaging</b>	0.125 l.

## DIRECTION FOR USE

<b>Surface preparation</b>	The surface must be clean and dry.
<b>Application method</b>	Brush, Roller
<b>Application</b>	Stir thoroughly before use.
<b>Application conditions</b>	The surface to be treated must be dry. During the application and drying period the temperature of the ambient air, the surface and the product shall be above +5°C and the relative air humidity below 80%. Good ventilation during the application and drying period quickens the drying process.

Drying time	+23 °C / 50% RH
- dust free	½ h
- overcoatable	1 h
Cleaning	Warm water and RENSA BRUSH brush cleaner. Wash the equipment immediately after use.

HEALTH AND SAFETY

Safety and precaution measures                      See safety data sheet.

Teknos Group Oy Takkatie 3, P.O.Box 107 FI-00371 Helsinki, Finland Tel. +358 9 506 091

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage [www.teknos.com](http://www.teknos.com). All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies.