	www.teknos.com
PRODUCT NAME 001 06 20.06.2017	FEIDOPOX primer ZG64-A6
20.00.2011	2C-EP-primer, High Solid
PRODUCT DESCRIPTION	Two component primer based on epoxy resin / poly amino-amid hardener, contains solvents. Active pigment: zinc phosphate.
INTENDED USE	Suitable as corrosion protecting primer for all kinds of structural steel work and in case of adequate surface preparation also for galvanized steel parts. Preferred fields of application are: crane constructions and objects in the chemical industry, petro chemistry, steel construction for hydraulic engineering, shipbuilding and mining etc.
SPECIAL CHARACTERISTICS OF THE COATING	FEIDOPOX primer ZG64-A6 is fast-drying, has a very good levelling, very good corrosion protection and is for multifunctional application
TECHNICAL DATA	
Gloss	mat
Topcoats	Depending on requirements products of type FEIDOPOX, FEIDOPUR or FEIDOPLAST.
APPLICATION DATA	
Brusing and Rolling	After mixing the components the product is ready-to-use.
High pressure spraying	Application is carried out with a spraying viscosity of 25 – 35 sec. / 4mm. Air pressure: 3.0 – 4.0 bar Nozzle: 1.5 – 1.8 mm
Airless spraying	Usually in delivery form, if necessary max. 10% (by weight) FEIDOSOLV thinner VK14 can be added.
	Minimum pressure: 120 bar Nozzle: 0.38 – 0.48 mm

The information on this data sheet is normative and based on laboratory tests and practical experience. Teknos guarantees that the product quality conforms to our quality system. Teknos accepts, however, no liability for the actual application work, as this is to a great extent dependent on the conditions during handling and application. Teknos accepts no liability for any damage resulting from misapplication of the product. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest version of Teknos data sheets, material safety data sheets and system sheets are on our homepage www.teknos.com.