

	www.teknos.com
PRODUCT NAME 001 06 20.06.2017	FEIDOPUR primer ZG23-G1 2C-PUR-priming filler, Medium Solid
PRODUCT DESCRIPTION	High quality 2component priming filler, mat, based on polyurethane (PUR).
INTENDED USE	For the coating of steel parts with high requirements regarding corrosion protection. Main application fields are e.g. commercial vehicle construction, cases-, plants and engine constructions. Suitable for construction and agricultural machinery. Very good process ability.
SPECIAL CHARACTERISTICS OF THE COATING	The product is sandable, temporarily non-chalking and therefore suitable for exterior storage. FEIDOPUR priming filler ZG23-G1 is active pigmented and provides good corrosion protection. ZG23-G1 confirms to the requirements of the Liebherr-standard AA 2 QA 325 055.
TECHNICAL DATA	
Gloss	mat
Topcoats	Depending on requirements products of type FEIDOPUR e.g. ZD55 or ZD35.
APPLICATION DATA	
Brushing and Rolling	Only small areas
Airless spraying	The processing is done in delivery form after mixing the components. If necessary FEIDOSOLV thinner VZ46- can be used for adjusting the spraying viscosity.

The information on this data sheet is normative and based on laboratory tests and practical experience. Teknos guarantees that the product quality conforms to our quality system. Teknos accepts, however, no liability for the actual application work, as this is to a great extent dependent on the conditions during handling and application. Teknos accepts no liability for any damage resulting from misapplication of the product. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest version of Teknos data sheets, material safety data sheets and system sheets are on our homepage www.teknos.com.