

ISOLIERGRUND 4610-00

Water-soluble, low-odour insulating primer for interior use

ISOLIERGRUND 4610-00 is a water-soluble, low-odour 1C primer for isolating and blocking off interior substrates contaminated with active substances in the wood, nicotine, bitumen, tar and water stains.



TECHNICAL DATA

| | |
|-----------------------------------|---|
| Solids | Approx. 56% by weight |
| Theoretical spreading rate | 150 g/m ² ; 6.6 m ² /kg |
| Colours | White. |
| Density | Approx. 1.4 g/ml |
| Storage | Storage temperature is +5 °C - +30 °C. Store in a tightly closed container. |

DIRECTION FOR USE

| | |
|----------------------------|---|
| Surface preparation | Every substrate must be well-cleaned, dry and free from grease and oil. |
| Application | Stir or shake the product well for several minutes before use, if necessary by machine. |

| APPLICATION ADVICE | | | | | |
|--|--------------------|----------|--------------|------------------|--------------|
| Wood substrate raw | | | | | |
| | Product | | | Applied Quantity | |
| Primer | ISOLIERGRUND 4610 | | | 150 g/m² | |
| Primer | Filler | | | | |
| Recoating | Colour lacquer | | | | |
| For further application proposals please ask our representative. | | | | | |
| APPLICATION | | | | | |
| | Viscosity | Dilution | Nozzle in mm | Pressure in bar | Spray Cycles |
| Airless / Airmix Spray Application | Delivery viscosity | 0-5% | 0.33 | | 1-2 |

| | |
|-------------------------------|--|
| Application conditions | Recommended temperature for surroundings and product: +15 °C-25 °C. Do not apply below +10 °C. |
| Drying time | +23 °C / 65% RH |
| - dust free | after 35 minutes |
| - touch dry | after 50 minutes |
| - overcoatable | after 5 hours |
| Cleaning | Wash the equipment immediately after use. Water, REINIGUNGSMITTEL S 8200-98. |

HEALTH AND SAFETY

| | |
|--------------------------------|---|
| Safety and precaution measures | See safety data sheet. |
| First aid | We recommend wearing personal protective clothing even in cases where no local regulations are in force. CH: The precautions according to local regulations (SUVA) with respect to hygiene and equipment must be observed. |

Teknos Group Oy Takkatie 3, P.O.Box 107 FI-00371 Helsinki, Finland Tel. +358 9 506 091

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com. All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies.