

METRO 9110-00

Universal paint stripper

METRO 9110-00 is a paste-like universal paint stripper which is highly effective against practically all application materials in the coating trade. The product does not leave any discolouration on the wood.



TECHNICAL DATA

Fields of application	Furniture, Fixed furniture, Kitchen, Kitchen furniture, Stairs, Interior doors, Exterior doors, Window shutters
Solids	Approx. 61% by weight
Theoretical spreading rate	500 g/m ² ; 2 m ² /kg
Colours	Colourless.
Density	Approx. 0.986 g/ml
Storage	Storage temperature is +5°C - +30°C. Store in a tightly closed container.

DIRECTION FOR USE

Surface preparation	Every substrate must be well-cleaned, dry and free from grease and oil.
Application method	<p>Brush</p> <p>To speed up the stripping process, we recommend thoroughly sanding/scratching the surface to be stripped with 80-100 grain sandpaper before applying METRO 9110-00.</p> <p>Cover large areas with plastic film (PE) to optimise the stripping effect. Check the effect from time to time. Stripped layers should be removed with a stainless steel spatula. Do not use metal-steel pads. Use solvent-resistant plastic non-woven cloths. Repeat the procedure if necessary.</p> <p>After removal of the old coating, clean the surface with REINIGER 4559-98 (removal of residual coating stripper etc.). Then let the wood dry thoroughly.</p> <p>New application with sanded finish.</p>

Application

Shake or stir product well before use.

APPLICATION ADVICE		
Old coatings		
	Product	Applied Quantity
	METRO FIT NEW (apply generously)	ca. 500 g/m²
	<p>To speed up the stripping process, we recommend sanding/scratching the surface to be stripped with sandpaper with grain 60-120 before applying Metro Fit New.</p> <p>Cover large areas with plastic film (PE) to optimise the stripping effect. Check the result from time to time. Remove stained layers with a stainless steel scraper. Do not use metal-steel wadding. Use solvent-resistant plastic fleeces. Repeat the process if necessary.</p> <p>After removing old paint, clean the surface with V4559 cleaner (removal of remaining paint stain residues, etc.). Then allow the wood to dry thoroughly.</p> <p>Reconstruct with wood sanding ...</p>	
For further application proposals please ask our representative.		

Application conditions

Recommended temperature for surroundings and product: +15°C-25°C. Do not apply below +10°C.

Drying time

+23°C / 65% RH

Cleaning

Wash the equipment immediately after use. REINIGER 4559-98

HEALTH AND SAFETY

Safety and precaution measures

See safety data sheet.

First aid

We recommend wearing personal protective clothing even in cases where no local regulations are in force.

CH: The precautions according to local regulations (SUVA) with respect to hygiene and equipment must be observed.

Teknos Group Oy Takkatie 3, P.O.Box 107 FI-00371 Helsinki, Finland Tel. +358 9 506 091

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com. All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies.