

OLICLEAN 123

Cleaner

Cleaning agent in the form of a concentrate for professional use. Clear liquid, a mixture of mild alkaline substances and emulsifiers. Does not cause corrosion. Soluble in water in any proportions. Very good cleaning properties already at 1% concentration. It creates foam.

OLICLEAN 123 is designed for washing and degreasing metal structures prior surface preparation and application of protective coatings. It can also be successfully used for cleaning and degreasing object in the machine industry, mechanical and car workshops also for internal and external cleaning of means of transport.



TECHNICAL DATA

Recommended substrate	Metal
pH	10.7
Density	Approx. 1 g/ml
Storage	The storage stability is shown on the label. Must be stored tightly closed and kept cool and dry.

DIRECTION FOR USE

Application

It may be used in the wide range of concentrations. Depending on the sensitivity of the surface, the type and degree of soiling and the cleaning technique used, it is recommended to prepare aqueous solutions in concentrations of 1 to 10 %. For washing zinc and aluminium surfaces, use only solutions. Contact of these surfaces with the solution should not last longer than 10 minutes. Solutions of cleaning agent can be applied either by hand using a brush, as well as by means of a spray. After application, allow it to penetrate the surface contamination at approximately 10 - 15 minutes, and then rinse with clean water. Do not allow the solution to dry on the surface to be cleaned. Increasing the temperature of the solution (to 80 °C) improves the efficiency and speed of cleaning. Use at temperatures above 0 °C.

HEALTH AND SAFETY

Safety and precaution measures

See Material Safety Data Sheet.

Contains: C10 Alcohol ethoxylate 3 - 5%, dipropylene glycolmethylether 1-3 %, non-ionic surfactants - < 5 % and amphoteric surfactants - < 5 %.

Freezing point - 0°C, Boiling point - 100°C.

Teknos Group Oy Takkatie 3, P.O.Box 107 FI-00371 Helsinki, Finland Tel. +358 9 506 091

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com. All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies.