

# RENSA FLOOR POLISH 4580-30

Polymer dispersion for the care and maintenance of all parquet and cork floors with a water-resistant finish



RENSA FLOOR POLISH 4580-30 is a polymer dispersion for the care and maintenance of all parquet and cork floors with a water-resistant finish. Maintains and protects old floors, restoring their (satin) matt or matt finish. Enhances the natural grain of the floor and intensifies its colour.

pH value: approx. 8.5 (concentrate)

Information on contained substances (according to EU recommendations):

Less than 5 % non-ionic surfactants. Additional ingredients: Care ingredients, auxiliaries and fragrances.

## TECHNICAL DATA

Fields of application	Floors
Solids	Approx. 50% by weight
Theoretical spreading rate	25 g/m <sup>2</sup> ; 40 m <sup>2</sup> /kg
Colours	Colourless.
Gloss (60°)	30
Density	Approx. 1.01 g/ml
Storage	Storage temperature is +5°C - +30°C. Store in a tightly closed container.

## DIRECTION FOR USE

Surface preparation	Every substrate must be well-cleaned, dry and free from grease and oil.		
Application method	Cloth, Smooth roller		
Application	Shake or stir product well before use.		
	APPLICATION ADVICE		
	Water-resistant finished parquet and cork floors		
	Product	Applied Quantity	
Care	RENSA FLOOR POLISH 4580	25 g/m²	
	UV-sealed finished parquet		
	Product	Applied Quantity	
Care	RENSA FLOOR POLISH 4580	25 g/m²	
	For further application proposals please ask our representative.		

### Application conditions

Recommended temperature for surroundings and product: +15°C-25°C. Do not apply below +10°C. Ideal surface and object temperature for application: +18°C-22°C. Avoid application in direct sunlight. Underfloor heating systems must be adjusted well in advance.

<b>Drying time</b>	+23 °C / 50% RH (dry film 20 µm)
- dust free	after 40 minutes
- touch dry	after 3 hours
- overcoatable	after 1 day
- through dry	after 6 days
	Can be walked on after initial care: After 6 h. Can be walked on after maintenance: After 2 h.
<b>Cleaning</b>	Wash the equipment immediately after use.

## HEALTH AND SAFETY

**Safety and precaution measures** See safety data sheet.

## ADDITIONAL INFORMATION

<b>Maintenance instructions</b>	<p>Initial care: Wait for at least 3 weeks before thoroughly cleaning hardwood floors. If the floor is very dirty, use RENZA PRO CLEAN 4582-00 as a pre-treatment.</p> <p>Let dry for at least 12 h, ideally overnight.</p> <p>Maintenance: Remove dirt and dust with a vacuum and/or by mopping. Add 1 part of RENZA FLOOR POLISH 4580-30 to 5 l of cleaning water (equivalent to 2%).</p> <p>Also refer to our brochure "Perfect parquet floor care".</p> <p>For more information on wood floor surface treatments and their use, visit <a href="http://www.parkett-verband.ch">www.parkett-verband.ch</a>.</p>
<b>Additional information</b>	<p>Adhesive strength according to DIN EN ISO 2409: GT 0</p> <p>Abrasion resistance (Taber Abraser) DIN 68861: &lt;80mg</p>

**Teknos Group Oy Takkatie 3, P.O.Box 107 FI-00371 Helsinki, Finland Tel. +358 9 506 091**

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage [www.teknos.com](http://www.teknos.com). All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies.