

RENSA PRO CLEAN 4582-00

Alkaline basic cleaner

RENSA PRO CLEAN 4582-00 is an alkaline basic cleaner with strong dissolving power for old residues of wax, care and maintenance products and polymer dispersions for parquet and cork floors with a water-resistant finish. Basic cleaning should be carried out by a parquet floor specialist.

pH value: approx. 8.5-9 (concentrate)

Information on contained substances (according to EU recommendations):

Below 5 % anionic surfactants, below 5 % non-ionic surfactants, 5 % NTA. Additional ingredients: Solvents, auxiliaries and fragrances.



Fields of application	Floors
Solids	Approx. 0% by weight
Volatile organic compound (VOC)	Approx. 16 g/l (DIRECTIVE 2010/75/EU)
	The VOC value provided is the average value for factory produced products, and
	consequently it will be subject to variations between individual products
	covered by this Technical Data Sheet.
Theoretical spreading rate	50 g/m²; 20 m²/kg
Colours	Colourless.
Density	Approx. 1 g/ml
Storage	Storage temperature is +5°C - +30°C. Store in a tightly closed container. Store
	in a cool, dry place, locked away and out of reach for children (with safety lock).

DIRECTION FOR USE





Application method

Cloth, Smooth roller

Wear rubber gloves during application. Ensure good ventilation of the rooms. Spot test at an inconspicuous place as a precaution. Do not use on metal and painted furniture surfaces. Apply undiluted to the cleaned floor with a mop, avoid the formation of puddles. Remove the film of the cleaning solution after a short exposure with a single disk machine and red or beige pad. To limit the exposure time of the cleaning solution to the minimum, treat the floor successively in small sections. If possible, work in pairs with one person removing the cleaning agent and the second wiping up the dirty solution. After 30 minutes at the earliest, initial care can be carried out with RENSA WOOD OIL POLISH.

Application

Stir or shake the product well for several minutes before use, if necessary by machine.

	APPLICATION ADVICE	
Water-resistant finished floors		
	Product	Applied Quantity
Cleaning	RENSA PRO CLEAN 4582	
	(apply undiluted)	
Oil-treated hardwood and c	ork floors	
	Product	Applied Quantity
Cleaning	RENSA PRO CLEAN 4582	
	(diluted 1:1 with water)	
Lacquered surfaces		
	Product	Applied Quantity
Cleaning	RENSA PRO CLEAN 4582	
	(diluted 1:1 with water)	
For fu	urther application proposals please ask our repres	entative.

Application conditions

Recommended temperature for surroundings and product: +15°C-25°C. Do not apply below +10°C. Ideal surface and object temperature for application: +18°C-22°C. Avoid application in direct sunlight. Underfloor heating systems must be adjusted well in advance.

Drying time	+23°C / 50% RH (dry film 20 um)

Cleaning Wash the equipment immediately after use. Water.

HEALTH AND SAFETY

Safety and precaution measures	See safety data sheet.
First aid	We recommend wearing personal protective clothing even in cases where no
	local regulations are in force.
	CH: The precautions according to local regulations (SUVA) with respect to
	hygiene and equipment must be observed.

ADDITIONAL INFORMATION

Maintenance instructions Also refer to our brochure "Perfect parquet floor care".



Teknos Group Oy Takkatie 3, P.O.Box 107 Fl-00371 Helsinki, Finland Tel. +358 9 506 091

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com. All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies.