

SATU LAUDESUOJA

Protection for benches in the steam-room

SATU LAUDESUOJA Protection for benches in the steam-room is a colourless and odourless protection containing paraffin oil for wooden surfaces. It forms a dirt and water repellent but breathable coat. SATU LAUDESUOJA emphasizes the natural colour of wood.



Use: Treatment of benches in the steam-rooms of saunas, wooden kitchen table tops etc. Suitable for untreated and previously oil treated wooden surfaces. Can also be used for treating wall and ceiling panels in steam-rooms.



TECHNICAL DATA

| | |
|---|---|
| Certificates, approvals and classification | M1 classification, Finnish Key Flag |
| Fields of application | Sauna |
| Recommended substrate | Planed wood |
| Solids | Approx. 100% by volume |
| Volatile organic compound (VOC) | The product is not included in the EU VOC directive. |
| Practical spreading rate | Applied once onto a smooth surface: approx. 10 m ² /l. |
| Colours | Clear. |
| Density | Approx. 1 g/ml |
| Storage | Must be stored tightly closed and kept cool. Must not freeze. |
| Packaging | 0.25 l, 1 l. |

DIRECTION FOR USE

| | |
|----------------------------|--|
| Surface preparation | Clean new surfaces from dust and dirt. Wash previously oiled surfaces with RENSA SAUNA sauna cleaner and rinse thoroughly with water. If the wooden surface has previously been varnished or treated with protection for sauna, the surface must be sanded bare. |
| Application method | Brush, Cloth, Sponge |
| Application | Stir thoroughly before use. Apply to a clean and dry wooden surface 1 to 3 times depending on the absorption properties of the surface. Wipe off excess oil 30 min after the application. |

Application conditions

The surface to be treated has to be dry. During the application and drying period the temperature of the ambient air, the surface and the product shall be above +10°C and the relative air humidity below 80%. Good ventilation during the application and drying period quickens the drying process.

| | |
|-------------------------|--|
| Drying time | +23°C / 50% RH |
| - dust free | 1 h |
| - next treatment | 2 h |
| - dry to use | the following day |
| | The drying process will be slower in cold and/or damp. Sauna must be preheated and ventilated before taking into use. |

Cleaning

Warm water and RENSA BRUSH brush cleaner. Wash the equipment immediately after use.

HEALTH AND SAFETY

Safety and precaution measures

See safety data sheet.

ADDITIONAL INFORMATION

Maintenance instructions

The surface can be cleaned by wiping with a neutral (pH 6 - 8) detergent. Detergent and dirt are removed by wiping and/or rinsing the surface with clean water. Use a cleaning cloth, soft sponge or similar for cleaning. Avoid coarse brushing or heavy abrasion. Follow the dilution and other instructions of the detergent producer when using detergents.

Teknos Group Oy Takkatie 3, P.O.Box 107 FI-00371 Helsinki, Finland Tel. +358 9 506 091

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com. All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies.