Teknos Deutschland GmbH Am Kirchberg 1 63755 Alzenau Germany T +49 60 23 961 0 F +49 60 23 961 262 info@teknos.de www.teknos.de



TECHNICAL DATASHEET

Page:1 of 2

Product name: TEKNOGROOVE AQUA 292-145 ALL COLOURS

Colour code: ALL COLOURS

Description & Intended use:

This product is recommended for the industrial lacquering of wood-based substrates. Waterborne, hydrophobe pigmented top-coat for v-groove-coating of PDL or DPL flooring with vacumat-systems.

Characteristics:

Viscosity: 24 ± 2 sec. DIN 4mm/20°C*

Density at 20°C: $1,2 \pm 0,2 \text{ kg/l}$

Solid Content: 50 ± 10 by weight %

VOC: max. 5 %

Classification: No migration of hazardous materials such as heavy metals.

Application:

Preparation: Stir well before use

Hardener: None

Thinner: If required, adjust viscosity with water

Viscosity: As delivered

Film Weight: n.a.

Application: Vacuum varnish/ transferdisc

Drying: Jet-air dryer or IR-dryer

Substrate: Industrial v-groove-coating of PDL or DPL flooring

Storage: The product should be stored between 5°C and 30°C. At a temperature

of 23 ± 2°C the product has a shelf life of up to 12 months, from

produce date, in its original sealed trading unit. Higher temperatures

reduce the shelf life. Protect from sunlight and frost.

^{*}Determined on day of product release

Teknos Deutschland GmbH Am Kirchberg 1 63755 Alzenau Germany T +49 60 23 961 0 F +49 60 23 961 262 info@teknos.de www.teknos.de



TECHNICAL DATASHEET

Page:2 of 2

Product name: TEKNOGROOVE AQUA 292-145 ALL COLOURS

Colour code: ALL COLOURS

Cleaning: Clean equipment with water directly after use.

Precautions: Refer to Health and Safety Data Sheet.

Health & Safety: Refer to Health and Safety Data Sheet.