Teknos Deutschland GmbH Am Kirchberg 1 63755 Alzenau Germany T +49 60 23 961 0 F +49 60 23 961 262 info@teknos.de www.teknos.de



TECHNICAL DATASHEET

Page:1 of 2

Product name:TEKNOGROOVE AQUA 293-140 ALL COLOURSColour code:ALL COLOURS

Description & Intended use:

This product is recommended for the industrial lacquering of wood-based substrates. Waterborne pigmented top-coat for v-groove-coating of PDL or DPL flooring with vacumatsystems.

Characteristics:

Viscosity:	34 ± 5 sec. DIN 4mm/20°C*
Density at 20°C:	1,2 ± 0,2 kg/l
Solid Content:	59 ± 5 by weight %
VOC:	max. 5 %
Classification:	No migration of hazardous materials such as heavy metals.

Application:

Preparation:	Stir well before use
Hardener:	None
Thinner:	If required, adjust viscosity with water
Viscosity:	As delivered
Film Weight:	n.a.
Application:	Vacuum varnish/ transferdisc
Drying:	Jet-air dryer or IR-dryer
Substrate:	Industrial v-groove-coating of PDL or DPL flooring
Storage:	The product should be stored between 5°C and 30°C. At a temperature of 23 \pm 2°C the product has a shelf life of up to 12 month, from produce date, in its original sealed trading unit. Higher temperatures reduce the shelf life. Protect from sunlight and frost.

*Determined on day of product release

Application technology aduice, technical data or recommendations are carried out to the best of our ability, albeit non-binding exluding warranty and limitation on liability. This data sheet will be rendered invalid as soon as replaced by a revised version. Please request the latest version.

T +49 60 23 961 0 F +49 60 23 961 262 info@teknos.de www.teknos.de



TECHNICAL DATASHEET

Page:2 of 2

Product name:	TEKNOGROOVE AQUA 293-140 ALL COLOURS
Colour code:	ALL COLOURS

- **Cleaning:** Clean equipment with water directly after use.
- Precautions: Refer to Health and Safety Data Sheet.
- Health & Safety: Refer to Health and Safety Data Sheet.

Application technology aduice, technical data or recommendations are carried out to the best of our ability, albeit non-binding exluding warranty and limitation on liability. This data sheet will be rendered invalid as soon as replaced by a revised version. Please request the latest version.